


MITH Electronics Enthusiasts Mail Order Catalogue 1988/9





Multiply DSXpress' better service! Take our 6 ways to place your order, multiply our 4 ways to receive your order . . . the answer's clear: our 24 hour despatch is unbeatable!

6 Ways to Order

(1) Phone: Quick and Easy!

All it costs is a local call: from anywhere! Our Credit Card Orderline is ready to take your call.

(2) Fax: You keep a copy!

So simple: and you can order 24 hours a day by fax! Call (02) 888 3631 to fax your order through.

(3) Telex: We're ready!

Most businesses have telex — you can place an order by telexing (AA) 20036.

(4) Telegram: In a hurry?

Your telegram can be delivered by hand, or to our telex machine. Telegraphic address: Diksmit, Sydney.

(5) Viatel: It's up-to-date

As more and more people switch on to Viatel, so did we! Look up the electronic ordering system on page 345720

(6) Mail: the old faithfull!

We're proud of our mail order service — it's been going over 20 years. You can check out DSXpress by posting an order today!

4 Ways to Receive

Low-cost delivery methods, with freight subsidised by DSXpress. Check out our rates: you'll be surprised.

(1) Air Freight

It's quick — normal delivery to most areas in Australia is next day! And we'll even air freight overseas.

(2) Road Freight

We go anywhere . . . especially with heavy and bulky items. Very handy in the back blocks.

Australia Post will get your parcel there! It's reliable - and it's quick! Yes, we even subsidise packing and postage!

(4) Courier it!

DSXpress couriers orders all over Sydney for customers who simply can't wait! And we'll even charge goods to your credit card.

24 Hour Despatch

The equation is complete: your order is despatched within 24 hours of receipt (assuming the goods are in stock!). Your order is valuable to us: it doesn't lie around in a pile for a few days until someone gets around to it!

Trust DSXpress: you'll find there is a real difference!

All Major Credit Cards Accepted

We accept all the major credit cards: Bankcard, Visa, Mastercard, American Express, Diner's Club . . . as well as cheques, money orders, bank drafts, etc.

Have you tried DSXpress?


If you can't make it to a DSE store, DSXpress is ready to serve you! Any catalogue item can be ordered through DSXpress — and DSXpress guarantee your order will be on its way at most within 24 hours usually it's same day! The same friendly service. The same great products. The same low, low prices. They're all yours at DSXpress. Join the DSXpress family — you'll be glad you have a relative in the business!





24 HOUR DESPATCH

DICK SMITH ELECTRONICS EXPRESS ORDER SERVICE



For full index see page 99

Dear Customer,

Welcome to the 1988 Dick Smith Electronics Hobbyist and Enthusiast Catalogue.

You've probably already noticed that this catalogue is different from previous years. For a start, it's thinner!

Does this mean that Dick Smith Electronics has less products to offer the hobbyist and enthusiast this year?

No! Exactly the opposite, in fact. If you have a close look at the Hobbyist and Enthusiast Catalogue, you'll find that's all it has in it: hobbyist and enthusiast products.

One of the things you, the hobbyists and enthusiasts, even the technicians, engineers and other electronics professionals, told us is that you're only occasionally interested in "consumer electronics": the fun products, the phones, the audio products and so on. You wanted a catalogue of your own, containing the products YOU were interested

So here it is!

100 pages devoted to hobbyist and enthusiast products — that's about a 10% increase since last year (look for all the "New for 88" emblems.

Of course, there is also a "Consumer Electronics" catalogue available from Dick Smith Electronics.

This issue marks 2 decades in this exciting business — and we're more committed than ever before to offering the complete needs of the serious hobbyist.

With regards,

Jeff Grover, Managing Director



Looking for a Gift Idea?



The Dick Smith Electronics catalogue is crammed full of gift ideas for the

But what do you choose?

Make it easy on yourself: give your favourite hobbyist a DSE Gift Voucher, so they can make their own choices!

DSE Gift Vouchers are available from your nearest Dick Smith Electronics store.




Amateur Radio 70-73

Communications

CB & Marine



TV Antennas



Books




82-85

Data Section



86-98

PLEASE NOTE: This is a reprint of our 1988 Hobbyists Catalogue. While products and prices were current at press time (August 1988) currency fluctuations, Government Policies and other causes beyond our control may force price changes, product differences, etc. Please enquire at your nearest Dick Smith Electronics store or authorised re-seller for latest prices and product avalability.



DICK SMITH DARLINGTON, SA. **Australian Store Locations**

CHERMSIDE, QLD.

FYSHWICK, ACT.

NSW Swift & Young Sts. T55 Terrace Level Shop 1, 65-75 Main St 2 Denison St Shop 2, 1B Cross St, Warringah Mall Campbelltown Mall Queen St Shop 235, Archer St Entrance 147 Hume Hwy 164 Pacific Hwy 99 Donnison St 4 Florence St 99 Donnison St 4 Florence St Elizabeth Dr & Bathurst St 450 High Street 621-627 The Kingsway 173 Maitland Rd, Tighes Hill Lane Cove & Waterloo Rds George & Smith Sts Cnr Henry & Riley Sts 818 George St 125 York St Treloar's Bldg, Brisbane St Treloar's Bldg, Brisbane St 263 Keira St ACT 96 Gladstone St

96 Gladstone St
VIC
Creswick Rd & Webster St
145 McCrae St
Shop 46,Box Hill Central,Main St
260 Sydney Rd
Shop 1, 176 Lonsdale St
Hawthorn Rd & Nepean Hwy
1150 Mt Alexander Rd
Shop 11/13 Footscray Plaza
Nepean Hwy & Ross Smith Ave
Shop 9 110, High St
Shop 1, 399 Elizabeth St
Bridge Rd & The Boulevarde
Shop 2, 141 Maroondah Hwy
Springvale & Dandenong Rds
QLD
157-159 Elizabeth St

QLD
157-159 Elizabeth St
166 Logan Rd
42-44 Florence St
Gymple & Hamilton Rds
2nd Level Western Entrance
Redbank Shopping Plaza
Queen Elizabeth Dr & Bernard St
Gold Coast Hwy & Welch St
Bowen & Ruthven Sts
Kings Rd & Woolcock St
Cnr Pacific Hwy & Kingston Rd
SA
77 Grenfell St
688 Port Road

Main South & Flagstaff Rds Shop T25, Elizabeth City Centre Main North Rd & Darlington St

Albury	(060) 21 8399
Bankstown Sq	(02) 707 4888
Blacktown	(02) 671 7722
Bondi Junction	(02) 387 1444
Brookvale	(02) 905 0441
Campbelltown	(046) 27 2199
Chatswood Chase	(02) 411 1955
Chullora	(02) 642 8922
Gore Hill	(02) 439 5311
Gosford	(043) 25 0235
Hornsby	(02) 477 6633
Liverpool	(02) 600 9888
Maitland	(049) 33 7866
Miranda	(02) 525 2722
Newcastle	(049) 61 1896
North Ryde	(02) 88 3855
Parramatta	(02) 689 2188
Penrith	(047) 32 3400
Railway Square	(02) 211 3777
Sydney City	
	(02) 267 9111
Tamworth	(067) 66 1711
Wollongong	(042) 28 3800

Fyshwick (062) 80 4944 **Ballarat**

(053) 31 5433 (054) 43 0388 (03) 890 0699 (03) 383 4455 (03) 794 9377 (03) 592 2366 (03) 379 7444 (03) 689 2055 (03) 783 9144 (052) 43 8804 (03) 326 6088 (03) 326 6088 (03) 879 538 (03) 547 0522 Bendigo Box Hill Box Hill
Coburg
Dandenong
East Brighton
Essendon
Footscray
Frankston
Geelong
Melbourne City
Richmond Ringwood Springvale (03) 547 0522

(07) 229 9377 (07) 391 6233 (070) 311 515 **Brisbane City** Buranda Cairns Chermside (07) 359 6255

(07) 288 5599 (079) 27 9644 (075) 32 9863 (076) 38 4300 (077) 72 5722 (07) 341 0844 Redbank Rockhampton Southport Toowoomb Townsville Underwood

(08) 232 1200 (08) 347 1900 (08) 298 8977 (08) 255 6099 (08) 260 6088 Beverley Darlington Elizabeth

WA Wharf St & Albany Hwy 66 Adelaide St William St & Robinson Ave Raine Square, 125 William St Shop 40A, Lower Level Cat & Fiddle Arcade 20 Stuart Hwy

New Zecland Store

442 Karangahape Rd
1795 Great North Road
Victoria Road & Baeley Avenue
Manse & Stafford Streets
450 Anglesea Street
440 Cuba Street, Alicetown
Cnr Khyber Pass & Park Rds
26 East Tarmaki Road
P16 Lydney Place 16 Lydney Place 289 Cameron Road 154 Featherson Street

Cannington Fremantle North Perth Perth City (09) 451 8666 (09) 335 9733 (09) 328 6944 (09) 481 3261 Hobart (002) 31 0800 Stuart Park (089) 81 1977

Locations Auckland City Avondale Christchurch (09) 394 402 (09) 886 696 (03) 50 405 (024) 741 096 (071) 394 490 (04) 662 022 (09) 278 2355 (04) 376 654 (075) 87 071 (04) 739 858 Hamilton Lower Hutt Newmarket Papatoetoe Porirua Tauranga Wellington (04) 739 858

Major DSE Authorised Stockists

NSW Major Dae Authorised Si	OCKISIS	
Sound Components, 244 Beardy St	Armidale	72 4981
Ballina Electronics, 102a River St	Ballina	86 7022
F.R.H. Electrical, 27 Station St	Bowral	61 1861
Hobbies & Electronics, 21 Oxide St	Broken Hill	88 4098
Newtronics, 131 Pacific Hwy	Charlestown	43 9600
Coffs Harbour Electronics, Shop 3		
Coffs Harbour Mall Park Ave	Coffs Harbour	52 5684
Deni Electronics, 220 Cressy St	Deniliquin	81 3672
Chris's Hi-Fi, 1/100 Talbragar St	Dubbo	82 8711
Miatronics, 166-170 Banna Ave	Griffith	62 4534
Lyn Willing Electronics, 32 Lawrence St	Inverell	22 1821
Moree Electronics, 26 Balo St	Moree	52 3458
Headware, 136 Church St	Mudgee	72 3895
Nowra Electronics, 218 Adelaide St	Nowra	21 0722
Strad Music Centre, 279-281 Clarinda St	Parkes	62 3366
Hall of Electronics, The Horton Centre, 124 Horton St		
Phillips Electronics, 60 Forsyth St	Wagga	21 6558
Keith Donges Electronics, 186 Boorowa St	Young	82 1279
VIC	20.020,000	
Morwell Electronics, 35 Holmes Rd	Morwell	34 6133
Phillips Electronics Pty. Ltd., 137 High St	Shepparton	21 9497
Marrtronics, Shop 12, Norfolk Plaza, 743 Raglan Pde	Warrnambool	62 9870
QLD		
Bob Elkin Electronics, 81 Bourbong St	Bundaberg	72 1785
Electro-Mart, 9 Tay Ave	Caloundra	91 8533
Splitec, Shop 5, Cartwright Centre, Nicklin Way	Kawana	94 7349
Stevens Electronics, 42 Victoria St	Mackay	51 1723
Keller Electronics, 218 Adelaide St	Maryborough	21 4559
Hutchessons Communications Centre, 5 Elizabeth St WA	Mt Gambier	25 0400
Micro Electronics, 133 Lockyer Ave	Albany	41 2077
Batavia Lighting & Electrical, 98a Chapman Rd	Geraldton	23 1842
Dave's Oscitronics, 1st Floor.	Gerardon	20 1012
Savings House, Hedland Place	Karratha	85 4836
Ivan Tomek Electronics, 30 Anderson St	Port Hedland	73 2531
TAS	. Oit iicalaila	70 2007
A.I. Electronics & Hobbies, 165 William St, Fourways	Devonport	24 8322

page 4

HEAD OFFICE: Ph (02) 888 3200

Cnr Lane Cove and Waterloo Roads, North Ryde NSW

Postal Address: PO Box 321, North Rvde NSW 2113 Australia FAX: (02) 888 3631 Telex: AA20036 Cables: 'DIKSMIT' Sydney



DICK SMITH ELECTRONICS SS EXPRESS ORDER SERVICE

ORDERS [TOLL FREE] (008) 22 6610

SYDNEY AREA ORDERS AND ALL ENQUIRIES: (02) 888 2105 FAX. Mail. Telex and Cables as above.

SERVICE AND SPARES:

Sydney Service Centre & Spare Parts (02) 888 3077 (03) 429 5817 **Melbourne Service Centre** (07) 391 8096 **Brisbane Service Centre** (062) 86 2875 Canberra Service Centre

Other capital cities: Service enquiries through your local store.

All Dick Smith Electronics stores are "depots" for lodgement of warranty and general service repairs. To save you time and money please lodge repairs with the store nearest you (we pay freight charges between store and service centre).

Your local store can also obtain spare parts against a firm order and deposit, normally within a few days.

PRODUCT HOTLINE

(02) 888 2002 Mon-Fri. 9am to 5pm EAST

For queries, problems and information about the DSE range of computers and high-tech products.

DSE BULLETIN BOARD

(02) 887 2276

24 hours


V21/V22 (300/300 or 1200/1200 baud, auto sensing) 8 data bits, 1 stop bit, no parity.


Uploading of files using all popular transfer protocols. And best of all . . . it's FREE!



becoming an authorised stockist

products, or purchasing goods in commercial quantities, please call DSE Wholesale on Head Office number above.





page 5

DSES


They look so good your friends won't believe you built them!

You should insist on a quality Dick Smith Kit. As the number one kit supplier in the Southern Hemisphere, a DSE kit is your guarantee of quality and value. Here's why:

- ★ We use only brand new, prime spec components: Beware of other kit suppliers who may use manufacturer's seconds or inferior components —just to save a few cents!
- We guarantee the quality of our kits by including our unique kit quality control card in every kit. In the unlikely event of a problem, we know we can help!
- ★ We build a prototype of EVERY kit: not just where possible, or where we feel like it, but every kit. We find out the problems before they affect you!
- ★ We re-write the instructions in clear, easy-to-understand terms: and every kit includes our exclusive "Guide to Kit Construction". Building a Dick Smith Kit is a breeze compared to other kits!
- We hold spare parts for all current kits: even the difficult and hard-to-get parts are held as spares. If you need a spare part, any DSE store will be able to get it for you: fast!

- We take the hard part out of building kits: most constructors have difficulty with slots, holes and panels. So we do them for you on most kits. And on complex kits our pc boards are solder masked to help you get your kit going: first time!
- We have the exclusive "Sorry Dick, it Doesn't Work"
 service available on complex kits. If you get into trouble, we can
 get you out of it for a fixed service fee, which you know before you
 start building the kit!
- We have the exclusive "Too Hard for Me, Dick" service: if you think a kit is too hard for you to build, you can return before you start construction (ie before any inner packs are opened) for a full refund of purchase price!
- We take pride in our kit range: it's not only the largest range, it's the best range: a kit for everyone from the absolute beginner to the highly experienced. And it's constantly being upgraded as new kits come out in the magazines. Don't settle for second best Dick Smith Kits are the ones to build!

DICK SMITH NO. 1 IN KITS FOR MORE THAN 20 YEARS



DO IT YOURSELF. . . AND SAVE!

It's true! Building a Dick Smith Kit will save you money!

When you buy a piece of commercial equipment, you're paying for someone else's time to put it together. When you build a Dick Smith Kit, you supply the labour — so you save!

But you save even more: you'll find that the cost of the individual components in the kit is more than the cost of the kit (that's if you could buy many of the specialised components often in today's kits!).

However, no-one builds a kit just to save money: you build it for the satisfaction. You build it because it teaches you electronics skills. You build it because it's something that's not easily affordable. Or you build it for a dozen other reasons!

But Dick Smith Kits gives you the opportunity to. . .

DO IT YOURSELF

The FunWay Into Electronics... value plus gift packs!

FunWay 1, 2 & 3 Giff Box Sensational value: contains

two projects selected from each of the three popular FunWay kits... Over \$120 value for only \$85! This is one of the most inexpensive ways to

learn about electronics... ideal gift for children because it entertains and educates. The pack contains all three books and a selection of the most popular and stimulating projects from each. Build a Flashing Brooch, Wireless Microphone, Cricket and Mini Amplifier plus much more! Cat K-2680

\$85


Shipping Weight: 1.5kg Shipping Size: 430 imes 295 imes 50mm

FunWay Jumbo Giff Box

Here's even bigger value! This pack isn't called the Jumbo pack for nothing; it's chockabloc with over 30 projects and a quality soldering iron to

build them all. Almost \$180 value at a price most parents can afford... and what price can you place on your children's future... this may be the best gift a parent can give. Cat K-2690

Shipping Weight: 2.5kg Shipping Size: $430 \times 295 \times 40$ mm \$149



To build these projects you

FunWay One Project Kit

Enables you to build any of the first ten projects in FunWay One. And because the components are not soldered, they are all reusable so you can build any other of the first ten projects, too.



glows if the circuit is

Continuity

Indicator

complete.

Just like a multimeter - it will

complete circuit or an open circuit. A light emitting diode

show you if you have a

2. Transistor Tester As well as telling you if your transistor is okay, it shows



3. Water Indicator

Do your plants need a drink? This simple circuit will tell you how much water is in the soil!

4. A Light/Dark Indicator Using a light dependent resistor, it will light a LED if light falls on it. The type of detector used in some alarms.

Want to add flashing lights to a model train layout? This project will do it for you!



6. An Electronic Siren

A mini version of the siren on Police cars! Fantastic to add to toys!

7. Dog and Cat Communicator

Dogs and Cats can hear sounds we can't! You could be able to talk to your pup in secret sounds!

8. A Decision Maker

As used by top executives and politicians! Just press the button and it will decide for you: Yes or No!

9. Morse Code

Communicator Amateur Radio operators send Morse code all over the world. You can learn the code too (or send secret messages!)!



10. Music Maker

Your own electronic organ And it really will play simple



components are connected by screwing them into our unique 'breadboard' system with cut-out plans showing where the components actually fit.

And even more: you'll learn what each circuit symbol looks like as you use it! Cat B-2600

FunWay 1: The ideal introduction for beginners from 6 to

Where it all began! The best selling manual now

used as an introductory textbook in countless schools, colleges, youth groups, etc etc around the

FunWay 1 assumes you know absolutely nothing! It

connect them into the circuit, even how to go on

For complete safety, no soldering is required. All

will show you what the components look like, how to

with further experiments with your circuit when they



All the components AND FunWay 1 Book in a great pack - everything needed to build any of the projects in FunWay 1! PLUS our specially manufactured re-usable plastic 'breadboard' - a great way to build not only the FunWay 1 kits, but also to 'mock-up' other circuits as you become more advanced.

AND EVEN MORE! Everything is housed in a multidivision plastic tray, which is fantastic for housing components in, both now and in the future.

The FunWay 1 Gift Box makes an ideal birthday or Christmas present... and who knows: it could be the start of an absorbing lifetime hobby in electronics, or even an exciting career! Cat K-2605

1 battery clip

hook-up wire

• the re-usable plastic

copy of FunWay Into

Electronics, Volume 1

Batteries, morse keys,

etc. not included.

parts tray PLUS a

baseboard

Here's what you get:

- 24 resistors
- 18 capacitors
- (including a variable type) screws & washers
- 2 transistors
- 1 integrated circuit
- 2 LEDs
- light dependent resistor
- 1 diode
- potentiometer speaker
- ferrite rod aerial
- 1 crystal earphone
- 1 audio transformer

Parents Note: FunWay projects have been designed to be completely safe for even the youngest constructor. They are all battery operated and use no dangerous voltages



To build these projects you

FunWay One Project Kit 11-20

Contains the more specialised components required to complete the last ten projects (11-20) in FunWay 1. Note: you will also need the 1-10 kit above to build these projects. Cat K-2610



11. Sound Effects Generator

Ever wondered how many of these sound effects are made in the movies? Build this and you can make some of your



12. A Crystal Set

Free radio - no batteries to buy, nothing to turn off! Listen in to your favourite station!

13. One Transistor Amplifier

Build your own amplifier: it can bu used with the crystal set and other projects if you

14. Beer Powered Radio

Yes, it actually runs on beer (or Coke!)! Listen in (as long as you don't drink the battery!)!




15. Two Transistor Amplifie

Even more power — enough to drive a speaker so you can listen in without headphones.

16. The World's Simplest Transmitter

Just like the young Marconi, you can transmit Morse Code across the room!





18. CB Radio Receiver

Listen in to the truckies and other CBers. And you don't have to spend \$\$\$ on a CB!

19. Amateur Radio Receiver A radio receiver to listen in to ham operators plus other stations in the 2-6MHz bands.

20. Radio Booster Amplifier A radio frequency amplifier to give other radios even better











You've built all the projects in FunWay 1 — and looking for something new. Something bigger. Something better. Something more exciting...

Here it is: FunWay 2! It takes over where FunWay 1 finishes, with 20 exciting new projects to try out.

But these projects are different! They're all built the modern way — on printed circuit boards. Which means, of course, all components are soldered into position.

Don't know how to solder, or use printed circuit boards? No worries, FunWay 2 teaches you how. You'll find out how to get a good solder joint, and how to avoid the pitfalls.

and the projects themselves have all been specially chosen to be 'useful'. Just look at the project on the right and you'll agree! They're all battery operated, so there's no danger either!

Also the projects themselves have all been specially chosen to be 'useful'. Just look at the project on the right and you'll agree! They're all battery operated, so there's no danger either!

Also includes features on pioneers of electronics, plus 'how to use a multimeter'.

PLUS! Specially printed labels to make your circuits look really professional! Great for school projects, too! Cat B-2605







GIFT PACK

Here's a gift bargain for the budding electronics genius: our FunWay 2 Gift Pack. Specially selected for value, it includes all the beginner needs to build a kit!

- Here's what you get:
 A copy of FunWay, Volume 2
 A top quality DSE soldering
- iron worth over twenty dollars on its own!
- A pack of solder
- A fresh 9 volt battery

\$**30**95



PLUS! A Wireless Microphone Kit: by far our most popular FunWay kit! It can be used as a microphone or even a secret "bug"!

FunWay 2 Gift Pack: the gift that keeps on giving Cat K-2620

Shipping Weight: 700g Shipping Size: $380 \times 220 \times 50$ mm

FunWay 2 Kits!

There's something here for everyone! Sage — simple — economical — fun! Each kit contains brand new, guaranteed components.

Make it as the latest in electronic jewellry, or a burglar warning light, etc. The choice is yours and it's easy! Cat K-2621



2. Ding Dong Doorbell

Yes, it actually sounds like a great old fashioned doorbell. But it's electronic: and you can build it! Cat K-2622

3. Morse Code Trainer

You can turn this audible alarm into just about anything requiring sound. Even for Morse code — and it's fun to learn! Cat K-2623

\$4 295

Universal Time

Eggs too hard? Time them with this little timer. It really works - set it for a few seconds to 15 minutes!



9. Mosquito Repeller Do mozzie repellers really work? Build this one and find out. Based on university research, intriguing! You won't hear it — but the mozzies will! Cat K-2629

\$795

10. Intercom Amplifier Use to make the intercom

(Project 18) or use as a general purpose amplifier. Really handy, good sound output too! Cat K-2630

\$795

11. Wireless Microphone

Just like the 'bugs' used in spy movies! Transmits to any standard FM radio in another room or next door, etc. You can really hear it all! Cat K-2631

12. Light Activated Switch Useful in many security

applications around the home etc. if a light goes on, the

switch works. You could even

use it to trigger a burglar alarm. Cat K-2632

13. Metal/Pipe Locator

before drilling holes.

Extremely handy for locating pipes, wires, etc. in walls

Surprisingly effective for such a simple circuit. Cat K-2633

\$795

6. Mini Organ

Snazzy little circuit uses the back of the PCB as the easy! Cat K-2626

Just as much fun using it as it is building it! And it is really random — no cheating with

this dice! Cat K-2625

7. Pocket Transistor Radio Building this small set will

teach you a lot about the fundamentals of radio. And then you'll have fun using it too! Cat K-2627

\$4295

8. Touch Switch 14. Sound Activated

Ever wondered how those lift buttons worked? Build this touch switch yourself and you'll be able to work it out. Variety of functions explained. Cat K-2628



Switch

Very practical! You could use this alarm to protect your home and property! Uses any of the normal alarm triggering devices. Cat K-2635

Picks up sound and triggers. Use as a telephone bell

extender without breaking Telecom regulations or in

security applications. Cat K-2634

\$4295

16. Electronic Siren

Just what you need with the alarm! Also makes a great sound effects circuit — and FunWay 2 tells you what to do! Cat K-2636



17. LED Level Display

Hook it up to your stero and i can warn you of dangerous overloads. Looks pretty nitty too - the LEDs light up in time to the music! Cat K-2637



18. Intercom Unit

Build your own intercom and use it around the home. Practical, simple to build with the intercom amplifier (Project 10). Cat K-2638

19. LED Counter Module
A perfect introduction to the world of integrated circuits. And this useful counter can be used for a huge variety of counting applications -just for fun! Cat K-2639

20. Shortwave Receiver You will be able to tune a


variety of shortwave stations or, with simple modifications, emergency services and amateurs, etc. Easy and fun to build. Cat K-2640



Please note:

The kits do NOT include instructions. All information is published in FunWay Volume 2, which is necessary before construction can begin on any

NOTE: Cases show are not included in basic kits.



FunWay 3 Kits!

Here are the exciting FunWay 3 projects, each of them fully explained in FunWay into Electronics, Volume 3. You can't go wrong because all the instructions are right the instructions are right there in the book — along with useful tips on how to really make your projects look snazzy with the labels supplied in the book, how to fit these into zippy boxes.. Your projects will be real



3. Cricket

Here's a ton of fun! Hide the cricket: when the lights go out it starts chirping. Turn the lights on or make a noise and it stops. Makes it so hard to find!!! It really is infuriating! Cat K-2663



6. Mini Colour Organ

Your very own disco colour organ — but ours is battery operated — so it's much safer than mains devices! Connect it to your radio, cassette or stereo for a real lightshow!

\$**13**95



9. Binary Bingo A great school project: it's a fun game — but even more it demonstates binary numbers very well. And they're the basis of all computers! It seems pretty simple to play... but try it! Cat K-2668



other two books.

But the projects are just as fascinating to build, so they're still FUN! Have a look at the projects at right, and you'll see that there really is a great range something for everyone!

Another 100 pages of fun: that's FunWay Volume 3.

It's the logical progression for those who have

book, but many of the projects can be built in a number for forms — so there are virtually as many 'individual' projects in FunWay 3 as there are in the

And because the FunWay 3 projects are more complex, they are dealt with in rather more detail. More explanation, more construction details - so

you learn much more with FunWay 3.

worked through FunWay 1 and 2. It's for the more advanced hobbyist, because FunWay Volume 3 projects are all based on Integrated Circuits. There are ten projects in the

And they're even more fun to play with when they're built. Like FunWay Two, FunWay Three includes deluxe projects labels printed on specially coated paper in the back of the book. Use these with Zippy Boxes, and your project looks a million dollars! Cat B-2610



Light and Sound

What versatility! It's really 6 projects in one: you just build the form you want — a LED flasher, a mini strobe flasher, police siren, motor boat sound effects, continuity tester and Morse Code practice oscillator. Cat K-2665



4. Mini Stereo Amp

Want an amplifier for the 'walkie' stereo or radio? Don't be tied to 'phones: use this project and listen in comfort! Or you can build this into a mini PA amplifier. Cat K-2667



Lock Switch

You can make a game make a real electronic 'lock' with this one. Use it to control an alarm, a door control, etc. You set the combination you want — or change it when you wish. Try and beat this one — if you can! Cat K-2666



real 'live' musical synthesiser
— and it's live because it uses YOU as the note generator! You get an amazing range of control over the sound. Cat K-2669

\$4995



2. Two Up

Australia's 'national game' has finally been converted to electronics. And you don't have to find any King George pennies! Simulates the throw, the spin and the final result. Come in spinner! Cat K-2661



C'mon Guvnor — leave the auto alone. That's the FunWay 3 Minder telling villains that it is looking after the car! It's actually doing much more makes a great 'lights on' warning and 'door open' warning as well as a pseudo burglar alarm. Cat K-2660

\$995



8. Lil Pokey

You'll have a ball with this one and you don't risk losing a single cent! A digital project which not only shows how the one armed bandit works - it teaches you how logic circuits work, too. Cat K-2662



And when you've finished FunWay 3???

You're ready to build just about any of the kits from the Dick Smith range — and that's a lot of kits to choose

You'll be able to solder properly, identify all components, read circuit diagrams, even use test equipment!

You could even be ready for career in electronics! And it all starts with Dick Smith's FunWay into Electronics.



popular kits in the FunWay Three book... and we throw the book in FREE! Yes, you get the Electronic Cricket project (known to his fiends as Nocturnalis Stridulus Grilledae) plus the Miniature Amplifier projects — together valued at \$31.60 — and as a bonus, the FunWay Three book itself at no extra

Fantastic gift idea... also makes ideal school project material. And this book gives details on how to really dress up your kits for top presentation... and

Whether you want ot learn more about electronics, or just have fun building interesting circuits, you won't do better than with FunWay into Electronics. And the FunWay 3, you really move up into the

electronics 'big time'. This fantastic bonus pack will get you started. Cat K-2670





Full command over your hi-fi system Without moving from your chair! The IR Remote Preamp comprises a complete preamp in which all functions can be selected by infrared remote control. And it's loaded with features! Plug it into your existing system via the tape

monitor loop or use it with a power amp in a new system.

An incredible array of LEDs give you a constant status report on the entire system. The bargraph volume display automatically indicates bass, treble, balance (up/down) while these functions are being set — it then returns to the volume mode. All panel controls on the amp are pushbutton and the IR controller has 21 chrome plated buttons to select all the available functions. Sit back! Relax! Let your fingers do the working!

• 1V output suits most amplifiers. • 6 metre IR control range. • 8 pairs of RCA sockets for source connection. • 3-pin mains socket for powering an accomp. amp. • Functional design (353 x 231 x 63mm) amp. • Compact IR controller (136 x 70 x 27mm). • Phono, tuner, CD, Auxiliary and tape monitor outputs. • Source selection LEDs. • Status LEDs. Gat K-4003

Shipping weight: 3.35kg Shipping size: $400 \times 260 \times 90$ mm

Wanda And Woam Wiv A... Walkabout Wadio



This portable radio kit puts the life back into AM reception! Using a cunning TRF circuitry system the original audio bandwidth transmitted by the station is largely maintained — AM comes alive! The project is inexpensive, uses a minimum of components and it's easy to build. Circuit provides an RF amplifier which delivers up to 120mV into 64 omhs to drive a pair of 32 omh headphones. As a result the circuit draws less than 3mA - so the 1.5V AA power source is likely to last up to twelve months. It's increwible value. Weally!! Cat K-2720

Shipping Weight: 280g Shipping Size: 63 × 132 × 185mm

As described in ETI

Stereo Control Unit


Use it as a stand alone Stereo Control Unit/Preamp, match it up to your existing power amp or one of our kits (K-3440/2). Either way you get a high quality stereo control unit at a fraction of commercial prices. The kit can easily be constructed by a novice and features the full range of controls, inputs and outputs! Cat K-3045

Specifications: Rated Output: 1V RMS into 10k ohm Sensitivity @ 1kHz — Phono: 3.2mV RMS Line: 178mV RMS Phono Overload: 133mV RMS

Tone Controls Bass: 60Hz ±12dB Treble: 15kHz ±13dB Stereo Separation -Line: -70dB Phono: -68dB S/S&N @ 1kHz flat -



Phono: -75dB ref. at 10mV RMS input Line: -80dB ref. to 200mV RMS input **Frequency Response** Line Inputs: 20Hz: -2.5dB 20kHz: -0.5dB Phono Preamp: RIAA/IEC equalisation within ±2dB (30Hz -15kHz)



Graphic Equaliser


Get total control and flexibility with your sound system. With cut and boost of up to 13dB per channel you can make up for deficiences in your listening area or sound source and even create special effects. (Big, booming bass: bewdy!) You can even make equalised tapes of those precious records. Features professional quality brushed aluminium front panel. Cat K-3500

Specifications:

Boost and cut: max. 13dB Steps: 10 in each stereo channel (individually controllable). Freq. response (Eq 'IN'): 10Hz to 10kHz

±0.25db (-1db @ 20kHz) Shipping Weight: 6kg Shipping Size: $400 \times 265 \times 90$ mm

As described in EA



Power Up Your Walkie! Walkman Amplifier



The problem with trying to share your Walkie music is that you've got to dance cheek to cheek — that's alright sometimes, but it could give people the wrong impression!

With the Walkman Amplifier Kit all the gang can listen to your Walkie WITHOUT losing its portability. What's more, it's incredibly easy to build and you can have it up and running in a couple of hours. It's powered by an internal battery or a 12V DC plug pack. Cat K-2722 Mini short form kit, PCB and instruction only.

signal amplitude measured at 80dB on another channel

It also has the popular

components and a

printed circuit board

alarm applications.

Cat K-3512

complete with kit. It is intended for novelty or

Shipping Weight: 130g

'ding dong' plus an alarm tone. A few more

Specifications:

Test Conditions: 4 ohm load, +12V supply 400mV ptp input at 1kHz

Frequency Response (-3dB point): 40Hz to above 100kHz Sensitivity: about 0.6V
Total Distortion: between 0.1 & 0.3%

Output Power (rms): 0.8W per channel Cross-talk: 400mV at 1kHz injected in one channel with

(Short Form Kit Only)

PICK MICH

Shipping Weight: 50g

Melody Door Be

Music Generator Your standard door bell? Booorrr — Rrrring! Here's the kit that even a beginner can have This is a great little kit for the beginner or the experimenter. It uses a very special IC which is pre-programmed to play two tunes.

working in no-time! You can select between three instruments, any one of 16 melodies or a different melody each time. Imagine greeting the pest exterminator with 'Eency Weency Spider' or the butcher with 'Mary had a little lamb' or the shrink with 'Coo Coo Waltz'! Selection is easy, it's housed in a neat $50 \times 90 \times 150$ mm zippy box and the (2 × AA) batteries last 6 months or more! Cat K-2726



Wireless Stereo Headphone Link



Cat K-4006

There's nothing better than listening to your favourite music through headphones. can have it as loud or soft as you like and there's no extraneous noise to interrupt. But then, there's always the cable! Too short? — You make it longer, no worries. No matter what you do with it though, somehow, someone will always trip over it. And you can be sure, there's nothing so painful as having your ears ripped off by a pair of tripped over

The DSE Stereo Infrared Headphone Transmitter/Receiver allows you to enjoy high quality sound reproduction on your headphones without messy cables! It solves the cable problem, allows you to listen to your favourite program while the rest of the family listens to theirs and it's ideal for anyone who's hard of hearing!

Both the Transmitter and Receiver are packaged in compact cases, so they're not going to clutter up the table, television or benchtop. Range is sufficient for a greater than average size room. Simply plug them in and point them towards one another — it's that easy! In a small room it will even work with reflections off the walls.

Volume control on both transmitter and receiver Compact case — 68 × 136 × 26mm (Both)
 Screened aluminium front panel Great range
 Suits 32-100 ohm headphones or

high efficiency speakers

Transmitter power — 12V plug pack
Receiver power — 9V battery

FM stereo transmission

each

As described in EA



page 10

VIDEO/AUDIO

20W Module

players, musical instruments, sound projectors, etc. A handy device for any hobbyist to add to his work bench. Uses discrete transistors for reliability which provide the ideal opportunity for the hobbyists to gain an understanding of how an audio amp works Cat K-3445

Supply voltage (power output): 35V (19W), 30V Shipping Weight: 1150g Pack Size: 100 × 175mm (12W), 20V (6.6W)

lodule

Incredible reliable — yet very simple to build. The complete amplifier on one pcb — all you do is add a heatsink, connect to power... and go! Perfect for band use, PA, even as half a stereo pair (performance is that good!). Heatsink brackets included ready to bolt onto suitable main heatsink. Cat K-3440

Cat No. 3440 Supply Voltage: 33V @ 1.2A Response: 5Hz to 50kHz (+0, -3dB) Noise Level: -100dB Sensitivity: 50mV



As above, but double the output. Use two for stereo, or even use in bridge for double output! (Get up to a massive 200W output!) Specifications similar to above except for power (100W into 4 ohms) sensivity (1V) and supply. (40-0-40V @ 2.4A). Cat K-3442

Shipping Weight: 207g

Power Supply above modules

The electronics to suit either two 50 watt modules or one 100 watt module, including speaker de-thump circuitry but **not** including transformer. Choose the transformer according to the number of modules and power output required. Cat K-3438

Shipping Weight: 173g Shipping Size: 160 × 90 × 30mm



Incredibly Easy To Build! Bookshelf Speakers

A low cost, compact loudspeaker system that's not only a cinch to build but performs like speakers that cost \$\$\$ more!

The kit uses the Magnavox 6MV nominal 15cm driver, is suitable matched with the Magnavox 3AC tweeter and designed with the universally highly-regarded Theile/Small parameters. With a second-order crossover network for both bass and tweeter and an enclosure volume of 16.7 litres: The result — superb performance!

Designed so that anyone, even with little or no woodworking experience, can end up with a professional looking speaker system finished in simulated woodgrain to match most modern furnishings. What's more, they sound even better than they look!

Woofer -

Size: 15cm with 38mm voice coil. Free air resonance: 47Hz Volume: 19.3 litres

Qts: 0.36

Size: 81mm closed back construction Frequency response: Beyond 18kHz

Roll Off: 12dB/octave Elliptical Filter Resonance Notch: 1.3kHz Approx.

Complete System -

Frequency Response: 50Hz - 18KHz
Power Handling: Nominal 40 Watts. Will comfortably

handle full power 100W per channel amplifier on normal program material. Cat K-4000

\$249



For The First Time In Years — The Project You've Been Asking For...

A Low Cost Stereo \$4995 Amplifier

These days everything's getting more sophisticated and more EXPENSIVEI Time and time again YOU'VE asked for it — "a low cost amp that provides reasonable power, good performance but doesn't have all the bells and whistles that command a high price.

A great little stereo amplifier that can be readily constructed by anyone with a modicum of experience building electronic projects. The Stereo 2000 amplifier delivers creditable performance and offers all the facilities required of any stereo amplifier used as the heart of a stereo system — and it does it at a remarkably LOW price!

Designed with the experimenter/hobbyist in mind, every opportunity has been taken to produce a kit with the greatest versatility and minimum price. You can mount it in your own case or our optional, superbly engineered steel case (Cat H-2900) which is tailored especially for this amp. We figured you'd have a suitable transformer floating around in your junk box so you'd save a few bucks there as well. However if you don't, our M-6672 is just right for the job.

Whichever way you look at it, the Stereo 2000 Amp is just what you've been looking for!



Performance:

Continuous Output Power (RMS) — One Channel: 11.8W Both Channels: 8.8W

Harmonic Distortion: <0.05% Frequency Response — Phono Input: RIAA/IEC equalisation within ±2dB (30Hz to 15kHz) Line Level Inputs: -2dB @ 20Hz & 20kHz

Input Sensitivity (10W RMS 1kHz) -Phono 3.8mV

Overload Point (at 1kHz) 140mV Line Inputs 200mV

Hum and Noise - Phono: -73dB Line Inputs: -81dB

Tone Controls ±12dB at 60Hz ±12dB at 15kHz

SHORT FORM KIT

Includes PCB, all components but no case or transformer.

Features:

Phono, Tuner, CD, Tape and Aux Inputs

Stereo/Mono, Source/Tape selection Compact Design — Everything on one PCB (including push-button switches inputs and outputs)

- Detent Type volume control
 Centre position detent on bass, treble & balance
- Includes professionally finished, silk screened and pre-punched front panel.
- Easy construction!

10-150 watt Speaker **Protection Relay**

The do-it-yourself speaker protection kit! A universal amplifier monitor/speaker protection device which can be used as a stand alone system with its own power supply or can be powered from the amplifier's own power supply.

The system has a delay to eliminate 'thumping' with power-up, detects DC offset levels from output stage, features hold-off delay after fault detection, can be used as a clipping detector, can be preset to indicate when maximum power level is reached and more!

Performance:

Minimum offset detection voltage: 0.775V
 Detection delay (± 1V in): 500mS (± 10V in): 60mS

 Tripping frequency (8 ohm load) — below 1WRMS: 3.5Hz - 6.25WRMS: 5Hz

-50WRMS: 10Hz -225WRMS: 15Hz

• Initial turn-off delay: 3.5sec

 Minimum input comparison voltage • (equivalent 10WRMS into 8 ohms): ± 13V

Cat K-4008



TELEVISION/VIDEO/AUDIO

Teletext Decoder

 bringing you the latest in technology at a fraction of the normal cost. Teletext — that mine of information given out free by a lot of TV stations — hasn't really taken off in Oz: mainly because of the cost of Teletext Televisions (most are around or over the big \$1000 mark!) It's a pity, really because there is so much information available — and the system will expand greatly when there is more acceptance. Teletext information is transmitted during the otherwise 'useless' period between each TV frame (the black line you see with colours flickering if the vertical hold is out!) All you need is this

adaptor to pluck out the information, and hold it for display on the TV screen. You can have Teletext only, or a mix of Teletext and picture, or even news flashes and, perhaps most important of all, captions for the deaf on many programs. We've kept the price way, way down by designing this Teletext converter to be used in conjunction with a VCR (or the TV tuner above!). Check with your local TV station(s) to ensure Teletext or captions are being transmitted before commencing construction! Cat K-6315



As described in EA

Shipping weight: 3.7kg Shipping size: 400 x 265 x 95mm

Poor TV signal area? Build the

TV Masthead Amp (Mk2)



Don't put up with lousy TV (we can't do much about the content, but this should fix the pix!) Reduces or even eliminates snow and compensates for cable loss. Cannot be used in strong singal areas to amplify distant weak signals. Covers both UHF and VHF TV bands plus FM radio bands. Includes 240V supply in price Cat K-3232

Shipping Weight: 1kg Shipping Size: 270 \times 165 \times 95mm


AM Stereo Decoder

There's no need to buy a new receiver to enjoy stereo sound. DSE's AM Stereo Decoder Kit can be built right into many tuners for full stereo output. And you build it yourself and save \$\$\$! Features Motorola MC 18020P integrated circuit. Provides excellent stereo by taking the AM IF amp output. decoding the C-QUAM signal and providing leftright channel audio outputs. Cat K-3415

Best results are obtained using synthesized

Shipping Weight: 3.6kg Shipping Size: $400 \times 260 \times 125$ mm

As described in FA





Stereo Simulator

Wish those old video movies had modern stereo sound? This lowcost gadget turns almost any mono signal into amazingly good synthetic stereo! Cat K-3421

Shipping Weight: 525g Shipping Size: 185 × 135 × 75mm



With this great little kit you car sound like a Dalek, Darth Varder, a Cylon, or any one of a dozen rabotic spin-offs! A versatile unit. it may also be used for special effects on electric guitars and other musical equipment.

Shipping Weight: 275g Shipping Size: 185 × 135 × 65mm



Video Enhancer

If the sound of your VCR is crook what about the video! Especially when you're making copies of tapes (yes, the ones you shot yourself of course). Make sure you don't lose detail when dubbing: use the EA video enhancer. Very simple to use: all control is via one knob. And unlike most enhancers, you can cut as well as boost (ideal for softening harsh pictures). Cat K-3463

 240 volt operated Shipping Weight: 900g As described in EA

UHF to VHF Converte

The old set still has a great picture, it seems like such a waste of money to throw it out just for the sake of one station. Now, there's no need!

With the UHF Converter you can get UHF channels 28 to 63 (That means SBS) on your old set! What's more, the circuit goes together easily and there's no need for any alignment or adjustments — all you do is put it together and plug it in!

After investigating the possibilities we found the most practical and economic way to convert to UHF was to use a standard UHF tuner module which has been modified to have its output at one end of the low VHF intermediate frequency of 36.87MHz - so that's just what we did!

What we got, was an easy to build, low cost converter that saves heaps on new television prices, performs admirably and is housed in a compact 93mm × 40mm × 25mm all steel case. What you get — is a huge saving! Cat K-3236

As described in AEM.



Mixer/Preamp Module

Perfect for band use — or any general purpose mixing application. 4 inputs allow virtually unlimited choices: guitar, mic, organ, line, inputs, etc. with each input fully adjustable for gain

and impedance. Also includes bass, treble and "presence" control. Drives any of above amplifier modules directly, and uses same power supply.

Shipping Weight: 175g Package Size: 100 × 175mm

LED Level Meter and show that (instructions show how). Or you can build a pair and have a true stereo level meter. CALL CONTRACTOR

Here's the one the beginner can build - and add to a mono or stereo amplifier to give a level meter just like those found on \$\$\$ imported amplifiers! You can build one and use it to show either a mono amp, one channel of a stereo amp or sum the channel outputs

> Has 10 green LEDs for display, two red LEDs for maximum power indication. PCB is designed to-have readout at right angles for easy mounting.

Requires 10-16V at around 50mA (usually taken direct from preamp supply). Cat K-3370

Shipping weight: 75g Package size: 100 x 75mm

As described in EA.

Stereo Preamp



The amazingly versatile unit can be built as a magnetic cartridge preamp (for upgrading your stereo), a tape preamp or an auxiliary preamp with 40, 55 or 80dB gain. It is extremely simple: uses only one special IC and is very small, all parts fit on a PCB less than 65mm square. It does not need a special power supply as any reasonable power supply from 10 to 40V will do. Frequency response is well beyond 20kHz. Full instructions are supplied. Cat K-3427

Shipping Weight: 50g Package Size: $140 \times 100 \times 20 \text{mm}$

As described in ETI.

SECURITY/CAR PRODUCTS

Save by installing your own alarm... Save even more: **Build Your Own Alarm!**

At least the equivalent of commercial units costing \$\$\$\$ more! All the features you need for complete protection — perfect for home, office, factory, etc. Cat K-3424


- 6 instant & 2 delayed sectors
- Security key operation
 Inbuilt mains supply & battery back-up
- · Siren driver, relay (bell) output
- And much more!

Complete kit including case and all electronics: Shipping weight: 3.85kg

Carton size: 320 x 185 x 235mm

Back-up battery to suit: 12V 1 2Ah Gell Cell Cat S-3315

As described in FA



Alarm Sensors

All DSE kit alarms work with standard security sensors (reed switches, passive I/R, pressure mats, etc. etc).

Very latest IC technology **Optical Motion** Detector

Use as part of an alarm — or as a door minder etc. A special optical IC actually detects movement by change in light level. Two modes — "guard" for sensing movement, and "search" for beam cutting operation. Self contained (battery operated). Cat K-2721

As described in FA



4 Sector Home Alarm

A "bare bones" alarm controller without the frills and with a really low price tag. The perfect alarm for anyone wanting to "build it in". 4 sectors means a complete home or office system can be built around it. Ready to assemble, complete with on-board pcb connectors. Requires 12V DC @ 500mA. Cat K-3254

Shipping weight: 220g Carton size: 173 x 65 x 102mm

As described in ETI

Transistor Assisted Ignition

Electronics Australia's high energy version of their previously incredibly popular kit. Now gives even better performance than before with circuit mods enabling high efficiency and stability, plus spe al radial fin design heatsink and die-cast box to dissipate unwanted heat. Ideal for use in all conventional ignition vehicles (doesn't work too well on diesels!) Cat K-3301

- Eliminates 'crossfire' problems on older 'CDI' circuits
- Dwell extension gives longer, hotter spark Compatible with modern
- electronic tachos.


Ignition Killer

As described in EA

Nothing's more frustrating than a car that doesn't go. And imagine how much more frustrating a thief finds it! This ingenious circuit makes the ignition mis-behave theory is the thief will pinch someone else's car instead! Cat K-3255

Shipping weight: 320g Carton size: 185 x 63 x 132mm

As described in EA



Car Alarm UHF Remote Switch

The do-it-vourself way to car alarm convenience. A remote switch for your existing car alarm. Cumbersome keys are now a thing of the past with this easy to build kit idea.

The kit consists of a 304MHz receiver, decoder IC and output relay on a single PCB which is installed in a compact aluminium

The receiver in the DSE kit is small enough to fit on your keyring yet (unlike some other kits available) large enough to accomodate all the components easily. After installation you can remotely switch your existing car alarm from distances up to 40 metres. Kit options include momentary flasher indicator and peizo alarm or siren capability for alarm set, Cat K-3256

Deluxe Car Alarm

Superb protection for your car. One of the best alarms around -- even better than most commercial units. Build this and your car shouldn't join the 70,000 or so stolen each year! Cat K-3252

- Delayed and instant alarm inputs
- Provision for back-up battery
- Siren output (doesn't rely on vehicle horn)

Shipping weight: 2kg Carton size: 225 x 200 x 225mm

As described in EA

		•		
: 0				
• = -	THE OPERATED ON OUR WAITE OF	CAR BURGLAR ALARM		
	AUTHOR BATTERS	CAR BURGLAR ALARM		
: 4				
	VERN LE RATTERS	and the second		
- 1	HONE TO A THE INSTANT	vi/m ()		
18.41	Bolton Company and INPUTS	11 HOREN		
•	MONTH OF THE THE INPUTS			
	•			

Car Alarm Mk II

An economy alarm for your car — with all the right features! Specially developed to minimise false triggering — but highly sensitive to any electrical use within vehicle (starter, brakes, internal lights, etc). Housed in a virtually waterproof die-cast box to minimise ingress of fumes, moisture, etc, with terminal block for easy connection to vehicle. Cat K-3253

Shipping weight: 650g Carton size: 185 x 63 x 132mm


\$2995



Budget Car Alarm

Low cost protection — that works! Stripped to the "bare bones" this single pcb alarm senses voltage drop in your car's electrical system, hide it virtually anywhere you like — it's easy to install and even has a visual warning for thieves. Cat K-3250

Shipping weight: 75g



LED Tacho

Don't spend a fortune buying a tachometer - build your own and save! Displays engine speed in an analogue form in an illuminated row of LED's. Instructions included a great kit! Cat K-3240

Shipping weight: 160g Carton size: 178 x 105 x 60mm

Bike Anti-Swipe

An effective Motorcycle Alarm designed for maximum security at a reasonable price!

Easy to build and install — even if you don't know much about electronics! Features LED alarm indicator, auto reset and provision for external sensor switches. Connect it to your existing horn or to a siren. Suits all 12V systems can be engaged by toggle or keyswitch and it's mounted in a compact Zippy Box. Cat K-3249



Amateur Transceiver

Not only do you build it yourself and \$ave, you build it yourself and LEARN! How long has it been since you built a good piece of home brew? How many of those forgotten skills soldering, component identification, alignment and so on need sharpening? Build this HF transceiver! It will give you any 500kHz segment between 2 and 30MHz — with commercial quality specs to boot! Everything is included — case, silk-screened panel, all components, even a microphone — PLUS our special step-by-step instruction manual to make it just that much easier. Cat K-6330

Specifications:

Frequency: Any 500kHz segment between 2 and 30MHz (See below)
(80 metre module supplied with kit) Modes: LSB, USB, CW Supply: 13.8V DC, 4.5A max on transmit Bandwidth: ±8kHz (-25dB) Sensitivity: 0.3uV (10dB S+N/N)
Selectivity: 6dB @ 4kHz, 60dB @ 7kHz
Image rejection: better than 50dB Power Output: 30W PEP, 15W CW Harmonic suppression: better than 60dB Transceiver Size: 175 × 210 × 55mm Shipping Weight: 2.05kg

Carton Size: 213 × 295 × 96mm **UPGRADE KITS:**

Fit the upgrade kit you want to get the band you want! Each kit handles a 500kHz segment, more than covering the amateur bands with the exception of 10 metres (bottom 500kHz segment covered)

40 metres: Cat K-6332 **15 metres:** Cat K-6334 **20 metres:** Cat K-6333 **10 metres:** Cat K-6337

All one price

described in FA

100W HF Linear **Amplifier**

Designed for the HF Transceiver (above) but also perfect for use with a huge range of QRP commercial gear, in the range of 3 to 15 watts output. Based on 2SC2290 RF power transistors, it gives around 10 to 14dB gain so up to 100W output could be obtained from a very modest input. The circuit is wide band and has only 3dB drop-off at 28MHz. A switchable low-pass filter is included. Includes carrier-operated Rx/Tx switching. Cat K-6331

Specifications:

Frequency: All amateur bands from 2-30MHz Output Power: 100W, (CW & AM), 150W PEP (SSB) Input Power: 5W max (CW), 10-15W PEP max (SSB) Supply: 13.8V DC 3rd Order IMD: < -0.5dB Shipping Weight: 2kg Carton Size: 225 × 120 × 190mm



As described in FA

Shortwave Antenna

Why spend hundreds of dollars on a good receiver if you are only using a piece of string for an antenna? Get the best reception from your receiver with this high quality short wave antenna. Contains long wire antenna, lead-in, polyrope and egg insulators. Cat K-3490

- Designed especially for DSE by short wave expert
- Complete and ready to assemble Needs no soldering
- Instructions included

Shipping weight: 790g Pack size: 300 × 375 × 30mm



Morse RTTY Decoder

Receiving and decoding Morse and Radioteletype is almost al problem is that it ties-up your computer. At least, up until now it did.

This project is hooked up between the audio output of a receiver and a dot matrix printer, it will decode and print out most Morse or RTTY transmissions without using your computer.

With both narrow and wide filters for RTTY, a time detector/demodulator circuit and a digital section based on the Z80 microprocessor running at 4MHz. The design means, that in the case of RTTY, the original formatting of the transmitted text is preserved. The Morse decoding program self tracks from around 5WPM to more than 40WPM.

Connection to the printer is via DB25 connector (standard IBM printer cable) and power is supplied from a safe extra-low-voltage source. Includes pre-punched and screened case panels! Cat K-6339

As described in AEM.

Shipping Weight: 800g



A Big Sting For Your Six Metre... **100 watt Booster Amp**

How's this? 100 watts from a tiny 6 watts input. The DSE 6M All-Mode Power Amplifier is straightforward to assemble and align, and it's compatible with low power portables to base stations of 10 watts or more output.

DX'ers all know that while you can get away with a modest rig there's just no substitute power! This great kit features carrier operated relay, over-voltage and transient protection, switchable between-syllable delay for SSB, relative output power metering, remote DC output... and more! Cat K-6349

Performance:

Amplification Mode -Continuous Power Output: 120W CW Saturated Power Output: 150W CW

Gain: 12 to 14dB Modes: CW, AM, FM & SSB Input VSWR:1.5: 1 1dB Bandwidth: 50 to 54MHz Harmonics: -63dB (2nd Harmonic) Standby Mode

Input VSWR: 1.1:1 Insertion Loss: 0.2dB

Shipping Weight: 2kg As described in AFM



Nifty 3-Band Shortwave Radio Tunes You Into The World!

It's been a long time since anyone produced anything new in shortwave radio kits — here's one that will get you back to the nitty-gritty of construction techniques.

The Three Band Radio Receiver uses a single AM radio IC and gives you all the benefits of sophisticated design without using lots of components. With automatic gain control over a range of 86dB you'll get a clean signal right next to a transmitter or even thousands of kilometres away. It's ideally suited for mobile use and includes a noise suppression choke to minimise interference from ignition systems and has provision for an optional DX/Local switch. Cat K-6355

Frequency -Band 1: 0.48-1.9MHz Band 2: 2.15-7.7MHz Band 3: 6.12-17.12MHz



VK Powermaster

Huge 25A peak with suitable transformer! That's power... and it's simple to build. For HF gear, linears, and so on, this one has the comph you need. Short-form kit: you choose the transformer you want to suit the output required. Cat K-3448

M-2010 transformer gives 14A continuous M-2000 transformer gives 6A continuous

Shipping Weight depends on transformer Carton Size: 230 × 385 × 160mm

PLUS TRANSFORMER

Pre-punched Aluminium Case

Variable Power Supply: 30V/1A

Ideal for laboratory, amateur/experimenter or technician use. Adjustable up to 30 volts at up to 1A - very handy! Includes full metering and overload protection. Cat K-3475

Shipping weight: 2.3kg Carton size: 213 × 293 × 96 mm





DEGREE OF DIFFICULTY

- * Beginner
- ** Intermediate
- ★★★ Experienced!







DSE Commander: 2m Amateur Transceiver

By far our most popular amateur kit: well over 2000 sold throughout Australia and New Zealand. Far better than buying a ready-built 2m rig: the specs more than match most commercial transceivers costing two, three and more times the price. And it covers the full 144 to 148MHz 2m amateur band, including standard repeater offsets (±600kHz) built in. Again matching the style of our other amateur transceivers, the Commander comes complete with microphone, mobile mounting bracket and full construction manual. Nothing more to buy to get you onto 2m: just connect your antenna and 12V supply. Cat K-6308

Specifications: Frequency: 144-148Mhz in 10kHz steps (5kHz offset) Mode of operation: FM Supply req: 13.8V DC 2.5A (15W output) Receiver: Dual Conversion Superheterodyne

Sensitivity: 0.5uV for 12dB quieting Selectivity: Better than 60dB at ±25kH₂ Power output: 10W nom, 15W max Complete with full repeater capability ($\pm 600 \text{kHz}$) Transceiver Size: 175 \times 210 \times 55mm

Shipping Weight: 1.6kg Carton Size: 213 × 293 × 96mm

As described in EA.

100W VHF Linear Amplifier

Cut through the noise on 2 — and put out a whopping signal with this one. 100W continuous output (in fact, 120W with 15W in!) And from only 2W drive you'll still get a healthy 40W + out. Uses high quality co-ax relays for minimum noise and minimum loss. 13.8V DC required at 15A for maximum output. Cat K-6313

Shipping Weight: 2.1kg Carton Size: 293 × 213 × 96mm

As described in EA.



2m GaAsFET Preamp

When you're scratching for that last femtovolt, a low-noise GaAsFET preamp could be just the answer. The big advantage (especially for satellite work) is the low noise, with around 15dB gain (at 146MHz). It's designed to mount up the stick — where it should be — with hardware supplied. Also supplied are low-loss co-ax relays, the diecast box... everything! Cat K-6311

Gain: Approx. 15dB at 146MHz Device Noise: 1.5dB at 800MHz falling to under 1dB

Bandwidth: 144-148MHz Insertion Loss: 0.6dB DC Supply: 12 Volts Connectors: BNC Type Case: Prepunched, virtually water-tight

diecast aluminium Mounting: Masthead bracket and clamp supplied

Shipping Weight: 1.2kg Carton Size: 267 × 160 × 90mm





ORDER BY PHONE

DSE Explorer 70cm (UHF) Amateur Transceiver

The original — and still one of the most popular kits. 70cm is less crowded — there are less mugs and yahoos — so many amateurs prefer to work the UHF band in peace. The DSE Explorer is the perfect, low cost way to do it. And another big advantage of this kit is it really teaches you to be a good constructor: UHF is not at all kind to sloppy work so if you want the kit to give optimum performance, your workmanship has to be pretty good. Cat K-6300

Specifications:

Frequency: 438.025-439MHz in 25kHz steps No of channels: 40

Mode of operation: FM Supply req:13.8V DC 2A (5W output) Septivity: -6dB 7.5kHz; -60dB 15kHz

Adi. chan rejection: Better than 80dB Power output: 5W (typical) Transceiver size: $175 \times 210 \times 55$ mm

Shipping Weight: 1.5kg Carton Size: 213 × 293 × 96mm

As described in EA. \$4

80Ch. Explorer Upgrade Kit

More channels for the Explorer UHF transceiver! This simple circuitry will give your DSE Explorer extended frequencies and adds 40 channels in the 439 to 440MHz region. As described in EA.

That Professional Finish

Give your DSE Explorer that professional look! This kit supplies you with a new look pre-punched front panel to accommodate an S-meter and a repeater switch PLUS you get the circuitry to drive the S-meter. Great idea! Cat K-6302

70cm GaAsFET Preamp

Like its 2m brother, the UHF GaAsFET preamp will pull in signals you didn't even ere there! Wide bandwidth and low noise (60MHz; 1.5dB typ) ensure optimum performance with receivers or transceivers. Handles up to 100W CW switching designed for masthead use (full mounting kit included). Requires only 12V DC @ 400mA, Cat K-6309

Gain: Approx. 13dB at 438MHz Device Noise: 1.5dB (Typical) Bandwidth: 420-480MHz Insertion Loss: 0.6dB DC Supply: 12 Volts Connectors: BNC Type Case: Pre-punched diecast aluminium Mounting: Masthead bracket and clamp supplied

Shipping Weight: 1.25kg Carton Size: 160 × 267 × 90mm




UHF All Mode Power Amplifier

As described in EA.

50 watts out from just 2 watts of drive? Sounds too good to be true! 14dB gain with a 10MHz bandwidth — and you can internally adjust the centre frequency anywhere from 430-480MHz. All harmonics and spurii are at least -60dB. Includes carrier detect switching with coax relays for minimum noise and loss. Input SWR typically less than 1.2:1 and insertion loss (bypass) less than 0.9dB. Cat K-6307

Shipping Weight: 1.5kg Carton Size: 293 × 213



Pre-punched front & rear panels plus heatsink

As described in AEM.

Bipolar UHF Preamp

Based on BRF91, ultra-small board fits inside transceiver or receiver. 2dB or better noise figure, bandwidth 400-500MHz. Cat K-6306

Shipping Weight: 60g Pack Size: 100 × 175mm

As described in ETI.

VHF GRAS FET PREAME



Microwave Leakage Detector

Microwave ovens are fantastic — but are they completely safe? Yours could be leaking dangerous radiation! Check it out with this handy meter. No batteries required. Cat K-3095

Shipping weight: 152g Carton Size: 175 x 105 x 60mm \$4295



Many people believe negative ions are good for you! We're not sure — it could be a placebo effect! Build one of these and you be the judge. It's a fraction of the price of commercial units — but includes all parts required, including the important ioniser needles. Cat K-3333

Shipping weight: 550g Carton size: 267 x 90 x 160mm



Note: Cannot be

used with high

efficiency tubes.

Fluoro Starter

Do your fluorescent lights go blink, blink, blinkety blink when you switch them on? This substitute electronic starter solves that problem and gives a smooth rapid start EVERY time you switch on. And all the parts are housed in a standard starter casel Far outlasts conventional starters as well as prolonging tube life. Cat K-3082

Shipping weight: 54g
Carton size: 200 x 90 x 25mm

Speed Controller

A completely new circuit offering unbelievably smooth control and torque — even at very low rpm. Yes, it's even better than the previous model! New design includes 'in line' plugs and sockets for extra convenience. Suits virtually all 'universal' (brush type) motors. Cat K-3084

Shipping weight: 730g Carton size: 190 x 70 x 130mm



It's here . . .

The Discolight!

Move over, Musicolor: here is the Discolight! It's Silicon Chip's latest design which makes all previous 'colour organs', 'chasers', 'strobes' and similar devices quite obsolete.

Why? Because the Discolight does all of these - and more! Here's what it will do for your next party:

- Convert audio direct from an amplifier's speaker terminals (in parallel with speaker), or direct from its own internal microphone, to driver four channels or bands of coloured lights (up to 600W each channel).
- · Forward, reverse or auto-reversing chaser patterns
- · Simultaneous strobe on allafour channels
- Alternating pairs of channels flashing
- Music modulation or internal oscillator available on chaser, strobe and alternate modes.

... and so much more! In short, it's the **complete** lighting control centre for a huge variety of users from the home party, through amateur and professional stage work, sound and lighting installers for TV stations, theatres, etc - right up to (and including!) discos, dance halls, clubs, etc etc etc.

If you think we're raving about the new Discolight . . . you're absolutely right! Cat K-3150





Infrared 240 volt Controller

How many times have you wanted to switch a power point 'ON' or 'OFF' when it's across the room? Now you can switch any appliance virtually by pointing your finger! With this fantastic Infrared Remote Control Switch, you can switch on the TC, lamp, radio or many mains appliances without moving from the comfort of your bed or chair. The transmitter is housed in specially designed case about the size of a matchbox — so it's easy to carry in your pocket or clip to your shirt or belt. It'll operate up to 12 metres from the switch and it's specailly designed for minimum interference. Cat K-3428

Shipping weight: 720g Carton size:267 x 90 x 160mm

Spare Transmitter for above: *

Just in case you misplace one — or so someone else can have control! Same transmitter as is included in main kit. Cat K-3429

Shipping weight: 50g Bag size: 100 x 175mm





8-Channel IR Remote Controller

Taking it easy has never been so easy! Just think about the possibilities — remote control for your TV, CD, VCR, model railway or even mains powered appliances such as lamps, alarms, heaters, the coffee perculator... almost anything!

Build yourself one of the most convenient, labour saving kits we've ever seen. This remote control up to 8 functions plus mute and Up/Down! What's more, it allows you to customer build the kit to suit your own specific application — construct with all functions or just those required. Front panels are screened on both transmitter and receiver for a professional looking finish.

IR Transmitter

For use in conjunction with the IR Receiver (K-3434). Housed in sturdy plastic case with prepunched and screened panel and 12 function buttons. Cat K-3433

\$5995

Receiver Cat K-3434



Soldering Iron Temperature Controller

One iron can do ALL your work! What's more — it can be your existing soldering iron. At last, there's an inexpensive way to have a fully regulated, adjustable temperature control soldering system.

Think about it - no more cooked components, no more tracks lifting off pcb's less chance of dry joints — in short, less construction time and a more reliable product! Look at these features. Cat K-3479.

- 240 volt mains operated
- Selectable 20-70 watts
- Constant, adjustable temperature
- Range can be adjusted



Power Mains Appliance Off A Car Battery! **12-230V** Inverter

A compact 300VA 12/230V inverter that's ideal for farms, campsites, building sites, etc. - anywhere remote mains power is required.

The Auto-Start feature means that — unlike most inverters — you use virtually NO power until an appliance is switched on. Comes with double general-purpose mains outlet and durable plastic case. Cat K-3478

Nominal Supply Voltage: 12V DC Output Voltage: Up to 240 (RMS)
Frequency: 50Hz crystal locked
Maximum Load: 300VA





NiCad F-A-S-T Charger

whenever you NEED them, the batteries are flat! With the ETI NiCad Fast Charger you can get NiCads to near rated capacity in a hurry. And it can't overcharge either!

NiCads not only tolerate a fast charge but benefit from it in terms of recovery and apparent capacity. If you use NiCads at all — you'll find this project a great time saver.

- 2.4A constant current
- Timer controlled
- Charges up to 12 volts of cells in series
- 250mAh (7 min) 4Ah (2hrs) charge rates
- Mains powered



GET YOUR TEETH INTO A REAL PROJECT!

Imagine Being Able To Say... "I built it myself!"

A fully 'AT' compatible computer and it can be yours for hundreds of \$\$\$ (thousands even) less than an off-

This is the computer you thought you'd never afford to own, but when you Build-It-Yourself... you can!

WHAT ABOUT FEATURES? There's no compromise. The DSE Baby 'AT' has all the features you'd want and more... at work or home. Take

- Up to 1Mb RAM
 Up to 3 x 1.2 Floppy or hard disks
 Selectable 6, 8, 10 & 12MHz clock speeds
- 80286 CPU
- pansion slots sive 200 watt power supply
- Fully 'AT' Compati
- Modular Construction everything fits without hassles or soldering!
 All PCB's are pre-assembles and tested!
- Full 12 months warranty on all components
 Heavy duty steel case with flip-top lid
 Custom build it according to your needs and finances

IT'S EASY TO BUILD

Because the DSE Baby 'AT' is designed as a modular computer system, everything fits together — holes line up, PCB's just slot in and all connecting plugs and cables are supplied. So, unlike other kit computers on the market, it's a cinch to build... without soldering, drilling, etc.

What's more, all modules come with comprehensive, easy to follow instructions — there's no guess-work involved! It's easy and you'll learn about computers as you go.

There's only one way to get yourself more computer than the DSE Baby 'AT' - and that's to pay a lot, lot

Basic System

Baby 'AT' Motherboard: With 8 expansion slots, back-up battery, speaker, manual and all IC's except RAM. Cat X-1000

Heavy Duty Case: Just 430mm square steel case covered in quality bone crinkle finish. It's predrilled and complete with hinged lid. Cat X-1005

200W Power Supply: More than enough for full expansion. Cat X-1010

Keyboard: 84 Key 'IBM' format. Cat X-3820

Disk Controllers: Floppy Controller — Up to 2 x 360K or 1.2Mb drives. Cat X-2014

Disk Drive: 1.2 Floppy Disk Drive. Complete with cables. Cat X-2200

Graphics/Parallel Printer Card: CGA & Parallel printer. Cat X-2010

256K Memory: Fast (120ns) top quality 41256 RAM chips. 9 required per 256K bank. Cat Z-9313

Detailed system instruction manual. Cat X-1004

Just add the monitor of your choice

BASIC SYSTEM ONLY



Range of pre-assemble cards available - graphic disk controllers, ports, et

'Baby AT' mother boar with 8 expansion slots & provision for 1Mb RAM

1.2Mb Floppy and/or 20Mb Hard Disk

SPECIFICATIONS:

- Nother Board: 80286 CPU
- 6, 8, 10 & 12MHz speed (selectable) Provision for 256K, 512K, 640K or 1024K RAM on board
- CHIPSet technology & ICs 7 Channel DMA
- 16 Level Interrupt Award BIOS (fully licensed)
 - Real time clock on board (battery b/u)
 - 8 Input/Output Slots (6 with 62 and 36 pin connector, 2 with 62 only)
- **CMOS Memory to Maintain System**
- 1420

\$540

1440

\$220

\$239

429

1249

*29°5

\$480195

- 199
 - - 80287 Co-processor socket provided
- Configuration
 IBM PC/AT compatible
 All LSI & RAM IC's fully socketed

- Hard/Floppy Disk Controller: — Controls 1 or 2 hard disks Ind. standard ST-506/ST-412 Interface
- Up to 2048 cylinders Up to 16 read/write heads
- Data transfer rate 5Mb/s
- cata uanster rate SMD/S
 Controls 1 or 2 floppy disk drives
 Interface similar to FD-55F minifloppy
 Double density 320/360Kb or 150/180Kb
 High density 1.2Mb
- Rated to work up to 12MHz Graphics Cards:

MGA, CGA & EGA available

- Ports:
- Keyboard port on motherboard Parallel, serial & game ports on interface
- Monitor port on appropriate graphics card

ALSO AVAILABLE

Plug-In Cards: MGA & Parallel Printer. Cat X-8141 \$149

EGA with Hercules compatibility. Cat X-2013 \$399 Serial/Parallel/Games Port Card. Cat X-2012 \$139

101 Key Expanded Keyboard: With direction keys and extra function keys. Cat X-3821 \$149 Hard/Floppy Cont Cat X-2008 \$249 oller: Handles 2 of each Hard/Floppy drives

20Mb Hard Disk: Complete with cables. Cat X-2203 \$399

Function Generator

With Digital Readout



An essential piece of test and design gear for all hobbyists, amateurs, service technicians ... produces sine, triangle and square waves from below 20Hz to 170kHz with a very wide range of output levels too. An idea companion to our other build-it-vourself test equipment. Cat K-3520

CHECK THESE FEATURES:

- Frequency range from below 20Hz to 170kHz in three ranges.
- Continuously variable output level from 3mV to
- 600 ohms (nominal) output impedance.
- Sine, triangle and square waveforms.

VHF Wattmeter

How efficient is your system? Here's an inexpensive way to measure your VHF power output AND the efficiency of your antenna system. Now you can get the most



out of your equipment! It's relatively easy to assemble and also has a switch so you can meansure the reflected power back from your antenna. Comes with attractive black anodised case and everything you need to complete the project. Cat K-6316

Specifications: Usable Frequency Range: 144-148MHz
Maximum Power: 150.watts
Ranges: 0-150 watts

Accuracy: ±10% Impedance: 50 ohms Directivity: >20dB Insertion Loss: <0.1dB Connectors: SO239

hipping Weight: 740g Shipping Size: 267 × 90 × 160mm

UHF Wattmeter

Pre-punched aluminium case



Shipping Weight: 720g Shipping Size: 267 × 90 × 60mm Now there's an inexpensive way to check you UHF power output and the efficiency of your antenna system! Here's an easy to assemble wattmeter which not only measures the power output of your transceiver but also has a switch so you can measure the reflected power back from your antenna. The kit contains everything you'll need and can be assembled in next to no time! Cat K-6312 Accuracy: ±10%

Impedance: 50 ohms Directivity: >20dB

Insertion loss: <0.1dB Connectors: BNC Usable Frequency Range: 430-480MHz Maximum Power: 50 watts Ranges: 0-10 watts 0-50 watts

Catch the bug! **RF Field Strength Meter**



Specifications

Bandwidth: 3 to 1000MHz Gain: Internal amplifier gain 100 times Output: Meter shows relative field strengths Pre-punched aluminium case

Shipping Weight: 784g Shipping Size: 270 × 160 × 90mm



As described in AEM.

LCD Meter Panel versatile accurate panel meter using a large liquid crystal

display for low power consumption. The PC board design allows for maximum flexibility to cater for varied mounting arrangements. The low cost makes it ideally suited as a readout device on many projects, at both amateur and professional level. Cat K-3450

As described in EA

Input impedance: greater than 1012 ohms Input bias current: ±2pA
Conversion method: dual slope

Reference: internal 100ppm Power supply: ±5V to ±15V DC 1mA @ ±5V

Display 3½ digit LCD Full scale reading: 200mV Accuracy: less than 1 digit Resolution: 100uV Polarity: automatic



Triangle wave linearlity better than

maximum output level).

Pre-punched front panel

R-L-C Bridge

Measure the values of new and used components easily and simply. You can measure resistance, (10 ohms to 10Meg-ohms), capacitance (10pF to 10uF)

and inductance (down to a few hundred microhenries). The RLC bridge does more than a

multimeter, and is easy to use. The complete kit of parts includes a specially printed front panel.

Battery not supplied. Cat K-3468

Measures unkown components

Shipping Weight: 700g Size: 267 × 90 × 160mm

Shipping Size: 245 × 72 × 220mm

Shipping Weight: 1.2Kg

Square wave rise-time of 0.4us (6V/us at

Negligible overshoot, droop or ringing.
 Readout accuracy ±2% ±one digit.

Amplitude stability better than 0.1dB on

Power consumption of 7W at 240V AC.

1% at 1kHz.

all ranges.

RF Attenuator Box Amateurs know just how valuable a good

attenuator is... and how expensive they normally are! Here's value: up to 63dB attenuation (in 1dB steps from 0dB) from 50 to 500MHz — and it's \$\$\$ less than equivalent commercial units. Just think of the uses:

- Antenna gain measurement
 Fox hunts and radio direction finding
- Receiver/transmitter matching
 And countless other amateur/CB/professional
- Pre-punched and screened front panel.



Rated at 1/4 watt, with a 50 ohms input impedance. Connectors are standard BNC. so it is perfect for "in line" use. Cat K-6323

Shipping Weight: 225g Unit Size: $195 \times 60 \times 40$ mm

As described in AEM.

Speedy fault finding Transistor Tester

another Transistor Tester! This one tests bipolar transistors, diodes, F.E.T.'s and even S.C.R.'s and P.U.T.'s. This practical low-cost test instrument is simple enough to be built by a beginner and then provide him with a valuable piece of test equipment. You can get experience in building, then use it to learn about the operation of semiconductors, or use it for more serious checking. Ideal for the beginner and serviceman alike, or in schools. Battery operated and supplied with one of our 50mm meters in a deluxe Zippy case. Cat K-3052



Requires 9V battery Cat S-3106 \$1.85 extra Pre-punched front panel.

Shipping Weight: 350g Shipping Size: 185 × 63 × 132mm

As described in EA

Zener Diode Tester



for the service bench, perfect for the hobbyist too. Now you have no worries about all those diodes with markings rubbed off — is it a Zener or is it a signal diode? You'll get a direct readout — in volts of the Zener voltage of 400mW and 1W Zeners from 3.3 to 50 volts (2 ranges). If you're the type rith a well-stocked junk box mostly full of unidentified junk, this is for you. Cat K-3051

Pre-punched front panel

As described in ETI.

TV Pattern Generator

A build-it-yourself bargain for the serviceman

With just seven IC's you get three patterns: dot, crosshatch and blank raster. Not bad value, huh? An indespensable aid for the servicemen or hobbyist — and this one's small enough to carry around anywhere.
Includes deluxe front panel and VHF modulator. Operates from plug-pack adaptor (9V DC). Cat K-3472

Shipping Weight: 260g Shipping Size: 185 × 63 × 132mm

As described in EA





TV Colour Bar & Pattern **Generator**

The serviceperson's right hand man!

If you're in the trade, this has to be a cinch to build!

Portable, the pattern generator is powered by a 12 volt AC plug pack and provides 8 patterns bars, red/white/black screen, cross-hatch, vertical/ horizontal lines and dot pattern. Sure better value than ready made models! Cat K-3473





1GHz DFM for under \$300: complete!



As described in AEM

Yes, it's true. a 1GHz (that's 1000MHz just in case!) digital frequency counter with typical sensitivity of around 20mV — and even more, it's delightfully simple to build! Based on the very latest technology LSI chips, this outstanding design features specifications at least the equal of commercial units costing many times the price. And even more, it looks good — again, the equal of commercial units. The tried-and-tested twin pcb construction technique is used to virtually eliminate the chance of wiring errors — placing this kit firmly into the "hobbyist" category. You don't need an electronics degree to put it together! Cat K-3437

Features:

- Everything included nothing extra to buy.
 8 digit LED display
- Silk-screened pre-punched front and rear panels
- Housed in quality instrument case
 Mains power supply included
 a ranges cover 20Hz to 1000MHz

Ranges	Gating Time	Resolution	Input Impedance	Input Sensitivity
20Hz to 10MHz	1s	1Hz	1M//50pF	40mV (type <20mV)
20Hz to 80MHz	1s	10Hz	1M//50pF	40mV to 50MHz, 200mV above
30MHz to 1GHz	1.28s	100Hz	50 ohms	40mV to 50MHz, 20mV above

eadout Accuracy: ± least signigicant digit, ± timebase accuracy Timebase Accuracy: ±1 part per million for 0-40°C ambient temperature Maximum Input: 5V RMS on 10 & 80MHz, 5V p-p 1GHz input (optional 10V)

Shipping Weight: 1.1kg Shipping Size: 245 × 72 × 220mm

3 Digit Counter

can use it with a minimum of external components Designed for maximum flexibility (display can be removed for external mounting and with a very wide voltage 5-15V). Cat K-3451

- LED display
 Up to 2MHz counting speed
- Clock enable
- Wide power supply range
 Very comprehensive manual included!

Shipping Weight: 107g Shipping Size: 100 × 175mm bag



Turn your old TV into a

Got an old B&W TV gathering dust in the corner? Turn it into an audio CRO! That's right: this remarkable kit turns any surplus B&W (or even surplus colour) TV set into a 300kHz audio oscilloscopel It gives a good display at low frequencies, making it ideal for Hi-Fi and audio display applications. All it needs is 100mV to drive it to full screen deflection. The large screen size means that it



gives a dramatic display: just think of the non-technical applications of such a device: promotions, Hi-Fi showrooms etc. If you can't afford a proper CRO -this could be the answer! Cat K-3060

Shipping Weight: 550g Carton Size: 216 × 70 × 126mm

Yes, your own \$3 **CRO for ONLY**

V Field Strength Me

Technicians... antenna installers... anyone dealing with FM/TV antenna installations or adjustments — it's just the kit you've always wanted! Solves one of the major problems with getting the best from any system by indicating the best antenna position.

Battery operated (with charging circuit) or it can be operated via external DC 9V to 14V. You can even use it to convert a video monitor into a TV set! Great for difficult antenrinstallations. Includes in-built audio monitor. Cat K-6329

\$499

As described in EA

Bands: 3

Frequency Coverage: (0-5) 46.25-102.25MHz (5A,6-11) 138.25-216.25MHz (UHF 21-69) 471.25-855.25MHz

Channel Presets: 4

Gain Control: Manual Attenuator with scale Antenna Impedance: 75 Ohm, Belling Lee connector Video Output: Sync tip level 2.5V p-p. PAL Input Power: 9-14V DC @ 500mA (Or internal battery)

Battery not included Size: 270 X 160 X 90mm Shipping weight: 1kg




Sine & Square

Wave **Oscillator**

Covers frequencies from 15Hz to 150kHz. This is one of the most useful pieces of equipment on the experimenter's bench. This simple design is easy to build and a great performer. Runs from a 9V battery. All parts are supplied including specially printed front panel, attractive 'Zippy' case and full instructions. Battery not included. Cat K-3469

Basic Specifications: Frequency: 15Hz to 150kHz in 4 ranges Distortion: <0.1% 20Hz to 15kHz

As described in EA.



TEST-EQUIPMENT

Budget Mini Multimeter

A great little multimeter for anyone starting out... or for anyone who is likely to knock their multimeter around a lot. For way under \$20 you get an 11 range, 2000ohm/volt pocket sized meter that's ideal for most of the general test work we all do. It's rugged and reliable, measures just 92 x 60 x 30mm and weights in at only 158g. Throw one in the tool box in case! Cat Q-1010

> Ranges: DCV: 10, 50, 250 & 1000 ACV: 10, 50, 250 & 1000 DC: 100mA Res: x10, x1k dB:-10 to +62 sitivity: DC and AC

Looking for value?

18 Ranges including Battery Check

Small on size — but big on performance. As well as all the expected ranges, you'll also get a handy battery checker for 1.5 and 9 volt cells — save \$\$\$ on batteries! Featuring good sensitivity (10,000 ohms per volt) and carefully chosen ranges for maximum usefulness, this small meter is ideal for the hobbyist's bench or toolbox. Mirrored scale for minimising parallax errors, and deeply recessed plugs to ensure you don't get "zapped". Cat Q-1015

Ranges: DCV: 2.5, 50, 250, 1000 ACV: 10, 50, 250, 1000 DC: 10, 250mA Res: x10, x1k Batt check: 1.5 & 9V, replace/?/good

- Diode and fuse protection
- 18 ranges plus dB

dB: -20 to +62

- Shipping weight 150g
 Shipping size (blister pack):
- 105 × 190 × 35mm

Multimeter with audible continuity tester

A compact, reliable multimeter with an added bonus: a built-in buzzer for continuity testing! Also has a battery checker PLUS 10A DC range — not normally found on low-priced multimeters! On top of this, you get a high sensitivity (20,000 ohms per volt) meter mirrored scale and large banana plugs for sure contact. Cat Q-1022

- Diode and fuse protection
 19 ranges plus dB
 Built-in battery checker plus continuity checker
- Shipping weight: 450g
- Carton Size: 150 x 130 x 45mm Meter Size: 135 x 92 x 40mm
- Weight: 330g

A two-in-one Multimeter & **Logic Tester**

Virtually two instruments in one! It's perfect for digital circuit troubleshooting because as well as normal multimeter functions it also has a built-in logic tester! Three LEDs give 'HIGH', 'LOW' and 'PULSE' states of logic circuits. 18 voltage, current and resistance ranges, with 20K ohm/V sensitivity DC and 8K ohm/V AC. Shielded movement is unaffected by external magnetic fields. The ideal serviceman's multimeter. Cat Q-1026

- Built-in Logic Tester
- 20 Ranges Diode & Fuse Protection
- Carton Size: 150 x 130 x 50mm
- Shipping Weight: 336
 Meter Size: 140 x 92 x 30mm
- Weight: 240g

Ranges: DCV: 2.5, 10, 50, 250 & 1000 ACV: 10, 50, 250 & 1000 DC (mA): 5, 50, 500 & 1A Res: x1, x10, x1k Batt: 1.5V, 9V Continuity dB:-8 to +62

Ranges: DCV: 0.3, 3, 12, 60, 300, 1200 ACV: 6, 30, 120, 300, 1200 DC: 0.6, 3, 30, 300mA Res: x1, x10, x1k, x10k dB: -10 to +63 Logic: (test 5V) Lo - 1.5V Hi - 3V Pulse -3.3MHz



Multimeter Replacement **Lead Sets**


Always losing your multimeter leads? Join the club! And shoving a bit of wire into the hole is a little dangerous... Here's the solution: a replacement lead set. 900mm long multistrand leads, colour coded red and black, with standard "tip" ends (100mm long probes & 20mm long points) and 1.5mm multimeter terminal points the other (as used on our Q-1010 and many other multimeters). Buy a couple of sets. just in case! Cat W-4504






"Banana" Plug **Multimeter Lead Sets**

Similar to previous multimeter lead set, but instead of the fine point these have standard 4mm banana plugs - as used on most modern multimeters including digitals. And the 4mm banana plugs also fit standard terminals as used on our Q-1230 bench meters and many other test instruments. So now you can get a spare set of multimeter leads AND a spare set of leads for all your other test gear. Colour coded red and black leads, 900mm long with probe points one end. Cat W-4508



IC **Multimeter Test Leads**

The best of both worlds: standard 4mm multimeter plugs one end, but on the other they have insulated IC clips. A "must" for anyone working with IC's (or any other circuits). Allows you to "hook on" and leave hands free for adjustments, other tests. etc. Colour coded red and black, 900mm long leads. Cat W-4509



Coiled Test Leads Self Retractina

You know the problem of meter leads cluttering up the bench? It won't happen with these leads: they're coiled and return to the coiled shape after being extended. A red and black pair with 1.5mm meter tip plugs. Cat W-4520





TESTEQUIPMENT

Electronic FET VOM Reads P-P & RMS!

Very few multimeters can read peak-topeak voltages: this one can! And even more — because it's electronic, you can adjust the pointer to centre scale for nulling. That's versatile! This extra rugged meter is professional quality: ideal for the service bench or the field — but it's price is more for the hobbyists. And with a single range switch there's no mad lead swapping every time you want to change measurements. It's overload protected, mirrored 90° scale for really accurate reading. Required two "AA" and one 9V

- battery. Cat Q-1143
- Shipping Weight: 730g
 Shipping Size: 200 \times 21 \times 90mm
 Meter Size: 125 \times 170 \times 50mm,
- weight 480g
 Full electronic (FET) operation
- High input impedance

The Best of Both **Worlds: Analog/ Digital Display**

Digital multimeters are great: no misreading, no parallax error, high accuracy . . . but!

Many users don't like the loss of dynamics: because dmm's sample at fixed time intervals, changing values in a circuit are often lost.

Here's the answer: a digital multimeter which displays in "bargraph" form. 105 step bar graph gives 1% resolution with a fast 10 per second sampling. A 10× expansion switch immediately expands the scale for more precise readings — and a data hold switch freezes the reading immedaitely prior to pressing. Or a maximum hold function memorises the maximum reading, but readings continue.

- Shipping Weight: 250g
 Cat Q-1777
 Shipping Size: 145 × 86 × 34mm
 Auto positive or negative indication
 Continuity and diode check functions inbuilt

Our Lowest Cost Digital is a Top **Performer**

The new DSE Q-1440 Digital Multimeter proves that price doesn't necessarily equal performance! Despite its low cost, it has the features and specifications of many top-of-the-line digitals costing many times as much. Latest IC technology is used to acheive the lowest possible component count — ensuring reliability, accuracy, stability and really rugged, easy-to-handle instrument.

Includes fully shrouded proved for maximum safety Requires only one 9V battery. Cat Q-1440

Includes fully shrouded probes for maximum safety.

- Shipping Weight: 250g
 Shipping Size: 130 × 115 × 35mm
 Meter Size: 65 × 22 × 110mm
- Sloping readout for maximum visibility
 Input impedance 1Mohm DC

Low Cost Digital with Data Hold

So simple to use - yet highly professional specifications. When you want a digital multimeter that offers you flexibility without a high price tag, it's hard to go past this

With well-thought-out ranges, it also includes a "data hold" function (great when you can't watch the display all the time) a diode checker, and also a DC range of 10 amps: very handy! All this in a meter with 10Megohm input resistance, excellent RF shielding and a clear, wide angle display for easy, accurate reading. Cat Q-1521

- Shipping Weight: 250g
 Shipping Size: 113 × 43 × 163mm
 Up to 2000 hours battery life (9V alkaline)
- Single knob range changing
- Safety recessed & shrouded
- connections
- Meter Size 150 × 74 × 35mm

Pariges: DCV: 0.3, 1.2, 12, 30, 120, 300, 1200 (10M ohm input imped) ACV: 3, 12, 30, 120, 300, 1200V (plus pk-pk; approx 1MHz) DC: 0.1uA, 0.3, 3, 30, 300mA, 12A AC: 12A

Decibels: -10 to +63
Resistance: X1, X10, X100, X10k, X1M
AC Bandwidth: 1MHz

Ranges: DCV: 100mV, 2.5, 10, 50, 250, 1000V CSM imp)
ACV: 10, 50, 250, 750V (minimum 5k/v)
DC: 2.5, 25, 250mA
Res: 250 ohms, 2.5, 25 250k, 2.5M
Cont: 250 ohms max, buzzer <100 ohms approx. Diode: Reads Vf on display, approx. 0.5mA

Ranges: DCV: 2, 20, 200, 1000 (1Mohm) ACV: 200, 500V DC: 2, 20k, 200mA Res: 2k, 20k, 200k, 2Mohms Diode and Transistor check.

Ranges: DCV: 2, 20, 200, 1000 ACV: 200, 750 DC: 2, 200mA, 10A Res: 2, 20, 200k, 2M Diode: Checking range reads Vf



Multi-Piece Test Lead Set

What value! Budget set designed for the hobbyist, techician, etc. Long (1.2m) red and black test leads usable in their own right with 4mm banana plugs one end and 1.5mm probes the other. Also included are a pair of e-z hooks and a pair of open-end lugs. The 1.5mm probes plug into these to change the probe type. Simple but it works very well indeed. Cat W-4523

All housed in protective plastic wallet. Wallet size: 160 x 85 x 20mm






Universal Test Lead Set

The professional model: the ultimate set for the engineer, technician or advanced hobbyist. It's a screw-together system which allows virtually unlimited choices in probe types and ends.

- The set comprises 21 pieces:
 Red & black "curly" test leads which stretch out to over 2m, with 25mm insulated handles one end and 100mm handles the other.
- 4 x 18mm long 1.5mm probes
- 2 x open-ended spade lugs
 2 x 100mm long 1.5mm probes
 - 4 x alligator clips 4 x 4mm banana plugs
 - 2 x right angle adaptors
 - · All housed in a plastic protective wallet

To make the test leads you want, just screw in the connectors you want. It's that simple! And it suits virtually any meter or test gear available. Cat W-4528



DMM Lead Set

Designed espcially for modern digital multimeters (such as our Q-1510, Q-1512 and Q-1515 DMM's) this superb lead set features fully shrouded right-angle meter plugs (no chance of exposed metal to zap you!), 1.1 metre long cables, and a unique threaded 1.5mm probe with 100mm handle. The purpose of the thread is to allow other tips: a pair of threaded alligator clips is supplied which, when screwed on, are also fully shrouded for complete safety. Cat W-4510

Also available, replacement test leads to suit DMM's such as our Q-1500, Q-1505 and Q-1600. Cat W-4511 (Similar to W-4510 without alligator clips.)

Shipping weight: 85g Shipping size: 210 \times 80 \times 20mm





Ultra-flexible Multimeter Cable

Designed especially for test gear use, this 512 strand (yes, count them: 512 wires!) cable will take the bends, kinks and knots that would destroy conventional cable. And because there are so many strands, cable resistance is very, very low - not measurable on most test equipment. Of course, this cable is also ideal for connection to moving parts (eg car door speakers, machinery, etc) where continuous movement would break normal cable. Cat W-4016

Pack contains 2 metres each of 3mm red and black cable (4 metres total).



ESTEQUIPMENT

Safety Yellow 3.5 Digit with Tr. Diode & Continuity plus **Battery Checkina**

At last! Someone's got away from basic black or basic grey in a multimeter! This one has all the usual ranges, including current to 10A and resistance to 200 megs, but it also has a continuity checker with a fast 100ms response time, a diode and transistor checker, plus a battery checker - it tests under actual load conditions. It takes a single 9 battery (and tells you if it's low!) and comes complete with a flip-down handle that doubles as a stand. Cat Q-1445

- Shipping Weight: 288g
- Shipping Size: 140 × 130 × 40mm Bright yellow colour with large LCD
- Continuity buzzer, transistor checking
- Battery checking under load
 Meter Size: 72 × 128 × 33mm

Hanges: DCV: 0.2, 2, 20, 200, 1000V ACV: 0.2, 2, 20, 200, 650V DC: 200uA, 2, 20, 200mA, 10A AC: 200uA, 2, 20, 200mA, 10A Resistance: 200, 2k, 20k, 20k, 2M, 20M,

Translator Check: Hfe
Dlode Check: 1mA, 3.2V
Continuity: Buzzer
Battery Check: 1.5V (@ 200mA), 9V (@ 6mA)

Safety Yellow 3.5 Digit with Cap, Tr, **Diode & Continuity**

Very similar to our Q-1445 multimeter, with slightly different ranges to suit different purposes. This one features a capacitance checker (2nF to 20uF) in place of the battery check ranges, and goes to 20 megohms as its top resistance range. Features very high overload ection (at least 500 volts DC, up to 1200V DC on most ranges), and the meter is fuse protected. Resolution is a very respectable 100uV/100nA, with a very fast 300ms cycle time (3 readings second) so you aren't waiting forever for the display to catch up with the circuit. Comes complete with a flip-down handle that doubles as a stand. Cat Q-1465

- Shipping Weight: 241.7g
- Shipping Size: 140 × 130 × 40mm
 Bright yellow colour with large LCD
 Continuity buzzer, transistor checking too
- Capacitor measurement up to 20uF
- Meter Size: 72 x 128 x 33mm

Ranges:
DCV: 0.2, 2, 20, 200, 1000V
ACV: 2, 20, 200, 655V
DC: 200uA, 2, 20, 200mA, 10A
AC: 200uA, 2, 20, 200mA, 10A
Resistance: 200, 2k, 20k, 200k, 2M, 20M
Capacitance: 2, 20, 200nF, 2, 20uF
Translator Check: He
Diode Check: 1mA, 3.2V
Continuity: Buzzer

Autoranging 3.5 digit with memory!

A new model — updated and improved! It now includes transistor gain measurement, data hold, and improved ranges. Autoranging means you don't have to worry about which setting you're on: a boon for the service technician who doesn't know quite what to expect — or for the beginner who doesn't know! And it has auto polarity PLUS high levels of overload protection on all ranges — it won't let you make an "oops". Fast 1/2 second cycling means you're not left in the dark with old readings. either. It features a "lo ohms" setting which limits o/c voltage for in-circuit resistance measurements, and the handy buzzer sounds at 1.9 digits so you don't even have to look at the display. The auto-ranging is switch selectable, with manual ranging giving extended resolution (150% auto range). Cat Q-1516

- Shipping Weight: 250g Shipping Size: 180 × 155 × 55mm
- Auto ranging for hands-free operation · Continuity buzzer, transistor checking
- High overload protection

Meter size: 75 × 150 × 34mm

Ranges:
DCV: 0.2, 2, 20, 200, 1000V
ACV: 2, 20, 200, 750V
DC: 20, 200mA, 10A
AC: 20, 200mA, 10A
Resistance: (10) 2k, 20k, 200k, 2M, 20M
(hi) 200, 2k, 20k, 200k, 2M, 20M
Transistor Check: Hfe
Continuity: Buzzer

3.5 Digit LCD with Diode, Continuity and Temperature

A reliable, value-packed LCD that's ready for work! With many more ranges than most metres in its price bracket, this one includes full ranges of AC and DC current (up to 10A) with 6 different voltage ranges too. But more than this, it will check those diodes in your junk box as well as give a digital temperature readout. It's overload protected (up to 1kV DC or 750V AC) on all ranges, and with 12mm digits it's easy to read and easy to use. (Input impedance is a very high 10M/100pF on ranges. Cat Q-1511


- **Shipping Weight: 330g**
- Shipping size: 120 × 200 × 70mm
 Meter Size: 170 x 87 x 42mm


- 1000 hours battery life
 Temperature readout Probes included
- · Checks diodes too

Ranges: DCV: 0.2, 2, 20, 200, 1000V ACV: 0.2, 2, 20, 200, 700V DC: 200uA, 2, 20, 200mA, 2, 10A AC: 200uA, 2, 20, 200mA, 2, 10A Resistance: 200 ohms, 2k, 20k, 200k,

Zm, 20m Temperature: -20 to 1370 degrees C Diode Check: 2.8V @ 3mA Continuity: Buzzer









Covers, Pouches, etc

Protect your, multimeter...

Q-1011 — Soft protection cover for both \$950 Q-1010 meter and leads.

- Soft protection pouch to any of Q-1510, Q-1511 or Q-1512.

\$095

\$095

\$995

\$2495

Q-1513 — Soft protection pouch to suit any of Q-1515 or Q-1516.

Q-1522 — Flexible but hard cradle to suit Q-1515 or Q-1516. Impact absorbing, suitable for either desk/ bench use or wall mounting.

Q-1668 — High density rubber cover to protect your meter from the rough stuff. Suits Q-1666.

Q-1667 — Hard leather-like case to suit Q-1666. With carry strap and internal divider to hold test probes, etc. Clip on lid means you don't have to remove meter when testing.



Small Jumper Set



Great value for the hobbyist, experimenter, technician, etc. 9 piece jumper set with small insulated clips Colour coded. Cat W-4570

\$575





4 piece colour coded jumper set with medium sized clips. Ideal for those circuits with a little more 'beef'. Cat W-4571

Hook Type

This is a great idea for a jumper set. Two piece colour coded leads with right-angle claw hooks to get a good grip on components, etc Cat W-4572



Resistance **Substitution** Wheel

Convenient size with large, easy to read value selection that enables you to select values from 5 ohms to 1M ohm in 36 steps by using most common divisions. Complete with leads and insulated crocodile clips. Cat Q-1410



TEST-EQUIPMENT

LCD Multimeter Cap/Transistor Checker

Not just the usual voltage, current and resistance ranges — though it's certainly got those — it also checks capacitors (2 ranges, up to a whopping 20uF!) PLUS transistors and diodes. And even more: it's got an audible continuity checker. Plus other features — such as automatic zero of all ranges, high surge voltage protection, automatic overrange indication, high current measurement (10AC & DC) etc, etc — makes this the one digital multimeter you can do just about everything with! Looks like you'll have to check it out! Cat Q-1500

- Shipping Weight: 625.4g
 Shipping Size: 170 x 140 x 50mm
 Meter Size: 162 x 88 x 36mm
- Weight: 340g

Ranges:
DCV: 0.2, 2, 20, 200, 1000
ACV: 0.2, 2, 20, 200, 7000
DC: 20004, 2, 20, 200mA, 10A
AC: 2, 20, 200mA, 10A
Res: 200, 2k, 20k, 20k, 2M, 20M
Cap: 2000pF, 20nF, 20nF, 2uF, 2uF
Transistor: Displays Hfe
Continuity: Buzzer & LED at <30 ohms
Diode Check: displays Vf (2.8V@1mA)

All normal range PLUS a **Frequency Reading**

It's finally happened: a digital multimeter with frequency reading... as well as all the advanced features of a top DMM (capacitance, transistors & diodes, continuity, etc) the Q-1505 also features direct frequency readout to 200kHz. Ideal for audio and general service work — now there really is one piece of test gear that does everything. And it even reads to 20A AC/DC! Cat Q-1505

- Shipping Weight: 570g
 Shipping Size: 190 x 150 x 50mm
 Frequency to 200kHz
 Current to 20A

- Transistors, diodes & capacitance too

4.5 digit with Data **Hold Function** What was the result? With most meters.

digital or analogue, the reading is but a moment in time. If you miss it... The DSE moment in time. If you miss it... The DSE Q-1600 solves the problem: hit the "data hold" button and the reading is frozen on the display — until you clear it. Very handy for test and evaluation procedures, standard service work, etc. Another highly unusual feature is its 20A range – double most meters. And that's on both DC and AC. Add to that transistor and diode checking, capacitance, plus buzzer and LED continuity, and you have one of the most versatile meters ever produced

- Shipping weight: 570g
 Shipping Size: 190 x 150 x 50mm
 Meter Size: 176 x 90 x 40mm
- Weight: 380g "Data Hold" function
- Up to 20A current reading
- Capacitance & transistors too

Digital with Bargraph Probably the best multimeter you'll ever

Double the Accuracy!

"4000 Count"

own! Most 3.5 digit multimeters are based on a "2000" count display, which is fine until you go above 2 units. Then accuracy suffers. 4.5 digit meters are available, but expensive. This one overcomes the difficulty by going half way between: it counts to 4000 units.

But there's more: it also includes a bargraph display to show the dynamics of constantly changing circuits. This, coupled with auto ranging, memory, auto power down, etc. makes it sensational value for money. Cat Q-1666

- High accuracy and high resolution
 At least 10Mohm impedance on DC
- Illuminated, large LCD scale.

Ranges: DCV: 400mV, 4, 40, 400, 1000V (at least DCV: 400mv, 7, 7, 1000mms)
ACV: 4, 40, 400, 750V (at least 10Mohms/50pF)
DC: 40, 400mA, 10A
AC: 40, 400mA, 10A
Resistance: 400 ohms, 4, 40, 400k, 4, 40Mohms
Continuity: 400 ohms Continuity: 400 ohms Diode: 0-2V

Ranges:
DCV: .2, 2, 20, 200, 1000
ACV: .2, 2, 20, 200, 750
DC: 200uA, 2, 200mA, 20A
AC: 2, 200mA, 20A
Res: 200, 2k, 20k, 200k, 2M, 20M
Cap: 2000pF, 200nF, 20uF
Translators: He
Diodes: VI Frequency: 20kHz, 200kHz (max. 250V)

Top quality rubber insulated probes/

Ranges:
DCV: 0.2, 2, 20, 200, 1000V
ACV: 2, 20, 200, 750V
DC: 200uA, 2, 200mA, 20A
AC: 2, 200mA, 20A
Resistance: 200, 2k, 20k, 200k, 2M, 20M
Capacitance: 2, 20, 200nF, 2, 20uF
Transistor Check: Hie
Continuity: Buzzer & LED

Top quality rubber insulated leads included







Mini Size Fully insulated with plastic shroud almost

fully covering clip. Easy to solder to, or can be used solderless by using crimp lugs.

Overall shroud length 32mm Red: Cat W-4550 Black: Cat W-4552



Large Size

Similar to mini clips, but capable of larger current carrying capacity. Also usable in soldered or solderless mode.

Overall shroud length 50mm Red: Cat W-4554 Black: Cat W-4556

Giant Size

Intended for battery connection, these clips have wide, flat jaws which open to almost 15mm for battery terminals, etc. High current capacity because of the wider connecting surface.

Overall shroud length 70m Red: Cat W-4558 Black: Cat W-4560

\$**A** 95



connection, and so on.

Clips

Colour-coded spring-loaded clips with

insulated handles for temporary circuit

mock-ups, battery and power supply

Feature tiny hooks to connect around component leads or pins without shorting to the next lead or pin. Plunger action exposes hook, releasing plunger withdraws hook into shroud for maximum safety.

Mini Size

Perfect for IC work, etc, because of the small size. Hook size allows up to 1.5mm diam pins to be connected. Lead enters through handle and solders direct to probe.

Overall length 40mm Black: Cat W-4586

Coloured: Cat W-4588 95¢

Large

Slightly larger than left, similar to the famous E-Z Hook but much lower in price. Easy to solder to, works on same principle with 1.5mm diam wire/pin handling capacity.

Overall length 57mm Black: Cat W-4582

25

Giant

Famous Miyama brand hook probes with I-o-n-g probe to get into difficult places.

Overall length is 137mm, most of which is the handle! No-soldering design: test leads connect into handle with thumbscrews Hook capacity approximately 3mm.

Overall length 137mm Red: Cat W-4589 Black: Cat W-4590



TESTEQUIPMENT

Hand-Held RC **Oscillator**

A really worthwhile addition to your test gear: a hand-held oscillator that's small enough to take anywhere. About the same size as a digital multimeter, it gives you 23 ranges of sine and square waves (switchable) between 20Hz and 1.5kHz, plus a ×100 range: 46 settings in all. Continuously variable amplitude and a -20dB attenuator built in gives total control. And you can sync the signal if you wish. Output is standard 600 ohms. Cat Q-1220

Complete with clip test leads

Features:
• Adjustable threshold for DTL/TTL or

Specifications:
Range; ×1 20Hz to 1.5kHz
×100 2kHz to 150kHz
Accuracy: 20Hz to 100kHz ±3%
above 100kHz ±55%
Output control: 0dB, -20dB + fine adjust
Output impedance: 600 ohms ±10%
Waveform: Square or Sine, switchable
Square wave: 9V p-p max, rise time
<0.5us Sine wave: 1.2V rms
Shipping weight: 220g
Carton size: 115 x 35 x 160mm
Max. distortion: 0.3% THD

3-State **Logic Probe**

technician or hobbyist. Much easier than technician or hobbyist. Much easier than and more practical than tying up your multimeter or CRO: you'll be able to tell at a glance what the logic state is of the circuit under test by seeing which LED is glowing. Power is obtained from circuit under test (5V) via test clips, and the probe point is fine enough to touch individual IC legs, etc. "High", "Low" or "Pulse" states are revealed by individual LEDs. And it's small enough to be held in one hand, leaving, your other hand free for adjustments. Cat Q-1272

Adjustable threshold for DTL/TTL or CMOS circuits.
Two modes of operation: pulse (with time stretching so you don't miss quick pulses!) and mem (holds display until cancelled).
Low circuit loading (approx. 30uA input)
Tested to 12.6MHz.

Shipping weight: 96g Carton size: 230 x 120 x 20mm

Absolutely Safe!

AC Voltage Finder

An absolutely essential piece of test equipment for electricians, maintenance workers, amateurs, hobbyists, etc. etc. When we say absolutely safe, we mean it: this sensor works by sensing the electromagnetic field — no connection to the cable under test is required AND it works through insulation.

Senses any AC voltage above approx. 60 volts with both a visual (LED) and aural (buzzer) indication. It can detect the difference between active and neutral/ earth to tell you which one "bites"! Cat Q-1530

- Pocket size with pocket clip
- Battery operated (lasts for years
 NO CONNECTION TO CIRCUIT
- UNDER TEST REQUIRED
- Operates through many levels of insulation
- Great for finding breaks in cables, too.

Specifications:
Minimum detection voltage approx. 60V

Size: 135mm long × 15mm dia.

Power source: 2× G13 batteries
Checks: cables, fuses, circuit breakers, outlets, etc. by determining whether AC is connected.

An age-old problem

12V Auto **Voltage** Checker

One of the most difficult items to electrically check is the good old car. Everything is plugs and sockets - they make it so hard to get at! Here's the easy way: the cable-piercing checker. Just slip it over the cable concerned, slide the needle point through the insulation and presto! 3 led scale gives low, mid or high voltage reading. Also checks spark plugs and leads. Cat Q-2000

- No batteries required (powered by
- A must for the home mechanic or
- auto electrician Handheld — only 165 × 22 × 17mm

Specifications:
Measures in three ranges, all indicated by LEDs: ow — up to 3V Medium — up to 12V Good — up to 13V plus HT (indicated by neon)











Ideal for photographers, video users, laboratories — anywhere there's a need to measure light quickly and accurately! The DSE Digital Lux Meter is fantastic value — you'll pay twice as much at a photo store. Accurately measures up to 50,000 LUX over three range selections and comes complete with it's own carry case! Cat Q-1400

• 0-50,000LUX • Auto Zero • Low Battery Intercent • 13mm Display • 150-200 Hours Continuous Use

Shipping weight: 195g Shipping size: 130 x 80 x 40mm

Even measure windspeed!

Imagine the applications: boating, sporting, scientific, commercial, aviation... now you can get a highly accurate measurement of true windspeed in the palm of your hand! Measures speed in knots, miles per hour or metres/second - and displays results on a 3 digit LED display. Sapphire jewel bearings for minimum resistance, maximum life. Complete with lanyard, pouch and comprehensive instructions. Cat Q-1405

Specifications:

Accuracy: normally 3% maximum (4% on "knots") Range: 99.9 mph, 87.9 knots, 8790 feet/min, 44.8 m/s

Size: 29.5 x 66 x 118mm Weight: 85g Shipping weight: 95g



\$459

E-Z Cable Checker

The name says it all! Every roadie, every band in the world needs one of these. Even the amateur sound recordist, club or church PA operator — anyone involved in audio cables will find the E-Z Check invaluable. Simply plug your cable in — Cannon, 6.5mm mono or stereo, RCA or BNC — and a series of LEDs tell you if it's okay. Imagine the time savings when searching for that elusive cable fault. Works equally well with patch cables having different connectors on each end (eg Cannon to RCA). Requires only single 9V battery (not included). Rugged, heavy-weight steel case

with heavy duty non-scratch rubber base. Cat Q-1532

Specifications:

3-pin checking for Cannon and Stereo 6.5mm 2-pin checking for RCA and BNC Push-button LED indication

Power: 9V battery

Unit size: 138 × 90 × 70mm Shipping weight: 728g Carton size: 160 × 115 × 80mm



TEST-EQUIPMENT

Professional Quality... **Professional** Performance:

6.5MHz CRO

oscilloscope is: probably the most useful piece of test gear you can own

Here's what it offers:

- Retrace blanking for a much clearer
- 10mV per division vertical sensitivity 250mV/division external horizontal
- sensitivity

 10Hz to 100kHz, plus external timebase
- Internal or external sync
- Useable response to beyond 6.5MHz

Ideal for the shack, the work bench, in service work, in the classroom and also electronics (apart from the tube!) means fast warm-up and extremely low drift.

Specifications:
Vertical bandwidth: DC to 6.5MHz (-3dB)
Attenuator: 1/1, 1/10, 1/100 and ground
Horizontal sensitivity: 250mV/div or more
Timebase: 10Hz to 100kHz
Sync: External or internal
Input Impedance: 1 Meg/35pF
Shipping weight: 4.2kg
Carton size: 400 × 200 × 250mm

20MHz Dual Trace CRO

with inbuilt component checker

You could buy one of those big-name oscilloscopes (the ones with the big-name price tags) and you probably wouldn't get all the features of the DSE CRO. It's a fully professional quality dual trace model offering outstanding performance for the

- 20MHz bandwidth (-3dB)
- Use in single or dual trace mode Dual trace in chopped or alt mode
- Complete with 2 probe sets
- Inbuilt component checker for capacitors, inductors, transistors, diodes, zeners, etc.
- And much, much more! Shipping weight: Approx. 10kg Carton size:530 x 320 x 430mm

Specifications:
DC-20MHz (-3dB), with less than
17.5ms rise time and 3% overshoot
Deflection: 5mV/div to 5V/div in 10
calibrated steps (1-2-5 sequence)
Accuracy: +/-3%
Timebase: 0.1us/div to 2/div in 20
calibrated steps (1-2-5 sequence)
Uncalibrated control to at least 5/div
Triggering modes: peak or normal from
either/both channels or external
Trigger Sensitivity: 0.5V/div
Sweep delay: 0.1us to 10ms in 6 steps

Transistor Dip Meter

Anyone working with RF circuits will tell you one of the handiest pieces of test gear to have around is a "dipper": an instrument which detects resonances by showing a "dip" in a meter. The advantage is no physical circuit connection is required (it works on inductive or capacitive coupling) so a dipper is ideal for working on live RF circuits. At last there's a Transistor Dipper which won't break the bank - but has performance and specs right up there with units costing \$\$\$ more. The ARRL tells what to look for in a dipper — mechanically and electrically stable, good coils, a headphone connection and battery operated. The DSE Transistor Dipper satisfies all these requirements and more! Cat Q-1335

Specifications: Frequency range: 1.5 to 250MHz Frequency selection: 6 colour coded plug-in coils Crystal Oscillator: 1.15MHz


odulation: Approx. 2kHz sine was supply: Internal 9V battery

Especially for 27MHz CB:

Power, SWR & built-in **Field** Strength

Find out all about the set output, the antenna SWR, even the directional qualities of the signal (great for mobile installations), 50 ohm meter can be left permanently in-line or taken out for field strength measurements. Full instructions are provided to make sense of the readings — even for the non-technical person. Cat Q-1350

Specifications:
Power: 10W full scale
Frequency: 28-30MHz
Impedance: 50 ohms
Connectors: SO-239
Unit Size: 57 × 55 × 64mm
Shipping Weight: 390g
Carton Size: 105 × 90 × 70 mm






60MHz ×1/×10 CRO Probes (pair)

Anyone who owns a dual trace CRO will appreciate this! Universal probe which has ×1/×10 switch, comes with wandering earth lead and insulating shroud in handy plastic pouch. The best news is that you don't get one — but a pair! Cat Q-1247 Specifications:

Specimications: Working Voltage: ×10 — 600V (AC p-p) or ×1 — 300V (DC+AC p-p) Input Capacitance: 13.8pF 72.5pF Input Resistance: 9Mohm 237 ohm Bandwidth: 60MHz

ALSO AVAILABLE!

Single 100MHz Probe. With $\times 1/\times 10$ and all the most used features. Cat Q-1245



Battery Lamp and Fuse Tester

Make sure you're not throwing away a fortune! Checks a huge range of 1.5V-9V cells actually under load: the only way to check them! Even checks NiCads, calculator, watch and photographic batteries. Also checks miniature lamps and cartridge fuses for continuity. Cat Q-1525

Can be used as NiCad battery charger with optional 6V adaptor (M-9525).



Shipping weight: 200g Shipping size: 100 x 90 x 70mm



DC Bench Ammeter

The ideal economy benchtop meter. Measures current in two ranges: 0-5 & 0-10 amps DC. With easy to read 80×80 sloping scale so its great for demonstration work With 4mm banana terminals. Cat Q-2130

Size: 140 × 110 × 100mm



Bench Voltmeter Cheaper and more convenient than a

multimeter... perfect for schools, demonstration, etc. Measures voltage in two ranges: 0-20 & 0-10 Vdc with ±2.5% accuracy. Large scale 20 volt scale is easy to read at a glance so it's ideal for automotive service and test applications. Cat Q-2140

Size: 140 × 110 × 100mm **Shipping Weight 340g**

MODEL 181







Quality Screwdrivers

High impact, chrome vanadium blades and insulated handles makes these just the thing for electrical work. Tradesperson or hobbyist, there's just the thing for that hard to get screw.

Mini Drivers

Mini is right! Just the size for precision models, turntable cartridges, etc. At our low prices you can afford to buy a couple in case you lose

Flat Blade: Cat T-6010 Philips: Cat T-6015

Size: L 30mm D 1.6mm H 25 x 7mm

Shipping weight: 5g 95 ca.

Stubby **Drivers**

Great for confined spaces —or that tough screw which needs extra muscle. You can really get a grip on these! Flat Blade: Cat T-6020

Philips: Cat T-6025 Size: L 38mm

D 6mm H 45 x 30mi Shipping weight: 50g

Standard

Ideal for general purpose electronic work. Spot-on for 1/8 whitworth!

Flat Blade: Cat T-6030 Philips: Cat T-6035

Size: L 75mm

D 3.2mm H 57 15mm Shipping weight: 30g

Popular

The best "all-round" size for most jobs. Our most popular

Flat Blade: Cat T-6040 Philips: Cat T-6045

Size: L 100mm D 5mm H 74 x 16mm

95

Shipping weight: 75g

Medium Duty

Big enough to get a good strong grip and plenty of leverage. Add this to the rest of the range and you've got the right tool for just about

Flat Blade Cat T-6050 Philips Head Cat T-6050

Blade Size: 150mm × 6.5mm (D:5mm) Handle: 95 × 25mm

Heavy Duty

Everyone needs a big gun sometimes! Strong enough for the toughest work -ideal for the tradesman.

Flat Blade: Cat T-6060 Philips: Cat T-6065

Size: L 200mm D 7mm H 100 25mm Shipping weight: 100g

Baby **Driver Set**

Handy plastic wallet containing 5 of the most widely used drivers:

2.6mm flat blade 1.6mm flat blade jeweller's

"00" size Philips

Ideal for electronics, model makers, repairs, etc. Cat T-4340

4mm spintight

Shipping weight: 75g Pack size: 160 x 90 x 10mm



21 Piece Metric **Utility Set**

This set has to be seen to be believed. 20 piece nickel chrome molybdenum steel with chrome plated handle presented in a handy transparent plastic box.

The set includes:


3 blade screwdrivers — 1.5, 2.5, 3.5mm 2 Philips screwdrivers — No. 1 and No. 3

Hex Allen keys — 1.5, 2.0, 2.55mm

5 open end spanners — 4.0, 4.5, 5.0, 5.5, 6.0mm 5 spintights — 3.0, 3.5, 4.0, 4.5, 5.0mm tommy bar 1 awl 1 handy assembly

You will be proud to have this excellent quality set in your tool range. Great value for money! Cat T-4365

Shipping weight: 153g Pack size: 130 x 85 x 20mm



10 Piece Mini Tool Kit

There's even a hammer in this one! Mini kit is just right for repair and general hobbyist work. And if it doesn't work... use the hammer! Cat T-4380 Containe

2 flat blade drivers, 2.0mm and 1.4mm

2 Philips drivers, size 02 and 03

• 1 magnet

1 3-prong catch

1 magnifying glass

• 1 mini hamme

1 pair tweezers

Shipping weight: 190g Pack size: 150 x 100 x 22mm

IC Insertion Tool

Don't damage fragile IC's: this IC insertion tool keeps the pins shorted together and in the right place while you get the right position. Handles 14 and 16 pin IC's in standard DIL package.

Shippping weight: 20g Pack size: 105 x 20 x 10mm

Steel Rule

300mm hardened spring steel with deep etched black graduations. Non-rusting, complete with plastic sheath. Cat T-5145

Shipping weight: 50g Pack size: 350 x 35mm x 2mm



6 Piece **Precision Set**

These chrome plated screwdrivers are presented in a plastic storage case. A free running top on each driver gives operator ease of blade drivers from 1.4mm to screwdrivers, No. 0 and No. 1. these are quality screwdrivers at a low price and a very handy set to have around. Cat T-4360

Shipping weight: 148g Pack size: 130 x 70 x 20mm



Allen Key Set So here's an ideal set for

the workshop. 7 gunmetal finish Allen keys in a plastic wallet. Sizes 1.4mm, 1.5mm, 2mm, 2.4mm, 2.5mm, 3mm, 4mm. They are ideal for most European and Japanese equipment that have Allen screws. Cat T-5080

Shipping weight: 35g Shipping size: 100 × 55 × 5mm

\$425

Deluxe Pin Vice

Stored inside the body are two double-ended locking collets that can be used to hold anything from 3mm diam. down to virtually nothing. That could be small drills (fantastic for drilling PCBs!), screwdriver blades (now you don't have to throw broken blades out!) awl points, scribers, reamers, needles and pins, etc. etc. Cat T-5115

Shipping weight: 55g Shipping size: 70 × 150 × 15mm

IC Extraction Tool

The perfect way to remove IC's without damage. Works with all DIL packs, no bent pins and no static damage! Operates like a pair of tweezers hooks! Cat T-4650

Shipping weight: 20g Pack size:

100 x 175 x 10mm





Screwdriver Very handy little item to have around: it's a standard flat blade screwdriver, but inside is a neon indicator to warn you of dangerous voltages. Operates from about 90 volts (AC or DC). Ideal for anyone working with mains circuits. A life saver! Cat T-4005

Shipping weight: 16.5g Pack size: 120 x 20 x 20mm





This has to be one of the most useful. safest tools we've ever seen. Detects the presence of AC voltage above 60 volts — And it doesn't rely on contact!

AC Electric Finder

Gives sound and visual warning. distinguishes between positive negative and earth and requires single handed operation. With one of these in your toolkit finding live wires and faults is easy and SAFE! Batteries last for years. Cat Q-1530

TV Alignment Kit A versatile set of four general purpose tools

to cover all shapes and sizes of cores. They are made from tough plastic. Ends suit hex cores from 2 to 3mm plus slotted cores from 1.5 to 2.5mm. Cat T-4540

Shipping weight: 21kg Shipping size: 250 x 80 x 0.5mm

Screwdriver Type

Ideal for handyman and TV technician this plastic screwdriver has a steel spring tip. Suitable for trimmers and mini IF's. Cat T-4520

Shipping weight: 12g Pack size: 260 x 10 x 10mm





Curved Needle Nose

30mm long blade with 5mm curved ends. Point is under 1mm across so they're great for really fine work. 105mm long overall. Cat T-3251

Pack size: 141 x 119 x .130mm Shipping weight: 50g

Economy Range Stainless Steel Tools

Especially selected range offering the hobbyist a great selection — at an affordable price. Quality construction with toughened cutting edges for long life, heavily insulated grips in a range of yuppie decorator colours, removable springs, and so on. And they're priced low so the hobbyist can afford them (professionals can get tax deduction on more expensive tools!)

Straight Needle Nose

Similar to above, with even finer end! They're even better than pointy tweezers! Cat T-3252

Flat Nose

Serrated edge blade with wide (3mm) flat ends — ideal for holding those awkward nuts and bolts! Similar size to above.

ALL ONE PRICE

Tweezers § **Pointed**

Great for holding small nuts, components and delicate instruments, wires, etc. Also great for removing ticks! Fine points. Cat T-4620



Serrated Jaw

Has flat serrated jaw for positive grip. Shipping weight: 20g Unit size: 130 x 10mi

Economy Wire Stripper

Large adjustable range. Hardened jaws will last a long, long time. Great value at around half the price of other makes.



Deluxe Wire Stripper

A completely automatic wire stripper. Only one hand operation is required to complete stripping operation. The multiple sized head allows a wide range of wire from 1mm to 3.2mm to be stripped. Ideal for servicemen, TV technicians, hobbyists etc. Cat T-3620

Shipping weight: 300g Carton size: 180 x 90 x 30mm

Scissors Clamps

Made of stainless steel with screw joint. These scissor clamps are 127mm long so they will reach hard-to-get-atplaces. They can be used as a third hand for small items as they can be locked on to the articles they are holding.

Shipping weight: 25g Pack size: 125 x 70 x 10mm

Universal Tweezer Quartet

What ever you want to tweeze, this'll do it! 4 different 110mm tweezers with fine pointed blades, with flat blades, curved tips and even reverse squeeze (squeeze to release!). All housed in plastic wallet.

Shipping weight: 75g Pack size: 100 x 210 x 10mm

Pearl Catch

For reaching into awkward places. 3 pronged tweezer with syringe action. A must for small nuts, washers, etc. Great for servicemen, jewellers, hobbyists, etc. Cat T-4660

Shipping weight: 30g Pack size: 70 x 170 x 10mm



Economy Wire Wrapper/Stripper

simplest! That's the case with this 'nofrills' wire wrapping and stripping tool: puts professional style wire-wrapping techniques within reach of the average hobbyist, Cat T-3650

Shipping weight: 40g Pack size: 100 x 175mm x 10mm



Sometimes the best tools are the

Needle Nose Pliers

Tweezer-like ends for reaching into almost inaccessible places and flat blades so delicate components won't be damaged. 40mm long blades with 15mm opening at end. Cat T-3266

Shipping weight: 150g


Flat Nose Serrated Pliers

Fine (2.5mm) ends with serrations along blade mean extra grip when you really need it. 12.5mm opening with 40mm long blades. Cat T-3267 Shipping weight: 150g

Famous Piergiacomi Hand Tools... available from DSE!

are known for their outstanding quality and reliability. They're the choice of professionals - and now DSE has available this superb range. Expensive? Yes, they do cost more than our hobbyist range; but once you feel the quality, feel the precision, you'll realise they're worth every cent! There's a Piergiacomi for every purpose... all tools feature heavily insulated handles with sprung action blades and locking bush.

MADE IN ITALY



Cutting Nipper with back-angled cut

Designed especially for pcb soldering work. The cutting edge is on the opposite side to normal allowing a 1mm pigtail to remain ready for soldering — or allowing clearance of the soldered joint if you trim the pigtails after soldering. Clever - and it works! Blade opening 7mm, handles up to 1.3mm copper wire. Cat T-3261

Shipping weight: 150g

\$1695

Cutting Nipper with standard cut Ultra-precision cutter with standard angled blades allowing

completely flush cutting. Special safety feature: spring in blade prevents flying pigtails. Blade opening 4mm, cutting capacity 1mm

Shipping weight: 150g

Inclined Frontal Cut Nippers

Very easy to handle, allowing leads to be cut 1.5mm from plane perfect for soldering or to clear soldered joint. The blade tip is angled at 30° to allow access to tight spots. Blade opening 9mm, cutting capacity 1mm copper wire. Cat T-3263

Shipping weight: 150g



\$4695

\$095

Inclined Cutter and Bender

Two birds with one stone! Not only cuts the pigtail, but bends it away from pcb so the component won't fall out. Fantastic! Makes pcb assembly a breeze — and solves one of the biggest bugbears of hobbyists! Blade opening 6mm, cutting capacity 1mm copper wire.

Shipping weight: 150g

Shears



0

\$095

For larger cutting jobs — like mini scissors but with the extra strength needed to get through metal, plastics, etc. 18mm length blades means they'll handle coax cable, etc. Blade opening 10mm, cutting capacity 1.6mm copper wire. Cat T-3265 Shipping weight: 150g





Lug Crimping Tool

quick and reliable connections, crimping beats soldering anytime! Do it easily with this versatile crimping tool - it also cuts and strips wire! Complete in pack with lugs ready to use. Great value and a must for your workshop! Cat T-3520

Shipping weight: 180g Pack size: 85 x 250 x 10mm



Ripper Nipper

Our most popular nipper: high Japanese quality with box joint and hardened cutting edges, with insulated handles for electrical work. 15mm blades opening to over 10mm. Overall length length 10mm. Cat T-3561

Shipping weight: 60g Pack size: 100 x 175 x 10mm



68 piece Multipurpose Repair Kit

multimeter? This set hase everything else - and then some! Auto electric checker (6-12-24V), heavy duty pliers, crimp terminal set... with 60 assorted crimp lugs, insulation tape, even connecting wire!. A must for the hobbyist, technician - or even the



Shipping Weight: 1050g Carton Size: 150 × 310 × 47mm

38 piece Deluxe **Repair Kit with Multimeter**

Everything for quick and easy wiring repairs — with no soldering! Ideal for automotive and hobby use. Here's what you get: • Multimeter • Crimp Tool • Pliers • 2 Screwdrivers • Neo Tester (rated to 500V) • Selection of crimp lugs. All in a handy, heavy duty carrying case. Perfect for throwing in the car — just in time! Cat T-4832

Shipping Weight: 1100g Carton Size: 170 × 325 × 42mm



for the car!

210 Piece Solderless Terminal Set

Multipurpose solderless, insulated terminal set that's ideal for hobbyists, technicians, automotive use, etc. Includes spade terminals, ring terminals, male/female push-on, bullet, hook and butt connectors. In handy, 18 compartment plastic case for easy selection. Cat T-4828



Nibbling Tool



Shipping Weight: 220g Carton Size: $180 \times 115 \times 20$ mm

High Speed Mini Drill Kit

MINIATURE TWIST DRILLS Suitable for PC Board work

0.8mm Cat T-4825 1.0mm Cat T-4820 1.1mm Cat T-4819

For the hobbyist, technician, toolmaker, etc... this superb mini drill kit is hard to beat. Very high speed — up to 30,000 rpm (depending on voltage used) with a high torque, it's great for drilling, polishing, grinding, deburring, engraving, routing, buffing, carving, sanding, etc, etc. Kit comes complete with four high speed steel twist drills, three collets, grinding bit, spanner and tommy bar, plus DC power cable and plastic case.

- 12-35V DC operated (external)
 Chuck sizes 0.4-1.5mm, 1.7-2.9mm, & 2.8-2.4mm.
 Weight only 400g, size 105mm × 42mm diameter.



Computer Service Kit

Anyone who owns or works with computers will find this invaluable! 12 piece computer service kit with just the right tool for all those awkward repairs, services, etc. With IC inserter and pin straightener, IC extractor, 3-claw holder, tweezers, philips and flat-head screw drivers, nutdrivers, reversible torque screwdriver, needlenose pliers... and it's all in a handy zippered case. Cat T-4839

Size: 230 × 155 × 35mm

21 piece Tool Kit



WHAT AN ASSORTMENT

22 individual pieces in a handy plastic pack (you'll never lose them!): • 5 open ended spanners 4.0-6.0mm • 2 Phillips head screwdrivers • 3 Allen key drivers • 5 nut drivers 3.0-5.0mm • 5 flat screwdrivers • 1 tommy bar. Quality made - a complete set for the hobbyist or technician. Cat T-4830

Shipping Weight: 575g Carton Size: 340 × 150 × 22mm

Tapered Reamer

An ideal tool for enlarging holes on thin metals, plastics, wood, etc. Great for chassis bashers, hobbyists, servicemen. Made from the highest quality heat treated steel, comes complete with tommy bar. Tapers from 4mm to 22mm. Cat T-4920

Shipping Weight: 170g Carton Size: 200 × 75 × 25mm



ARLEC

What versatility! It sands. It polishes. It engraves. It erases. It mills. It's one of the handiest tools you can have in your arsenal! This fantastic hobby machine is a 10,000 RPM power tools you can have in your arsenal! Inis tantastic hobby machine is a 10,000 RPM power head which does all of the above with the attachments supplied. And because it operates from low voltage (240V plugpack included!) it's safe. Includes the Supertool and plugpack, 2 milling cutters, 1 wire brush, 1 grinding wheel, 4 high speed drills, 5 chuck collets (0 to 4mm), eraser sticks and instructions. Cat T-4754

Includes 240V Plug-Pack Adaptor

Complete with ON-OFF switch on the body for convenience.

ONLY \$6995

Shipping Weight: 1.068kg Carton size: 260 × 210 × 60mm

Supertool Accessories:



Set 4 PCB **Drills**

Top quality high speed steel twist drills in all popular PCB sizes: 1.2, 1.0, 0.8, and 0.6mm. Cheaper than buying singly! Cat T-4756

\$895



Grinding **Bits**

Shape, sand and grind your projects to per fection. 3 pieces, different shapes. Cat T-4758



Cutting Discs

Set of 6 mini cutting discs, with arbor, for cutting metal and plastic. Essential for the serious hobbyist.

95 Set of 6



Engraving/ Milling Bits

Set of three cutters designed to make short work of any engraving or milling job. Fine and medium hex head plus fine round head. Cat T-4764



Erasers

Make short work of rubbing out! Two different types to cover both ink and

Set 5 ink Cat T-4760

Set 5 pencil \$4.95



Pack of 3 wire brushes for polishing, cleaning, etc. Cat T-4768

Arlec Mini

Need a third hand? Here's one that won't let go! The mini vice from Arlec attaches to any table, desk, bench, etc. (up to about 40mm thick). 50mm wide jaws hold tight — opens up to around 60mm for those big jobs. More than strong enough for cutting, filling and other testing applications. Cat T-4748

Shipping Weight: 500g Carton Size: 250 × 170 × 60mm

\$**45**95



Compartment Case

Made of extremely strong plastic, with clear lid so you can see exactly what's inside. The internal compartment holders move so you can suit it to a huge variety of parts, nuts and bolts, bits and pieces, etc. Sliding catches ensure the lid stays closed: even if you drop it! Consists of case and two tiers of trays and one extra deep tray. Size 290 × 220 × 45mm. A must for the hobbyist. Cat H-2596

Shipping Weight: 902g Carton Size: 290 × 220 × 45mm

Save \$23.00



Arlec - Easy Etch Engraver

You know how easily tools and valuables go for a walk — never to be seen again! Well, here's a great way to identify them.

Steel bit lets you engrave metal, plastic, wood, etc with your name or a security number (your driver's licence number is a good one) for positive identification. Comes with 12V plug pack

and long cord. Cat T-4753



Stackable Drawers

Total flexibility: that's the superb drawer system from Dick Smith Electronics. Large (114 imes57 × 130mm) cases containing either one or two drawers. Precision dovetail system means you can stack them both vertically and horizontally. Large handle on each drawer plus index

One drawer per box: Cat H-2584 Two drawer per box: Cat H-2585

Both types:

Shipping Weight: 172g Carton Size: $114 \times 57 \times 130$ mm



SOLDERING

The Professional 'Pocket' **Soldering System**

The totally portable professional soldering system fr Portasol. The equivalent of 10-60watts of power with temperature adjustment up to 400 degrees Celsius

Just the thing for hobbyists, technicians, repairers. anyone who needs to make repairs, alterations, etc on

- Look at what you get! —

 Pocket sized, temperature adjustable iron
- 4 Tips including hot knife and blow torch!
- Tip cleaning sponge
- · Heavy duty plastic case with clip-on iron stand
- Butane powered refills in seconds

 Average 90 minutes continuous use Cat T-1374 Spare tip to suit Cat T-1375 \$12.95

95 Butane **Soldering Iron**

Unit size: 172mm long x 20mm diam Shipping weight: 80g

Just the size of a marker pen - ideal for

on-the-spot repairs.

Blister pack size: 100 x 300 x 25mm

Spare tip to suit: Cat T-1371 \$12.95

Totally portable, 'all-in-one' soldering iron that fits easily in a shirt pocket... and it's made in Ireland no joke! Uses refillable 'butane' - the type used in ordinary cigarette lighters. Provides an amazing 60 minutes continuous use at a full 60 watts. Simple 'finger-thumb' turn adjustable temperature control provides an equivalent to 10 to 60 watts: enough for a variety of repair jobs. Detachable cap features a built-in ignition system which uses replacement flints. Ideal for servicemen, handymen and hobbyists... the best thing to come out of Ireland since the 'snakes'! Cat T-1370

Quality 30 Watt 12 Volt Iron

Start talking quality soldering irons and you'll find yoursel talking Australian made Weller. This 12V 30 watt model gives you plenty of power (anything less and you'd never get the job done) for those on-site repairs, etc.

Lightweight, it comes with battery terminal clips and has replaceable

Spare Tips To Suit. Cat T-1321/22 \$395 ea.

Varitemp Iron

The experts will tell you no two solder jobs are the same: some need high heat: use the same on some semis and you'll cook them! Here's the answer: Variable temperature — the right heat for every application! And the temperature adjustment is right there on the handle: that's convenient! Interchangeable tips means total flexibility. Cat T-1350


Features:

- 25 watts total capacity
- 240V operated
- Stainless steel
- Electricity Authority Approved

Accessories to Suit:

Spare Tip (medium) Cat T-1351 \$4.95 Spare Tip (large) Cat T-1352 \$4.95 Spare Tip (conical) Cat T-1353 \$4.95

Shipping weight: 75 g Blister pack size: 345 x 150 x 50mm Iron length: 210mm



DSE Low Voltage Heavy Duty 12V Iron

30 watts capacity means this iron is ideal for all those electrical repair jobs around the car, caravan, etc. Comes complete with 2 metre cable car cigarette lighter plug, ready for instant use. Or use it around the home with virtually any 12V supply — AC or DC (anything over 2.5A is ideal). Balanced grip and lightweight, great for pcb assembly and other general electronics work too. Cat T-1910

Iron length: 230mm Shipping weight: 120g Blister pack size: 300 x 160 x 30mm

Tip to suit Cat T-1913 \$1.50

DSE Mini

Super slim 6W iron - with quick heating capability - just the thing for precision soldering on computers, PCBs, etc. Even plugs into your car's cigarette lighter with optional cigarette lighter plug for easy auto repairs. Low voltage: 12V AC or DC @ 500 mA. Cat T-1920

Shipping weight: 45g Blister pack size: 272 x 77 x 25mm Iron length: 150 mm

Replacement Tips

Copper Wedge Cat T-1921 \$3.95 Copper Conical Cat T-1922 \$3.95

DSE Hobby Iron

A general purpose mainspowered iron for project building. service and repairs and other low-heat work. Iron element is rates at 15 watts so is ideal for the hobbyist - too much heat cooks some components! Made for DSE by Weller, iron comes in blister pack complete with detailed soldering hints on back.

Shipping weight: 233g Pack size: 110 x 300 x 40mm



Spare tips to suit: Pack of two. Cat T-1312 \$4.95







Scope Cordless Solder Gun

For soldering where you want it, when you want it. Powerful enough to handle the same jobs as 60W mains irons, but inbuilt NiCads give you up to 100 solder joints away from power points and extension cords. Includes plugpack for overnight charging; heats in just six seconds and takes standard Miniscope spares. Supplied with charger, two spare elements and two spare bits. Cat T-1600

Shipping weight: 66g Carton size: 70 x 50 x 30mm

Scope Transformer 3.3V at 30A

Made just for Scope Irons — low voltage means less danger of damage to sensitive components. And there's an electrostatic shield for even more protection. Tough polypropylene case complete with iron

Shipping weight: 1.7kg Carton size: 163 x 83 x 105mm



Adcola RS-30

Reliable iron for general service or production area and ideal for the hobbyist. High impact orange plastic handle and complete with Triciad 3mm long life tip. Cat T-1820

Shipping weight: 220g Blister pack size: 340 x 140 x 50mm Iron length: 205mm



Adcola RS-50 For those heavier soldering jobs this

Adcola is ideal: service work, assembly, etc. Has heavier element for more power (16 watts) and a larger long life Triciad 5mm tip. Thousands of Adcolas are used in electronics every day. Cat T-1825

Shipping weight: 225g Iron length: 205mm



Adcola Duotemp

Professional quality - at a hobbyist price. The Duotemp has two temperature settings normal for everyday service and assembly work, plus a bush button "boost" for fast heating or heavy duty soldering. And a vaof tips for specialist applications is available. If you don't need a variable temperature iron, the Duotemp could be just what you need. Rated at 21 watts, 240V AC. Cat T-1830 Shipping weight: 227 g Carton size: 345 x 145 x 50mm





DSE Solder Station

A professional soldering station at a hobbyists price!

If you're serious about good soldering, there is only one way to do it — with a temperature controlled soldering iron. Until now, temperature controlled irons have been expensive. But Dick Smith Electronics have solved the problem! The DSE Auto Temp offers you the best quality at an unbelievable low price. Features fully variable control (from around 200° to over 500° Celcius) with a temperature meter temperature control (from around 200° to over 500° Celcius) with a temperature me to show you what's happening. And it's fully approved by the Energy Authority. The station comes complete with lightweight iron holder and cleaning sponge, with a comprehensive instruction manual with full servicing information included - just in case you need it. Cat T-2000

Shipping weight: 1.75kg Carton size: 225 x 90 x 180mm

Quality Accessories to suit

Tip medium chisel Cat T-2002 \$5.95 Tip thick chisel Cat T-2004 \$5.95 Tip fine conical Cat T-2006 \$5.95 Element and barrel Cat T-2008 \$19.95 Sponge replacement Cat T-2010 \$1.95

Tips for older stations: Tips with solder to suit earlier model

Medium Cat T-2003 Thick Cat T-2005 Fine Cat T-2007 All one price

Royel Professional Soldering Station

When quality really counts you need the best you can get. Royel is it: temperature sensing is done right at the tip for instant reaction — and the zero voltage switching regulator means no interference and perfect control. Cat T-2050

Complete station includes:

• Control Unit with 200° to 400°C range

- CT6-1 pencil iron with "Armclad" tip and rating equivalent to 50 watt conventional irons
- Auxillary ground clip lead
- Sponge & well

Instructions

\$499




Shipping weight: 2.6kg Carton size: 310 x 295 x 155mm

Fine Cat T-2051 Large (Bevelled) Cat T-2054

All one price \$595

Multi-purpose Stand



Holds boards or components firmly in rubber faced vice. Angle of vice may be varied widely in three dimensions for greater accessibility to board. Convenient soldering iron holder also adjustable. Adjustable spool holder for solder & desoldering wick. Ideal for the hobbyist or professional. Leaves both hands free. Cat T-5700


Leaves both hands free.

Half Price

Shipping weight: 1.7kg

Carton size: 250 x 185 x 45mm

Soldering **Iron Stand**



Few things are more dangerous than a hot soldering iron left on a bench! Solve the problem with the DSE soldering iron stand. Suits most medium size irons — DSE or other brands. Very stable cast base with tip cleaning well, large plated spring steel coil to keep the hot tip safely out of harms way. Base has screw holes to fix to bench if required. Cat T-1302

Replacement Sponge Cat T-2010 \$1.95

Shipping weight: 305g Carton size: 160 x 65 x 122mm

Soldering Accessories

Desoldering



Simple and efficient. Simply squeeze bulb, hold up to molten solder and release bulb. Solder is sucked straight up. Use for blow cooling too! Cat T-2580

Shipping weight: 58a

Carton size: 135 x 40 x 40mm

Solder Sucker



Teflon tip and a nozzle sweeper as well. Light thumb release mechanism for the removal of solder from the board. Don't pay twice the price — a top quality import from Dick Smith Electronics. Cat T-2560

Spare Teflon Tip to suit \$3.95

Shipping weight: 110g

Pack size: 88 x 320 x 25mm

Soldering Aid



For anyone working with pcb's this is an essential part of the tool kit. In a handy plastic pouch, you get:

- · Fine point and slotted end probe
- Scraper end and wire brush probe
- Angled scriber and scraper probe Aluminium heatsink

Protect your valuable components while soldering — and make solder joints that last - with this low-cost set.

Pack size: 190 x 95 x 10mm

Desoldering

Desoldering made simple! Specially treated copper braid soaks up solder like blotting paper... just melt the solder with your iron and apply the braid. Capillary action takes the solder into the braid — just cut off the solder-filled section. Very convenient roll package. Cat N-1682

10 up \$2.65

Shipping weight: 156g Carton size: 160 x 20mm



Solder



Hobby Packs

Just the right amount of solder for the average project (eg an amplifier board, alarm, etc). And because some constructors favour a thicker gauge, we have both 0.71mm and 1.25mm packs. Top quality electronic grade (Corrosion

0.71mm (22g) hobby pack (9 metre length) Cat N-1636 Both sizes:

Shipping weight: 30g

1.25mm (17g) hobby pack (4 metre length) Cat N-1638 10 up \$1.75

Shipping weight: 40g

50mm Solder Rolls

Same solder as in above hobby packs, but on 200g bulk rolls. Ideal for the workshop, lab, production line, etc. **Both sizes:**

5 up \$6.00

50mm roll containing -200 grams of 0.71mm (22g) solder.

50mm roll containing

200 grams of 1.25mm (17g) Solder. Cat N-1619

Complies to AS1834 Australian Standard



ALU-SOL

Aluminium-based solder for soldering dissimilar metals particularly aluminium and alloys, (if you've ever tried it with conventional solder you'll know how hard it is to do!) Alu-Sol is specially made for the purpose — it requires no other flux or special preparation. All you need is a good, hot iron (hotter than normal soldering).

50mm roll containing 100 grams of

1.6mm (15g) Solder.

Cat N-1625

Shipping weight: 110g 10 up \$10.95 **Heatsink** Clip Set

\$695

Spring loaded, plier grip clips for heat sensitive components and leads. Made of aluminium for high thermal conductivity, 2

types one straight and one angled, both 75mm long! Cat T-2620 Shipping weight: 20g

Carton size: 170 x 80 x 0.5mm

Top Quality Solder Aid Set

When there's no room for error with your PCB work and you need to be certain the job's right - you'll want the best quality tools.

You can even use this one for re-stringing dials. made from the highest quality materials so you know it'll give you years of reliable service. Cat T-2610

Contains

- Guide fork tool
- Reamer point and knife point
- Scriber
- Heatsink clip
 Stainless steel bristle brush
- In handy plastic pouch







LECTROLUB

Clear **Acrylic** Spray

A fine colourless spray that is ideal for the protection of front panels, etched screen print or Letraset lettering. Will moisture proof components. TV aerial terminations etc. 125g can. Cat N-1011

\$595



Matte Black Spray Paint

A quick drying matte finish paint, also ideal for touchup. Gives your project a really professional finish. Also used to increase thermal efficiency of plain aluminium heatsinks. Great for car touch-up too. 175g spray can. Cat N-1070

\$**2**95



Matte Silver Spray Paint

Anti-glare silver paint for a smooth, elegant finish to that special project. Quick drying paint is ideal for front panels, cases, etc. 150g spray can. Cat N-1076



Nickel Screening **Spray Paint**

A nickel-based paint coating for electromagnetic and radio frequency interference (EMI/RFI) applications. Resistivity of 0.7 ohms per square metre at 50 microns thickness. Takes to large range metals, plastics, etc. 200g spray can. Cat N-1049

\$26⁹⁵

CRC 2-26 Spray

A moisture removing, cleaning pressure pack. Not only does it clean, but it also leaves a film of protecting silicone that does not dry out. Ideal for pots, switches and contacts. Ideal for loosening stubborn nuts and bolts. Will protect your car from salt and moisture. Use it on the ignition system to stop frustrations during wet weather starts. 400g. Cat N-1060

250



A highly efficient, high pressure solvent highly recommended for cleaning tuners, switches, plugs and sockets commutators potentiometers, relays, etc. Non-corrosive, low toxicity. Complete with long tube. 300g spray can. Cat N-1040

\$750



Spray Cleaner

Non-toxic, non-explosive and non-flammable cleaning and degreasing spray. It leaves no residue so is suitable for electronic and electrical components as well as computer, tape recorder, VCR's, etc. Complete with long range nozzle. 250g spray can. Cet N-1051

\$495



packaged in pen form with a pocket clip. The pack has a unique retractable tube system to reach into those inaccessible areas. Nondrying lubricant for use with electronic gear, automotive, office and domestic equipment, etc. Ideal for servicemen, Cat N-1047

Butane Gas

Just like the one you use for

your cigarette lighter! 100g

ideal for your Portasol

economy butane refill that's

soldering iron or any butane powered device. Cat N-1081

Refill

Electrolube

2X Lube Pen

The state of the art electro-

mechanical lubricant.

\$650



Heat Sink Compound

This heat transfer compound is applied to the base and mounting studs of transistors and diodes. It is also an effective thermal coupler for any heatsink device where efficient cooling is required.



Circuit Lacquer

A specially formulated spray for the protection of PC boards. This is a solder through lacquer so boards previously sprayed with PCL-2 can be soldered in service. 350g spray can.



Air Duster

550g of high pressure inert gas for cleaning circuit boards, equipment, etc. Ideal for those places you can't get to with a brush or where there's a big risk of damage. Cat N-1050



Permagard Moisture **Displacement**

Displaces water and moisture, penetrates lubricates and provides protection against corrosion. in 250g spray can. If you've already got some in the workshop — put some in the car! Cat N-1065

\$7750



Contact Cleaner Lubricant

Improves electrical contact, reduces wear, suppresses arcing, loosens sulphide and tarnish film, inhibits corrosion and maintains stable low contact resistance. In handy 300g can with spray tube. Cat N-1042

795



Heat **Transfer** Compound

From Electrolube, specialists in chemical service aids to the electronics industry. Heat transfer compound comes in 10ml syringe for easy application. Cat N-1200

Non silicon Non metallic



Freezer

Spray

Instantly freezes components down to minus 50 degrees Celsius! Ideal for servicing electrical & electronic equipment with intermittent problems. Also shrinks shafts, bushes, etc; cools components while soldering. Complete with long reach tube. 350g spray can. Cat N-1056



Silastic 732RTV

Adheres to and seals/ insulates just about anything. Acid curing for an economical joint in rubber, wood, metal, glass, plastic etc. 75g tube. Cat N-1225



Silastic 738RTV

When you need a specialist alant where corrosion or high current is a concern then this Neutral Cure Silastic is just the answ 85g tube. Cat N-1226



Flux Remover

Cleaning excess flux of pcb's used to be a chore: not any more! Spray flux remover dissolves flux, makes it simple to remove. Service work, technicians remove the flux that hides a dry joint. Hobbyists: remove the flux from messy solder jobs! Large 400g spray can.



5000!! Instant repairs for

thousands of applications, No clamping, no fuss Super Glue in 3ml tube. Cat N-1220



Coloured Insulation Tape

Six colours to choose from! 18 metre rolls by 19mm wide for insulating and harnessing wire and looms. Just the thing for colour coding wire. Looks good but doesn't last on the garden hose. Cat N-1359/64

10 up 90¢ ea.



Heat Shrinkable Tape

Just wrap it on wire or joints, apply heat and it becomes permanent, tight fitting insulation. Rolls of Oft in black, 19mm wide, Cat N-1365





	SILIC	ON T	RAN:	SIST		SS		
Type No. BC159 BC327 BC328 BC337	Cat No. Z-1359 Z-2240 Z-2242 Z-2190	Price Ea .20 .35 .30	Price 10 up .15 .30 .25	POI PNP PNP PNP NPN	Vce 20 45 25 45	Ic (mA) 100 800 800 800	P(tot) (mW) 300 800 800 800	Ft (MHz) 150 100 100 200
BC338 BC107 BC108 BC109 BC179 BC549C	Z-2252 (See DS547) (See DS548) (See B549) (See BC159) Z-1329	.30	.25 .35	NPN NPN	25 30	100	500	300
BC639 BC640 BD139 BD140 BD262	Z-1388 Z-1389 Z-1443 Z-1444 (See BD682)	.65 .65 .95 .95	.55 .55 .85 .85	NPN PNP NPN PNP	80 80 60 80	1A 1A 1A 1A	1W 1W 8W 8W	130 50 250 75
BD263 BD681 BD682 BUX80 BF115	(See BD681) Z-1462 Z-1460 Z-2150 Z-1560	\$1.95 \$1.95 \$7.95 \$2.25	\$1.75 \$1.75 \$7.50 \$2.15	NPN PNP NPN NPN	100 100 400 30	4A 4A 10A 30	40W 40W 100W 145	1 1 8 230
BF184 BF199 BF469 BF470 BFR91	Z-1604 (See BF173) Z-1635 Z-1636 Z-1691	\$1.95 \$1.75 \$1.75 \$1.95	\$1.75 \$1.60 \$1.60 \$1.75	NPN NPN	12	36	180	5GH
DS547 DS548 DS549 DS557 DS558	Z-1300 Z-1308 Z-1319 Z-1340 Z-1348	.15 .15 .15 .15 .15	.12 .12 .12 .12 .12	NPN NPN NPN PNP PNP	45 30 30 45 25	100 100 100 100 100	500 500 500 300 300	300 300 300 150 150
MJ2955 MJ15003 MJ15004 MJE340 MJE2955	Z-1800 Z-1808 Z-1810 Z-2010 Z-2005	\$2.95 \$9.25 \$9.25 \$2.25 \$2.25	\$2.75 \$8.75 \$8.75 \$1.95 \$1.95	PNP NPN PNP NPN PNP	60 140 140 300 60	15A 20A 20A 500 10A	115W 250W 250W 20W 75W	4 2 2 - 2
MJE3055 MRF660 PN3563 PN4258 TIP31B	Z-2008 Z-2508 Z-2180 Z-2326 Z-2020	\$1.95 \$34.95 .60 .70 \$1.95	\$1.75 \$32.95 .50 .60 \$1.75	NPN NPN PNP NPN	60 12 12 80	10A 50 50 3A	75W 200 200 40W	2 600 700 3
TIP32B TT797 TT800 TT801 2SC710	Z-2024 (See 2N4030) (See 2N4030) (See 2N3019) Z-2512	\$1.75 \$1.95	\$1.60 \$1.75	PNP	80	ЗА	40W	3
2SC1096 2SC1674 2SC2166 2SC1969 2SC2694	Z-2500 Z-6005 Z-2501 Z-2502 Z-2505	\$2.95 \$1.45 \$8.95 \$5.75 \$39.95	\$2.65 \$1.30 \$8.50 \$5.25 \$37.95	NPN NPN NPN NPN NPN	30 20 30 75 20	4A 20	10W 250 20W 1.5W 75W	60 600 150 175
2SC3355 2SC3358 2N2222A 2N3019 2N3055	Z-6006 Z-6007 Z-2069 Z-2068 Z-1804	\$1.95 \$1.95 .95 \$1.95 \$2.50	\$1.75 \$1.75 .85 \$1.75 \$2.25	NPN NPN NPN NPN NPN	40 30 40	800 1A 700	500 800 2.86	300 100 100
2N3904N 2N3905A 2N3948 2N4292 2N4427	Z-2070 Z-2071 Z-2260 (See PN3019) Z-2506	.45 .45 \$5.95 - \$4.25	.30 .30 \$5.90 \$4.10	NPN PNP PNP NPN	60 40 60 20	15A 200 1A 400	115W 310 800 315	.08 200 100 500

FIELD	EFFECT TR	ANSISTORS

Type No.	Cat No.	Price	Price	Pol/		SS		gs (off)	
		Ea	10 up	Const	V@lg	(uA)	Min	Max @	Vds
MFE131	Z-1849	\$3.25	\$2.95	NCH MOS					
MPF102	Z-1832	\$1.35	\$1.20	NCH J	25	10	0.5	8	15
MPF106	Z-1840	\$1.40	\$1.30	NCH J	25	1	0.5	4	15
2N5245	Z-2335	\$1.75	\$1.50	NCH J	30	1	1	6	15
2N5484	Z-2340	\$1.10	\$1.00	NCH J	25	1	0.3	3	15
2N5486	Z-2073	\$1.15	\$1.05	NCH J	25		2	6	15

GERN	AAD	JIIIM	TDAR	TOIDL	ODC
SERIE				49191	

Type No.	Cat No.	Price Ea	Price 10 up	Pol	Vce		P(tot) (mW)	Ft (MHz)
AC187	Z-1080	\$2.25	\$2.00	NPN	15	1A	1W	1
AC188	Z-1082	\$2.95	\$2.65	PNP	15	1A	220	

POWER MOSFETS

Type No.	Cat No.	Price Ea	Price 10 up	Pol/ const.	Vdss (min) V @ Id	ld (max) A
2SJ48	Z-1816	\$9.95	\$9.05	PCH MOS	-120 -10mA	-7
2SK134	Z-1815	\$8.95	\$8.15	NCH MOS	120 10mA	7

GaSaFETS

3SK 121 Z-1845 \$5.95 \$5.50

SILICON SMALL SIGNAL DIODES

IN914 Z-3120 .05 .04

SILICON RECTIFIER DIODES

Type No.	Cat No.	Price Ea	Price 10 up	PIV	If mA	Use
IN4002	Z-3202	.10	.08	100	1	General Purpose
IN4004	Z-3204	.10	.08	400	1	General Purpose
IN4007 IN5404	Z-3207 Z-3222	.15 .35	.13	1000 400	3	General Purpose General Purpose
IN5408	Z-3228	.45	.40	1000	3	General Purpose
BYX98300	Z-3242	\$5.95	\$5.50	300	10	Stud Mount

RECTIFIER BRIDGES

WO-4	Z-3304	.95	.85	400	1.5	Mini Bridge
PO-4	Z-3306	\$2.75	\$2.40	400	6	General Purpose Bridge
PR40	7-3334	\$6.25	¢5 75	400	25	Heavy Duty Bridge

GERMANIUM DIODES

Type No.	Cat No.	Price Ea	Price 10 up	PIV	If mA	Use
OA47	Z-3232	\$1.45	\$1.25	25		Gold Bonded General Purpose
OA95	Z-3050	\$1.25	\$1.10	90		General Purpose Point Contact

HOT CARRIER DIODES

Price Price Ea 10 up 5082-2800 Schottky diode Z-3230 \$2.50 \$2.30

POWER TRANSISTOR SOCKETS







LIGHT EMITTING DIODES

Type No.	Colour	Size	Cat No.	Price Ea	Price 10 up	If (mA)	Vf @ 20mA	Intensity @ 20mA	Notes	
	Grn/Red	5mm diam	Z-4070	.75	.65					
ESBR5501	Red	5mm diam	Z-4075	\$1.75	\$1.65	50	1.7	200mCd	High Intensity	
TL4211	Red	3mm diam	Z-4077	.25	.20	40	2.1	3.5mCd	Premium Quality	
TL4231	Green	3mm diam	Z-4079	.30	.20	40	2.1	5.0mCd	Premium Quality	
TL4251	Yellow	3mm diam	Z-4081	.30	.25	40	2.1	5.0mCd	Premium Quality	
TL4291	Orange	3mm diam	Z-4083	.35	.30	40	2.0	7.0mCd	Premium Quality	
TL4213	Red	5mm diam	Z-4085	.40	.35	40	2.1	4.0mCd	Premium Quality	
TL4233	Green	5mm diam	Z-4087	.50	.45	40	2.1	6.0mCd	Premium Quality	
TL4253	Yellow	5mm diam	Z-4089	.50	.45	40	2.0	6.0mCd	Premium Quality	
TL4293	Orange	5mm diam	Z-4091	.50	.45		2.1		Premium Quality	
TL3215S	Red	2mm diam	Z-4093	.60	.55	40	2.1	1.2mCd	Rect. Prem. Qual.	
TL3235S	Green	2mm diam	Z-4095	.60	.55	40	2.1	1.2mCd	Rect. Prem. Qual.	
TL32555	Yellow	2mm diam	Z-4097	.60	.55	40	2.1	1.2mCd	Rect. Prem. Qual.	

LIQUID CRYSTAL DISPLAYS

Type	Digit	Construction	Cat	Price	Price
No.	Size		No.	Ea	10 up
LCD4.5	10mm	41/2 digit liquid crystal	Z-4175	\$16.95	\$16.25

LED 7 SEGMENT DISPLAYS

Type	Digit	Construction	Cat	Price	Price
No.	Size		No.	Ea	10 up
LT313	8mm	Common Cathode	Z-4103	\$2.75	\$2.50
LT312	8mm	Common Anode	Z-4117	\$2.75	\$2.50
FND560	13mm	Common Cathode	Z-4150	\$2.95	\$2.70
LT547E	13mm	Common Cathode	Z-4151	\$2.95	\$2.70
LTS546AR		Common Anode	Z-4145	\$2.95	\$2.70

SILICON CONTROLLED RECTIFIERS

Economy Pla					1	
Туре	Vdrm	It(A)	Use	Cat No.	Price Ea	Price 10 up
C203B C106Y1 C106D C122E*	200 30 400 500	0.8 4 4 8	Small Current Sensitive Gate Sensitive Gate AC Switch	Z-4310 Z-4315 Z-4320 Z-4332	\$1.75 \$1.35 \$1.75 \$3.45	\$1.50 \$1.20 \$1.35 \$3.25

TRIACS

Economy	Plastic P	ack				
SC141D	400	6*	AC Switch	Z-4510	\$2.45	\$2.25
(*May be	Q4006L4	or 2N63	343, both 8A)			
SC151D	400		AC Switch	Z-4520	\$2.95	\$2.70
(&May be	BT139/50	00 - 500	V. 16A)			

TRIGGERING DEVICES

Type No.	Device Type/Description	Cat No.	Price Ea	Price 10 up
ST4	Assymetrical trigger diode — suitable trigger for SC141/151	Z-4740	\$1.95	\$1.50
MOC3021 BR100-03	Opto-coupled triac driver Diac	Z-4516 Z-4710	\$3.45 .75	\$3.05 .65


TRANSMITTING VALVES

6146B, 6JS6C and 572B transmitting valves are no longer stocked in DSE stores, but are normally available as spare parts in our Service Centre. They may be ordered through any DSE store or direct from the Service Centre (see address on page 5.)

ULTRASONIC TRANSDUCERS

Highly sensitive transmit/receive pair for alarms, level detectors,

TV remote control, etc. Data sheet available.



ZENER DIODES

Type No.	Cat No.	Price Ea	Price 10 up	Voltage	Power
IN746	Z-3401	.25	.20	3.3V	400mW
IN750	Z-3403	.25	.20	4.7V	400mW
IN751 IN752	Z-3405 Z-3407	.25	.20 .20	5.1V 5.6V	400mW 400mW
114752	2-3407	.25	.20	5.6V	40011100
IN753	Z-3409	.25	.20	6.2V	400mW
IN957	Z-3411	.25	.20	6.8V	400mW
IN961	Z-3413	.25	.20	10V	400mW
IN963	Z-3415	.25	.20	12V	400mW
IN965	Z-3417	.25	.20	15V	400mW
IN4728	Z-3515	.35	.30	3.3V	1W
IN4730	Z-3519	.35	.30	3.9V	1W
IN4732	Z-3523	.35	.30	4.7V	1W
IN4733	Z-3525	.35	.30	5.1V	1W
IN4734	Z-3527	.35	.30	5.6V	1W
IN4735	Z-3529	.35	.30	6.2V	1W
IN4736	Z-3531	.35	.30	6.8V	1W
IN4737	Z-3533	.35	.30	7.5V	1W
IN4738	Z-3535	.35	.30	8.2V	1W
IN4739	Z-3537	.35	.30	9.1V	1W
IN4740	Z-3539	.35	.30	10V	1W
IN4742	Z-3543	.35	.30	12V	1W
IN4744	Z-3547	.35	.30	15V	1W
IN4745	Z-3549	.35	.30	16V	1W
IN4746	Z-3551	.35	.30	18V	1W
IN4747	Z-3553	.35	.30	20V	1W
IN4749	Z-3557	.35	.30	24V	1W
			1000		
IN4751	Z-3561	.35	.30	30V	1W
IN4752	Z-3563	.35	.30	33V	1W

VOLTAGE REGULATORS

Type No.	Description	Cat No.	Price Ea	Price 10 up
TO-92 CASE				
LM78L05CZ	3-Terminal 5V 100mA positive regulator	Z-6108	\$1.15	.95
LM78L12CZ	3-Terminal 12V 100mA positive regulator	Z-6110	\$1.15	.95
LM78L15CZ	3-Terminal 15V 100mA positive regulator	Z-6111	\$1.15	.95
TO-220 CAS	E 1888 - 1888 - 1888 - 1888 - 1888 - 1888 - 1888 - 1888 - 1888 - 1888 - 1888 - 1888 - 1888 - 1888 - 1888 - 188			
7805	3 terminal 5 volt 1A positive regulator	Z-6545	\$1.15	.95
7812	3 terminal 12 volt 1A positive regulator	Z-6552	\$1.15	.95
7815	3 terminal 15 volt 1A positive regulator	Z-6554	\$1.15	.95
7905	3 terminal 5 volt 1A negative regulator	Z-6555	\$1.35	\$1.15
7912	3 terminal 12 volt 1A negative regulator	Z-6556	\$1.35	\$1.15
7915	3 terminal 15 volt 1A negative regulator	Z-6557	\$1.35	\$1.15
LM350	Adjustable 1.2-32V 3A regulator	Z-6561	\$7.95	\$7.15
LM317/T	Adjustable 1.2-37V 1.5A regulator	Z-6541	\$2.75	\$2.50
TO-3 CASE				
LM350	Adjustable 1.2-32V 3A regulator	Z-6560	\$9.50	\$8.95
LM317/K	Adjustable 1.2-37V 1.5A regulator	Z-6542	\$6.95	\$6.50
DIL OR ROU	ND CASE			
LM723	Adjustable 2-37V 150mA regulator	Z-6362	\$1.65	\$1.45

UNIJUNCTIONS

Type No.	Device Type/Description	Cat No.	Price Ea	Price 10 up		
2N6027 DS2646	Programmable unijunction (sim. D1 Unijunction (similar 2N2646)	3T1) Z-1780 Z-1786	\$1.15 \$1.95	\$1.05 \$1.70		

OPTO-ELECTRONICS

Device Type/Description	Cat No.	Price Ea	Price 10 up
Silicon Photo Diode with lens	Z-1950	\$1.60	\$1.45
Silicon Darlington phototransistor	100		
with lens	Z-1952	\$1.20	\$1.10
Silicon Photo-diode	Z-1956	\$3.35	\$3.05
Infra-red LED	Z-3235	\$1.25	\$1.15
Cadmium Sulphide (CdS) light dep-			
endent resistor, similar range ORP12	Z-4801	\$1.25	\$1.15
Opto Coupler — LED & photo diode			
in DIP package	Z-4804	\$1.50	\$1.35
	Silicon Photo Diode with lens Silicon Darlington phototransistor with lens Silicon Photo-diode Infra-red LED Cadmium Sulphide (CdS) light dependent resistor, similar range ORP12 Opto Coupler — LED & photo diode	Silicon Photo Diode with lens Silicon Darlington phototransistor with lens Silicon Photo-diode Infra-red LED Cadmium Sulphide (CdS) light dependent resistor, similar range ORP12 Opto Coupler — LED & photo diode	Silicon Photo Diode with lens Z-1950 \$1.60 Silicon Darlington phototransistor with lens Z-1950 Silicon Photo-diode Z-1956 \$3.35 Infra-red LED Z-3235 \$1.25 Cadmium Sulphide (CdS) light dependent resistor, similar range ORP12 Opto Coupler — LED & photo diode

74C/4000 SERIES CMOS

Type No.	Description	Cat No.	Price	Price
74C00 74C14 74C926 4001 4002	Quad 2 input NAND gate Hex Schmitt trigger 4 decade counter 7 seg. output Quad 2 input NOR gate Dual 4 input NOR gate	Z-5410 Z-5413 Z-5414 Z-5601 Z-5602	Ea \$1.25 \$1.50 \$15.95 .65	10 up \$1.10 \$1.35 \$14.95 .60 .50
4007	Dual comp pair with inverter	Z-5607	.80	.65
4009	Hex inverter buffer/level shift	Z-5609	\$1.35	\$1.25
4011	Quad 2 input NAND	Z-5611	.70	.65
4013	Dual D edge triggered flip flop	Z-5613	.90	.80
4015	Dual 4 bit shift register	Z-5615	\$1.45	\$1.30
4016	Quad analog switch	Z-5616	\$1.45	\$1.30
4017	Decade counter/divider	Z-5617	\$1.45	\$1.30
4019	Quad AND/OR select gate	Z-5619	\$1.15	.95
4020	14 bit binary counter	Z-5620	\$1.65	\$1.55
4022	Divide by 8 counter	Z-5622	\$1.85	\$1.65
4023	Triple 3 input NAND gate	Z-5623	.95	.85
4024	7 stage ripple counter	Z-5624	\$1.15	\$1.05
4025	Triple 3 input NOR gate	Z-5625	.80	.75
4026	Decade counter/7 segment divider	Z-5626	\$3.65	\$3.40
4027	Dual J-K flip flop	Z-5627	\$1.15	.95
4028	BCD to decimal decoder	Z-5628	\$1.65	\$1.45
4029	Preset up/down binary decade counter	Z-5629	\$1.75	\$1.65
4030	Quad EXCLUSIVE OR gate	Z-5630	.95	.80
4040	12 stage ripple counter	Z-5640	\$1.65	\$1.50
4044	Quad R/S flip-flop	Z-5644	\$1.45	\$1.25
4046	Phase-locked-loop	Z-5646	\$1.95	\$1.75
4047	Monostable/Astable multivibrator	Z-5647	\$1.95	\$1.75
4049	Hex inverter/buffer	Z-5649	\$1.00	.90
4050	Hex non inverting buffer	Z-5650	\$1.00	.90
4051	8 channel analog multiplexer	Z-5651	\$1.75	\$1.65
4066	Quad analog switch	Z-5666	\$1.15	\$1.05
4069	HEX inverter	Z-5669	.80	.75
4071	Quad 2 input OR gate	Z-5671	.90	.75
4081	Quad 2 input buffered AND gate	Z-5681	.85	.75
4082	Dual 4 input AND gate	Z-5682	.80	.75
4093	Quad 2 input NAND Schmitt trigger	Z-5693	\$1.40	\$1.20
40194	4 bit bi-direct shift register	Z-5694	\$3.75	\$3.40
4511	BCD/7 segment decoder/driver/latch	Z-5730	\$2.45	\$2.20
4516	Presettable up/down counter	Z-5738	\$2.95	\$2.50
4518	Dual BCD up counter	Z-5740	\$2.15	\$1.95
4520	Dual binary up counter	Z-5742	\$1.95	\$1.75
4526	4 bit programmable down counter	Z-5744	\$2.15	\$1.95
4528	Dual Monostable Multivibrator	Z-5748	\$1.95	\$1.75

74HC

Type No.	Description	Cat No.	Price	Price
74HC00	Quad 2 input NAND gate	Z-5800	Ea . 95	10 up . 75
74HC02	Quad 2 input NOR gate	Z-5802	.95	.75
74HC04	Hex inverter	Z-5804	.95	.75
74HC08	Quad 2 input AND gate	Z-5808	.95	.75
74HC11N	Triple 3 input	Z-5811	.95	.75
74HC14	Hex Schmitt-Trigger	Z-5814	\$1.50	\$1.35
74HC27	Dual J-K flip flop	Z-5827	.95	.75
74HC30	8 input NAND gate	Z-5830	.95	.75
74HC32	Quad 2 input OR gate	Z-5832	.95	.75
74HC74	Dual D-type edge triggered flip flop	Z-5874	.95	.75
74HC76	Dual J-K master/slave flip flop	Z-5876	\$1.25	\$1.10
74HC85	4 bit magnitude comparator	Z-5885	\$1.95	\$1.75
74HC86	Quad 2 input EXCLUSIVE OR gate	Z-5886	.95	.80
74HC123	Dual re-triggerable monostable	Z-5910	\$2.90	\$2.70
74HC138	Expandable ¾ decoder	Z-5915	\$1.25	\$1.10
74HC139	1 of 8 decoder/multiplexer	Z-5920	\$1.25	\$1.10
74HC157	Quad 2 input multiplexer	Z-5925	\$1.95	\$1.75
74HC165	Par load 8 bit shift register	Z-5930	\$2.25	\$2.05
74HC174	Hex D-type flip flop	Z-5935	\$1.95	\$1.75
74HC221	Dual mono multivibrators (S/trigger)	Z-5940	\$3.95	\$3.65
74HC244	Octal buffer/line driver	Z-5950	\$2.45	\$2.25
74HC245	Octal bus transceiver	Z-5955	\$2.95	\$2.70
74HC367	Hex bus driver & 3 state o/p	Z-5960	\$1.75	\$1.60

74LS SERIES

	/4L3 SEKII	50		
Type No.	Description	Cat No.	Price Ea	Price 10 up
74LS00	Quad 2 input NAND gate	Z-4900	.75	.70
74LS01	Quad 2 input NAND gate, o/collector	Z-4901	.75	.70
74LS02	Quad 2 input NOR gate	Z-4902	.75	.70
74LS04	Hex inverter	Z-4904	.75	.70
74LS05	Hex inverter, open collector	Z-4905	.75	.70
74LS08	Quad 2 input AND gate	Z-4908	.95	.85
74LS10	Triple 3 input NAND gate	Z-4910	.75	.70
74LS13	DL 4in NAND Schmitt trigger	Z-4913	.75	.70
74LS14	Hex Schmitt trigger	Z-4914	.85	.75
74LS20	Dual 4 input NAND gate	Z-4920	.80	.75
74LC21	Dual 4 input positive AND gate	Z-4924	\$1.25	\$1.15
74LS27	Triple 3 input NOR gate	Z-4927	.85	.75
74LS30	8 input NAND gate	Z-4930	.95	.80
74LS32	Quad 2 input OR gate	Z-4932	.95	.85
74LS37	Quad NAND buffer	Z-4937	.95	.85
74LS47	7 segment dec buffer	Z-4947	\$1.50	\$1.40
74LS54	2 way AND or inv	Z-4954	.95	.85
74LS73	Dual J-K flip flop	Z-4973	\$1.25	\$1.15
74LS74	Dual D-type edge trig. flip flop	Z-4974	\$1.15	\$1.05
74LS75	Quad bistable latch	Z-4975	\$1.45	\$1.25
74LS76	Dual J-K master/slave flip flop	Z-4976	\$1.20	\$1.10
74LS83	4 bit full binary array	Z-4983	\$1.95	\$1.75
74LS85	4 bit magnitude comparator	Z-4985	\$1.45	\$1.25
74LS86	Quad 2 input EXCLUSIVE-OR gate	Z-4986	\$1.25	\$1.15
74LS90	Decade counter	Z-4990	\$1.35	\$1.25
74LS95	4 bit L-R shift register	Z-4995	\$1.35	\$1.25
74LS109	Dual JK flip flop	Z-5109	\$1.15	\$1.05
74LS123	Dual monostable multivibrator	Z-5310	\$1.45	\$1.25
74LS132	Quad 2 input NAND Schmitt Trigger	Z-5283	\$1.95	\$1.85
74LS139	ONE OF EIGHT Decoder multiplexer	Z-5285	\$1.40	\$1.30
74LS153	Dual 4 input multiplexer	Z-5286	\$1.20	\$1.10
74LS157	Quad 2 input multiplexer	Z-5287	\$1.75	\$1.50
74LS165	Par Load Shift Register	Z-5288	\$2.45	\$2.20
74LS174 74LS175	Hex D-type flip flop Quad D flip flop	Z-5290 Z-5291	\$1.40 \$1.50	\$1.20 \$1.35
74LS190	Up/down decade counter	Z-4999	\$1.85	\$1.70
74LS191	Up/down binary counter	Z-5191	\$1.85	\$1.70 \$1.35
74LS192	Sync dec up/down ctr	Z-5192	\$1.50 \$1.85	
74LS193	Bin sync up/down ctr	Z-5193		\$1.65
74LS196	Decade counter	Z-5196	\$2.45	\$2.20
74LS221	Dual mono multivibrators (S/trigger)	Z-5296	\$2.25	\$1.95
74LS241	Octal buffer/line driver	Z-5293	\$2.25	\$1.95
74LS244	Octal buffer/line driver	Z-5294	\$2.75	\$2.50
74LS245	Octal bus transceiver	Z-5299	\$2.75	.50
74LS367	Hex bus driver & 3 stage o/p	Z-5292	\$1.15	\$1.05
74LS373	Octal 3 stage latch	Z-5295	\$2.45	\$2.20
74LS374	Octal D-type flip flop	Z-5297	\$2.45	\$2.20

LSI & SPECIAL DIGITAL

Type No.	Description	Cat No.	Price Ea	Price 10 up
XR2211	FSK Demod PLL IC	Z-2511	\$11.95	\$10.85
11C90	650MHz ECL pre-scaler	Z-5361	\$16.95	\$15.45
DS1488	RS-232C Quad line driver	Z-5370	\$1.95	\$1.75
ULN2232	Light motion detector IC	Z-6009	\$13.95	\$12.95
ICL7106	LCD digital voltmeter	Z-6300	\$15.95	\$14.95
LM1872N	Radio control receiver	Z-6104	.95	.85
8087-1	Maths 10MHz co-processor	Z-9107	\$799	
80287-3	Math Co-Processor	Z-9106	\$899	
8087-2	8MHz Math Co-Processor	Z-9105	\$599	
2732A	4K × 8 EPROM	Z-9209	\$10.95	\$9.95
HM6116P-4	2K × 8 CMOS Static RAM	Z-9308	\$7.95	\$7.45
Z-80CPU	Microprocesor CPU	Z-9100	\$4.95	\$4.45
2114	1K × 4 static RAM	Z-9306	\$3.95	\$3.75
4116	16K × 1 dynamic RAM	Z-9310	\$2.96	\$2.75
4164	64K × 1 dynamic RAM	Z-9312	\$7.95	\$7.45
41256	256K DRAM 120ns	Z-9313	\$24.95	\$25.95
4464	DRAM 120ns	Z-9316	\$29.95	\$28.95
41256	256K DRAM 150ns	Z-9315	\$27.95	\$26.95

VARISTORS

Contrary to what their name suggests, varistors are not resistors in the true sense, but a special type of semiconductor. They are used as protection devices in power supplied, etc. They are normally high resistance, but if their rated voltage is exceeded (eg by a spike, etc.) they rapidly become a low resistance device.

When placed across the supply rail, they have no effect until a spike occurs. They will then allow a high current to flow, blowing the fuse or tripping other protection devices.

Device	Rated	Cat No.	Price	Price
	Voltage		Ea.	10 up
V8ZA1	5V	R-1800	\$3.25	\$2.95
V275LA20A	275V	R-1802	\$3.95	\$3.50



LINEAR & GENERAL PURPOSE

Type No.	Description	Cat No.	Price Ea	Price 10 up
ADC0802LCN	. 8 bit A — D convertor	Z-6833	\$19.95	\$18.95
DAC0800LCN	8 bit D to A convertor	Z-6834	\$6.95	\$6.25
LM311	Voltage comparator	Z-6048	\$1.45	\$1.20
LM319N	High speed comparator	Z-6049	\$4.95	\$4.50
LM334Z	Temperature sensor/current source	Z-6810	\$3.45	\$3.20
LM335H	Precision temperature sensor (TO-46)	Z-6050	\$4.95	\$4.50
LM335Z	Precision temperature sensor (TO-92)	Z-6051	\$3.95	\$3.50
LM336BZ5-0	5V Reference source	Z-6037	\$5.95	\$5.80
LM339N	Quad comparator	Z-6039	\$1.10	.95
LM380	Audio power amplifier	Z-6080	\$2.65	\$2.50
LM382	Low noise stereo preamplifier	Z-6082	\$3.75	\$3.50
LM386	Audio power amplifier	Z-6086	\$1.95	\$1.70
LM394C	Dual diff. supermatched pair	Z-6083	\$8.45	\$7.95
LM567	Tone decoder	Z-6167	\$2.45	\$2.20
LM2917	Frequency to voltage/current source	Z-6112	\$3.95	\$3.50
LM3046N	NPN Transistor array	Z-6107	\$2.45	\$2.20
LM3909	LED flasher/oscillator	Z-6109	\$3.50	\$3.25
LM3914	10 LED driver	Z-6295	\$6.15	\$5.75
MC10116L	Triple differential amplifier	Z-5415	\$2.95	\$2.70
MC13020P	CQUAM stereo AM decoder	Z-5420	\$8.95	\$8.25
NE/DS 555	Universal timer	Z-6145	.60	.50
NE556	Dual timer	Z-6146	\$1.25	\$1.15
OM350	Wideband VHF/UHF amplifier	Z-6185	\$15.95	\$13.95
SN76604N	Servo amplifier (RC)	Z-6835	\$6.95	\$6.75
TA7205	General purpose CB audio IC	Z-2503	\$6.95	\$6.35
TL555CP	Timer (CMOS version 555)	Z-6144	\$1.95	\$1.75
UPC1615G	10-1000MHz 260B Amp IC	Z-6008	\$2.95	\$2.50
XR-2206	Function generator	Z-6820	\$11.95	\$10.95
ZN414Z	One-chip AM radio	Z-6520	\$2.95	\$2.75

LINEAR OPERATIONAL AMPLIFIERS

Type No.	Description	Cat No.	Price	Price
CA3080	Transconductance op amp	Z-6024	Ea	10 up
CA3130T	Fet input op amp	Z-6025	\$2.95 \$4.95	\$2.20
CA3140	Fet input op amp	Z-5417	\$1.95	\$4.50
LM301	General purpose op-amp	Z-6040	\$1.25	\$1.75 \$1.10
LM308N	General purpose op-amp	Z-6045	\$1.95	\$1.75
LM324	Quad op amp	Z-6102	\$1.25	\$1.10
LM3900	Quad 'Norton' op amp	Z-6100	\$1.45	\$1.30
LM13600N	Dual transconductance amplifier	Z-6113	\$2.95	\$2.70
LM311N	Voltage comparator	Z-6048	\$1.45	\$1.20
LM1458N	Dual Op Amp	Z-6028	\$1.45	\$1.20
LM10CLN	Op amp/voltage ref	Z-6084	\$4.95	\$4.50
NE5534P	Low noise op amp	Z-6090	\$3.95	\$3.75
TL071CP	JFET op amp	Z-6030	\$1.45	\$1.20
TL072CP	Dual JFET op amp	Z-6032	\$1.95	\$1.75
TL074CP	Quad JFET op amp	Z-6034	\$4.95	\$4.50
TLC251	Prog. low power (CMOS) op amp	Z-6021	5.95	\$5.50
uA741	General purpose op amp	Z-6382	.95	.85
uA4136	Quad op amp	Z-6105	\$2.45	\$2.20

THERMISTORS

Thermistors are primarily heat sensing devices. The heat is normally generated within the device itself by the current flowing through it. As the heat changes, so does the resistance of the thermistor.

There are basically two types: NTC or negative temperature coefficient (an increase in temperature brings a decrease in resistance), or PTC (increase in temperature brings an increase in resistance.). Other more specialised types may even combine both characteristics

General Purpose NTC Thermistor

Used in amplifiers, power supplies, etc. for temperature sensing purposes. Has 100k resistance at 25°C, with a -5.2% change per degree C. Thermal time constant 17 seconds, maximum dissipation $\frac{1}{2}$ W. Rated at 0 to 55 degrees C. Cat R-1797

"Polyswitch" PTC Thermistors

A failure in your amplifier can easily cause hundreds of dollars damage to your speakers. In the worst case, it could cause a fire.

For just a few dollars, you can protect your hi fi (and your home!) against this happening with Polyswitch PTC Thermistors.

At normal operating currents, they have very low resistance (see table). Once their rated current is exceeded, they go very high until the current drops to within rating. This makes them ideal for speaker protection and for many other "overload" applications.

Two type are available — to suit various types of systems. Installation is simple: they go in series with the individual speakers (ie, inside the speaker cabinet).

	A			Price	Price	
Device	Application	Norminal Resistance	Cat No.	Ea.	10 up	
RDE050	Tweeter	0.4 ohms	R-1798	\$5.95	\$5.50	
RDE115A	Woofer/Midrange	0.12 ohms	R-1799	\$5.95	\$5.50	


Prototype Breadboards

Now designing projects is so simple — with these prototype assembly boards. No more bird's nests. No more shorts. No soldering! Just plug the components and connection leads into the board. And if one board isn't enough, they can easily be paralleled up!


Mini Project Board 80 x 60 x 8mm board with 58 groups of 5

80 x 60 x 8mm board with 58 groups of 5 connected terminal points. Grid is laid out in alpha-numeric format for simple "track" identification, and the board is supplied with a pad of overlays so you can mark out circuitry for later use or for transferring to pock matrix board. 6:4.4514

pcb/matrix board. Cat P-4614
Shipping weight: 375g
Carton size: 230 x 180 x 25mm



Giant Project Board




Similar to above, but this one has a whopping 128 groups of terminal points. Overall board size 178 x 67 x 8mm, also has 8 bus lines of 25 connected terminals. Dependable corrosion-free terminals for long life and circuit reliability. Cat P-4615

Shipping weight: 115g Carton size: 180 x 70 x 20mm \$4895

Project Boards PLUS!

A complete mini work bench! This one has 256 groups of 5 connected terminal points plus 16 bus lines of 25 connected terminals. But that's not all: the 130 x 170mm board is housed in a plastic "work bench" complete with three terminals (for power connection, input/output, etc). Overall size is 150 x 225 x 20mm. **BONUS**: Work pad included for circuit working.

Shipping weight: 375g Carton size: 230 x 180 x 25mm




And one with a panel!

128 groups of five terminal points plus 8 bus lines of 25 points in a protoboard measuring 173 × 65 × 8mm. Housed in a plastic work bench measuring 115 × 190 × 15mm, complete with provision for a front panel with holes for pots, switches, even TO-3 transistors! Three terminals are also included for connection. Cat P-4617

Shipping weight: 245g Carton size: 200 x 125 x 25mm

\$2495



But how do you connect to 'em?

Prototype Boards are designed to accept standard component leads — resistors, capacitors, etc — so ordinary pigtails are fine for small connecting leads. Any bigger... and you'll need the breadboard connector packl Tough plastic case contains 14 different sizes of jumper from 2.5mm to 125mm in length, with 25 jumpers in each size. All sizes above 2.5mm are covered with different coloured pvc insulation for circuit identification and protection. Cat W-4012

Shipping weight: 30g Pack size: 120 x 110mm bag.



\$**24**95

ELECTROLYTICS

Electrolytics come in a range of different shapes and sizes but (with the exception of the bipolar type below) they have one thing in common: they are polarised and must be connected into circuit correctly. As you will note, very large capacitances are possible with electrolytic types.

AXIAL (RT) TYPE

VAL. IN uF	VOLT-	CAT NO.	PRICE 1-9	PRICE 10 up	
0.47	63	R-4010	.35	.30	
1.0	350	R-4015	.35	.30	_
2.2	63	R-4020	.45	.40	2
3.3	25	R-4025	.45	.40	
4.7	25	R-4030	.45	.40	-13
4.7	63	R-4035	.45	.40	800
10	16	R-4055	.35	.30	10
10	25	R-4060	.45	.40	
10	63	R-4065	.35	.30	A B
22	25	R-4086	35	.30	6
22	63	R-4091	.35	.30	
33	16	R-4095	.35	.30	
47	16	R-4105	.35	.30	
47	25	R-4110	.35	.30	-
47	63	R-4115	.45	.40	
47	350	R-4120	\$3.95	\$3.50	
100	10	R-4125	.35	.30	
100	25	R-4130	.45	.40	
100	63	R-4135	.75	.65	
100	350	R-4140	\$3.45	\$3.20	
220	16	R-4145	.45	.40	
220	25	R-4150	.55	.45	
220	63	R-4155	\$1.45	\$1.20	
470	16	R-4160	.70	.65	- 1
470	63	R-4165	\$1.75	\$1.50	- 1
1000	16	R-4175	.95	.80	- 55
1000	25	R-4180	\$1.45	\$1.30	(
1000	35	R-4185	\$1.85	\$1.60	
1000	63	R-4190	\$2.75	\$2.50	
2200	16	R-4196	\$1.35	\$1.20	
2200	25	R-4201	\$1.95	\$1.70	
2200	35	R-4206	\$2.65	\$2.40	
2200	50	R-4211	\$3.25	\$2.95	-
4700	35	R-4215	\$4.95	\$4.65	

SINGLE ENDED (RB) TYPE (PCB MOUNTING)

0.47	50	R-4290	.25	.20	
1.0	50	R-4295	.25	.20	
2.2	25	R-4300	.25	.20	
4.7	25	R-4310	.25	.20	
10	25	R-4315	.25	.20	
22	25	R-4319	.25	.20	
35	10	R-4330	.30	.25	
33	35	R-4340	.30	.25	
47	25	R-4350	.35	.30	
100	16	R-4360	.35	.30	
100	25	R-4370	.35	.30	
220	16	R-4380	.45	.40	
220	25	R-4390	.75	.65	
330	10	R-4397	.75	.65	
330	25	R-4400	.75	.65	
470	10	R-4407	.75	.65	
470	16	R-4410	.75	.65	
470	50	R-4420	.75	.65	
680	16	R-4435	.75	.65	
1000	16	R-4440	.95	.75	
1000	25	R-4450	\$1.05	.95	
1000	50	R-4457	\$1.95	\$1.60	
2200	25	R-4460	\$1.65	\$1.45	l
6800	10	R-4470	\$1.95	\$1.25	
10000	10	R-4480	\$3.95	\$3.65	
10000	40	R-4483	\$11.50	\$9.95	

METAL CAN TYPE

VAL	VOLT-	CAT NO.	PRICE	PRICE
IN uF	AGE		1-9	10 up
5600	40	R-4570	\$24.95	\$23.95
8000	75	R-4590	\$17.75	\$16.50
10000	40	R-4595	\$12.50	\$12.00



BI-POLAR ELECTROLYTICS

These electrolytics are specially made not to be polarised. They are designed for use where the voltage polarity across them changes — for example, in speaker cross-overs. They have a 40 volt rating.

VAL	CAT NO.	PRICE	PRICE	0
IN uF		1-9	10 up	
2.2	R-4600	.45	.35	
3.3	R-4605	.45	.35	
4.7	R-4610	.45	.35	//
6.8	R-4620	.45	.35	// 11
10	R-4630	.75	.60	0 11
22	R-4640	.85	.75	- //

PREFERRED VALUES:

Most capacitors are supplied in 'preferred values'; however, some - particularly electrolytics - are not. (For example, 640uF where you might expect 560 or 680 uF). If you have a circuit specifying a particular value electrolytic and the one you're supplied with is not the exact value, it is normally quite safe to use it. Electrolytics usually have a very wide tolerance anyway, so if you get stuck you'll probably find a value in either direction will work just as well.

POLYESTER

Often called 'greencaps' because they're very often green in colour. Polyester capacitors are the most widely used of all types, in a huge variety of circuit applications. These polyester types are all rated at 100V or more. See data section for marking codes used.

VALUE IN uF		PRICE 1-9	PRICE 10 up	VALUE IN uF	CAT NO.	PRICE 1-9	PRICE 10 up	
0.001	R-2010	.25	.20	0.039	R-2075	.25	.20	
0.0012	R-2012	.25	.20	0.047	R-2080	.25	.20	
0.0015	R-2015	.25	.20					
0.0018	R-2018	.25	.20	0.056	R-2085	.28	.25	
0.0022	R-2020	.25	.20	0.068	R-2090	.28	.25	
0.0027	R-2027	.25	.20	0.082	R-2095	.28	.25	
0.0033	R-2025	.25	.20	0.1	R-2100	.35	.30	
0.0039	R-2030	.25	.20	0.12	R-2102	.35	.30	
				0.15	R-2105	.35	.30	
0.0047	R-2035	.25	.20	0.18	R-2107	.35	.30	
0.0056	R-2040	.25	.20					
0.0068	R-2045	.25	.20	0.22	R-2110	.35	.30	
0.0082	R-2050	.25	.20	0.27	R-2115	.45	.40	
0.01	R-2055	.25	.20	0.33	R-2120	.45	.40	
0.012	R-2057	.25	.20	0.39	R-2125	.45	.40	
				0.47	R-2130	.65	.56	
0.015	R-2060	.25	.20					
0.018	R-2062	.25	.20	1.0	R-2135	\$1.40	\$1.20	
0.023	R-2065	.25	.20	2.0	R-2140	\$1.90	\$1.70	
0.027	R-2067	.25	.20	3.3	R-2145	\$2.95	\$2.70	
0.033	R-2070	.25	.20			0.000	2000	
50.775045790							Of Street, or other Designation of the last of the las	

HIGH VOLTAGE POLYESTER

Similar to above range, but offering a very high voltage rating: 630 volts! Ideal replacements for most capacitors used in valve circuits.

VALUE IN uF	-	PRICE 1-9		VALUE IN uF		PRICE 1-9	
0.01	R-2160	.45	.40	0.1	R-2170	\$1.15	\$1.05
0.022	R-2162	.40	.36	0.22	R-2172	\$1.35	\$1.20
0.033	R-2164	.75	.65	0.33	R-2174	\$1.65	\$1.40
0.047	R-2166	.75	.65	0.47	R-2176	\$1.75	\$1.50

POLYSTYRENE

With a low temperature coefficient and very high voltage rating, polyester capacitors are ideal for use where stability and voltage rating is important.

VAL. IN uF	CAT NO.	VAL. IN uF	CAT NO.	VAL. IN uF	CAT NO.	
33pF	R-2807	120pF	R-2821	180pF	R-2825	
39pF	R-2809	150pF	R-2823	560pF	R-2837	
47pF	R-2811	220pF	R-2827	680pF	R-2839	
56pF	R-2813	270pF	R-2829	820pF	R-2841	
68pF	R-2815	330pF	R-2831	1000pF	R-2843	
82pF	R-2817	390pF	R-2833			
100pF	R-2819	470pF	R-2835			

High Tolerance Polystyrene 0.1uF 1% 63 volt R-2780 1-9 90¢ 10 up 80¢

All polystyrene above one price: 1-9 80¢ 10 up 70¢

HIGH VOLTAGE **POLYCARBONATE**

Specifically intended for mains and other suppression applications, there capacitors are rated at 250 volts AC continuous.

VALUE	VOLTAGE	CAT NO.	PRICE 1-9	PRICE 10 up
0.001uF	250V AC	R-2740	\$1.15	\$1.05
0.01uF	250V AC	R-2730	\$1.15	\$1.05
0.047uF	240V AC	R-2725	\$1.30	\$1.20
0.1uF	250V AC	R-2720	\$1.75	\$1.50

VARIABLE TUNING GANGS


60pF to 160pF miniature solid dialectric tuning capacitor suitable for replacement in many transistor radios. Ideal for new

Cat R-2970 1-9 \$1.50 ea 10 up \$1.30 ea

10 to 50pF tuning gang, air spaced, as used in ranges of "Howes" Amateur Radio Kits (Cat K-6326, 7, 8). Cat R-2980 1-9 \$6.95 10 up \$6.50 ea



Resin dinned electrolytics which use a tantalum dielectric, giving a very low leakage but a high capacitance for the size of the package. See data section for marking codes.



CERAMICS

104K

Use ceramics when low inductance is important; for example, in many RF circuits. They offer a huge range of values and are all rated at 50 volts or higher.

VAL. IN uF	NO.	VAL. IN uF	CAT NO.	VAL. IN uF	CAT NO.	
1pF	R-2215	27pF	R-2245	470pF	R-2299	
1.5pF	R-2217	33pF	R-2247	560pF	R-2301	
2.2pF	R-2219	39pF	R-2249	680pF	R-2303	
2.7pF	R-2221	47pF	R-2251	820pF	R-2305	
3.3pF	R-2223	56pF	R-2253	0.001uF	R-2307	
3.9pF	R-2225	68pF	R-2257	0.0022uF	R-2309	
4.7pF	R-2227	82pF	R-2259	0.0033uF	R-2311	
5.6pF	R-2229	100pF	R-2285	0.0047uF	R-2313	
6.8pF	R-2231	120pF	R-2287	0.0056uF	R-2315	
8.2pF	R-2233	150pF	R-2289	0.0068uF	R-2317	
10pF	R-2235	180pF	R-2291	0.0082uF	R-2319	
12pF	R-2237	220pF	R-2293	0.01uF	R-2321	
15pF	R-2239	270pF	R-2295	0.022uF	R-2323	
18pF	R-2241	330pF	R-2296	0.033uF	R-2325	
22pF	R-2243	390pF	R-2297	0.047uF	R-2327	

All one price 1-9 15¢ ea. 10 up 13¢ ea.

SPECIAL CERAMICS 60V rating

Special large capacitance ceramics for special applications.

0.1uF	R-2360	1-9	.30	10 up	.25	
0.22uF	R-2370	1-9	.45	10 up	.40	
High vol	tage ceram	ic (rated	at 3kV) f	or mains s	uppressio	on,

1.75

10 up

1.50

R-2400 **CERAMIC FEEDTHROUGHS**

Ideal for bypassing DC supply lines, RF amplifiers, noise suppression on motors, etc.

0.001uF 50V R-2851 1-9 .65 10 up .55

HIGH DISCHARGE (STROBE) CAPACITOR

Used in circuits such as photographic strobes or flashes where heavy discharge currents occur. Rated at 250 volts AC with

discharge resistor built in.

R-2855 6.5uF 250V AC 5.25 each TRIMMER CAPACITORS

RANGE CAT NO. PRICE EACH 10 UP 9.8-60pF R-2930 4.2-20pF R-2935 \$1.40

Automotive Suppressors

Capacitive and Resistive ignition noise suppressors for 0.5uF Bypass Capacitor

Standard "cure-all" for noisy coils, pumps switches, etc. Cat A-7902

Coax "Feedthru" Capacitor 0.5uF capacitor is designed to handle up to 60 amps — ideal for alternator and generator suppression, etc. Cat A-7928

Spark Plug Resistor 50k ohm resistor built into spark plug cap. Screw thread accepts standard HT lead. Cat A-7908 \$4 50



1495

HT Lead Resistor 50k ohm resistor with screw thread both ends for in-series mounting in spark plug leads. Cat A-7904



Using your 'easy find' resistor table..

Simply follow the 'value' column down on either side until you find the particular value

you requ	ire, and then	run across the tc.). That's the	column heade	d by the type of	f resister (e.g.	metal
VALUE	1/4 W	1/4 W	1/2 W	1W	5W	VALUE
OHMS	Metal Film 7¢ each	Carbon Film 5¢ each	Carbon Film 6¢ each	Carbon Film 14¢ each	Wire Wound 60¢ each	OHMS
	100 or more 5¢ each	100 or more 3¢ each	100 or more 4¢ each	100 or more 12¢ each	10 or more 50¢ each	
	St each	J¢ cacii	44 04011	124 000	R-1600	0.1
0.1 0.47					R-1601	0.47
1.0		R-1002	R-1202	R-1402	R-1602	1.0
1.2 1.5		R-1004 R-1006	R-1204 R-1206	R-1404 R-1406	R-1604 R-1606	1.2 1.5
1.8		R-1008 R-1010	R-1208 R-1210	R-1408 R-1410	R-1610	1.8 2.2
2.2 2.7		R-1012	R-1212	R-1412	11-1010	2.7
3.3		R-1014 R-1016	R-1214 R-1216	R-1414 R-1416	R-1614	3.3 3.9
3.9 4.7		R-1018	R-1218	R-1418	R-1618	4.7
5.6 6.8		R-1020 R-1022	R-1220 R-1222	R-1420 R-1422	R-1620 R-1622	5.6 6.8
8.2		R-1024	R-1224	R-1424	R-1624	8.2
10 12	R-0526 R-0528	R-1026 R-1028	R-1226 R-1228	R-1426 R-1428	R-1626 R-1628	10 12
15	R-0530	R-1030 R-1032	R-1230 R-1232	R-1430 R-1432	R-1630 R-1632	15 18
18 22	R-0532 R-0534	R-1034	R-1234	R-1434	R-1634	22
27	R-0536	R-1036	R-1236	R-1436	R-1636	27 33
33 39	R-0538 R-0540	R-1038 R-1040	R-1238 R-1240	R-1438 R-1440	R-1638 R-1640	39
47 56	R-0542 R-0544	R-1042 R-1044	R-1242 R-1244	R-1442 R-1444	R-1642 R-1644	47 56
68	R-0546	R-1046	R-1246	R-1446	R-1646	68
82	R-0548	R-1048	R-1248	R-1448 R-1450	R-1648 R-1650	82 100
100 120	R-0550 R-0552	R-1050 R-1052	R-1250 R-1252	R-1452	R-1652	120
150 180	R-0554 R-0556	R-1054 R-1056	R-1254 R-1256	R-1454 R-1456	R-1654 R-1656	150 180
220	R-0558	R-1058 R-1060	R-1258 R-1260	R-1458 R-1460	R-1658 R-1660	220 270
270 330	R-0560 R-0562	R-1062	R-1262	R-1462	R-1662	330
390	R-0564	R-1064	R-1264	R-1464	R-1664	390
470 560	R-0566 R-0568	R-1066 R-1068	R-1266 R-1268	R-1466 R-1468	R-1666 R-1668	470 560
680 820	R-0570 R-0572	R-1070 R-1072	R-1270 R-1272	R-1470 R-1472	R-1670 R-1672	680 820
1k	R-0574	R-1074	R-1274	R-1474	R-1674	1k
1.2k 1.5k	R-0576 R-0578	R-1076 R-1078	R-1276 R-1278	R-1476 R-1478	R-1676 R-1678	1.2k 1.5k
1.8k	R-0580	R-1080	R-1280	R-1480	R-1680	1.8k
2.2k 2.7k	R-0582 R-0584	R-1082 R-1084	R-1282 R-1284	R-1482 R-1484	R-1682 R-1684	2.2k 2.7k
3.3k	R-0586	R-1086	R-1286	R-1486	R-1686	3.3k
3.9k 4.7k	R-0588 R-0590	R-1088 R-1090	R-1288 R-1290	R-1488 R-1490	R-1688 R-1689	3.9k 4.7k
5.6k	R-0592	R-1092 R-1094	R-1292 R-1294	R-1492 R-1494		5.6k 6.8k
6.8k 8.2k	R-0594 R-0596	R-1096	R-1296	R-1496	R-1708	8.2k
10k	R-0598	R-1098	R-1298	R-1498		10k
12k 15k	R-0600 R-0602	R-1100 R-1102	R-1300 R-1302	R-1500 R-1502		12k 15k
18k 22k	R-0604 R-0606	R-1104 R-1106	R-1304 R-1306	R-1504 R-1506		18k 22k
27k	R-0608	R-1108	R-1308	R-1508	0.5	27k
33k 39k	R-0612 R-0614	R-1112 R-1114	R-1312 R-1314	R-1512 R-1514	same o ou	33k 39k
47k	R-0616	R-1116.	R-1316	R-1516	the s	47k
56k 68k	R-0618 R-0620	R-1118 R-1120	R-1318 R-1320	R-1518 R-1520	P. Re	56k 68k
82k	R-0622	R-1122	R-1322	R-1522	r 10 price	82k
100k 120k	R-0624 R-0626	R-1124 R-1126	R-1324 R-1326	R-1524 R-1526	is fo	100k 120k
150k 180k	R-0628 R-0630	R-1128 R-1130	R-1328 R-1330	R-1528 R-1530	to- 100-	150k 180k
220k	R-0632	R-1132	R-1332	R-1532	esis in a	220k 270k
270k 330k	R-0634 R-0636	R-1134 R-1136	R-1334 R-1336	R-1534 R-1536	the robta	330k
390k	R-0638	R-1138	R-1338	R-1538	all to	390k
470k 560k	R-0640 R-0642	R-1140 R-1142	R-1340 R-1342	R-1540 R-1542	n for nixec	470k 560k
680k 820k	R-0644 R-0646	R-1144 R-1146	R-1344 R-1346	R-1544 R-1546	PLEASE NOTE: The 100 up price shown for all the resistors is for 100 of the same type and value. Resistors can NOT be mixed to obtain a 100-up price. Refer to our bulk packs for mixed value resistors at huge savings!	680k 820k
1M	R-0648	R-1148	R-1348	R-1548	ice s IOT stors	1M
1.2M 1.5M		R-1150 R-1152	R-1350 R-1352	R-1550 R-1552	p pri an N resi	1.2M 1.5M
1.8M		R-1154	R-1354	R-1554	00 up prs ca alue	1.8M
2.2M 2.7M		R-1156 R-1158	R-1356 R-1358	R-1556 R-1558	ne 1(sisto ed vi	2.2M 2.7M
3.3M		R-1160	R-1360	R-1560	E. B. T.	3.3M
3.9M 4.7M		R-1162 R-1164	R-1362 R-1364	R-1562 R-1564	alue	3.9M 4.7M
5.6M 6.8M		R-1166 R-1168	R-1366 R-1368	R-1566 R-1568	SE P	5.6M 6.8M
8.2M		R-1170	R-1370	R-1570	Pe a	8.2M
10M		R-1172	R-1372	R-1572	ā 4 a	10 M

Single Rotary Pots \$1.50 ea (10 up \$1.40 ea)

METRIC	LINEAR			METRIC	LOG
500	R-6802	50k	R-6809	10k	R-6820
1k	R-6803	100k	R-6810	50k	R-6823
5k	R-6805	500k	R-6812	100k	R-6824
10k	R-6806	1M	R-6813		
20k	R-6807	2M	R-6814		
IMPERI	AL LINEA	R		IMPERI	AL LOG
500	R-1801	50k	R-1809	10k	R-1820

R-1810

R-1812

R-1813

R-1814



Single Rotary Log Switch Pots \$2.95 ea (10 up \$2.75 ea)

METRIC LOG 10k R-6879 10k 1M R-6888

5k

10k 20k

R-1803

R-1805

R-1806

R-1807

500k

2M





Rated at 5 watts

100k



Dual Rotary Pots \$2.95 ea (10 up \$2.75 ea)

METRIC	LINEAR	METRIC	LOG
10k	R-6834	10k	R-1603
20k	R-6836	50k	R-6853
100k	R-6840		

IMPERIAL LINEAR R-1834 100k R-1840 R-1836 50k 20k




10k

Wire Wound Pots (Rated at 3 watts)

\$4.95 ea (10 up \$4.50 ea)

5	R-6901	100	B-6909	\$6.9	5 ea (10 up
10	R-6903	200	R-6911	1k	R-6915
25	R-6905	500	R-6913	2k	R-6917
50	R-6907			5k	R-6921



Mini Vertical Trimpots 50¢ ea (10 up 45¢ ea)

100	R-1929	2k	R-1937	50k	R-1945	1M	R-1953
200	R-1931	5k	R-1939	100k	R-1947	2M2	R-1954
500	R-1933	10k	R-1941	200k	R-1949		
1k	R-1935	20k	R-1943	500k	R-1951		



Lge Vertical Trimpots 50¢ ea (10 up 45¢ ea)

100	R-1956	2k	R-1960	50k	R-1964	1M	R-1968	
200	R-1957	5k	R-1961	100k	R-1965	2M2	R-1969	
500	R-1958	10k	R-1962	200k	R-1966			
1k	R-1959	20k	R-1963	500k	R-1967			



Horizontal Trimpots 50¢ ea (10 up 45¢ ea)

100	R-1760	2K	R-1767	50k	R-1775	1M	R-1783	
200	R-1761	5k	R-1769	100k	R-1777	2M2	R-1784	
500	R-1763	10k	R-1771	200k	R-1779			
11	D 1765	201	D-1773	2704	D-1781			



10 Turn Trimpots \$2.60 ea (10 up \$2.40 ea)

1k	R-1900
10k	R-1901
20k	R-1902
50k	R-1903
100k	R-1910
	20k 50k



Replacement pots for transistor radios, etc

Miniature Rotary \$1.20 ea (10 up \$1.10 ea)




As used in larger radios, cassettes, etc. With 25mm long fluted shaft and on/off switch. Grab some for the junk box! Also ideal for general use, res. 5K.



50k Slider Pot \$1.25 ea (10 up \$1.10 ea)

As used in Playmaster Graphic Equaliser. Quality 50k linear pot, 73mm length, 45m overall travel. Special knobs are available to suit (see knobs page). Cat R-1980






Premium LED Pack 100 premium LEDs

Not the usual mix, these: they're top quality - matched for brightness & colour. Standard 5mm size: at this price you can afford to use premium LEDs on all your projects! You get: sixty red, twenty green, ten yellow and ten orange. That's a hundred premium LEDs for a song! Cat Z-3015

Shipping Weight: 41g Shipping Size: 190 × 100 × 10mm



Signal Diode Pack 100 pieces

Another beauty! A selection of the types of diodes we all use for projects - from crystal sets to computers! Contains five OA90. fifteen OA91/DSOA91, five OA95, five OA47 germanium diodes, and a huge seventy (yes, seventy!) 1N914 silicon diodes. Keep a pack in the junk box! Cat Z-3005

Shipping Weight: 40g Shipping Size: 130 × 100 × 30mm



Metal Film Resistor Pack

300 precision 1% 1/4W E-12 metal film resistors

Our 1% metal film resistors are even better value when bought by the pack! Now there's no excuse not to use metal films in all your projects - especially at this price! Cat R-7015


Shipping Weight: 66g Shipping Size: $135 \times 100 \times 20$ mm



Premium 3mm red LED pack 100 pieces

Highly suited for labs, manufacturers, etc and even hobbyists building lotsa-leds projects! Premium quality (matched brightness) 3mm size LEDs, 100 in pack. Cat Z-4076

Shipping Weight: 26g Shipping Size: 210 × 100 × 10mm



Power Diode Pack 57 diodes & SCR's

Just the type of pack you've been waiting for: over fifty of the most used power diodes and SCR's (not useless, rubbish types!). You get: 10 each 1N4002, 1N4004, 1N4007 1A diodes, 10 each 1N5404 & 1N5408 3A diodes, two W04 1.5A 400V bridges, three C106Y1 and two C122E general purpose SCR's. Cat Z-3010.

Shipping Weight: 54g Shipping Size: $210 \times 100 \times 20$ mm




Greencap Pack Electrolytic Pack 60 Greencaps

No weird, rubbish values in this pack. Every

greencap is as used in a number of circuits. 100 volt rating, too — and the values are selected from .001uF to 0.22uF (60 capacitors in all). Cat R-7040

Shipping Weight: 35g Shipping Size: $100 \times 170 \times 25 \text{mm}$



Premium 5mm red LED pack 100 pieces

Similar to pack at left, again a highly useful pack for anyone using LEDs in volume. Savings are over 40% on single LED prices (so if you need anything over 60 LEDs, the rest are effectively FREE when you buy this pack! 100 5mm premium quality red LEDs. Cat Z-4084

Shipping Weight: 42g
Shipping Size: 210 × 100 × 10mm



E-24 Metal Film **1% Resistor Pack** 300 pieces

Now for those who need really precision resistors, we've added this superb pack of low noise 1% metal films to our range:in the full F-24 series. Consists of 300 pieces. covering 60 values between 11 ohms and 910 kohms; computer chosen for maximum usefulness. Cat R-7020

Shipping Weight: 64g Shipping Size: $130 \times 100 \times 30$ mm



55 Electrolytics

55 top quality single ended (pcb mounting) electrolytics. You're sure to find one here you need. Range from 2.2uF to 470uF, voltages from 10 to 25. Cat R-7030

Shipping Weight: 54g Shipping Size: 130 × 100 × 30mm



Signal **Transistor Pack** 100 pieces

A nack of the most-used transistors the hobbyist, technician or design lab can have. Comprises twenty each of DS547, DS548, DS549 NPN types (equiv. BC107, 8 & 9), fifteen DS557 & DS558 (equiv. BC557, 8) and ten BC159 PNP types. Incredibly handy to have around: just in case! And look at the to have around: just saving ... Cat Z-3000


Shipping Weight: 30g Shipping Size: 160 × 100 × 30mm



Resistor Pack 300 computer selected 1/4W types

Ideal for the professional and the hobbyist, 60 values specially chosen by the computer. Quality 5% types — huge savings on normal prices: less than 3¢ each! Cat R-7010

Shipping Weight: 70g Shipping Size: $130 \times 100 \times 30$ mm



Ceramic Pack

Over 60 Ceramics

Quality ceramic capacitors in a specially selected pack. Voltages from 50V - some as high as 630VW. Save a fortune over oneoff prices. Cat R-7050

\$695

Shipping Weight: 24g Shipping Size: 170 × 100 × 15mm

Metric Range












Black body with deep flutes down side for positive grip. White radius pointer. Size 13mm diam, 15mm deep.

Tiny elegant knob, finished

and pointer, 14mm diam, 12mm deep, Cat H-3820



10 or more \$1.20



Black finished knob with silver shoulder and white marker, 20mm diam, 22mm deep, Cat H-3830

\$4 75

10 or more \$1.60






Aluminium knob with fine serrations down top third of body. With pointer, size 21mm diam, 18mm deep.

\$4 75

10 or more \$1.60









10 or more \$1.60







The smallest of four matching project knobs. Integral pointer across top. size just 11mm body, 15mm skirt and 15mm overall. Cat H-3850



10 or more 85¢











10 or more 90¢







Larger again: great as a tone control or switch knob on amplifiers, etc. 20mm wide with 25mm skirt, 16mm deep. Cat H-3860



10 or more \$1.35



The largest of the series: ideal volume or other main control used in conjunction with above knobs. 35mm wide skirt, 28mm wide body and 18mm height. Cat H-3865

\$4 75

10 or more \$1.60



Imperial Range

These are mainly intended to be used as replacements on existing equipment. They fit standard ¼" shafts, and are tightened by a grub screw

Small knob with fluted sides, small skirt with dot pointer. Size 19mm diam, 14mm deep.

Another very popular knob.
The pointer runs right through

from the top to the edge of the

skirt, Silver insert, Size 26mm

diam, 15mm deep. Cat H-3772

25

10 or more \$1.15

\$4 45

10 or more \$1.25








A superb instrument knob with wide skirt, calibrated 1-10 in black on silver. Size 37mm diam, 15mm deep. Cat H-3770

\$4 95



A very popular knob for all instruments, etc. Very positive grip and wide skirt with white pointer engraved on top. Size 31mm diam, 15mm deep. Cat H-3766

\$4 25

10 or more \$1.15



Vernier Drive

Precision vernier drive designed for front panel mounting. 50mm diam. Cat H-3900


10 or more \$11.35



Imperial Extension Shaft

Machined brass shaft for imperial pot shafts, tuning gangs, etc. Cat H-3950

10 or more \$3.75





Quality Reduction Drives

For new projects or as a replacement this is a superb precision vernier drive. With smooth, positive movement for the finest control. Suitable for panel mounting, the compact 27mm diameter makes it ideal for those tight spots. Inbuilt lugs make mounting a breeze. Cat H-3901

10 or more \$8.95





Slider Knob Nicely finished in black

16MM

aluminium and designed for an equalizer slider pot. Overall 16mm long and 10mm in diameter. Suitable for a large range of projects or as a replacement.







Coloured Plastic Knobs

What a colourful idea! Now your projects can really look the part with these snazzy coloured knobs. Use them to colour code sections (great on multi-channel mixers, lighting consoles, etc). 16mm diam, standard metric (fluted shaft) fitting. Inserts can be changed to suit the occasion! Choice of four with-it colours: Red Cat H-3800, Orange Cat H-3802, Blue Cat H-3804 and Green Cat H-3806

10 or more \$1.85

Universal Panel Meters

Universal 100uA panel meters that can be easily adapted for just about any situation — Volts, Amps, mA... anything! There's two sizes to choose from so you can match all your equipment.

Combined with our 'Shunt Pack' (Q-2046) and Meter Instrument Labels (N-5751) the meters will operate over the range 100uA to 316mA and 1V to 100V. Higher currents can easily be satisfied by providing an approprite resistance. Scale is to the I.E.C. standard.

Superb styling and rugged contruction make these the ideal meter to finish your projects. Come with comprehensive instructions!



Small

Dimensions: Scale Area — 55 × 30mm Overall — 55 × 52mm Mounting: Hole Required — 45mm Bolt Holes — 38mm square Cat Q-2045

\$15⁹⁵

Large

Dimensions:
Scale Area — 96 × 49mm
Overall — 96 × 82mm
Mounting:
Hole Required — 65mm

Hole Required — 65mm Bolt Holes — 64mm × 80mm centres Cat Q-2065

Shunt Pack

Designed to suit the above panel meters but they're handy for most meter conversion.

Comes with shunt resistors from 1.1 to 1,000,000 ohms, resistance wire and instructions. Cat Q-2046

\$4 50

20

Level Meters

Particularly suitable for AM/FM tuner and receiver projects, but also ideal for a huge range of other projects. Meter scale size 35 x 15mm (same size as cut-out required); impedance 1k. Straw coloured meter face, looks really great back-lit.



\$<mark>6</mark>95 each



Signal Strength Tuni

250uA FSD scale labelled 1-10 Cat Q-2100

Tuning Centre Zero

Sensitivity is 250uA half FSD (in either direction) Cat Q-2095

Edge Level Meter

As used in many imported cassettes, amplifiers, etc. Graduated 1 to 10 with 'battery check' stripe under the main scale. Scale size 32 x 10mm, it is ideal for a fine level adjustment meter, audio or battery level, etc. Mounts with screws, hole centres 49mm.

500uA FSD 500 ohms Cat Q-2110



\$695

Moving Iron Range

The two most popular ranges for the hobbyist, etc. AC/DC moving iron metres in two scales. Note: moving iron meters are not highly accurate, but give good relative indication. Oval style meter measuring approx. 55mm (wide) × 58mm (high).

0-20V (AC & DC) Cat Q-2080



0-10A (AC & DC) Cat Q-2090



Standard Range Panel Meters

A high quality range of moving coil meters, with full scale accuracy better than 2%. Easily adapted to suit virtually any requirement. All the meters have a fine needle for optimum accuracy in reading, and all have mechanical zero adjustment. Mounting is by four bolts with nuts and washers supplied.

Mounting:

Hole required — 44mm

Dimensions: Scale area — 58 x 31mm Overall — 58 x 52mm

VU Meter


-20 ±3VU (1.228V/0dB)

> Cat Q-2050 \$4595

0-5A DC

0-5A (0.03 ohms shunt) Cat Q-2030

\$4595





0-20A DC (0.007 ohms shunt) Cat Q-2035 \$4595



3.5 Digit LCD Panel Meter

Replace d'Arsonval meters with LCD digital: this 3½ digit module makes it easy. "Full Scale" of 200mV or 2V (user selectable) and a super high input impedance (>100 megohms) makes adaption to a range of applications very simple. The meter can be self mounted — includes a mounting bezel to make your project look really professional. Comprehensive data sheet included, showing several circuit variations. Cat 0-2200

Features:
Single supply rail (9V)
Low supply current (2mA max)
High accuracy (.01% ±2 digits)
Auto zeroing and overrange inbuilt
Meter size: 71 × 46 × 21mm

Shipping weight: 100g Shipping size: 120 × 80 × 40mm



DICK SMITH ELECTRONICS EXPRESS ORDER SERVICE STD FREE (008) 22 6610 (SYDNEY AREA (02) CALL 888 2105)

DIRECT TO YOUR HOME!

You can't beat DSXpress! Any item from the Dick Smith Catalogue can be ordered through DSXpress, 24 hours a day, for lightning fast despatch and delivery right to your door — home, office, factory . . . anywhere!

You choose the deliver method — mail, road or air freight, even courier delivery in the Sydney area: and we even subsidise freight!

If you can't get to a DSE Store, let DSXpress come to you!

You can also order 24 hours a day by:

Telex: AA20035,

OR Fax: (02) 888 3631,

OR Cables: "Diksmit", Sydney,

OR By Mail:

DSXpress P.O. Box 321, North Ryde NSW 2113

Packs

Pack of five clip-on heatsinks for TO-220 type semis (also adaptable to other types). Size 25 x 20mm, spring-type connection ensures good metal contact for efficient heat transfer. Cat H-3415

Shipping weight: 9g Shipping size: 120 x 80 x 30mm



Versatile Power Heatsink

The ingenious design of this heatsink makes it possible to mount it either flat on a panel, or at right angles to it (eg inside a case). The side fins also have tongue and groove so they may be joined sideways. Drilled version takes 2x TO-3's. Size is 78 x 110 x 33mm.

Undrilled Cat H-3460

Pre-drilled Cat H-3461



Economy Power Heatsink

Flag mounting with fins both top and bottom. Available in either drilled or undrilled versions, drilled accepts two power transistors of most types. TO-3, TO-126, TO-220, etc. Size 74 x 102 x 25mm. Thermal resistance mounting surface to ambient -1°C/watt (at 2ft/sec forced air flow). Mounting surface temperature rise above ambient with no forced air flow 60°C @ 30W heat dissipation level. Undrilled Cat H-3470


Shipping weight: 128g Shipping size: 160 x 110 x 30mm

Cat H-3470... \$4.50

10 up \$4.05

Pre-drilled Cat H-3471 Shipping weight: 105g Shipping size: 200 x 110 x 35mm

\$4.95 10 up \$4.25




TO-220 Heatsink High Efficiency Power Heatsink


With its thick base and radial fin design this heatsink is able to dissipate huge amounts of heat. It is black anodised for even greater efficiency. Thermal resistance mounting surface to ambient -1°C/watt (at 2ft/sec forced air flow). Mounting surface temperature rise above ambient with no forced air flow 60°C @ 30W heat dissipation level. Cat H-3422

Shipping weight: 132g Shipping size: 101 x 80 x 30mm

\$5.75

10 up \$5.45








Extra Heavy Duty Powerfin Heatsink

Similar to above heatsink in cross section. but three times the length. For those big projects where a lot of heat has to be removed. Cat H-3426

Shipping weight: 405g Shipping size: 102 x 303 x 30mm

Cat H-3426\$13.95

10 up \$12.95






Aluminium Heatsinks

Universal

Universal hole pattern allows the mounting of virtually all 'power' type semiconductors. Ribbed walls and black anodised finish for maximum efficiency. Cat H-3401



PCB Mounting

Just right for today's projects with eveything mounted on the pcb: two heatsinks that also mount on the pcb. Designed to be soldered direct to the tracks, with their fins mounted vertically for even more heat loss. Two handy types to

Large:

H pattern, 30 x 30 x 30mm, drilled to take a single flat-pack semiconductor (can be redrilled for other types). Cat H-3495



Small:

U pattern, 17 x 15 x 30mm high. Again, lled for a single flat-pack, with tapped 4BA hole. Cat H-3490




Round TO-5

Manufactured to exacting tolerances to ensure a snug fit and best possible heat transfer on TO-5 cases. Massive body allows rapid heat dissipation. Cat H-3412



Powerfin for TO-3

This heatsink gives the greatest possible heat dissipation in the smallest possible space. It is a unique fin design that gives a very high air to metal ratio (thermal rating approximately 5°C/watt). Measures only 50mm square x 26mm high, pre-punched to suit TO-3 case. Black anodised finish.



Mini

Because it suits virtually all flat (plastic type) semiconductors, this heatsink is used extensively on PCB, etc. Has vertical flutes for maximum thermal efficiency. Cat H-3402

Shipping weight: 10g Shipping size: 100 x 90 x 30mm

Cat H-3402.....

10 up \$1.25



HARDWARE

Self-Tapping Screw (Packs)

Ideal for projects or as replacements for lost screws. These units are Cadmium

N - 4 - 40 0i 40	05		Ea aa		
No. 4 x 12mm: Size 40	25	H-1612	\$1.30	\$1.20	109
No. 4 x 6mm: Size 40	25	H-1611	\$1.30	\$1.20	12g
No. 8 x 12mm: Size 30	25	H-1632	\$1.30	\$1.20	37g

Nylon Nuts and Bolts

Precision moulded from '66' white nylon. Fully insulated, will not shake loose, can resist high temperatures and they are corrosion free. These items are hard to get but we have them and they are ideal for transistor and heatsink use. Tough but light.



Description	Pack Qty	Cat No.	Price per pack	10 up	Wt.
12mm x 4BA cheese hd	10	H-1012	\$1.15	\$1.05	3g
25mm x 4BA cheese hd	10	H-1022	\$1.15	\$1.05	5g
4BA hex nut	12	H-1302	\$2.30	\$2.10	2g
4BA nylon washer	12	H-1452	\$1.15	\$1.05	2g
12mm x 6BA cheese hd	10	H-1032	\$1.15	\$1.05	1g
25mm x 6BA cheese hd	10	H-1042	\$1.15	\$1.05	4g
6BA hex nut	12	H-1312	\$2.30	\$2.10	2g
6BA washer	12	H-1462	\$1.15	\$1.05	1g

Steel Nuts and Bolts

1/8" Whitworth round head zinc plated just the kind of item that should be in your 'ready' box for future projects.

	Pack	Cat			
Description	Qty	No.	Ea	10 up	Wt.
9mm long	25	H-1052	\$1.15	\$1.05	18g
2mm long	25	H-1062	\$1.15	\$1.05	23g
5mm long	25	H-1072	\$1.15	\$1.05	29g
3mm hex nut	30	H-1322	\$1.15	\$1.05	15g
3mm s-proof washer	50	H-1472	\$1.15	\$1.05	6g
3mm metal washer	50	H-1482	\$1.15	\$1.05	14g

BA Type Nuts and Bolts

Both brass and steel types in

	Qty	No.	Ea	10 up	Wt.
12mm x 4BA bolt	25	H-1082	\$1.15	\$1.05	31g
4BA hex nuts (brass)	20	H-1332	\$1.30	\$1.20	15g
4BA flat washer (steel)	50	H-1488	\$1.15	\$1.05	12g
4BA s-proof washer	50	H-1486	\$1.15	\$1.05	7g
2mm x 6BA bolts	25	H-1092	\$1.30	\$1.20	22g
6BA hex nuts (brass)	25	H-1342	\$1.30	\$1.20	9g

6BA pack containing 12 of each 12mm bolts, brass nuts and shakeproof washers. A total of 36 units.

10 packs or more \$1.60

8BA pack containing 12 of each — 12mm brass bolts, nuts and washers. A total of 36 units. \$3.45 10 packs or more \$3.10

Cross pan-head screws to suit most switches with threaded mounting holes Two sizes to choose from, each pack




	_		
Ea	10 up		Wt.
H-1672	\$1.50	\$1.35	10g
H-1674	\$1.15	\$1.05	5g
	H-1672	H-1672 \$1.50	Ea 10 up H-1672 \$1.50 \$1.35 H-1674 \$1.15 \$1.05

High **Tensile Hex** Head

When strength is important, here's the answer: high tensile steel bolts, complete with washers and nuts, with hex head (allen key adjustment) for security. Two sizes to

Pack 1: 6BA size × 20mm (pack of 4) Cat H-1000 Pack 2: 4BA size × 20mm (pack of 4) Cat H-1010

\$ 795 10 up \$2.75



Big Pack of Screws!

always missing! 1/4" pk screws (self tappers to the uninitiated) a pack of around 500, Cat H-1625

Weight: 210g

10 up \$7.20



Metric Screv Packs

Description	Quantity	Cat No	Price	10 up	Wt.
Asst P/H	160pc	H-1500	\$3.25	\$2.05	55g
S/Tap Screws	150pc	H-1505	\$2.25	\$2.05	42g
Asst C/S					
S/Tap Screws	320pc	H-1510	\$5.95	\$5.45	
Asst P/H		H-1515	\$2.95	\$2.75	113g
Machine Screws	270pc				
Asst C/S					
Assorted Nuts	340pc	H-1520	\$4.25	\$3.95	
Asst Washers	680pc	H-1525	\$4.25	\$3.95	102g

Insulated Spacers

The ideal spacer for insulating the chassis from your PC board. They come complete with screws.

Description	Pack Qty	Cat No.	Price per pack	10 up	
10mm	5	H-1861	\$3.25	\$2.95	
15mm	5	H-1862	\$3.45	\$3.25	
20mm	5	H-1871	\$3.75	\$3.45	
25mm	5	H-1872	\$3.95	\$3.65	

Plated Brass Spacers

High quality nickel plated brass spacers. May be stacked for extra length if required.

4BA (1/8") clearance hole 6mm OD

Description	Pack Qty	Cat No.	Price per pack	10 up	Wt.
6mm	12	H-1831	\$4.95	\$4.45	16g
9mm	10	H-1832	\$3.45	\$3.25	9g
12mm	8	H-1833	\$3.45	\$3.25	9g
25mm	6	H-1834	\$3.45	\$3.25	11g

H-1843

H-1847


\$3 25

Hexagonal 4BA tapped 6mm OD

9mm 12mm

25mm

6 H-1842



\$3.45 \$3.45	\$3.25 \$3.25	9g 11g	
M	}		7
LIN			

Lin		
Ea	10up	Wt.
\$2.25	\$1.95	15g
\$2.45	\$2.20	18a

\$2.95

Pot Nut Pack

If you're typical of most hobbyists, your junk box contains a whole swag of . without nuts! This pack will solve the problem: an assortment of %" and metric pot nuts, plus washers, ready to use. Pack of 20. Cat H-1360

Circuit Board Supports

in position with sufficient clearance above the chassis. They snap into place and can be easily installed or removed by hand. They require a 4mm hole in the PC board and 4.75mm clearance hole in the chassis. Made of nylon. 9mm long.

Pack of 6

Transistor TO-3 **Insulating Cap**

fit over TO-3 transistors. Avoid shorts to chassis (which could blow the transistor or exposed high collector voltages (which could blow you!). Fit a cap to those TO-3's, Cat H-1918

Weight: 5g

Insulated **Transistor Mounting Kits**

TO-3 Type

A pack of four TO-3 transistor mounting kits (mica washer and 2 bushes). Specially selected to give maximum heat transfer. Cat H-1917

\$4 25 Weight: 2g 10 up \$1.15

TO-220 Type

Now there's no problem in mounting TO-220 type semis. Pack of 5 insulating washers and bushes. Cat H-1916

5 © Weight: 3g

5mm LED **Mounting** Bezels

Pack of 15

When making up projects that have LED power indication or otherise why not dress' your LEDs for that added professional touch. They work out at less than 10¢ each! Cat H-1910

10 packs or more \$1.45



MICA

Weight: 8g

HARDWARE

3AG PCB Fuse Clips

Made for soldering direct to pcb to give on-board fuse protection. Standard 3AG size, pack of eight means you'll get four fuse holders. Cat H-1700







Assorted Spade Lug Pack

Approximately 100 plated finish spade lugs which are ideal for a huge variety of hobbyist uses: speaker connections. earth terminals, automotive wiring, etc. They can be either crimped or soldering depending on the application. Range of sizes supplied. Cat H-1994

Weight: 88g

10 up \$6.30



Assorted Crimp Lug Pack

30 crimp lugs of various types, all with insulation already attached. Can be crimped with either crimping tool or a pair of pliers. 30 lugs and cable joiners in handy pack. Cat H-1996

Weight: 32a

10 up \$5.25



Assorted Metric Screw Pack

Over 200 pieces of the most popular small sizes: M2.5, 3 and 4 nuts and screws — cross, round and countersunk head. Plated finish, ideal to have on hand in the work

Weight: 67g

10 up \$7.45



Pack of 5 5mm dress nuts for standard miniature toggle switches. Makes that panel look really snazzy! Cat H-1912

Weight: 10g



Weatherproof Hoods

Again designed for standard miniature toggle switches, these screw onto the switch to prevent moisture ingress. Ideal for switches in marine applications (Note: only protect toggle, not rear of switch). Pack of 8. Cat H-1914

Weight: 15g



Right Angle Brackets

steel with Cadmium plating. They are ideal for projects where right angle mountings have to be made. They have a 3mm clearnance. Cat H-1895

Weight: 5g

10 up \$4.15 \$____50

Heavy duty grommets made of black rubber. Essential when cable passes through a metal chassis as they will prevent fraved cables and live chassis.

Hole Size	Bore		Price	10 up	Wt.	
8mm 16mm 12mm	5.5 6 9	H-1712 H-1716	\$1.45	\$1.25 \$1.25 \$1.10	8g 15g 13g	
_					_	



 no holes to bore in your chassis, you just stick these handsome black feet on! They have hundred of uses including being used on store bought equipment. Cat H-1745

Weight: 5g



10 up \$1.20

Big Feet!

Similar to above rubber feet, but these ones are 20mm square so they're ideal for bigger projects. Great for replacements, too. Use on commercial equipment to prevent scratches and marks. Pack of 4 feet. Cat H-1749

10 up \$1.75





Rubber Feet Screw-on

The conventional rubber feet that have a 3mm hole for screw mounting. Made of black rubber, they can also be cemented on to your project. Cat H-1736

8 in a pack Weight: 10g **\$4** 35

Super Stick Acrylic Bumpons

Yeh, we know. What a name! But they're probably the best "rubber" feet you'll ever find for projects, even for your appliances (videos, cassettes, etc.). Tough acrylic means they won't wear — but they won't scratch either. And they're super self-adhesive: just peel them off their backing paper and stick in position. Amazing? No — but useful! Pack of four Bumpons. Cat H-1740

10 up \$1.10

Cable Clamps

These are heavy duty Nylon cable clamps and are a must for terminating power cords and all cables, especially in projects Wt.

Cables up to 6mm diam. Cables up to 8mm diam. 5 H-1966

95¢ 95¢ 95¢ 80¢ 80¢ 80¢ 5 H-1964



Cables up to 5mm diam.



Two-part Clamp

Serrated teeth in both parts of these clamps mean positive locking. Include holes through both parts to enable nailing to walls, etc. Heavy duty, pack of five. Cat H-1972

10 up \$1.75

pack of 5

Cable Ties

When making any project, that little extra professionalism will make the job look better. These units will handle up to 20mm diameter and down to 2 single wires. Cat H-1970

Weight: 12g

Ş**4 2**5 10 up \$1.15

Anchor Cable

Called "anchor" because they'd tie up the QE2! Huge 292mm long, hold large groups of cables (almost 90mm diameter if pi still equals 3.14159268). Pack of 50 ties.

Weight: 110a



10 up \$5.50

Not quite as big as above, but still a healthy 156mm — and there's still 50 in the pack! Includes mounting hole for screwing/nailing in position if required. Cat H-1969

Weight: 50g



10 up \$3.60

Cord Clamp

This is a self-locking grommet that maintains a secure grip on the cable without the use of separate clamps. Both a grommet and a clamp in one! Fits 3 core miniflex or equivalent cable size. Hole size 12 to 16mm. Cat H-1724




\$**4** 45

10 up \$1.25

How many hours have you spend stripping, soldering and insulating wire? Forget it in the future! These brilliant connectors join wires instantly. All you have to do is lay the two wires to be joined inside the connector and squeeze the connector together with pliers. Can be used in car wiring, trailer wiring, etc. Hundreds of uses. 2 per pack. Cat H-6720



10 up 85¢



With Both Aluminium And Plastic Lids...

The New Zippy Box

The box most preferred by the major electronics magazines because of its quality and versatility! Now, with every DSE Zippy Box you get an even better finish with a tight fitting plastic and recessed aluminium lid - Yes, two lids with each box!

Not only does the plastic lid have a better finish with smooth rounded corners, but it makes it much easier to seal the box against the elements. Fantastic for projects that are exposed to the weather, etc.

Each DSE Zippy Box has deep ribs for extra strength and are ideal for mounting PCB's without worrying about screws. There's a great range of sizes to suit just about any Price Price


Small — UB5		Ea.	10 up
Cat H-2855	28 × 54 × 83mm	\$2.40	\$2.20
Medium — UB3			
Cat H-2853	41 × 68 × 130mm	\$3.00	\$3.25
Large — UB1			
Cat H-2851	50 × 90 × 150mm	\$3.95	\$3.75
Giant — UB2			
Cat H-2852	60 × 113 × 196mm	\$5.50	\$5.10

\$220

Plastic Instrument Cases

66 x 46 x 30mm

Moulded case for small projects. Complete with 'matrix' style assembly board, lid has flange mounts. Case size 66 x 46 x 30mm. Ideal for car projects! Cat H-2765



95 x 45 x 145mm


This precision instrument case, exclusive to Dick Smith Electronics has a specially designed vent system to allow for free circulation of air. Its unique snap together design means that no screws are required. With front and back panels included this case is ideal for small projects. Size 95 145 x 45mm. Cat H-2503



130 x 75 x 130mm

Heavy slotting makes this the ideal power supply case — or other heat generating projects. Includes both front and rear panels, slot system makes for easy pcb mounting. 130 x 130

\$095 10 up \$9.30



155 x 65 x 160mm

Similar to above case, but more suited to mounting PCB's: contains 16 slots for vertical mounting of 145mm long pcb's (up to 55mm high), also has 23 mounting points for horizontal pcb(s). Very attractive grey colour with black crinkle finish front and rear panels. Box size 155(w) x 65(h) x 160(d)mm. Cat H-2508

Shipping weight: 320g Shipping size:180 x 160 x 40mm

10 up \$9.25 200 x 95 x 140mm

Attractively styled black ABS case complete with handle ideal for test gear, power supplies, etc to be moved around. Off-white front and rear panels slot into place. Case contains slots for speaker, cooling, etc. Case Size: 200(w) x 95(h) x 140(d)mm. Cat H-2506

Shipping weight: 420g Shipping size: 220 x 70 x 140mm

200 x 65 x 160mm

A superb case for all 'instrument' type projects, and many more. Case splits apart for ease of working, comes complete with 4 rubber feet and assembly screws. Amazingly versatile allowing for various PCD mounting positions, front and rear panels are moulded plastic for ease of working (they can be replaced with aluminium panels if required). Size approx 200 x 160 x 65mm. Cat H-2505

Shipping weight: 385g

210 x 55 x 175mm Designed for use with out UHF Transceiver Kit (K-6300), but superb for a large range of instruments, communication equipment, projects, etc. Features removable front and rear panels, easy PCB mounting. Provision for mounting bracket too. Size 210 x 175 x 55mm. Cat H-2520



PJ Box

90 x 56 x 32mm

Nicely finished black plastic case for those smaller projects. Made in two identical halves which snap together or can be glued for a watertight seal which makes it ideal for all-weather projects. Cat H-2857

2 Sizes

Superb instrument case with heavy slotting for mounting PCB and extra strength. Has an abundance of mounting points for fixing horizontal PCB's. Finished in grey with black front and rear panels. Complete with case screws and mounting

cat H-2507 250 × 190 × 80mm \$17.95 10 up \$17.25 Cat H-2508 150 × 155 × 60mm \$9.75 10 up \$9.25



"Pocket" Case

A tiny (57 x 36 x 17mm) case intended for pocket or keyring transmitters: infra-red, ultrasonic, UHF, etc for alarms, garage openers, etc. Moulding has provision for 12V lighter battery (VR22) (battery clips included) plus push button (also included). PCB size to 45 x 32mm, case has pocket clip on back. Cat H-2497

Shipping weight: 20g


Junction Case

Unique design intended for use as low voltage junction point (eg in cars, for hifi, etc). Gives extra security for the junction. Includes mounting plate and cover with room for able entry both sides. Would also take small pcb to 40 x 45mm, Cat H-2830

Shipping weight: 50g

)50 10 up \$2.25

10 up \$2.70



Metal Cabinets


projects, especially those with meters, control, etc. which need to be mounted on the front panel. They consist of an aluminium base, slots, and selftapping screws complete with cup washers. All-inall a case you'd be proud to put you prestige projects into. They come in an attractive two-tone

		Ea	10 up	Wt.
102 x 56 x 83mm	Cat H-2741	\$5.95	\$5.50	180g
150 x 61 x 103mm	Cat H-2742		\$5.95	280g
150 x 76 x 134mm	Cat H-2743	\$6.95	\$6.60	340g
185 x 70 x 160mm	Cat H-2744	\$9.95	\$9.50	440g

"Horwood" Instrument Cases

the world - Horwood cases feature removable front and rear panels, lids, and front-mounted handles to make them look really professional. Available in two sizes:


203 x 102 x 254mm. Weight: 1 kg Cat H-2455 \$29.95



Boxes Precision die-cast boxes have always been expensive, but these boxes prove you don't have to pay through the nose! English and Australian made, and you save a fortune over inferior models! These and you save a fortune over inferior models! These are the ones with channelled walls for easy PCB mounting — and they're ideal for RF circuits because the lid forms a very effective screen. They're also great for circuits involving heat — remember diecast aluminium makes a great heatsink. And these boxes will withstand incredibly high temperatures: up to 600°C! Complete with

Diecast Aluminium

		Ea	10 up	Wt.	
190 x 60 x 110mm	Cat H-2201	\$18.95	\$17.95	546g	
150 x 50 x 80mm	Cat H-2206	\$12.95	\$11.95	296g	
120 x 40 x 65mm	Cat H-2211		\$7.75		
100 v 25 v 50mm	Cat H 2221	\$6.75	\$6.45	204g	



Extruded Aluminium Cases 310 x 75 x 250mm. Weight: 1.2kg Cat H-2465 \$31.95 Superb range of cases based on a


specially made 18 gauge aluminium extrusion giving cases which are ultra strong, ultra reliable. The extrusion measures 76 x 102mm - and is available in three different lengths. Internally, there are four slots for insertion of pcb's without use of screws (pcb width 92 or 71mm). End plates fasten into corners of extrusion with PK screws. Includes 2 end plates and 8 screws.

76mm length Cat H-2420 \$14.95 Weight: 180g Case size: 102 x 76 x 76mm

102mm length Cat H-2425 \$16.95 Weight: 230g Case size: 102 x 76 x 102mm

153mm length Cat H-2430 \$18.95 Weight: 330g Case size: 102 x 76 x 153mm

a



All-steel Project Case

Two-part case ideal for all your small instruments, etc. Twin 'U' construction, top is slotted for ventilation. Size 160 x 130 x 50mm. Finished in Blue with metalic base. Cat H-2762

\$Q95 Shipping weight: 380g

10 up \$9.50

19" Rack Mounting Case

Quality black instrument case fits standard 19" racks, overall they're 4.2 x 25 x 14cm. Supplied flat, assembly takes just a couple of minutes. Heavy gauge (3mm) front panel; top and bottom prepunched for ventilation. Cat H-2481

195 Shipping weight: 330g

Aluminium Boxes

Just the snot for those weekend projects that get left lying around! Put them in an economical aluminium box... The boxes come in two pieces which slide together — they even come with screws to hold them together! Versati

		Ea	10 up	Wt.
110 x 51 x 70mm	Cat H-2300	\$3.75	\$3.40	80g
104 x 60 x 46mm	Cat H-2305	\$3.75	\$3.50	69g
127 x 102 x 76mm	Cat H-2320	\$4.95	\$4.50	148g
133 x 76 x 54mm	Cat H-2325	\$4.50	\$4.05	104g
152 x 132 x 103mm	Cat H-2330	\$6.75	\$6.10	251g
180 x 158 x 118mm	Cat H-2335	\$9.95	\$9.35	364g



Low Cost Amp Metalwork

Two part assembly which fits together to form case and chassis. Pre-drilled and punched, it's designed for our Low Cost Amp (K-4001) but you'll find it ideal for many custom built amps. Case is vented and comes with screws! Cat H-2900

10 up \$18.95



DSE Zip-Rack There's only one rack system built in Australia that encompasses all the quality and features of

a professional system at a budget price! The multi-system designed to handle both standard (19") and non standard equipment. Don't settle for second best! Only DSE has the genuine Zip-Rack which offers heavy duty

genuine 2Ip-nack which others use light duty), nylon caps for surface protection (the others let you scratch the desk), tough black corner moulds (they use SOFT grey plastic), two sizes to choose from and all these other features as well...

- Incredibly easy to assemble
- **Both Front and Rear mounting facilities**
- Integrated stand-off feet for maximum air
- Can be stacked to house ALL your equipment
- Allows non-standard equipment to be mounted
- Comes complete with Philips head screws, nylon washers and captive nuts for mounting.

 • Attractive anodised finish
- Measures 540 (W) × 360 (D) × 675mm (H)

Zip-Rack the quality mounting system for test gear, audio, video, hi-fi, PCB sub racks, kits...

More Space!

Also available is the larger Model 18RU measuring 540 (W) × 360 (D) × 943mm (H). measuring 540 (W) A 300 (D) A STRING STRING

Zip-Rack Equipment Tray \$1995

Specially designed tray lets you mount non-standard equipment on your ZIp-Rack. Includes nylon clips. Ideal for computer, CB, amateur, video, etc, etc! 485mm ($19^{\prime\prime}$) \times 330mm. Cat H-2471

Hardware Pack

Superior Rack

System...

Model 12RU Cat H-2469

Allows you to mount 19″ equipment directly into your Zip-Rack without using trays. Cat H-2472

\$995

AUDIO & SOCKE **AXR-LNR-31** Plug P-1166 Socket P-1266 PANEL SOCKET **PHONO** CANNON DIN **RCA** \$795 10 up \$7.15 2.5mm MINIATURE STANDARD AUDIO **PLUGS** 2 PIN LINE PLUG \$4 25 \$4 50 Red P-1420 Black P-1422 Plug RANGE **AXR-LNE-32** 10 up \$1.15 10 up \$1.35 50° 70 **AXR-3-11** 40 50° **PANEL PLUG** LINE SOCKET 10 up 45¢ 10 up 65¢ Metal Stereo Plug 10 up 35¢ 10 up 45¢ \$750 OI THE \$4 75 0 10 up \$6.75 10 up \$4.70 10 up \$1.60 LINE SOCKET Coloured boot to fit Plastic LINE SOCKET P-1232 **AXR-3-32** Cannon Line Plugs & LINE SOCKET PANEL PLUG Sockets 65¢ (6) Stereo: P-1286 **2 PIN LINE SOCKET** Red P-1615 Yellow P-1616 Red P-1410 Black P-1412 10 up 58¢ \$4 15 \$1 50¢ Green P-1617 10 up \$1.05 50 Blue P-1618 3.5mm MINIATURE 70 10 up 45¢ 10 up \$3.60 10 up 45¢ Socket STEREO PANEL Plug Red P-1132 CABLE ENTRY 4.5 DIA. 10 up 65¢ **SOCKET WITH** P-1231 **DPDT SWITCH** Ideal for headphone sockets The state of the s **AXR-3-12** 们 NEUTRIK P-1276 18.5 **3 PIN LINE PLUG** LINE PLUG \$4 95 P-1624 50° 60¢ \$4 25 Metal: \$ 195 10 up \$1.75 Red P-1424 Black P-1426 Neutrik in XLR, 10 up 45¢ 10 up 54¢ 10 up \$1.15 10 up 70¢ 10 up \$4.45 too!



\$4 20

10 up \$1.10

00000



in XLR plugs and sockets

LINE SOCKET WITH SWITCH

\$4 4 25 10 up \$10.15 RIGHT ANGLE LINE SOCKET

\$095 10 up \$8.95

HEAVY DUTY LINE PLUG Water & \$550 dust resistant

10 up \$4.95 **HEAVY DUTY** LINE SOCKET dust

\$610 dust resistant 10 up \$5.50

PLASTIC CHASSIS PLUG

\$725 10 up \$2.00

PLASTIC **CHASSIS SOCKET**

\$775 10 up \$2.50

PCB MOUNT

Mount the plastic chassis

plugs or sockets direct to a pcb.

P-1589 (above) shown with P-1590 vertical PCB mount fitted.

VERTICAL **PCB MOUNT** P-1590

HORIZONTAL **PCB MOUNT**

Both

\$4 25 10 up \$1.13

Metal Plug P-1162

\$4 50

\$895

10 up \$8.05

10 up \$1.35

LINE SOCKET

P-1631

\$050

10 up \$8.55

RF/DC JGS-&-SOCKET

UHF

CO-AXIAL

300 OHM

DC POWER

STAR PLUG

P-1670 2.5 & 2.1mm (as below) plus 2.5 & 3.5mm phono type all on one unit. Simply plugs

in a 2.5mm plug. Reversible polarity.

BATTERY HOLDER & SNAPS

(B)

COLOUR CODED LEADS

◍◍

12.7

- LONG FLAT

4 x "AA" SIZE

6 x "AA" SIZE

8 x "AA" SIZE

RECTANGULAR

BATTERY HOLDER

RECTANGULAR

HOLDER

\$4 00

HOLDER

10 x "AA"

\$**4** 75

\$4 45

HOLDER — SQUARE

10 up 90¢

10 up 90¢

10 up \$1.35

10 up 25¢

BATTERY SNAP Suit 216.

P-6216

30

PL-259

Coax line plug, wide back to suit RG8-U, UR67, RG213 THE R



10 up \$1.75

DI 259 As above, but narrow back to suit RG-58U, etc.

\$495 10 up \$1.75 **PL-259 REDUCER**

No soldering required, use with PL-259 to give tight fit for 50 ohm coax. Suit P-2310 (above). P-2360

60° 10 up 55¢ **SO239 JOINER**

Two sockets for use back to back with PL-259. P-2380



SINGLE MOUNT SOCKET

SO-239 To accept PL-259 plug. Single hole chassis mounting, Cat P-2342

10 up \$1.90

PANEL MOUNTING SOCKET BULKHEAD SO-239 to suit PL-259, Screw

mounting. P-2340 **\$4** 90



With PL-259 plug & SO-239 sockets P-2384

\$595 10 up \$5.35 **RIGHT ANGLE**

With SO-239 socket & PL-259 plug. Cat P-2382

\$395 10 up \$3.55

'N' CONNECTORS NICKEL PLATED Male Line Plug Cat P-2400 \$895

10 up \$8.10 Female Line Socket P-2405

\$895 10 up \$8.10



BNC

BNC LINE PLUG Suitable for RG58RU cable.



BNC PANEL


SOCKET Accepts P-2210. P-2220





PLASTIC LINE PLUG

\$4 20 10 up 90¢



PLASTIC LINE SOCKET \$420

10 up \$1.10 **METAL LINE PLUG**

\$4 80

10 up \$1.60



METAL LINE SOCKET

\$**4** 80



10 up \$1.60

PANEL SOCKET Suits P-2020, P-2021



P-2070

10 up \$1.26

75 OHM CABLE JOINER

Positive screw connection with plastic cover. Can be waterproofed. P-2075



\$4 50



10 up \$1.35 **TV WALL PLATE**

with 75 ohm socket Plastic wall plate with built in 75 ohm TV connector. Can also be used as a 75 ohm splitter. Cat P-2042

\$**1**95 10 up \$4.45

SKIRTING BOARD

SOCKET Makes neat installation around skirting boards. Complete with mounting screws. P-2044



\$495 10 up \$4.45



Suit ribbon cable. Comes with plug.



10 up \$1.05

SOLDERLESS PLUG

No soldering required: snap apart construction. P-2084

\$4 20

\$4 20



CABLE JOINER

An age-old problem solved! 300 ohm ribbon plug and socket, no soldering required. P-2086



UNIVERSAL

System of wall plates and inserts covering 3 major system... Just snap in the insert required.

WALL PLATES

Large and small, same size as standard light switch architrave plates



10 up \$1.60 **INSERTS**

P-2050

Small

P-2052

Push-fit inserts to suit above plates.





CAR RADIO ANTENNA

ANTENNA PLUG 75° 10 up 70¢ **CHASSIS MOUNT** SOCKET 10 up 70d



10 up \$2.65


10 up \$1.10 1.3mm PLUG 60 10 up 54¢





2.5mm PLUG













Extremely handy for operating recorders or any other 12 volt appliances in your car. P-1675



\$4 25 10 up \$1.15 ° Μф 1 x "D" SIZE HOLDER - SQUARE

4 x "C" SIZE HOLDER



9V CHASSIS/PCB MOUNT

10 up \$3.35

IC SOCKETS & PLUGS


Why endanger valuable IC's by soldering them directly into circuit? Take the safe approach: use an IC socket! It approach: use an IC socket! It makes service and repair of your project much, much easier too. There's an IC socket to suit almost all common ICs.



8 Pin Mini DIL Socket P-4080 10 up 18¢



14 Pin DIL Socket 10 up 22¢ 14 Pin DIL Plug \$2.40 10 up \$2.15 16 Pin DIL Socket 30¢ 10 up 27¢ 16 Pin DIL Plug \$2.50 10 up \$2.25 P-4162 18 Pin DIL Socket P-4180 10 up 32¢ 20 Pin DIL Socket 45¢ 10 up 40¢ P-4200 22 Pin DIL Socket 50¢ 10 up 45¢ P-4220 24 Pin DIL Socket 10 up 50¢ 28 Pin DIL Socket 60¢ 10 up 55¢ P-4245 40 Pin DIL Socket P-4250 10 up 60¢



14 Pin w/wrap DIL Socket \$2.00 10 up \$1.80 16 Pin w/wrap DIL Socket

10 up \$1.60 P-4262 \$2.50 10 up \$2.25 20 Pin w/wrap DIL Socket P-4264

10 up \$2.70 24 Pin w/wrap DIL Socket \$4.00 10 up \$3.60 P-4268



MOLEX IC SOCKET STRIP

Make your own IC Sockets!
Fantastic idea! Never run out of IC sockets — because you make your own. Just cut the required number of pins from the strip and solder them in. After you insert the IC, you break off the carrier strip (also helps protect the IC from static damage). Pack of 100 pins strip. pins strip. P-4504


\$275 10 or more \$2.50



8 SOCKE

MULTI PIN PLUGS AND SOCKETS

2 PIN LINE PLUG





29.5


70¢

10 up 65¢

4 PIN LINE PLUG



5 PIN LINE PLUG





5 PIN CHASSIS Socket for P-3120 P-3135

\$4 70

10 up \$1.60

10 up 65¢


COVER FOR P-3120 & P-3125 P-3140 70°

8 PIN CHASSIS SOCKET

\$4 95

10 up \$1.75






8 PIN LINE PLUG WITH COVER

\$4 95

10 up \$1.75





PLUGS - & **SOCKETS**

2 PIN PLUG & SOCKET - MOLEX



3 PIN PLUG & SOCKET - MOLEX

10 up \$2.05

ינדעו

\$725

4 PIN PLUG & SOCKET - MOLEX


10 up \$2.25 \$750



6 PIN PLUG & SOCKET - MOLEX

\$295

10 up \$2.70



12 PIN PLUG & SOCKET - MOLEX



QUICK CONNECT



10 packs or more \$1.35

MALE SPADE For P-5012. Pack of 10. P-5016 \$4 50 10 packs or more \$1.35

COVER FOR P-5012 & P-5016 \$4 50

10 packs or more \$1.35

DOUBLE ADAPTOR Pack of 10. P-5026 0 \$4 65

10 packs or more \$1.45

ROUND LUG 10 mm HOLE Pack of 12 P-5032



MINI SPACE TERMINALS Pack of 10 \$4 25 10 up \$1.10

BULLET TERMINAL Male — pack of 10 P-5006

\$4 55

10 packs or more \$1.40 DINA

PLASTIC COVER TO SUIT ABOVE Pack of 10 P-5007

95°

10 packs or more 85¢

BULLET TERMINAL pack of 10.

\$4 55

10 packs or more \$1.40



PLASTIC COVER TO SUIT ABOVE Pack of 10 P-5009

10 packs or more 85¢




BANANA

4mm PLUGS Red P-1710 Black P-1712 Yellow P-1714 Green P-1716 10 up 45¢



Red P-1720 Black P-1722 40 10 up 35¢




4mm SOCKET WITH **BINDING POST**

Red P-1730 Black P-1732 Yellow P-1734 Green P-1736




10 up 85¢

TO-5 suit 2N3053 etc P-4015








CRYSTAL SOCKET

TYPE K SMALL

10 up 85¢



TERMINALS **ETC**

MAINS TERMINAL **BLOCKS**

With nylon, mains terminal strip, two screws per terminal, a twelve way, or by cutting the strip, any number terminals. 240V AC rating. \$1.75 10 up \$1.60 H-6700

BARRIER STRIPS

Each terminal has two screws and two pre-tinned solder lugs. Mounting screw holes each end of the tough plastic




4-way	\$3.65
H-6704	10 up \$2.40
8-way	\$4.75
H-6708	10 up \$3.95
12-way	\$7.35
H-6712	10 up \$5.65

TAG STRIPS

Pre-tinned solder lugs firmly attached to phenolic board.
The centre lug extends to a foot, to make a convenient earth bracket



3-lug H-6403 10 up 35¢ 45¢ 5-lug H-6405 10 up 40¢ 6-lug H-6626 85¢ 10 up 78¢ 7-lug H-6407 60¢ 10 up 55¢



Designed for PCB mounting provide ideal method of connecting external lead



\$1.75 10 up \$1.60 3-way H-6745 \$2.45 10 up \$2.20 6-way H-6748 \$2.90 10 up \$2.65

MAINS VOLTAGE RATED \$2.30 10 up \$2.10

SPEAKER CONNECTORS

STEREO SPEAKER CONNECTOR

Positive locking connection. 4 terminals.

10 up 78¢




PUSH-BUTTON CAPTIVE CONNECTORS

Positive wire gripper with push-button release. Available in mono and stereo. Colour coded red and black.

2-way (Mono) 4-way (Stereo) P-1764 P-1765

\$4 95


10 up 85¢ ea. 10 up \$1.75 ea.




SCREW TERMINALS

Popular strips with screw terminals on one side of the phenolic strip with a mounting hole at each end.

90¢ 10 up 85¢ \$1.35 10 up \$1.20 2-way H-6622 4-way H-6624 6-way \$1.95 10 up \$1.75





SOLDER LUGS

ASSORTED SOLDER LUG PACK

Single & double ended types, 3.4mm hole. Pack of 50. P-5044



10 packs or more @3.35

COMPUTER **CONNECTORS**

PRINTER PLUG 57-30360 type, suits most printers. With cover. P-2680

\$4 250



PRINTER SOCKET 57-403360 Centronics type socket, P-2681

\$4250

PCB mount 10 up \$10.50

RGB MONITOR PLUG 8 PIN

\$4035





36 WAY IDC FLAT RIBBON **CENTRONICS TYPE** PLUG

\$4 250



10 up \$12.25

PIN IDC FLAT 25

RIBBON Plug P-2693 Socket P-2694

10 up \$9.40



PCB CARD EDGE IDC CONNECTORS 34-way P-2760

\$4050 40-way P-2762

10 up \$8.50

\$4 4 50


10 up \$9.50

50-way P-2764 \$4 425

10 up \$12.75

IDC FLAT RIBBON SOCKETS





34-way P-2750

\$550

10 up \$4.95 40-way P-2752

\$650 50-way P-2754 \$725

10 up \$5.85

10 up \$6.50

'D' TYPE CONNECTORS PLUGS (Solder Tail)



25 pin P-2690

\$370 10 up \$3.35 15 pin P-2687

\$325 10 up \$2.95 9 pin P-2684

\$975 10 up \$2.50

SOCKETS (Solder Tail)

25 pin P-2691

10 up \$4.50 15 pin P-2688

\$395 10 up \$3.55 9 pin P-2685


\$250 10 up \$3.15

BACKSHELLS Suit P-2690 & P-2691 P-2692

\$720 25 pin 10 up \$1.95 Suit P-2687 & P-2688

15 pin 10 up \$1.95 Suit P-2684 2685

9 pin \$720 1.6R REAR 3.2 DIA. 12



A B C 25-PIN 47 41.5 53.3 9-PIN 24.8 19.5 31 PIN R/ANGLE 25 PCB MOUNT

\$825

10 up \$7.40



GENDER BENDERS

Female Twin DB25 female connectors wired back to back, Cat X-3566

Male As above, but male DB25's. Cat X-3565 **Both**

\$**4 2**95

BREAKOUT BOXES

Twin male DB25 connectors with wire links supplied for temporary connection.

\$27⁵⁰

As above, but connections to be made internally and

\$095

ADAPTORS

3.5mm STEREO **SOCKET TO 6.5mm** STEREO PLUG

\$4 95



6.5mm STEREO **SOCKET TO** 3.5mm PLUG

\$495 10 up \$1.75

6.5mm SOCKET TO 3.5mm PLUG Cat P-6510

\$4 95

3.5mm SOCKET TO 6.5mm PLUG



2 x 3.5mm **STEREO PLUGS TO** 1 x 3.5mm STEREO PLUG

\$450



§6.5mm PLUG \$**4** 95



3.5mm SOCKET TO **RCA PLUG** \$4 95 Cat P-6540





10 up \$1.75



3.5mm PLUG \$4 95



6.5mm STEREO SOCKET TO 6.5mm PLUG Cat P-6570

\$4 95 10 up \$1.75

6.5mm STEREO SOCKET TO 6.5mm STEREO PLUG

\$4 95 10 up \$1.75 ea

1.3mm DC PLUG TO 2.1mm DC Cat P-6501

\$4 95 10 up \$1.75

3.5mm SOCKET TO

1 x RCA PLUG TO

2 x RCA SOCKET

3.5mm PLUG

\$4 95

10 up \$1.75

\$395

10 up \$3.55

BNC TO UHF PL-259 PLUG \$395

10 up \$3.55



25 10 up \$2.00





3.5mm PLUG TO 3.5mm SOCKET R/ANGLE

Cat P-6620 \$495 10 up \$4.45

3.5mm SOCKET TO 6.5mm PLUG STR R/ANGLE

Cat P-6625 \$495 10 up \$4.45


BNC TO UHF SO-239 SOCKET

10 up \$3.55



4 POLE METAL PANEL Mt. Plug

\$350



LINE SOCKET Suit P-1834

\$350 10 up \$3.15



TELECOM TYPE 605 PLUG 02 \$_150

PHONE

10 up \$4.05

TELECOM TYPE 610 SOCKET

\$ 1 50

10 up \$4.05

PHONE DOUBLE ADAPTOR

\$095

10 up \$9.00

MODULAR PHONE



MODULAR PHONE

SOCKET

10 up \$4.50

NEUTRIK MODULAR ADAPTOR SYSTEM

What a brilliant idea! Make up the adaptors and connectors you want to suit your application with the professional quality assurance of world-famous Neutrik.

Intended mainly for studio, broadcasting, live music and other "must work" situations, the Neutrik Modular System is also ideal for PA, bands, clubs, churches, etc. — or even the audio enthusiast who simply wants "the best".

Plugs/sockets are available in XLR, 6.5mm, BNC and RCA varieties, along with a switch to enable lines to be isolated right at the plug.

All modules have an internal (female) thread and are linked together with short or long housings. These can take internal transformers, small pcb's etc. Screw fittings are held together with "Locktite" or similar.

RCA PLUG P-1599 \$050

RCA JACK

BNC JACK

HOUSING

\$525

SYSTEM

MODULE

P-1604

\$259

CONNECTOR

CABLE OUTLET

P-1600

\$**8**10



10 up \$7.30

10 up \$12.95

10 up \$4.75

10 up \$2.35



XLR FEMALE PLUG

P-1592

\$735

P-1606

\$785

- LONG

SWITCH

\$995



SYSTEM HOUSING

DOUBLE POLE





10 up \$7.90

10 up \$7.07

10 up \$8.95

10 up \$6.97 6.5mm STEREO **PLUG** P-1597

6.5mm PLUG

10 up \$8.85

SYSTEM HOUSING 6.5mm STEREO - SHORT JACK P-1598 70 10 up \$6.60 10 up \$9.60






MICRO SWITCHES

Micro switches are used wherever a limited switching movement is required - they require only 2 or 3mm of blade movement to actuate. Very positive switching action when triggered - ideal for use in burglar alarms machinery guards and limit switches, tamper switches, etc. Cat S-1920

Features: SPDT Contacts Body Size: 10.5mm x 28mm Quick connect terminals 7.5°}



MINI MICRO SWITCHES

Tiny version of micro at left: just 20 x 10 x 6mm. SPDT contacts with mini quick connect terminals (just as easily soldered to!). Hole mounting 10mm apart. Actuator arm has curved end for cam or chain follower. Ideal for high quality equipment. Cat S-1922



TOGGLE SWITCHES

ULTRA MINIATURE DPDT

The contact rating to size ratio is very high with this miniature toggle switch. Ideal for models, miniature portable instruments, or any use where a high quality miniature switch is required. Cat S-1245

DPDT

125V AC 3A (240V AC 1.5A) Chrome toggle with colour

Body size: 8mm × 9.3mm Clearance: 13.5mm Complete with 2 nuts and



Gold plated connecting tips. \$795

10 or more \$2.65 each

ULTRAMINIATURE RIGHT ANGLE MOUNT

For soldering direct to horizontal pcb with switch emerging through vertical front panel. Very small size suits mini projects, ratings enough for mains switch. Cat S-1247

250V AC 1.5A Body size 8 × 5 × 20mm (including pins & toggle) Pins on 2.5mm centres (can be splayed) Front panel hole size 5mm diam



MINIATURE TYPES

Most popular range — specially imported — excellent

Due to the quality of these switches they can be used in many applications.

All feature: 125V AC 5A (240V AC 2A) Chrome toggle with colour Complete with two nuts and Mounting hole size - 6mm.



Body 8mm x 13mm, clearance 17mm. Cat S-1173 125V AC 5A (240V AC 2A)

10 or more \$1.55 each



Body 13mm x 13mm, clearance 17.5mm. Cat S-1174 125V AC 5A (240V AC 2A)

10 or more \$1.75 each

DPDT CENTRE OFF

Body 12mm x 12mm, clearance 20.5mm. Cat S-1286 125V AC 5A (240V AC 2A)

10 or more \$2.25 each


DPDT CENTRE OFF MOMENTARY ONE SIDE

As above S-1286 switch, but with a spring-return momentary position on one side. Cat S-1287

125V AC 5A M12 10 or more \$3.25 each



Body 13mm x 21.5mm, clearance 20.5mm. Cat S-1175



HEAVY DUTY DPDT

Amazing contact capacity!

Although this switch is miniature in size, it offers an enormous contact to size ratio. Ideal for use where high power levels are involved and small size is of prime importance. Cat S-1168

Chrome toggle with plastic cap. Body size: 12mm × 12.5mm Clearance: 20.5mm Mounting hole: 6mm

Features:

125V AC 10A

\$495

10 or more \$4.45 each

RIGHT ANGLE PCB MOUNTING

With extended right angle lugs for soldering direct to pcb. No mounting nuts required (there's no thread anyway!) Same style actuator as mini toggle switches above.

Chrome toggle and body Mounting hole 6mm

10 or more \$2.95 each

PCB Mounting Centre Off

Right angle legs for pcb mounting, double pole changeover type with centre off position. Size: Body 9 x 7 x 20 (inc toggle), legs 13mm extension. 120V AC 1A.

10 up \$2.95

PCB Mounting Changeover

As above, but without the centre off position. Also rated higher: 1A 250V AC, 3A 120V AC. Cat S-1249

10 or more \$2.65 each

Momentary Action Centre Off

Low voltage, high current switch for vehicle applications: ideal for electric car antennas, etc. Has two sprung positions giving DPDT action with centre off. Large actuating paddle. Cat S-1085

12V DC, 20A Body size 25 x 32 x 30 (not paddle), standard including **Mounting hole 12mm** 30mm paddle. 10 or more \$4.00 each

1

STANDARD SPST

A well designed switch in a bakelite case, It has a chrome toggle and is complete with two nuts and chrome ON/ OFF indicator plate. Ideal for electric projects and automotive use. Cat S-1215

Features: 125V AC 3A Body Size: 14mm x 26mm Clearance: 20.5mm **Mounting Hole: 12mm**

10 or more \$1.75 each

STANDARD DPDT

Same general features as the above switch. Cat S-1216

Features 125V AC 3A (240V AC 1.5V) Body Size: 18mm x 29.5mm Clearance: 23mm Mounting hole: 12mm



10 or more \$1.95 each

STANDARD DPDT CENTRE OFF

Rugged bakelite case, chrome toggle, red and black ON/ OFF/ON indicator plate and heavy duty solder lug terminals. This switch features heavy duty contact rating. Makes ideal motor reversing switch, eg electric aerial on cars. Cat S-1217

Features 125V AC 10A Body Size: 20mm x 35mm Clearance: 26mm Mounting Hole: 12mm

50

\$2.25 each



Waterproof Toggle

Fully sealed SPST toggle for low voltage applications. Toggle has rubber boot to ensure complete waterproofing. Ideal for marine use & other hostile environments. Cat S-1195

12V DC, 10A rating. Body size: 30 x 18 x 35mm Mounting Hole: 12mm

10 or more \$7.95 each


PIANO KEY DPDT

Ideal for audio and electronic projects. Superbly engineered and has a white toggle. Cat S-1393 Features:

Mounting Hole: 18mm Clearance: approximately 15mm Body Size: 20mm x 30mm

10 or more \$4.55 each






ILLUMINATED SPST (12V)

Intended for automotive use. The soft glow from the toggle is not distractive, but means the switch can quickly be located. 12V lamp operates from supply being switched, Cat S-1214

Features

12V DC, 16A contacts 9MM mounting hole Body Size: 28 x 15mm

\$ 25 10 or more \$3.95 each





WITC

PUSH BUTTON SWITCHES


ILLUMINATED SD MOMENTADY

This switch features a beautiful red 11mm square actuating button in an all black plastic case. Makes an excellent mains switch for projects. Cat S-1078 Features

125V AC 1A Body size: 18mm x 18mm Clearance: 34mm Hole cut out size: 18.5mm x

18.5mm






MINIATURE SP — NORMALLY OPEN

These are all plastic body with red illuminated push button bezel. Cat S-1102

Features: 125V AC 1A Body Size: 28.5mm x 10mm Clearance: 15mm Hole Size: 7mm



10 or more 75¢ each

SP ALTERNATE ACTION

The professional Miniature! Ideal for equipment where space is very limited. It features a positive push on/push off action. The actuating black plastic button is 10mm in diameter, Cat S-1197

Features Body Size: 11.5mm x 11.5mm Clearance: 22mm Hole Size: 6mm



10 or more \$3.95 each

DPDT MOMENTARY ACTION

This is an extremely high quality push button switch featuring precise micro switch type action. The plastic actuator button is small to conserve space whereby you can stack these switches side by side etc. Ideal for computer program switch. Cat S-1220 Features:

125V AC 3A Body Size: 13mm x 13mm Clearance: 14.5mm Hole Size: 6.5mm



10 or more \$3.95 each

SP ALTERNATE ACTION

This switch features a beautiful red 11mm square actuating button in an all black plastic case. Makes an excellent mains switch for projects. Cat S-1198

Features: 125V AC 3A **Body Size: 15mm square** Clearance: 28mm Hole Size: 12mm



SP MOMENTARY ACTION

As above switch, Cat S-1198, but with momentary action push/on. Cat S-1199


Features: 125V AC 3A **Body Size: 15mm square** Clearance: 28mm Hole Size: 12mm

10 or more \$1.75 each

PUSH BUTTON RED/BLUE

Red or blue mini push buttons - ideal for colour coding control panels, etc. Each handles up to 0.5A at 240V AC (1A 125V) and are momentary action (on when pushed). Switch size 14mm square; take 11mm x 12.5mm mounting hole.

RED: Cat S-1076



DOOR BELL PUSH BUTTON

The kind the Avon Ladies love! Standard white/black push button to suit most types of low voltage door bells. Two screws mount to any flat surface, Cat S-1077


10 or more \$2.65 each

ILLUMINATED PUSH BUTTON

Lamp 12 V @ 55mA

As used in car burglar alarms, control panels, etc. Alternate action switch with inbuilt 12V globe. Square finish body, round mounting hole. Cat S-1520

125V AC 3A Body Size: 14mm square Mounting Hole: 12mm Clearance: 40mm



PACK OF FOUR PUSH BUTTONS

Ideal for mounting on PCB's. These are momentary PUSH ON switches that have a positive click action. Ideal for alarm circuits, intercoms, custom keyboarde etc. Cat S-1200

10 or more \$2.95 each



SINGLE PCB PUSH BUTTON

Similar to S-1200 switches above, but one only Single pole, single throw switch with momentary contacts. Ideal for use with our H-1247 mini case.

Feautres: Size: 12mm dia × 15mm (inc pins) Pins on 5mm square Panel hole clearance 8mm square

10 or more 75¢ each

Ultramini Push Button

PCB Mounting (vertical) push button switch with changeover contacts. Intended for reset button, etc. Size 9mm x 5mm x 22m (inc legs & p/button). 120V AC 1A.

95 10 or more \$2.65 each

PCB MOUNTING PUSH BUTTON

Right angle leads for mounting on horizontal pcb's. Push button alternate switching (push on, push off). Cat S-1253

Feautres: Body size $12 \times 7 \times 17$ mm Lead spacing 4mm Front panel hole size 6.5mm

10 or more \$2.65 each

SPST LAMPSWITCH

Has many, many uses but is ideally suited to replacement of desk light switches. 240V AC 2A. Cat S-1205

10 or more \$1.75 each

DPDT LAMPSWITCH

Double Pole version of S-1205. Rated at 2A per pole, only slightly larger than single pole version. Suits same hole (11mm), body size just $23 \times 15 \times 13$ mm. 240V AC 2A/pole. Cat S-1210

50

10 or more \$2.25 each

Dashboard Switch

Pull on, push off single pole switch as found in many older vehicles (lights, wipers, etc.). Also ideal for truck use as it is rated at 24V (10A). Positive screw-in connections. Cat S-1190

Body Size: 20mm dia, 30mm long **Mounting Hole: 12mm** 1 10 or more \$3.95 each

Ultra Ultra Mini Vertical P/Button

SPST momentary action push button designed for vertical PCB mounting, also suitable for through-panel


120V AC. 0.5A Body Size: 5mm diam, 13mm long Mounting Hole: 5mm

10 or more \$1.75 each



ROTARY SWIT


DSE rotary switches are precision made to our exacting specifications. They feature easy-to-solder lugs (which are ideal for pcb mounting because of their small size), and have up to 12 positions or 6 poles on one switch plate. The switch shaft is the now standard metric (fluted) type which accepts any of our range of 6mm knobs (imperial knobs can be used with a small piece of shim brass or copper). The contacts are make before break (less clicking and popping!) and each switch comes with a matching washer and nut.



SPDT PCB MOUNT "PRESET"

Vertically mounting on pcb for preset applications. Insulated shaft makes it suitable for resonably high voltage applications; very sure break before make.





3-WAY BCD PUSH BUTTON

3 ganged push button switches with BCD coded outputs: ideal for use in computer circuits, with PLL's, etc. Decimal reading of BCD setting. As used in 2m transceiver kit.






4-WAY SWITCH PACK

This switch is ideal for audio switching in kit type amplifiers or similar applications. Each individual switch section is DPDT and is mechanically interlockede so that only one press button can be on at one time. Cat S-1904

Features: Mounting centre: 75mm Clearance: 22mm Push button size:

11mm centres spaced at 17.5mm





Same high quality as the above switch bank, same features and functions. Just one of the above switches.


10 or more \$1.95 each

SUB MINIATURE DPDT

Countless applications — amazing low price!

Sub-miniature type suitable for many types of projects, etc. So low in price it can be used for experimental projects, without regard to cost! Actuator is in black plastic, Cat S-2010

Mounting: 19mm centre Clearance: 12mm Body Size: 8mm x 23mm




Features.

SUB MINIATURE DPDT

Same as the S-2010 but features an attractive spun aluminuim actuator with black insert. Cat S-2020

10 or more 45¢ each



MINIATURE DPDT

This miniature switch has a spun aluminium actuator with black insert. Larger and heavier duty than the sub-

miniature range. Cat S-2040 Features. Mounting: 28mm centres Clearance: 14mm Body Size: 35mm x 13mm 10 or more \$1.25 each

MINIATURE DP3T

A versatile switch ideally suited to audio applications and for instruments, Cat S-2030


Features: Mounting: 19mm centre Clearance: 13mm Body Size: 8mm x 24mm

MINIATURE DP6T

10 or more \$1.00 each

A printed circuit board mounting switch with a massive six positions. Each position has a positive location to avoid problems. Cat S-2050

Features: Mounting: 27mm centres Clearance: 18mm Body Size: 8mm x 33mm



10 or more \$1.10 each

MINIATURE SP4T

As above, but with four positions. Ideal for input selection on printed circuit boards. Cat S-2060

Features: Mounting: 19mm centres Clearance: 12mm Body Size: 8mm x 25mm

10 or more 90¢ each

4PDT TOGGLE LEVER ACTION


This switch gives the smooth action of a slide switch but is actuated by an attractive spun aluminium toggle with coloured insert. Great for amplifier changeover switches because of their small size and attractive finish. Cat S-1301



8 WAY PCB DIL SWITCH

8 SPST rocker switches mounted in a DIL package Designed for PCB mounting and may be placed in blocks or rows without wasting space. Use for pre-programming, changing circuit constants and many more uses. Cat S-1608


10 or more \$2.25 each



SPDT SLIDE

Designed for vertical mounting direct on pcb. Ideal for circuits which require occasional changing of operating parameters. 5mm between pins. Body 13 x 6.75mm. 6A

10 or more \$2.65 each



DPDT SLIDE


As above, but capable of switching two individual circuits at the same time. Also has 5mm between pins — in both directions. Has mountings at 18mm, body 13 x 11.5mm.


10 or more \$2.00 each



DPDT "KNIFE" SWITCH

The old "aerial & earth" switches of Yore. Used today for changeover switches on TV antennas, etc, or any general purpose (low voltage!!) switching job. Cat S-1930





ROCKER SWITCHES

ILLUMINATED DPDT

Positive action, handsome black body, bright red illuminating rocker switches, 10amp, 240V. The terminating lugs on this switch will accept standard Utilux spade clips. Mounting is push in snap lock.

Features 240V AC 10A Body Size: 23mm x 30.5mm Clearance: 30mm Hole cut out size: 22mm x 27mm 240V NEON

Cat S-1506

10 or more \$3.55 each

12V VERSION As above, but 12V globe. Cat S-1507

10 or more \$3.55 each

ILLUMINATED SPDT

Attractive rectangular shape black switch with red illuminating rocker (240V neon). Terminal lugs accept Utilux spade quick connectors. Mounting is "snap lock". 240V neon. Cat S-1503 Features:

240V AC 10A Body Size: 14mm x 40mm Clearance: 29.5mm Hole cut out size: 12.5mm x

10 or more \$3.95 each

SPST MINI ROCKER

Intended mainly for vehicle applications — has quick connect lugs for easy connection. Takes rectangular cutout, 29 x 13mm. Push-to-fit. Cat S-1390


12V DC. 2A 10 or more \$1.55 each

1 21

SPST ILLUMINATED WITH BRACKET

Also for car use. Ideal for controlling driving lamp relays, etc: lamp inside switch lights when switch is on. (12V lamp). Complete with mounting bracket (can be removed for panel mounting in a 12 x 27mm cut-out). Cat S-1500

50 10 or more \$2.25 each



Dress Nuts

Pack of 5.5mm dress nuts for standard miniature toggle switches. Makes the panel look really snazzy! Cat H-1912

Weight: 10a

\$4 15



Weatherproof Hoods

Again desgined for standard miniature toggle switches, these screw onto the switch to prevent moisuture ingress. Ideal for switches in marine applications. (Note: only protect toggle, not rear of switch). Pack of 8. Cat H-1914

Weight: 15

ALARM SWIT

LARGE BARE REED SWITCH

Bare switch measures 40 x 5mm diameter, solid connection for ease of soldering, Cat L-5215



Great where space is a problem. Wire connections, great for camouflaging in wood-work, etc. 25mm long Cat S-1946

10 or more \$1.10 each

ACTIVATING COIL

Matches perfectly with the mini reed switch above. 430 ohm coil operates from 6 to 15V DC, gives you perfect isolation between two circuits (just like a relay!) Cat S-1948

¢ 10 or more 85¢ each



BARE MAGNETS


Tiny (26 x 8 x 8mm) magnets which operates either reed switch from approx. 10mm away. Huge range of applications. Cat L-5214



10 or more \$1.95 each

MERCURY "TILT" SWITCH SWITCH MOUNT SPDT

This is essentially a movement detecting switch. It is operated by changing the horizontal plane. A "ball" of mercury runs from one end of the elongated tube to the other as the position is changed. One end has a set of contacts that "make" with the mercury. It is basically a low current device but is suitable for such uses as movement detectors for car or bike alarms. Cat S-1935





Power Point

Safety Tester

3 Pin Plug \$4 95



The standard Australian 3-pin AC plug it has locked collar to hold cable tight and push fit cover to main body. Cat P-5400

3 Pin Piggy Back Plug


Standard 3-pin plug with 3 pin socket as well — doubles up one power point.

3 Pin Plug **Side Entry**



Standard 3 pin AC plug with cable entry on the side — ideal for using with awkward equipment, Cat P-5402

Suppressor Plug



Line Socket \$ 15



Ideal for making up extension cords — standard 3 pin AC socket. Cat P-5410

Surface Socket \$395



Standard 3 pin AC socket that can be screwed to boards or walls — ideal for workshop use. Cat P-5415

Double 🛅 Power Point \$1295



Replace old single outlets with a double: much more convenient. Cat P-5560

Rotary Fan Blower

Getting a bit hot under the collar? Use one of these superb rotary fans: FANtastic for any device that needs forced air cooling. And they can be mounted to suck or blow.

Clean Power

has to be the cheapest insural

systems, audio gear, etc

The unit comes with tw illuminated master swit

Spike Handling —

It's three devices in one! Protects you

spikes and surges, removes tenes

Standard size: 1202mm square x 40mm deep. Cat Y-8500 \$1
Mini size: 80 x 80 x 25mm. Shipping weight: 280g
Cat Y-8505 Shipping size: 87 x 85 x 35mm

3 Pin IEC Line Socket \$395

As used in huge range of computer, amateur, entertainment equipment. Female line socket, standard IEC. Cat P-5580

3 Pin IEC Chassis Plug

Male Chassis socket, as used with above plug. 3 pin vertical IEC pattern. Cat P-5585

Architrave 2 Switch \$495 Cat P-5570

Standard architrave switch - can be used to replace old, worn our units in your home. Positive action switching

Line Switch (\$695

High impact plastic moulded switch for insertion in any cord for remote on/off. Ideal for putting on/off switch in a floor standing lamp. 10 rating. Cat P-5515

Wall Board Clip \$4 50



for a mounting block. Cat P-5530 Light Socket

Light socket for payonet mount lamps.
Ideal replacement for light fittings. Comes in white plastic. Cat P-5510

Spotlight

Stop Spikes! Protect Your Electronics With





Noise Rejection

See-through 3 Pin Plug

Same as 3 pin plug at left, but see through so you can see faulty or broken

See-through Line Socket \$430

As above, but extension cord end. See through: for safety's sake. Cat P-5411

4-Way Power Board



Now one power point becomes four power points! Cat P-5613

Fluoro Starters \$4 50

Fluoro lights go blink, blink? Could be the starter: plug in one of these! Pack of two starters. Keep some handy just in

Blank **Plate** \$250

Same size as power point, but blank: ideal for gap-filling when you move points, switches, etc. Cat P-5535

Standard Mounting \$275



Mount power points, plates, etc on any surface including brick. Cat P-5531

Extension Cords



Cordlock

Stops plugs and sockets pulling apart dangerous and inconvenient. Added safety for your extension cords.



PER CE

16.

0

ڑ ن

Q,


97

Check newly installed power points, old homes, etc. Just plug in and light pattern reveals any faults. Cat P-5300 Double Adaptor

Standard 3 pin AC plug into 2 AC sockets enabling you to use 2 appliances on one outlet. Cat P-5440

\$795

Child-Proof Protector \$350 and AC sockets are normally placed in a



International not adapt voltage!!! Traveller Adaptors

Having trouble with power points overseas? Here's the answer! A neat little adaptor that converts our 3-pin plug to virtually anything used in the world. One piece (so you won't lose bits). Use active/neutral pins only: does not connect earth. Cat P-5652 \$2495

Aussie Adaptor

Just the thing for overseas visitors! Adapts Australian mains socket to accommodate European, American, Japanese and many other plug configurations. \$250

Now fits UK 3 pin system

Australian to **Overseas** Adaptors

Low-cost adaptors for specific areas. Even if you're going every where, you'll still save by buying the lot! These adaptors DO connect the earth pin

for safety.

All one price: \$795

Aussie to UK

Also Ireland, Singapore Hong Kung, Parts of Middle East, Africa and Asia.





Aussie to Europe Also Noumea, Tahiti, parts

of Middle East, Asia & Sth America, Cat P-5658

Aussie to U.S.A.

Also Canada, U.S. posessions. Cat P-5659



See Fuses overleaf (page 56)

Mains

Circuit

Breakers:


24 Hour Program Timer

Fantastic for security lighting, lamps, radios, electric blankets, pool filters... anything! It's so simple — just plug it into the mains socket, set the time and forget it.

Quality Australian made Click Timer allows you to set up to 24 on/off cycles (pins supplied for 3) in any day. Features auto/manual override switch and a modular design that doesn't intrude on adjacent power points. Cat P-5701

The Button: Cheap Insurance!

protects everything on that circuit (ie on other power points) from damage caused by power line spikes. Computers, videos, hi-fi. TV's industrial and domestic machines... all can be protected by The Button, Cat P-5310



Better than 10ns response time

 150 Joule rating (consumes no power except when a surge/spike is present).

• If you value your equipment, you'll value
The Button even more especially at our great value price! \$





Frequency: 1kHz to 100MHz
Attenuation: 20 to 40dB (variable ratio)

USES//RELAYS

Wide range of fuses in both popular styles: M-205 mini (approx. 20 × 5mm) and the popular 3AG (approx. 32 × 6mm). Remember, the lower the current rating of the fuse you use, the greater the protection afforded. All fuses 'fast blow' type for greatest protection.

3AC	TYPE	M-20	5 TYPE
100mA	Cat S-4449	250mA	Cat S-4412
150mA	Cat S-4451	500mA	Cat S-4415
250mA	Cat S-4453	1A	Cat S-4421
350mA	Cat S-4455	2A	Cat S-4423
500mA	Cat S-4457	5A	Cat S-4425
1A	Cat S-4461		
1.5A	Cat S-4465		
2A	Cat S-4467		
3A	Cat S-4469	750	
5A	Cat S-4471		
7.5A	Cat S-4473	10 up 20¢	
10A	Cat S-4475		1/8/
15A	Cat S-4477		
20A	Cat S-4479	//	/
25A	Cat S-4481		1/
30A	Cat S-4485		Trad
35A	Cat S-4487		///
			W

Thermal Fuses

Handle 10A at 250V. Two type to choose from: 96°C operating Cat S-4490 139°C operating Cat S-4491

\$4 45

10 or more \$1.30

Slo Blo Fuses

M-205 TYPE 3AG TYPE

250mA	Cat S-4300	250mA	Cat S-4350
310mA	Cat S-4305	500mA	Cat S-4355
500mA	Cat S-4310	1 AMP	Cat S-4360
1 AMP	Cat S-4315	2 AMP	Cat S-4365
2 AMP	Cat S-4320	5 AMP	Cat S-4370
			_



Auto Blade Fuses

Cat S-4505 5 AMP 20 AMP Cat S-4520 Cat S-4507 10 AMP Cat S-4510 30 AMP Cat S-4530 15 AMP Cat S-4515



Handy Fuse Wire Pack

Great for keeping a card of this in the fuse box — just in case! Card of 8,16, 20and 30A fuse wire. For light circuits, right up to the electric

80¢ 10 up 75c

Fuse Holders

Chassis or PCB

Easy to mount fuseholders in both popular sizes to suit 3AG or M205 fuses. Suit 3AG: Cat S-4257. Suit M-205: Cat S-4258

10 or more 55¢



Bayonet holders

Chassis or panel mounting fuse holder, accepts standard 3AG fuse. 13mm mounting hole required. Suitable for low voltage. Cat S-4206

\$4 25 10 up \$1.15



In-line Holders (3AG)

Protection for car radios, stereo, transceivers, etc. All plastic casing, takes standard 3AG fuse with spring loaded contacts for positive connection. Complete with 600mm lead at no extra charge. Suitable for low voltage Cat S-4277



3AG Fuse Clips (Pack of 8)

These fuse clips are ideal for mounting on PC boards providing flexibility and extremely good value. Cat H-1700

Throw The Fuse Wire Away! Replace them with...

Circuit Breakers

Sure beats scratching round in the dark for fuse wire that usually doesn't exist. Fits Federal type fuse holders. Just slip them in place of your old fuse. If circuit is tripped, getting the power back on is as easy as pushing a button!

Amp Rating Cat P-5908 10 Amp Rating Cat P-5910 15 Amp Rating Cat P-5915 16 Amp Rating Cat P-5920 20 Amp Rating Cat P-5925 30 Amp Rating Cat P-5929



Relays **Cradle Relays**

Our standard cradle relay range is perfect for hobbyist projects, industrial replacement, etc. They suit the sockets below if PCB mounting is required. Insulation effective to 500V at 50Hz, with contacts rated at 30W (1A or 100V). Operation time typically 6-10ms, relative time typically 3-4ms

Shipping weight: 7g Shipping size: 35 x 30 x 19mm

\$12.95 10 up \$11.95 10 up \$13.95

Cradle Relay Socket

Silver plated socket to suit Cradle relays, 4 C.O. type Cat P4734

Shipping weight: 2g Shipping size: 29 x 20 x 13mm

Voltage



12 volt 12 volt 4PDT Contact type Coil voltage 87 12V Nom. 12V Max. 17V Coil Resistance 325 ohms 185 ohms

Contact assembly 2 C/O 4 C/O 10.5 db. 🗜

PCB Mounting Relays

PCB Mounting Coax Relay

Mini pcb mounting relay with fully enclosed contacts. Coil rated at 12 volts, 80mA. Handles up to 1000MHz — so is ideal for all HF, VHF and UHF switching applications. Size overall 35mm square x 15mm high. Make up your antenna switching unit and save \$\$\$ on coax cable runs! Cat S-7402

Shipping weight: 18g Shipping size: 36 x 33 x 11mm



Cat S-7120

Ultra Miniature

Low cost mini relay for projects without a lot of spare room! Fits a standard 2.54mm matrix (eg Vero or DIL) boards and the 5V version interfaces (via suitable buffer) to TTL. Contact rating is 100V at 0.5A (res). SPST. Shipping weight: 4g

Contact current (max): Contact voltage (max): Nominal coil voltage: Coil resistance

S-7105 S-7112 100V AC 100V AC 56 ohm 320 ohm

Shipping size: 15 x 14 x 11mm Shipping weight: 6g Shipping size: 14 x 12 x 7mm

10 up \$5.35

Miniature


Small in size but very handy contact rating! The silver plated SPDT contacts will handle up to a massive 2 amps (at 24V DC or 100V AC). Nominally 8 to 12V operating, but will work ok up to 15 volts. Cat S-7120

Contact current (max): 2A Contact voltage (nom): 100V Nominal coil voltage: 8-12V Coil resistance: 225 ohm

Standard

Our most popular relay. Ideal for direct mounting on PCB's. Housed in plastic dustproof case: as used in a large number of EA and ETI projects.

SPDT DPDT Contact current (max): 5A 5A Contact voltage (max): 240V 240V Nominal coil voltage: 12V 12V Coil resistance: 180 ohm 200 ohm



10 up \$2.65 7.5

Shipping weight: 17g Shipping size: 30 x 30 x 12mm 10 up \$8.25

High Rating Power Relay

A small, but high capacity relay ideal for power switching with a massive contact rating of 10A. Great for switching 240V projects from transistor or IC control. Cat S-7200

Contact current (max): 10A Contact voltage (nom): 240V Nominal coil voltage: 12V Coil resistance: 160 ohm





Shipping weight: 8g Shipping size: 40 x 27 x 20mm

Cat S-7200 10 up \$9.50

12V Automotive Relays

Horn Relay

Heavy duty relay intended for use in 12 volt vehicle systems. Very high contact rating is ideal for horns, ignition, disables burglar alarms, etc. Negative switching only. SPST contact. Cat S-7302

Contact current (max): 20A Contact voltage (nom): 12V Nominal coil voltage: 12V

Shipping weight: 8g Shipping size: 35 x 27 x 20mm

Cat S-7302



contacts each rated at a massive ideal for such applications QI driver or wire both contacts. huge 60 amps single Contact current (max Contact voltage (nom): 12 Nominal coil voltage: 12 Shipping weight: 288g Shipping size: 10.5 x 10.5 x 54 Cat S-7304 \$24.95 10 up \$22.45



Pot Core Assemblies

Philips P36 assembly consisting of 2 cup cores. Replaces FX2242 36mm core diameter, Cat L-1436 \$7.95 10 up \$7.20 ea

Shipping Weight: 29g 1 Shipping size: 35 × 35 × 10mm

Former to suit cores. Cat L-1437 70¢ ea Shipping Weight: 8g Shipping size: 27 × 27 × 14mm 10 up 60¢ ea

455kHz Ceramic

Murata (CFW455E) the modern replacement of the IF transformer. Two resonators are coupled by an external capacitance to give maximum selectivity with a flat response. Typical selectivity 20dB min at ±10kHz with 3dB bandwidth of ±4.5kHz. Cat L-1610

Shipping Weight: 0.4g Shipping size: 0.5 × 4 × 4mm 10 up \$6.25

Telescopic Antenna

Deluxe antenna, ideal replacement for radios or use in projects. Multi section, tight fitting, chrome plated. Cat L-4902

Shipping Weight: 50g Shipping size: 160 × 0.5mm 10 up \$5.25

Aerial Rod with Coil

Complete Ferrite rod with pre-wound standard b/c coil. Suits 140-160pF miniature tuning gangs. Ideal for replacements in transistor radios. Cat L-0520 \$1.75

10 up \$1.60 ea



Coil Formers and Accessories

5mm former, subminiature (4mm core)). Code 822/1. Cat L-1010 Shipping weight: 5g
Shipping size: 18 × 5 × 5mm

70¢ ea
10 up 60¢ ea

6 pin base. Cat L-1015
Shipping weight 62
70¢ ea
10 up 60¢ ea Shipping weight: 6g
Shipping size: 13 × 13 × 7mm

Can to suit above 12.7 × 12.7 × 19mm. Code 7100. 50¢ ea Cat L-1020 50¢ ea Shipping weight: 9g Shipping size: 18 × 13 × 13mm

Slug Tuned IF/OSC Coil Pack

Ideal for experimenters and service technicians. Set comprises 1st, 2nd & 3rd 455kHz standard miniature IF transformers and standard b/c oscillator coil. Cat L-0260



Shipping weight: 10g \$2.50 Shipping size: $70 \times 60 \times 10$ mm 10 up \$2.25

Aerial Rods

F14 ferrite material for winding aerial and other coils onto. Operating range 0.1 to 2MHz. 200mm length, 9.5mm diam. Cat L-1401

Shipping weight: 67g Shipping size: 200 × 10mm

DC Smoothing Choke

Intended for car hi fi, communications equipment, etc. where ignition, alternator or other noise gets in through the power line. Use external to device either on its own (in series with positive supply) or in conjunction with capacitor for an effective L-C filter

Shipping weight: 38g Shipping size: $20 \times 15 \times 11$ mm



Balun Formers Toroids and Beads

Quality Neosid ferrite beads for general purpose use

35 032 28 (equivalent FX1115) single hole F8 grade ferrite. 5mm long 4mm diam with 2mm hole, Cat L-1430

40¢ ea 10 up 35¢ ea

35-001-31 bead with 6 holes, F29 ferrite material, size (nom) 10mm long × 6mm diam, holes 0.7mm diam. Equiv to 4312-020-31550, Cat L-1432

10 up 60¢ ea

35-033-35 bead, single hole. Similar to L-1430 but F29 ferrite, Cat L-1433

50¢ ea 10 up 45¢ ea

RF Chokes

33uH 47uH 68uH	L-1783 L-1787 L-1791	2.5mH 5mH 10mH	L-1824 L-1826 L-1830	
15uH 22uH	L-1775 L-1779		L-1820 L-1822	
8.2uH 10uH	L-1771 L-1773	560uH 820uH	L-1813 L-1817	
6.0uH	L-1769	470uH	L-1807 L-1811	
3.3uH 4.7uH	L-1765 L-1767		L-1803	
2.2uH	L-1763		L-1799	
1uH 1.5uH	L-1759 L-1761	82uH 100uH	L-1793 L-1795	

Suitable for VHF (F14) and VHF/UHF (F29) TV Baluns, wideband & pulse transformers, interference suppression, etc. F29 ferrite has 0.5dB loss 40 - 220MHz increasing to 1dB at 800MHz Packs of two in two sizes:

1050/1/F14 ferrites; 13.5 × 13.2 × 7.4mm Cat L-1340 1050/2/F29 ferrites;

6.5 × 13.2 × 7.4mm Cat L-1352 Pack of 2: \$1.49 each

10 packs or more \$1.35 each





Ferrite Cores

Pack of four F16 ferrite screw cores, 0.5 to 15MHz. 10mm long × 4mm diam, 0.5mm thread. Cat L-1302.

Pack of four F29 ferrite screw cores, 10 to 220MHz. 10mm long x 4mm diam, 0.5mm thread, Cat L-1307





\$1.35 pack 4 10 packs or more \$1.20 ea

RF Balun Kit

(and audio interference suppressor)

Contains a large, quality balun core (50.8mm deia.) with a quantity of heavy gauge wire, suitable for up to 1kW. Full instructions supplied. Can be used for a number of antenna types up to 30MHz. In most they will eliminate RF breakthrough from amateur and CB gear into audio amplifiers. If the speaker leads are wound through the core (as many turns as will fit) the core stops RF energy entering the amplifier in this way, Cat D-5350

Shipping Weight: 936g Shipping Size: $190 \times 110 \times 14$ mm

\$4895 10 up \$17.00



RF Toroid Kit

application notes, inducnomograph, Torg

oscillation t spectral range Shipping Weigl

10 up \$4.50 ea



Vholes Al

An opportunity to become part of Australia's most successful electronics retailer.

Have you ever wanted to run your own business but didn't know where to start? Are you a successful businessman wanting to get out of the rat race and be your own boss? Have you considered buying a franchise but couldn't see the value in the up front charges?

Dick Smith Electronics has the solution. For over ten years our Wholesale Division has supplied a selected authorized distributor network of independent retailers with our exclusive range of products. How could you miss with benefits like

- 1. The reputation and trademarks of Australia's most successful electronics retailer.
- 2. Prices that reflect the buying power of a \$65 million a year company.
- 3. Management systems and policies that pass on to you the inside secrets of DSE's success.
- 4. Advertising subsidized by DSE for local TV, press, radio and catalogue distribution
- 5. An exclusive retail territory.
- 6. Access to Dick Smith Electronics comprehensive range of products.
- 7. A four tiered bulk pricing structure.

To find out more contact:

The Wholesale Manager Dick Smith Electronics P.O. Box 321, North Ryde NSW 2113 Telephone: (02) 888 3200



Photo-Etch PCB Kit ER-4

It's so simple! Our Photo-Etch kit contains all the chemicals necessary to create professional circuit boards. Use the kit to generate your own 1 · 1 artwork or use magazine art, then use the patented Pos-Neg process to make a photo negative, sensitize and expose a blank copper board, then develop and etch it. The magazine page is not destroyed in this process. No darkoom or camera is required. All necessary materials are included: steel 125 × 150mm print frame, Pos-Neg film, film processing pack, yellow filter, 117ml negative-acting etch resist, 483ml resist developer, blank copper circuit boards, dry concentrated etchant 1:1 resist patterns and tapes, and complete instructions. NOTE: You will need to obtain trays and exposure light. Cat N-5700

You've asked for them: here they are!

A great new range of PCB designing and making aids, along with dial and panel markings etc, from Datak: one of the USA's largest suppliers. Everything you need, from donuts and tapes right through to circuit repair materials.

Contains one pattern sheet from 17 Jotdraft sets (including ones we don't stock!). A great starter pack. Cat N-5766

Pack of 40 different pcb targets and crosshair registration marks for precision pattern alignment (especially suitable for multi layer or double sided pcb's). Cat N-5820

These patterns make any DIP pattern. 48 in each pack with 40 leads. .100" × .600" centres. Scale: 1×. Cat N-5768

.080" OD \times .031" ID on precision .200" \times .300" centres. 380

.100" OD \times .031" ID on precision .200" \times .300" centres. 380

.125" OD × .031" ID on precision .200" × .300" centres. 380 donuts in set. Cat N-5774

.150" OD imes 0.31" ID on precision .200" imes .300" centres. 380

Targets and Registrations


Universal Dip Patterns

DONUTS -

donuts in set. Cat N-5770

donuts in set. Cat N-5772

donuts in set. Cat N-5776



Datamark and Jotdraft Dry Transfers

The easy and economical way to give that professional look to all your projects. Letters, numbers, marks or words there's a pack to suit just about every application. Works on metal, wood, paint, plastic and paper.

TITLES

Audio, TV, Hi-Fi Titles

Five 31/4" x 5" sheets covering audio, broadcast, recording and stereo areas and one letter/number sheet. In BOTH

Cat N-5753 Black Cat N-5754 White

Amateur

Cat N-5755 Black

Cat N-5756 White

Radio & TV

Designed for marking all RF and

communications equipment. Five

120 × 190mm sheets and one number/ letter sheet in black or white

Test & Industrial

Equipment

BOTH

A great selection for marking scopes, meters, analyzers,

plotters and most other test equipment. Five sheets plus number/letter sheet. Available in black or white.

BOTH



DIAL AND METER **MARKINGS**

Marks & Switch Patterns

Rotary switch patterns, arrows, lines, graduations and numbers. Three black and white assorted sheets. Cat N-5750

Meter Dial Patterns

Four sheets, 120 × 90mm with dialplate arcs and graduations let you design or modify meter scales from 25mm to 125mm in radius. Available in black.

\$4 450

PATTERNS

TO-18. 3 Pin PC pattern, 144 in set. Cat N-5760

TO-5. 3 Pin PC pattern, 84 in set. Cat N-5762

16 pin dual inline package PC patterns, 32 in set.

16 pin DIP. Narrow pads in set of 32 patterns. Cat N-5765 $.125 \times .053$

Precision slit tapes to make PCB design and construction easy. This black crepe tape is highly flexible with a strong adhesive to prevent peeling or creeping on the curves. All tapes come in 6 ft lengths.

N-5782 N-5784 .062" .080" N-5786 .093" N-5788

.031"

.040"

\$4 495

\$ 425

\$ 425

\$ 125

\$425

N-5780


- Scale 1x





871111111111111

8時[[]]



Cat N-5758 White \$295



Cat N-5757 Black



Contact Printing Frame ER-10

Large format (225 x 300mm) spring-loaded steel printing frame will accept 210 x 275mm artwork originals, protocopy film and sensitized printed circuit boards. Comes complete with glass, backboard, yellow Pos-Neg filter and instruction manual.

Yellow Pos-Neg Filter ER-17

Needed for all Pos-Neg exposure work. Take care — this filter can be damaged by many industrial solvents and ER-8 developer. Keep free of dust and fingerprints.

Cat N-5711

Negative Photo Resist ER-71

A liquid cinnimate resist in bottle with pump sprayer. The coated board is exposed to UV through a negative of the circuit pattern, then developed in Cat N-5905. Unexposed parts of the resist coat are dissolved while the exposed resist pattern stays to protect the copper when etched. One bottle contains 4000 sq mm. 117ml bottle. Cat N-5907

Negative Resist Developer ER-8

A solvent blend that will develop Cat N-5907 and other negative acting photo resist. Resist areas that are not hardened by UV light are dissovived away. Hardened areas are unaffected. Do not use with positive acting resists. 483ml. Cat N-5905

Ball Stylus/ Burnisher

DATAK dry transfers will transfer with an ordinary ball point pen and may be burnished with a thumbnail. Buy you'll do a better job and finish faster with a welldesigned tool. This metal ball applicator will transfer characters from .2mm up to about 6mm. The 2mm round polished tip fits into tight corners on PC's and panels and prevents letter distortion if your use excessive force. The other end has a 9mm flat flexible burnisher. Cat N-5715

\$4095

Positive/Negative Film Refills

This polyester base film is dimensionally stable and is capable of making a negative or a positive from either opaque translucent artwork in one step. No intermediate film is required. It will accept retouching with photo opaque, pencil, india ink or dry transfers.

ER-9 2 sheets 8 12" x 11". \$4 285

ER-5 6 sheets 5" x 6" Cat N-5705 \$4885

High Resolution Positive Resist



Now one off boards and prototypes can be made approaching factory standards — at a fraction of the price. Spray resist is simple to use, exposes to any UV source(even the Sun). Perfect for use with 1:1 tapes and pads. Develops in caustic soda solution or developer below. 75g spray can Cat N-1001 \$850

Buy in bulk and save!

Same RP50 Positive Photo Resist in bulk 200g pack. If you're making a lot of boards, buy the big size — it's cheaper! Cat N-1000

\$4595

Developer to suit

Safer and simpler than mixing up caustic soda solutions: just develop pattern in this, dry and etch. 250ml bottle of 4:1 concentrate — goes a long, long way. Cat N-1002



FAMOUS 'ELECTROLUBE' BRAND

Blank Printed Circuit Boards

Pre-cut high quality PC board with permanently bonded copper on one side - available in bakelite or heavy duty fibreglass.

Bakelite:	Cat No.	Each
150 × 74mm	H-5500	\$2.05
150 × 150mm	H-5505	\$3.65
300 × 300mm	H-5510	\$11.55
Fibreglass:		
150 × 74mm	H-5540	\$2.65
150 × 150mm	H-5545	\$4.95
300 × 300mm	H-5550	\$10.45

Clear Acrylic Sheet

Ideal for using over panels, etc - makes your project look really professional. Or use for inspection panels, protection devices, etc. 3mm thick, size is a very useful 150mm long x 50mm wide.

Aluminium Sheet

Blank aluminium sheet ideal for making up front panels, folding into small boxes, or general hobbyist work. 18 gauge, 305 x 305mm. Cat H-2560

\$460 **Marking Kit**

For those quickie boards (or where no photographic facilities are available) just draw this resist directly onto the pcb surface. Two different coloured pens plus eraser in a handy plastic wallet. Also ideal for repairing photoresist prior to etching Cat N-5175

Shipping weight: 36.3a Wallet size: 150 x 40 x 10mm

Ferric Chloride Etchant

Now supplied in a great new no-spill 500ml bottle of working solution (Ferric Chloride). No more fiddling around with beads and hot water. Cat N-5652

Note: due to corrosive nature, transport restrictions

Etching Kit

Everything you need for instant pcb's. Contains pc resist pen, etchant, resist solvent flux cleaning material and a sample of pcb. (See shipping warning on N-5652 etchant). Cat N-5650

Shipping weight: 951g Carton size: 280 x 120 x 80mm

4

PC Pins

These pins push through 2.54mm pitch matrix board or Veroboard to form solder terminals on both sides of the board.

Pkt 50 pins

PC Pin Connectors


Fits the H-5590 board pins. Has many uses. Cat H-5592

\$725

\$760

Plug-in IC Board

Fantastic plug-in printed circuit board, 2.54mm pin spacing to accept directly up to 14 x 14 pin or 16 pin IC's or up to 20 'Mini-Dip' IC's. Lands are silver plated and a 24 way 2.54mm plug is etched into one end of the board so that it can be used with a 24 way edge connector. An excellent high quality board for the hobbyist and engineer. 2.54mm spacing x 60(w) 100(I)mm. Cat H-5610



Matrix Board

Tough phenolic board with punched holes. Ideal for prototypes, bread boards, science or hobby projects. 2.54mm spacing x 75mm x 76mm. Cat H-5310

Printed Mounting



A handy 47 way mounting strip for resistors, capacitors and other components. Packs them in neatly. Terminals are numbered for easy circuit identification.

\$725

Now, you can modify or repair PCBs with Circuit Fix CF-1



The complete kit contains the springloaded clamp and guide, collet knife and blade. 154 assorted copper donuts, 32 square inches of copper foil and an instruction booklet.

Cat N-5900

Solder won't stick?

Tinnit **Electroless Bright** Tin Plate ER-18

Tinnit is designed to plate bare copper circuit boards to enhance solderability. It has also been used to plate edge card connector fingers on prototypes when a low, stable contact resistance is needed. but gold is not available or desired. One pint of Tinnit will plate up to 1500 sq mm of copper with approximately .001mm of bright tin. Plating takes 10 minutes in a fresh solution. Adhesion and solderability are excellent. No electricity is required. Tinnit has been successfully used to plate brass, bronze, iron and some carbon steels, the material is supplied as a dry mixture with an indefinite shelf life. When mixed with water, the solution has a life of approximately two months. You need add no acid for other materials to this solution. Tinnit contains all plating chemicals plus surfactants and cleaners to insure a perfect plate. 1 pint. Cat N-5730

Printed Stripboards

DSE specifications... plated strips alphanumeric grid

The most verstile board of the lot! Etched copper strips are predrilled and plated ready for solder. The alpha numeric grid facilities positive pin identification.

2.54mm spacing 76mm x 153mm. 2.54mm spacing


Cat H-5612 \$415

76mm x 76mm Cat H-5614 \$725

Versa Strip Board

A quality plated copper strip board similar to the English Veroboard. Continuous predrilled stripping on a high grade insulator. Packed in plastic sheath to assure you an untarnished, easy-to-solder surface. 2.54mm spacing x 95mm x 304mm. Cat H-5112

As H-5612 board, but with pre-cut short traces making it ideal for multi IC work Plated strips. Packed in a plastic sheath for Plated strips. Packed III a plasses protection. 2.54mm spacing x 76mm \$4.95



R.E.&.C.

Hook-up Wire

Flexible Light Cable

PVC insulated wire that is ideal for the hobbyist. Ideal for home brew projects, etc. 12 individual colours available - save confusion, 10 × 0.12

W-2220 Green W-2225 Cream W-2230 W-2226 White W-2227 W-2221 D Blue W-2222 Purple

W-2224 Grey 15¢ per metre 100m or more 8¢ per metre

Orange W-2223 Lt Blue W-2228

Medium Duty

Slightly thicker than the above wires, fully tinned and insulated. 10 × 0.25 Available in: Red Cat W-2240 and Black Cat W-2242 20¢ per metre

100m or more 17¢ per metre

Heavy Duty

23 x 0.2mm. Rated at 240V AC. 7.5 amps. Available in: Red Cat W-2260, Black Cat W-2262 and Green Cat W-2264 25¢ per metre

100m or more 22¢ per metre

Very Heavy Duty

32 x 0.2mm Rated at 240V AC, 10 amps. Available in: Brown Cat W-2280 and Blue Cat W-2282

100m or more 27¢ per metre

Ultra Heavy Duty

41/0.32 Insulated/sheathed. Rated at 240 Volts AC, up to 40A (int). Available in two colours.

Red Cat W-2286 Black Cat W-2288 85¢ per metre

100m or more 77¢ per metre

Rainbow Cable

12 colour coded strands of insulated conductor bonded together in a flat cable. Ideal for wiring looms or intercoms etc. Can be laid under carpets. Can be split and the individual wires used — same ratings as W-2220 series of wire. Each 12 X 0.12, Cat W-2045

\$1.90 per metre 100m or more \$1.71 per metre


Telephone-type Cable

This is the type of wire used by Telecom Australia for internal telephone wiring.

Ideal for intercoms or any other multi-wire circuit. Individually insulated and colour coded. Solid copper conductors, fully tinned for solder connection or good screw connection.

4 Conductor Cat W-2120 75¢ per metre 100m or more 68¢ per metre

12 Conductor Cat W-2140 \$1.55 per metre



Mains Cable

A standard power cable for use where an earth is required. Each wire is separately insulated and colour coded and all three cables are contained in a plastic sleeve to give double insulation. Cat W-2055
Rated at 240V AC and 7.5 amps

per metre 100m or more 90¢

4-Core Flex

Intended mainly for alarm applications where two conductors are used for alarm sensing and two for tamper protection or power supply, etc. Each conductor is 7/020, and individually insulated. Most alarm installations use between 50 and 100m Cat W-2100

5¢ per metre 100m or more 86¢/m

6-Core Flex Mains Rated

Intended mainly for older style rotators which require up to six conductors; also ideal for alarm installations requiring power, tamper and alarm connections. Cat W-2042

per metre 100m or more \$2.65/m

Fig. 8 Cable **Light Duty**

Ideal cable for use with hi fi systems for speaker connections or with intercoms. Twin plastic insulated conductors. 14 × 0.14 Cat W-2010 //// 25¢ per metre. 100m or more 19¢ per metre

Medium Duty

Ideal cable for connecting speakers to systems of up to 200 watts power. Heavy duty with low resistance for long runs with very low power loss. Colour coded for polarity reference.
Conductors 14 x 0.20. Cat W-2012

30¢ per metre. 100m or more 23¢ per metre

Heavy Duty

Heavy duty cable that's ideal for running 150W spot lights, etc on the car. Rated at 20A, red and black colour coded insulation for polarity. Conductors 26/0.3 Cat W-2025

85¢ per metre. 100m or more 77¢ per metre

Mains Rated

Ideal for use with extension lights, standard lamps etc., also ideal for use with speakers and intercoms if a lower resistance is required. 24×0.20 . Rated at 240V AC, 7.5A. With white PVC insulation. Cat W-2020

60¢ per metre. 100m or more 55¢ per metre

Bell Cable

Super thin two core cable that's ideal for connecting door bells, etc — where the cable is permanently fixed. 1/0.60 with white insulator. Cat W-2005

40¢ per metre. 100m or more 35¢ per metre

Auto Cable

2 × 26/0.32. Similar to fig. 8 cable, it's insulated and sheathed. The same wire used by the manufacturers in automotive wiring harnesses. Nominal conductor area of 2mm2. Black/red core colours, rated at 20A (int), Cat W-2027

99¢ per metre. 100m or more 89¢ per metre

"Big Stuff"

Low Loss Cable

Ideal for high power amplifiers' speaker lines, especially where any sort of distance is involved. 256 conductors of 0.127mm oxygen free copper for highest possible conductivity. Low dielectric constant clear PVC insulation. Cat W-2105
\$2.95 per metre. 100m or more \$2.25 per metre

Shielded Audio Cable

Mono Light Duty

PVC covered, light duty, very flexible cable that is ideal for patch cords, small microphones, etc. Colour — Grey. 45¢ per metre

100m or more 40¢ per metre

Twin Shielded

2 PVC covered twin shielded conductors. Ideal for microphones, audio patch leads hook-up wiring, etc. Flexible, light duty. Colour coded. Cat W-2034

65¢ per metre 100m or more 59¢ per metre

Twin Shielded

The same as the single conductor audio lead but with two conductors separately shielded in fig. 8 pattern insulation. Idea for stereo connection. Colour - grey.

85¢ per metre 100m or more 77¢ per metre

Heavy Duty Twin

Two conductors individually shielded and colour coded surrounded by a heavy duty outer insulation sheath. Ideal for use where heavy handling could destroy light duty cables i.e. rock groups etc. Cat W-2037 \$1.55 per metre

100m or more \$1.40 per metre

4 Core Shielded

All 4 conductors are individually shielded and covered by grey PVC insulation. Ideal for use with stereo systems that have DIN type connections. Cat W-2038

\$1.45 per metre 100m or more \$1.31 per metre

4 Core Flat

Just like above (W-2038), this one has 4 conductors individually shielded and insulated. This one though is FLAT and in black finish. Cat W-2039 \$1.35 per metre 100m or more \$1.20 per metre

Heavy Duty Mic Cable

Very heavy insulation and double cotton strengtheners make this the perfect cable for musicians, PA use, etc. — anywhere rough use is expected or accepted. Twin insulated conductors and single shield make it ideal for balanced lines too. Cat W- 2035

\$1.75 per metre 100m or more \$1.55 per metre

IDC Computer Cable

Made especially for IDC (insulation displacement connector) applications: flat, multi-strand cables in 4 sizes. (See plugs and sockets pages for IDC fittings).

Cat No 1-9m 10 up **Type** Cat W-2750 \$3.10 \$2.80 Cat W-2752 \$3.95 Cat W-2754 \$4.95 34 way \$3 45 Cat W-2756 \$5.50

Five core shielded cable intended for running data cables around buildings, etc., with minimum interference — pick-up or radiation. Wires are individually insulated with drain wire, and insulated from foil shield. Cat W-2040

\$4 85 per metre 100m or more \$1.65 per metre

12 Core Data Cable

Shielded cable for running data cables, 12 individually insulated conductors (7/.020) and drain wire, with foil shield for minimum interference. Colour - grey. Cat W-2041

\$2.50 per metre. 100m or more \$2.20 per metre

Coaxial Cable 75 ohm Air Space

High quality low loss TV coax for low signal area installations. Air cored (dielectric). similar size to 5C2V. Cat W-2082

100m or more 80¢ per metre

50 ohm RG58C-U Commercial

Commercial Grade RG 58 with ultra-fine (18 pitch) braid for lowest loss, lowest noise figure. You asked for better quality here it is! Cat W-2092

\$1.05 per metre 100m or more 95¢ per metre

50 ohm RG-213 Low Loss

For long runs with minimum loss, without going to the expense of Heliax. RG-213 gives better performance at VHF & UHF than RG-8. Cat W-2099 \$3.15 per metre

100m or more \$2.80 per metre

Mini 50 Ohm RG-178 Teflon

Able to handle up to 100 watts at 500MHz due to the Teflon insulation. This also means you can solder directly to the shield braid without melting the insulation. Incredibly small diameter, only 2.5mm! Ideal for wiring into transmitters etc, where space is a premium. High quality. Cat W-2088 1 metre pack — \$4.60 10 packs or more \$3.95 ea

Belden 9913 50 Ohm

Ultra Low Loss The highest grade coax we sell. Top quality

US made (similar to famous Heliax) with only 2.6dB/100ft attenuation at 400MHz (only 4.5dB at 1GHz!) 100% shield coverage. If you want the best, this is IT!

Cat W-2097 \$5.95 per metre

100m or more \$5.35 per metre

Builder's Cable

At last we've got it! You've been asking us to stock Builder's Cable for years — so here it is. The most popular cables are now available where you want them, at your nearest DSE store.

Twin & Earth

1/113 rated at 10 amps. Used mainly for light circuits, has insulated earth. Cat W-2060 \$1.25 per meter

100m or more 95¢ per metre

Insulated Twin

7/050, our most used builder's cable. Rated at 10 amps with multi-strand insulated conductors, it's great for light circuits with separate earth. Colour coded insulation. Cat W-2061

100m or more \$1.25 per metre

1/178 Twin and Earth

Rated at 25 Amps this one's ideal for power circuits. With insulated earth and large 2.5mm² conductors. Buy it in the length to suit the job or take advantage of our generous bulk prices.

\$1.95 per metre 100m or more \$1.75 per metre

Earth Wire

Annealed multi-strand Insulated (green/yellow) Earth Wire 7/067. Can be used as an earth wire or as antenna wire. Cat W-3010

100m or more 60¢ per metre 70¢ per metre

300 ohm Feeder

Suitable for indoor or outdoor use. (Black). 300 ohm feeder ribbon for connecting aerials to TV sets - low loss and maintains perfect balance, Cat W-2070

30¢ per metre

100m or more 23¢ per metre

Wire Packs:

The economical way to buy **Hook-up Wire Pack**

24 metres in total of 12 different colours (that's 2 metres of each colour) of the 10×0.12 mm hook-up wire. Ideal for the hobbyist, experimenter, etc.

12 colour pack \$2.90 10 up \$2.65

Resistance Wire Pack

Resistance wire suitable for the construction of wire wound resistors, small heater elements, shunts, etc. Also ideal for emitter resistors in high power amplifiers. Wire size: 28 B&S (diameter 0.32mm). Solderable: yes. Resistance: 1.852 ohms/ft. Non magnetic, corrosion resistant, Composition: 45% Nickel, 55% Copper. Maximum continuous service temperature: 540°C. Cat W-3200
4 meter pack — \$1.05 10 up 95¢

Instrument Test Lead Wire Pack

Special 512 strand (YES 512!) very flexible wire that is ideal for test leads or for connection to something that is moving. Very low resistance and only 3mm in diameter. Expensive — yes, but it will last for years. Pack contains 2 metres each of red and black (4 metres total). Cat W-4016

4 metre pack — \$8.95 10 up \$8.05

Spaghetti

Contains 30 lengths of assorted colours and diameters (each length being more than 150mm), that totals over 4.5 metres of spaghetti. Cat W-4040.

\$3.45 per pack. 10 up \$3.10.

Wire Wrapping Pack

This is a high quality insulated IC wrapping wire now in a convenient 5 metre pack — keep a couple of packs handy, you never know when you may need it! Cat W-4018 5 metre pack — \$1.95 10 up \$1.75

Tinned Copper Wire

High quality 25 gram roll of 22 SWG (approx. 20 B&S) tinned copper wire. Ideal for PC board links, hard wire jumper leads, chassis wiring, etc. 0.71mm x 8 metres to a roll Cat W-3022

Approx. 8 metres — \$3.50 10 up \$3.15

Enamelled Winding Wire

Coil winding, motor rewinding, transformer building are no longer a problem with these handy coils of enambed wire. **NOTE:** where possible this wire will be supplied with "Bixaflux" insulation. Simply heat wire with a soldering iron and insulation will flow therefore requiring no stripping.

Gauge B&S	mm		Length metres		Cat No.	Price	10 up
16	1.25	18	8m	100g	W-3116	\$4.50	\$4.00
18	1.0	19	12m	100g	W-3118	\$4.50	\$.400
20	0.8	21	18m	100g	W-3120	\$4.50	\$.400
22	0.63	23	24m	100g	W-3122	\$4.50	\$.400
23	.71	25	6m	25g	W-3123	\$3.25	\$2.90
24	0.5	25	9m	25g	W-3124	\$3.25	\$2.90
26	0.4	27	20m	25g	W-3126	\$3.25	\$2.90
30	0.25	33	50m	25g	W-3130	\$3.25	\$2.90
32	0.2	36	170m	25g	W-3132	\$3.25	\$2.90
36	.125	40	220m	25g	W-3136	\$3.25	\$2.90

Fuse Wire

Great for keeping a card of this in the fuse box — just in case! Card of 8, 16, 20 and 30A fuse wire. For light circuits, right up to the electric stoves! Cat W-3180

80¢ per pack 10 up 75¢



Heat Shrinkable Materials

Now we've got a great range of high flexibility, radiation cross linked, flame-retarded, heat shrinkable, military grade polyolefin tubing and compounds. With that sort of description it has to be good. Available in black, white and up to seven colours. Just the size, colour and length you're looking for!

He ad Chainle Ticking

E-&-C-A

Hear Sn	rink	IUDI	na	
Size	Cat No.	Colour	Price	10 up
1.2m × 1.6mm	W-4100	Black	\$2.30	\$2.0
1.2m × 1.6mm	W-4102	Colours	\$2.30	\$2.05
1.2m × 3.2mm	W-4104	Black	\$2.70	\$2.40
1.2m × 3.2mm	W-4106	Colours	\$2.70	\$2.40
1.2m × 4.8mm	W-4108	Black	\$3.30	\$2.9
1.2m × 4.8mm	W-4110	Colours	\$3.30	\$2.95
1.2m × 6.4mm	W-4112	Black	\$3.50	\$3.15
1.2m × 6.4mm	W-4114	Colours	\$3.50	\$3.15
1.2m × 9.5mm	W-4116	Black	\$3.90	\$3.50
1.2m × 9.5mm	W-4118	Colours	\$3.90	\$3.50
1.2m × 12.7mm	W-4120	Black	\$4.30	\$3.8
1.2m × 12.7mm	W-4122	Colours	\$4.30	\$3.85
Certified to US. I	Ail spec #	MIL-1-23	053/5.	



Available Colours: White, red, blue, green, yellow, orange, clear and green/yellow. Not all colours available in all sizes.

Encapsulating Heat-Shrink



Measures 150mm × 13mm diameter. Dual wall heat shrinkable material with an adhesive coating which flows during heating to form a Watertight Seal around components, splices, etc. This is a black finish material and is also flame retardant. Cat W-4135

\$4.95 10 up \$4.45

Connector Backshell



For forming a backshell on miniature 25 pin connectors. The ron on ming a backsnell on miniature 25 pin connectors. The boot snaps onto the back of the connector and is fixed with jack screws (provided). The heat shrinkable cable entry can be placed on a variety of cable diameters and strain relief is easily achieved by installing a collar onto the cable jacket. Finished in black. Cat W-4130

\$4.95 10 up \$4.45

4:1 Heatshrink



Ideal for cable jacket repair or installation over pre-installed connectors. Measures 150mm × 50mm. Unlike many over expanded products this one has a minimal longitudinal change which makes installation much easier. Black finish. Cat W-4140

\$6.95 10 up \$6.25

Pre-insulated Nylon Sealed Splices



DuraSeal preinsulated splices provide a waterproof adhesive seal for protection against corrosion, condensation, heat, etc. In packs of 10 they provide a 1:1 splice and are colour coded in red, blue and yellow, for use with an ordinary crimping tool.

Gauge (Size)	Cat No.	Colour	Price	10 up	
18-22 (0.5-1.0mm ²)	W-4145	Red	\$9.50	\$8.55	
14-16 (1.5-2.5mm ²)	W-4147	Blue	\$9.75	\$8.80	
10-12 (4-6mm ²)	W-4149	Yellow	\$9.95	\$8.95	

Fitted Mains Cord

2.0m 7.5A core flex with 3-pin plug on one end: ideal for all mains projects. Cat W-2057

10 or more \$3.15 each



75 Ohm Video

2m quality 75 ohm coax cable fitted with a variety of plugs and sockets to suit most TV, video recorder and computer applications.

Coax to Coax

Both male, fitted with standard coax type plugs. Usually used from wall outlets to TV/VCR etc. Cat W-1400

\$ 40

Coax to Coax

As above, but male one end and female the other - perfect for use as an extension cord, also used on some VCR's (particularly portables), Cat W-1405

\$ 40

RCA to Coax

Both male, for use with many types of VCR/TV combinations, also used in some wall outlet to TV combinations. Cat W-1286

RCA to BNC

Both male. Used on some VCR's as video output cable, also used on many computers to video monitors. Cat W-1290

BNC to BNC

Suits some VCR's and monitors, as well as a lot of professional recording equipment.

\$295

BNC to PL259

Again, used on many video recorders for video output. (Note: not suitable for most transceivers - 75 ohm use only). Cat W-1295

ADAPTOR SETS **Universal Video** Cable Set

Own a video cassette? Want to dub tapes? You must have one of these amazing cable sets. Doesn't matter what type: VHS, Beta, Umatic, Philips... this suits any to any! Comes with 2 metre audio/visual cable with phono plugs on each end, plus adaptors to suit BNC, UHF (PL-259), DIN, phono, etc. Every video enthusiast should have one! Cat W-1287

Shipping weight: 944g Shipping size: 295 \times 121 \times 37mm



The Complete **Headphone** Adaptor Kit

Everything you'll ever need to connect headphones to just about anything (except your head)! Comes with stereo 3.5 metre extension cord, 3.5 mm to 6.5mm and 6.4mm to 3.5mm adaptors, stereo to mono adaptor and double headphone adaptor all in a durable storage case. Cat C-4180

Shipping weight: 210g Shipping size: 200 imes 155 imes 30mm



COMPUTER CABLES

Parallel Printer Cable

Standard "Centronics" type printer cable with 36 pin Centronics plug (as used on 99% parallel printers) one end, 25 pin D socket the other. 1.7m long. Cat X-8614

Shipping weight: 340g Shipping size: 280 × 200 × 30mm

Serial Data Cable

2.35 metre serial cable with male DB25 plug one end, female DB25 socket the other. All 25 pins wired 1-1, etc. For serial printers, modems computer/computer connection and other data applications. Also ideal as extension lead for parallel printer cable (gives over 4m). Cat X-3564

Shipping weight: 390g Shipping size: 30 × 140 × 20mm

DC POWER

Car Lighter Power Lead

Fitted with lighter plug one end, 4 way star connector the other to suit most common DC input connectors, Cat P-1680



Midland Power Lead

(Suitable for a huge range of other transceivers with 3 pin plug.) Cat D-9001



\$ 195

DSE Transceiver Power Lead

Or other transceivers with 2 pin plug.

\$ 495

CB COAX LEADS

50 Ohm CB Coax Leads

Antenna Extension

1m 50 ohm RG58U coax fitted with PL-259 connectors at each end. Ideal for extending CB or HF amateur transceiver leads to allow antenna to be mounted further away Cat W-1370

Shipping size:

Shipping weight: 233g

Antenna Lead

Similar to above, but fitted with PL-259 plug one and lugs on other for connection to a variety of CB/amateur antennas. Cat W-1372

\$595 10 up \$5.35



CAR RADIO ANTENNA LEADS

1m Extension

Fully compensated (low signal loss) 1 metre lead. Ideal when your new antenna has a lead which is too short or if you're roof mounting your system. Cat A-7450

Shipping weight: 58g Shipping size: $260 \times 100 \times 30 \text{mm}$

4m Extension

Same as the above but this one's 4 metres long. Ideal for rear mounted antennas. Cat A-7452

Shipping weight: 177g Shipping size: $300 \times 100 \times 50$ mm

PHONE CORDS

10m Extension Reel With Double Adaptor!

Take the phone anywhere in the home, office or workshop. Wind the 10 metre cable up and it's kept neat and out of harms way. The inbuilt telephone double adaptor allows you to plug-in two telephones. or a phone and an

Cat F-5100 \$2495

answering machine,

or a phone and a ...!


Commander Extension Cord

8m telephone extension cord specifically intended for Telecom "Commander" phones and other 4-wire systems. Cat F-5102



Telephone 15m Cord With Double Adaptor

15m of phone freedon - plus a double adaptor for your cordless phone, answer machine, etc. Cat F-5103



10m Cord With Double Adaptor

A little shorter, a little cheaper. Also includes double adaptor! Cat F-5115



MAINS LEADS

'IEC' 2 Metre Mains Lead (1)

Approved 3 core 240V mains lead fitted with standard IEC line socket (as used on most computers, VCRs, transceivers, etc., etc.) and Aussie 3-pin plug on other. Cat W-1362

Universal Mains Leads \$295 0,0

Approved mains cable as used in a huge variety of imported audio, radio, video and other entertainment equipment. Two pin mains plug, approx. 2 metres cable and figure 8' type two-pin socket. Note: no earth lead! Ideal replacement cable, Cat W-1360

8.6mm pin spacing

Similar to above, but square-type connector with 7mm spacing suiting Sanyo and other modern audio equipment. Cat W-1361

\$295

Audio Adaptor Leads

5 pin DIN plug to 5 pin DIN plug (10 up \$4.05)

5 pin DIN plug to 2 x RCA plug Cat W-1020. (10 up \$4.45)

5 pin DIN plug to 4 x RCA plug Cat W-1040.

(10 up \$6.35) 5 pin DIN plug to 2 x 3.5mm plug Cat W-1050

(10 up \$4.95) 4 x RCA plug to 4 x RCA plug

Cat W-1060... (10 up \$6.35)

1 x RCA plug to 1 x RCA plug (10 up \$2.45)

1 x RCA plug to 1 x 3.5mm plug (10 up \$2.25)

1 x 3.5mm plug to 1 x 3.5mm plug Cat W-1090..... (10 up \$2,25)

1 x 6.5mm plug to 1 x 1.65mm plug (coiled lead) Cat W-1110.....

(10 up \$6.75) 4 metres coiled lead with 6.5mm stereo plug to 6.5mm stereo socket

Cat W-1120 (10 up \$6.75)

1 x 3.5mm plug to 1 x 3.5mm line socket Cat W-1150.

(10 up \$2.65) 1 x 3.5mm stereo plug to 1 x 3.5mm stereo socket

\$3.50 Cat W-1160 (10 up \$3.35) 2 x RCA plugs to 2 x RCA plug

Cat W-1180... (10 up \$4.45) 2 x RCA plugs to 2 x RCA plugs

(10 up \$2.65) 1 x 3.5mm plug to 2 x RCA plugs

(10 up \$4.05) 1 x RCA plug to 1 x RCA socket

\$2.50 Cat W-1280.... (10 up \$2.25)

L-o-n-g 'Phones Extension Lead

5m headphone extension lead specifically intended for walkie stereos and radios.
Complete with GOLD PLATED 3.5mm plug and sockets which are for long, long life and virtually no corrosion PLUS a gold plated 3.5 to 6.5mm adaptor. Cat W-1165



Coiled Microphone Cord

3 metres very flexible microphone cable, with 3 conductors plus shield. The ends of the conductors are pre-tinned and the whole cable is pre-coiled for easy use. Ideal for replacing microphone and headphone cables with appropriate sockets. Cat W-1365

Shipping weight: 95g Shipping size: 200 × 110 × 20mm \$ 125

"Y" Adaptor Cables

Two RCA connectors one end, one the other, wired in parallel. Cat W-1190 \$350

Two RCA connectors one end, a 3.5mm stereo connector other end, with each RCA wired to a separate channel. Cat W-1240

Lamps

Neons

Small pigtail type neon bulb as used in indicators, timing circuits, oscillators, etc. etc. Striking voltage 70-90 volts at 600uA. For 240V operation use 270K ¼W resistor (other voltages can be worked out from Ohm's Law). cat 8-3862





Tiny globe as used in many push buttons and flashing alarm lights. 12 volt, 60mA bulb with hard-wire (push-in) contacts. Cat S-3845

225

Halogen Torch Bulbs

At last the benefits of halogen have come to low voltage bulbs: whiter, stronger light. Less infra-red output so they're more efficient. In fact, the manufacturers say up to 300% brighter than conventional bulbs. And yes, they are more expensive — but so are batteries these days. So why waste power? Note: halogen bulbs operate at higher temperature so should only be used in torches designed for these bulbs. 3 voltages to choose from: all standard captive fitting.


2.8 volt — use with 2 x "D" batteries Cat S-3950 4.0 volt — use with 3 x "D" batteries Cat S-3955 5.5 volt — use with 6 volt lantern or 4 x "D" batteries Cat S-3960



ALL 3 / 93

Xenon Flashtube

Xenon-filled flashtube, as used in strobes, warning and safety applications, photographic work, etc. etc. And look at the bargain price: you'd expect to pay double! Operate from 200-400 volts (300V nominal) with 4kV trigger, 5 watts maximum input power. Cat 5-3882



Trigger Transformer to suit

4kV trigger transformer for above flashtube. PCB mounting type, 300V primary, 4kV sec. Cat M-0104



MES/LES Lamps

Miniature Edison Screw (MES) and Lilliput Edison Screw (LES) bulbs for dial lamps, etc. Standard 6 and 12 volt types. Ideal for all new work and replacements.



MES 50¢

6 volt Cat S-3806 6 volt Cat S-3836 12 volt Cat S-3842

Socket to suit MES bulbs. Cat S-3880





LES

Floodlamps

PAR 38 Coloured Bulbs

240 volt, highest quality pressed glass with internal reflector. Ideal for semi-rough handling (they are glass, after all!) — eg disco and lightshow use. All rated at 100 watts, ES (Edison screw) fitting.

Yellow: Cat S-3850 Red: Cat S-3852 Blue: Cat S-3854 Green: Cat S-3856

\$4095



ES Lampholder to suit:

Swivel Edison Screw lamp holder Batten mounting, swivels through 30°. Cat P-5620

\$750



'Blacklite' Globe

240V incandescent lamp especially made for emitting UV light. Standard bayonet (BC) fitting so you can plug it into an ordinary light socket. For parties, special lighting effects, etc. Cat S-3900

\$595



R80 Daylamps

Ideal for display, party or other decorative or warning purposes. Available in four colours; 240V operated. ES base.

Yellow Cat S-3851 Red Cat S-3853 Blue Cat S-3855



Argus T2L Magnifier/Lamp

reason to strain your eyes soldering intricate Pe Boards, and possibly ruining a project. To a T2L magnifier open your eye to a hold e working memod theirs is to a tip relies whe thermo plastic magnifier was 76 grass) provides 3 dioptre (1.75×) man heation. And the til the 40 watt incandescent lamp floot was relieved to the with light. The two spring land to the mean be extended up to 95cm, a microstrain magnifying head is adjustable for an optimum viewing angle. Suits either table/work bench or wall mounting. Cat S=4000

\$**99**5



Bezels

Miniature LED Bezel

Our most popular. Low current drain (20mA @ 2 volts) but offering high visibility. Smart chrome bezel, needs a 7mm hole, Two colours available:



Dual Colour LED Bezel

Red and green in one!

A fantastic idea! Two LEDs in one bezel — ideal for two-state indication (on/off, etc.). Chrome plated bezel, ideal for logic circuits, etc. Operates on 1.3-1.5V @ 25-30mA. cat S-3530



LED Mounting Bezels

When using LEDs on front panels, etc, use these self-locking bezels. Suit standard size (5mm) LEDs, and make a reatly neat job. They work out at around 9¢ each! (Pack of 15 bezels). Cat H-1910



Miniature Neon Bezel

A favourite because of its tiny size. Used a lot in mains powered projects — simply use 270k resistor in series. Requires only 7mm mounting hole, and the bezel itself is chrome-coloured. Remeber to use a series resistor with all neons — they tend to get unset otherwisel or 9.3552



240V Neon Bezel

Intended for 240 volt projects, this bezel can be wired direct to the mains. It has a series resistor actually mounted inside the bezel case. It requires a 9mm mounting hole, front of bezel is neat clear plastic resulting in high visibility red light from neon.



12V Bezel

A very attractive medium size bezel using a 12V LES bulb. The plastic lens is available in two colours (red and green) for various uses, and the lens itself is flat-topped, resulting in a modern appearance. The body of the bezel is chrome plated. Requires an 11mm mounting hole, and obviously 12volts AC or DC. Don't forget to order the colour you require.





ANSFORME


DSE2824

240V, 50Hz Primary: Secondary voltage: 3 5-0-3 5V & 7 5V 250mA & 10mA Secondary current: Terminations: Flying leads

Shipping weight: 116g Shipping size: 30 x 35 x 15mm

Cat M-2824

\$595 10 up \$5.35



DSE2840

240V. 50Hz Primary: Secondary voltage: 4.5-0-4.5V Secondary current: 150mA Flying leads Terminations:



10 up \$5.35

Cat M-2840 Shipping weight: 193g Shipping size: 45x 75 x 50mm

DSE2851

240V, 50Hz Secondary voltage: 6.3-0-6.3V 150mA Secondary current: Terminations: Flying leads

582, CEE

ENERGY AUTHORITY CERT. NO. C\$2204N

10 up \$5.35

Shipping weight: 193g Shipping size: 45 x 75 x 50mm

DSE2155

Primary: 240V 50Hz 6.3, 7.5, 8.5, Secondary voltage: 9.5. 12 & 15V

Secondary current: 1 amp Terminations: Shipping weight: 491g Flying leads

Shipping size: 100 x 60 x 50mm



ENERGY AUTHORITY CS2078N

DSE6672

Primary: 240V AC 15, 17.5, 20, 24, Tapped 27.5 & 30V secondary voltages: Secondary current: 1 amp Terminations: Solder lugs



10 up \$12.55

Shipping weight: 1.63kg Shipping size: 100 x 65 x 65mm

DSE1200

Primary: Secondary voltage: 240V 40V @ 10mA 19V @ 200mA 11.2V @ 450mA Flying leads

Terminations:

DSE0153

Primary: 240V AC Secondary voltage: 35-0-35V Secondary current: 2.5A Flying leads

Cat M-0153

Terminations: Shipping weight: 3.5kg Shipping size: 100 x

80 x 80mm



Secondary current: 2 2A Terminations: Flying leads Cat M-1990

10 up \$15.25

Shipping weight: 1.234g Shipping size: 100 x 90 x 60mm

DSE0144



Primary: 240V AC Secondary: 28-0-28V Secondary current: 2A Cat M-0144

Shipping weight: 2.4kg Shipping size: 95 x 80 x 70mm

DSE2000

Primary: 240V, AC Secondary: 18 volts @ 6A Terminations: Flying leads Cat M-2000



10 up \$31.45

Shipping weight: 2.5kg Shipping size: 80 x 95 x 65mm

DSE2010



Massive 18 volts at 14 amps continuous... ideal for high power rating power supplies, linear amplifiers, etc, etc. Compare our price with what you've had to pay in the past... What a bargain! Cat M-2010

Suits 13.8V 25A pk supplies As used in our VK powermaster kit

DSE 1602

Standard toroidal transformer suited to audio work. Terminations are soldered flying leads and it's supplied with neoprene rubber insulating disks and centering washer.

Primary: 240V AC Secondary: 2 × 35V @ 2.5A 2 × 15V @ 0.25A Size: 113mm OD × 48mm Cat M-1602

DSE 1600

Toroidal construction transformer, Ideal for amplifiers - low flux leakage, less hum, low profile. Comes with neoprene rubber insulation disks and centering washer for ease of mounting.



Primary: 240V AC Secondary: 2 × 45V @ 3.3A 2 × 15V @ 0.2A Size: 113mm OD × 58mm Shipping Weight: 2.55kg

Energy Authority fully approved

Low Cost Low Profile

Each transformer has two separate secondary windings which can be wired in series or in parallel. They are fitted with round pin terminations and include connectors. 240V AC



All one price! each 10 up \$26.95

PL12/20VA 2 x 6V@1.7A — 6V@3.4A — 12V@1.7A M-3596 PL15/20VA 2 x 7.5V@1.3A — 7.5V@2.6A — 15V@1.3A M-3597 W. 640g S. 110 x 50 x 65mm PL18/20VA 2 x 9V@1.1A — 9V@2.2A — 18V@1.1A M-3598 W. 650g S. 110 x 50 x 65mm

PL18/20VA 2 x 9V@1.1A — 9V@2.2A — 18V@1.1A M-3598 PL24/20VA 2 x 12V@.85A — 12V@1.7A — 24V@.85A M-3599 PL30/20VA 2 x 15V@.69A — 15V@1.3A — 30V@.69A M-3600

PL40/20VA 2 x 20V@.51A - 20V@1A - 40V@.51A M-3601

W. 660g S. 110 x 50 x 65mm W. 660g S. 110 x 50 x 65mm W. 670g S. 110 x 50 x 65mm W. 660g S. 110 x 50 x 65mm

PCB Mounting Transformers

Mounts directly onto the PCB which makes wiring incredibly simple. Two separate secondary wirings - can be series or parallel connected. Gives 24 volts at 0.21 amp in series or 12 volts at 0.42 amp in parallel. Great for hobbyists! Cat M-3590



10 up \$17.95

Audio Line Transformer

This transformer has been engineered to cover more than 95% of all PA — BGM applications. Suited to all speaker impedances. Multitapped for use with 100V or 70V lines. 52mm mounting centres.

- Multi-purpose matching transformer
- 4 watts rms rating 2, 4, 8, 16 ohms secondary
- 2.5K, 5K ohms primary

Shipping weight: 172g Shipping size: 65 x 40 x 40mm

\$650 10 up \$5.85



600 ohm/600 ohm Isolation Transformer

Intended for modems and other telephone line applications, isolates line from device to comply with Telecom regulations. Fully approved by Telecom Engineering branch

Need 115 Volts?

Quality stepdown transformer from Arlec for powering 115 volt equipment. Great for anything that comes from the USA. 240 volts input, 60VA capacity. Enclosed in sturdy metal case for safety it has US style 2-pin socket, fuse and 2 metre card with plug.



Shipping Weight: 3kg Dimensions: 88 × 132 × 68mm

Transistor Audio Transformers

Ideal for transistor radio replacements. good for transistor projects including oscillator circuits, requiring coupling transformers. Miniature size.

Model M-0222 - Primary


3k ohm . Secondary 3k ohm

• Use - coupling • Iron Core • Size 17(I) x 15.5(w) x 15(h)mm. Cat M-0222

Model M-0216 - Primary

- 1k ohm Secondary 8 ohm Use 350mW O/P
- Ferrite Core Size 15(I) x
- 14(w) x 11.5(h)mm. Cat M-0216







Regulated amateur transceivers (hand-helds

especially), etc. 12 volts DC regulated with terminals for easy connection. Makes a great service supply, too. Cat M-9545

12V @ 1.5A

Shipping weight: 1.5kg Shipping size: 180 x 170 x 90mm

13.8V/4A Peak

Need more oomph? Try this one: the high power Panther. For the 2m or small HF amateur transceiver, a supply for 'auto' equipment, even a bench supply for service work — you'll go a long way to find a better supply. With a 3 amp continuous (or 4A continuous at 75% duty cycle!) and a huge 8 amp instantaneous peak rating, it's ideal for those higher current and higher neak demand applications that the continuous at 75% duty cycle! higher peak demand applications that the above supply can't manage. Cat M-9547



- Heavily heatsunk for maximum output
- Colour coded output terminals
- LED indicator also shows overload or short circuit

Shipping weight: 2.25kg Shipping size: 200 x 145 x 115mm

3-6-9-12V PORARIL UNAVAILABI one a maximum of 1 amp at 3, 6, 9 and 12 volts DC. Simply plugs into 240V AC power socket — DC connections via screw terminals on front of unit. Ideal for use with alarm systems, intercoms, etc.

- Overload protection
- Simple screw terminal connection
- · High 1A output

Shipping weight: 7.25kg Shipping size: 200 x 90 x 65mm

Protect your computer system

ENERGY APPROVED



Jabel Line Filter

Spikes, spurgels and sundry other garbage on the mains can spell disaster for your poor computer. Even separate sections of the computer can cause mains hash (eg printer). This deluxe filter virtually eliminates most mains-borne garbage giving your computer a clean line of supply with which to operate. If you're having 'crash' problems with your computer — could be this filter will fix it! Rated at 240 volts, 2 amps. Fully approved by the Energy Authority. Cat M-9850


Shipping weight: 1.25kg Shipping size: 220 x 115 x 75mm

Car Voltage Converter

6, 7.5 and 9 volts output at 800mA

Most battery devices include an external DC connection. Use them in the car from your car battery via this voltage converter. Suitable for high current device, simply plugs into cigar lighter. Output has switchable polarity as well as voltage, includes 4-way connector plus battery "snap". Cat M-9584





3-6-9V DC

superb buys in this catalogue - many thousands have been purchased by people who know how to save money! It is a small plug-in unit that has three output voltages of 3, 6 and 9 volts DC at 200 milliamps possibly the three most used voltages on battery powered equipment. It is ideal for many battery driven items. Cat M-9525


Shipping weight: 305g Shipping size: 255 x 165 x 50mm

3-4.5-6-7.5-9-12V @

An extremely versatile supply ready for just about any application. Switchable output gives 6 different voltages ranging from 3V to 12V, at up to 300mA. Cat M-9526

795

Shipping weight: 300g Shipping size: 120 x 92 x 50mm



9V DC @ 200mA

For all equipment requiring 9V DC at a 9V transistor type battery or many other static hobby models that require 9V. Eliminator modules simply plugs into a 240V AC power socket. Cat M-9514

Shipping weight: 300g Shipping size: 120 x 92 x 50mm



12V AC @ 500mA

Ideal power supply for projects that require 12V AC at 500mA. Because the whole of the plug-pack is a transformer, you get a much higher current rating than other plug-packs. Rectifiers and filter components can be placed inside the project itself. Cat M-9555

Shipping weight: 300g Shipping size: 120 x 92 x 50mm



9V DC @ 600mA

Extra high power - ideal for 9 volt equipment which needs more than the low power-plug packs can provide (such as cassette recorders, etc). Cat M-9560

Shipping weight: 350g Shipping size: 100 x 50 x 50mm



AC Supply 6V 900mA

The biggest problem with most projects is fitting in the transformer! This one obviates the problem - keep the supply components inside, but the plug-pack hangs on the power point! With a very healthy 16V at 900mA, it's perfect for 12 volt DC supplies. Energy authority approved. Cat M-956

Shipping weight: 656g Shipping size: 105 x 65 x 95mm

7.2V Racing Pack NiCads

Powerful, long-life 7.2V packs designed for Tamiya and other

remote control cars. Totally reliable, the ideal choice for lasting off-track run and serious

competition staying power!

NICADS — Extra Value **Packs**

Save with NiCad battery packs! Long life, high power batteries for all you portable power needs.

STANDARD NICADS

Qty	Туре	Cat No.	Price
4 × AA	500mAh	S-3150	\$19.95
2 × C	1.2Ah	S-3152	\$23.95
2 × D	1.2Ah	S-3154	\$23.95
EVTDA	HEAVA	DIITY	

EXTRA HEAVY DUTY NICADE

4 × AA	600mAh	S-3160	\$24.95
2 X C	2.0Ah	S-3162	\$31.95
$2 \times D$	4.0Ah	S-3164	\$33.95

Extra Heavy Duty NiCads

For long life, high power and reliability. DSE carries an extensive range of heavy duty NiCads and it's extending all the time. Whatever your battery needs drop into your nearest DSE store and save!

Type		Cat No.	Price
AA	600mAh	S-3312	\$5.95
C	2.0Ah	S-3311	\$14.95
D	4.0Ah	S-3310	\$15.95
Sub C	Fast Charge	S-3324	\$5.95

NiCad Batteries

'AAA' size

10 up \$4.25

At last, you can get 'AAA' rechargeables! Now all those toys, calculators, etc using this popular size can benefit from the much lower overall cost of NiCads. 1.2 volts, 180mAh rating. Cat S-330

\$495

Use to replace standard 'C' size batteries. Higher capacity (1.2Ah) for longer use. Single cell.

10 up \$8.95



'AA' (penlight) size

Popular NiCad cells. Can be recharged up to 200 times! Rated at a massive 500mAh this battery is suitable for almost all devices using standard AA batteries, 1,2 volts Cat S-3300

10 up \$3.15

\$ 75



'D' size

Also rated at 1.2Ah, but has same physical size as standard 'D' battery. Used in models, toys,



'216' size

At last! A true 9V NiCad in the popular '216' (transistor radio) size. Don't be fooled by most models: they're really 7.2V! This one gives full output! 100mAh rating. Cat S-3308

10 up \$17.95



Exclusive Rechargea to DSE!! Recharg Ï Rechargeable

Nickel-Cadmium Battery

Toshiba Quality NiCads

Top quality NiCads from one of the world's biggest electronics manufacturers. The four most popular battery sizes to power... just about anything!

AAA 180mAh \$ 195

AA 500mAh



D 1200mAh

Car Battery Charger

This one will get you going — fast. With a high 4A charge rate it will completely charge a dead battery overnight; it could get you going in much less time. Complete with charge meter so you won't overcharge the battery. Top value!

Shipping weight: 1.5kg Shipping size: 200 x 95 x 150mm



NiCad Charger

Most devices these days allow for an external charger to be plugged in to charge NiCads (usually a 2.5mm socket). This charger is ideal for all NiCad packs from 6 to 10 cells (ie 7.2 to 12 volts). Fully approved by Electricity Authority
Cat M-9517



Arlec Slimline

Designed to charge the two most popular batteries quickly and reliably. The Arlec PS829 will charge up to 8 x 'AA' (Penlight) batteries and 2 x '9 Volt' simultaneously or in virtually any combination.

Simply plugs into the mains socket (reduces the voltage to 12 volts for safety) and the charging indicator lamps tell you it's working. Cat M-9512




NICAD CHARGERS Up To 8 Batteries At Once...

The DSE Charging Cabinet

The universal charger that'll do a big bunch of batteries at one time! Charges AAA, AA, C, D and 9 Volts in virtually any combination. That's right up to 8 cells and/or 3 × 9 Volts

Features indicator lights for each cell. reverse polarity protection, mains operation, test meter and more! Automatically selects 50mA, 120mA or 180mA depending on

battery size. Great buy! Cat M-9505



Multi Current Arlec Charger

In-situ charger for all NiCad types (AAA to 9V) with 4 different charging currents and 6 different connector types to suit all device sockets. Handles up to 10 NiCads at one

For High Capacity NiCads

Similar to DSE Charging Cabinet at left (same size and capacity) but this one is specifically intended for "High Capacity" NiCad batteries. Charges 600mAh AA, 1.8 & 2Ah C, and 4Ah D cells at their correct rates. (Same features as standard cabinet except no test meter on this model). Cat M-9506

Arlec Universal Charger

Just what you need for all your NiCads! Charges 9 Volt, 'D', 'C', 'AA' and 'AAA' batteries either singularly or in any combination — up to a maximum of five batteries at one time.

Charge rate automatically adjusts according to battery size and each battery position has an indicator lamp. The Arlec PS519 operates from mains power supply and has facility for testing 1,25 volt batteries. Cat M-9521



Top Name EVEREADY...

Heavy duty

Eveready Red batteries in 5 types. How's your lantern battery?

Qty	Туре	Cat No.	Price Each	Price 10 up
216	9V	S-3106	\$1.95	\$1.75
276P	9V	S-3210	\$14.95	\$13.95
2362	9V	S-3200	\$14.95	\$13.95
509	6V	S-3240	\$4.75	\$4.75
732	12V	S-3242	\$24.95	\$22.95
731	6V	S-3244	\$12.95	•
1015	AA	S-3100	65¢ (each
4005	•	0 0400	05+	



S-3102 S-3104 1050 95¢ each

Energizer

Top brand name, top quality! Eveready Alkaline Energizers, recommended for extra heavy duty applications where normal batteries turn up their toes. All normal sizes available; always guaranteed fresh and ever ready!

Qty	Туре	Cat No.	Price	Price
	1881		Each	10 up
Pack 2	'AAA'	S-3278	\$3.95	\$3.65
Pack 2	'C'	S-3282	\$4.25	\$3.95
Pack 2	'D'	S-3284	\$4.95	\$4.75
1x216	(9V)	S-3286	\$4.95	\$4.75
1 x 529	(6V)	S-3245	\$24.95	
Pack 4	'AA'	S-3287	\$4.95	



Photo	
PHOIO	
Batteries	2

You'll find a great range of batteries for your

camera equipment at DSE:				
Туре	Cat No.	Price		
2L76BPI 3V	S-3060	\$11.95		
S76BPI	S-3080	\$5.95		
A544BPI 6V	S-3289	\$7.95		



Calculator Batteries

Lithium calculator batteries now in the three most popular sizes. Suit a large range of scientific and statistical calculators. Blister packed for freshness

E-CR2025	Cat S-3330	\$3.75
E-CR2032	Cat S-3331	\$3.75
E-CR2016	Cat S-3332	\$3.75





Calculator/Games Batteries

The most popular Alkaline batteries for calculators and games from Eveready! In packs of TWO for economy and convenience.

Туре	Cat No.	Price	
Type A76 × 2 186 × 2 189 × 2	S-3061	\$3.95	
186 × 2	S-3062	\$3.50	
189 × 2	S-3063	\$3.50	
			_

Photographic Batteries

Individually packed Eveready Mercury Batteries as used in cameras and photographic equipment.

-		
Туре	Cat No.	Price
EPX13 (1.35V)	S-3065	\$5.25
EPX675 (1.35V)	S-3066	\$5.25


Mercury Electronics Series

As used in radios, small torches and for electronic instruments, etc. More Eveready

reliability and	quality in indi-	viduai pack.
Type E401 (1.4V)	Cat No. S-3070	\$ 5 25

General Purpose 'N' Size

The high performage Alkaline Battery used for small devices like remote controls for garage doors, etc. Comes in convenient pack of two as most used



Bulk Saving!

Get a 6-Pack of Eveready 'AA' Alkaline batteries and you'll save on individual prices! The AA is the most popular battery of all. It's used in radios, cameras, toys. hundreds of different appliances! Cat S-3290



Gel Cells No leak, rechargeable

There's no need to mess about with motorcycle cells, etc. for your alarm system and emergency supplies. Gel cell supplies high outputs without the mess of lead-acid batteries. Even keep it trickle charged via alarm or other mains supply. Measures: 125 x 95 x 35mm. With quick charge connectors. Cat S-3320

12V 1.2Ah

Mini Gel cell that's ideal for alarm applications... with enough oomph for other uses! Features colour-coded spade connectors. Measures 100 x 45 x 55mm. Cat S-3315

12V 6.5Ah

Heavy-duty, leak proof cell that's ideal for all general purpose applications: alarms, motorcycles, etc. Cat S-3322



Watch Batteries Equivalent Guide

Now you can get your watch/clock batteries at low cost!

		JIS	Eveready	Mallory	Hi Watt
Cat S-3292	\$2.95	G10	389	10L12	S-120
Cat S-3293	\$4.50	G13	S76	10L14	S-200
			303		
			357		
Cat S-3295	\$3.25	G12	386	10L24	S-150
	•		S41		
Cat S-3296	\$2.75	G8	391	10L130	
Cat S-3299	\$1.50	G3	392	10L125	S3-140
	•		S312		





Dick Smith Electronics Wholesale

Why buy from five or six small wholesalers when you can buy nearly all of your electronics needs from Australia's leading electronics wholesaler?

By purchasing product through DSE Wholesale, you will benefit from the following services:

- 1. A 4 tier wholesale price discount structure that provides additional discounts for quantity purchases.
- 2. One of the most sophisticated quality assurance programs in Australia.
- 3. An outstanding service organization with outlets in all capital cities and many of the outlying areas.
- 4. A distribution network which can quarantee immediate despatch of all orders.
- 5. One of Australia's largest inventories of components and consumer

If you are puchasing product in volume, you should contact DSE Wholesale, the full service wholesale supplier.

MICROPHONE


Uni-directional ynamic

A dynamic cardioid microphone ruggedly constructed so it is ideal for bands and PA work. Because of its cardioid polar pattern it is less sensitive to rear noises. Its dual impedance increases its range of uses. Great for the hi-fi buff, audio freak and because of its low price it would also be ideal for schools, colleges, etc. Cat C-1030

Specifications:

- Impedance 600 ohms and 50K ohm
- Freq. response 60-15kHz • Sensitivity -73dB (600
- ohms) & -54dB (50K ohm) 6 metres of cable with
- plug fitted
- Microphone holder i





Universal **Dynamic Mic**

Designed especially for AM and SSB besigned especially for Aivania GSE transceivers. This economical mic is supplied with a 5-wire (4 lead plus shield) 2 metre lead that can be adapted to any transceiver — even ones with electronic switching! Has a nominal 600 ohms impedance, can be re-wired with internal transformer for 50k. Supplied with a standard 4 pin socket. Cat C-1102

Shipping weight: 125g Shipping size: 120 x 105 x 25mm

Shipping weight: 150g Shipping size: 145 x 80 x 50mm

Mounting Clips

Magnetic: Cure a

dangerous dangling microphone with this clip. It attaches to the rear of most hand-held microphones. A strong magnet holds the microphone securely in ace to any ferrous surface.

Shipping weight: 40g Shipping size: 40 x 35 x 20mm



Screw-in: A simpler type clip, can be screwed to any convenient location — the mic is held securely by a spring in the clip. Complete with mounting screws. Cat C-1262

Noise

5000Hz. Cat C-1105

Cancelling Mic

Ideal for the amateur or CB'er. Noise

with a frequency response of 300-

ing is achieved by use of twin out-of-phase inserts. Fitted with a high quality PTT switch and coiled lead. Impedance is 250-600 ohms

Shipping weight: 15 g Shipping size: 50 x 25 x 10mm

Sundowner Hand Held Speaker Mic

Designed especially for the Sundowner UHF Hand Held (D-1807). Allow much greater flexibility for the operator with both speaker and microphone in one compact unit so you can leave the transceiver on your belt, etc. Cat C-1027



Quality Microphone Accessories

Omni-directional Dynamic

This budget priced general purpose dynamic microphone is ideal for recording purposes. It is high impedance to suit most tape recorders.

Specifications:

- 50K ohm impedance
- Freq. response 80-13kHz
 Sensitivity -54dB at 1kHz
- 6 metre cable, mic holder and 6mm plug supplied.

Stereo Electret



Outstanding value stereo microphone! Ideal for those who want quality but don't wish to pay a fortune for it. This is a uni-directional mic with built-in windscreen to protect against noise if used outside. Floating constructions helps eliminate vibrations and touch

Features:

- built-in on/off switch
- frequecy response 50-2000Hz sensitivity 64dB
- S/N ratio 40dB
- output impedance 1K ohm max. (At only 160g it's easy to handle!)
- · Comes complete with stand, 3 metre cord and plugs!

Tie Clasp Electret

Just like the microphones used by interviewers when they want the mic to be inconspicuous, but with this one you also get fantastic pick-up and perfect clarity. The microphone comes complete with tie-clasp and 2 metres cord, terminated with a 3.5mm phone plug. Being a low impedance device it is also ideal for use with your cassette recorder for recording the family or lecture notes, etc. Cat C-1060



Label Microphone Crystal Insert




Save a bundle with the very popular high impedance microphone which has a crystal insert. It is ideal for use with valve amplifiers. Chrome finish, looks smart and the price is so low! Experimenters can use this microphone as it is very rugged. Cat C-1010

Stand and **Boom Clip**



Powerful springs enable this clip to hold virtually any sized microphones securely and yet releasing is a simple two finger operation. Has standard microphone

Dynamic Cassette Mic



from becoming obselete. Cat C-1015

Electret



Making or repairing a microphone? This unit will fit most makes and has a high sensitivity with omnidirectional characteristics. Connection data supplied. Weighs only 1.5 grams! Cat C-1160

How To Describe The NEW Range Of DSE Speakers...

ASTOUNDING!!

Get The New Sound!

Got your new CD? Pity the rest of the system wasn't up to it! Why not replace those old speakers with our new range of high-tech drivers? You won't believe the sound.

We tried all the standard speakers around and found the only way to get the quality we wanted was to have our own manufactured... and here they are!

All are powerful high compliance speakers offering smooth transition right across the frequency range and feature huge magnets, polycarbon cones and specially designed, foam surround free-edge suspension system. The result — superb sound characteristics!



300mm (12")

Coil Impedance: 8 ohms Rated Input Power: 40 Watts Max. Input Power: 80 Watts Free Air Resonance: 25Hz ±5Hz Upper Frequency Limit: 6KHz Sensitivity: 96dB/W ±3dB @ Watt 0.5 metres Magnet Weight: 848g Cat C-2040

250mm (10")

Coil Impedance: 8 ohms Rated Input Power: 40 Watts Max. Input Power: 80 Watts Free Air Resonance: 40Hz +8Hz **Upper Frequency Limit: 6KHz** Sensitivity: 94dB/W ±3dB @ 1 Watt 0.5 metres Magnet Weight: 848g 1 Watt 0.5 metres Cat C-2041

200mm (8")

Coil Impedance: 8 ohms Rated Input Power: 30 Watts Max. Input Power: 60 Watts Free Air Resonance: 40Hz +8Hz Upper Frequency Limit: 8KHz Sensitivity: 92dB/W ±3dB @ 1 Watt 0.5 Metres Magnet Weight: 502g Cat C-2034

162mm (6½")

Coil Impedance: 8 ohms
Rated Input Power: 30 Watts Max. Input Power: 60 Watts Free Air Resonance: 55Hz +11Hz Upper Frequency Limit: 6Hz Sensitivity: 87dB/W ±3dB @ 1 Watt 0.5 metre Magnet Weight: 283g\$ Cat C-2042

25mm (1") **Dome Tweeter**

Coil Impedance: 8 ohms Effective Frequency Range: 2Hz -20KHz Sensitivity: 100dB/W @ 1 Watt 0.5

Magnet Weight: 152g Cat C-2044

Piezo Ceramic

This superb piezo-ceramic tweeter is an ideal replacement tweeter. Handles up to 40 watts continuous. Frequency response from 5kHz to 27kHz! Suits all 8 ohm systems. Can be used with or without crossover.



PCT 2000 Piezo

A high performance tweeter of exceptional quality! Fully enclosed, with removable stand and spring loaded connecter terminals. Cat C-2007

Features: • Handles 75W Impedance 1200 ohms/1KHz & 40 ohms/40KHz • Frequency response 3500Hz to 40000Hz Efficiency 90dB/1W at 1mm

57mm Mini Speaker If it's performance

you want this 57mm mini speaker has it - in fact we found that it offered more performance than speakers up to 75mm in diameter! Norminal impedance of 8 ohms makes it ideal for many purposes, Cat C-2222



10 up \$2.25

Economy Grille

Here's a high impact, 200mm plastic grille that has thousands of uses! If you want to place speakers into the wall or ceiling of your home then this grille

10 up \$2.95

makes an ideal cover. Also ideal on boats and in vehicles. Has four screw hole fitting points. Cat C-2646

Horn Speaker

cover for maximum security

Smaller version of C-2718 speaker,

installations. Plastic body means all-

designed for use inside a horn speaker

weather (under shelter!) operation and horn construction means incredibly high output compared to conventional

speakers. 8 ohm impedance, 10 watts


rating. As above, use with speaker

Crossover Networks

Impedance of 8 ohms and a crossove frequency of approximately 3kHz. The special inductor/capacitor circuit ensures good crossover characteristics. Can be used in your own designs for a 2-way speaker system. Cat C-2512

As used in the Playmaster 3/70L, 3/53L and 3/26L speaker systems. Has 8 ohm impedance. Two inductor network with non-polarised capacitors. Crossover frequencies of 1.5kHz and 5kHz plus high power handling capacity. Cat C-2513

Shipping weight: 418g Shipping size: 210 x 210 x 55mm



Hi Power L-Pad

Ideal for controller higher power speaker placed outside (eg for the BBQ or in a large play room). Can be mounted on a remote panel or in the speaker cabinet. Complete with instructions. Ideal for tweeter control. Cat C-7204

Constant impedance • 15w continuous - 30 peak

• Mono use 8 ohms impedance

Stereo L-Pad

Controls audio level (attenuation 30dB to 0.5dB) while maintaining constant impedance matching between amplifier and remote speakers. Panel or speaker enclosure mounting. Medium power rating into 8 ohms. Complete with instructions. Cat C-7205

2-Way Mini Speakers

rating of 30 watts RMS gives them plenty of punch!

More quality speakers intended for indoor use from Arista. Same heavy duty case and oustanding performance as C-2251 but this one

uses a 100mm honeycomb woofer with a 10oz magnet. With soft dome tweeter and a freq. resp. in the 60Hz - 20KHz range. A power

They're small enough to carry from room to room and you can mount

the quick release bracket (supplied) where you most often use them!

inbuilt siren oscillator). Alternatively use with our L-5115 electronic siren driver

Speaker Box Lining

Reflex Horn

Large 127 x 200mm rectangular horn

mounting bracket, ideal for hanging

output (ie any alarm controller with

under eaves etc for maximum sound

dispersion. Use in conjunction with any alarm controller offering 'speaker'

with huge 15 watts rating. Complete with

easy to handle. Fibre bonding ensures that this cellulose acetate insulation will remain resilient and not fracture or break down due to vibration. Weighs

approximately 300 grams/sq. metre and is 25mm thick by 700m wide recommended density for most speaker usage. Cat C-2662



20m or more \$3.50m

Mini Marine Hi Fi

Amazing sound from these Arista heavy-weights! Designed for use around moisture which makes them ideal for the boat, outdoor patio area (under cover), around the pool... anywhere!

Robust, rust resistant alloy case with recessed captive connectors and metal grille cover. Features 10.2cm polypropylene air suspension voofer, 25mm soft dome tweeter, 8 ohm impedance, freq. resp: 70-20,000Hz and a maximum power rating of 50 watts. Comes with mounting bracket. Cat C-2251

Shipping Size: 270 × 237 × 165mm Compact Size: 115(W) × 185(H) × 112(D)mm!

Cat C-2252

page 69







HF on a Budget Yaesu's New FT747GX

Budget: Yes! Low Performance: No! Yaesu's new FT747GX is designed to give the amateur the best of both worlds

It's probably the lightest 100W HF transceiver ever produced. At just 3.3kg and a tiny 238 imes 93 imes 238mm, that also makes in a great contender for mobile use.

A clear, unobstructed display and control layout make this a real joy to use. Unlike the "super rigs" around today, it has just 15 push button controls - including the on/off switch, and two dual pots for level controls.

All this in an all HF band (160 through 10 including WARC), all mode (FM optional) 100 watt (PEP, AM 25W) powerhouse that makes fht perfect first transceiver for the novice right through to the advanced amateur wanting to pack the most performance into the dollar! Cat D-2930

ALL THIS \$1395

Specifications:

Transmitter -

All amateur bands between 1.5 and 30MHz

LSB, USB (J3E), CW (A1A), AM (A3E) & optional FM (F3E) 100 Watts output (PEP/DC< SSB/CW/FM)

25 Watts carrier output (AM)

Spurious — <-50dB harmonic, <-40dB non-harmonic

SSB Suppression — Carrier <40dB, unwanted sideband <50dB Receiver

100kHz to 29.9999MHz continuous

Conversion: CW,SSB,AM double conversion, FM triple conv. Sensitivity (10dB S+N/N, >1.5MHz) 0.25uF SSB/CW, 1.0uV AM Selectivity (SSB, CW/N, AM/N, -6, -60dB) - 2.2/5kHz

Image rejection — >70dB 1.5 - 30MHz IF rejection — >60dB 1.5 - 30MHz

A worthy successor to the 726 . . .

Yaesu's New 4 Bander FT-736R





6m - 2m - 70cm - 26cmIn one amazing transceiver

Why just dream of talking beyond Earth? With the new Yaesu FT-736R VHF/UHF, you can discover some of the best DX happening — on moonbounce. Tropo. Aurora. Meteor Scatter. Or satellites.

The FT-736R is the most complete, feature-packed rig ever designed for the serious VHF/UHF operator. But you'd expect this of the successor to the legendary FT-726R.

For starters, it comes equipped with SSB, CW & FM operation for 2m and 70cm (430 to 450MHz!) with two additional slots for optional 6m or 23cm modules.

Crossbanding is built in. Satellite tracking (normal and reverse modes) keeps you on target through a transponder. You get 25 Watts output on 2m & 70cm, 10 Watts on 6m and 23cm. 100 memories let you store shifts, frequency, mode, etc in each.

Discover the FT-736R today. But first make sure your shack has plenty of room for exoctic QSL's! Cat D-2920

- All modes on all four VHF/UHF bands 6m, 2m, 70cm, 26cm (with all modules installed)
- Full duplex crossbanding
- Up to 25W output
- Dual VFO's plus 100 memories
- Inbuilt RF Speech Processor, IF shift and IF notch filters, CW and FM wide/narrow IF filters, VOX, Noise Blanker, 3-stage AGC

Add-on modules:

6m Module:

Full 50 to 53.9988MHz coverage with 0.15uV receiver sensitivity (SSB, 13dB S+N/N), 10W transmitter output. Cat D-2921

Complete with 2m and 70cm modules: \$3495

26cm Module:

At last! 1.2 gigs accessible to the average amateur! 1240 to 1300MHz coverage, 10W output, Cat D-2922

Note: The FT-736R and its associated modules are not normal stock lines in most DSE stores. Normally held in one store in each capital city, or available within 3 days from warehouse.

MATEUR-RADI

Here it is: Yaesu's **FT767GX**

All mode all band all singing all dancing all all!

What are you looking for in an amateur transceiver? The absolute very latest technology that is available? Every possible feature to drag that signal in where others cannot... or to make sure yours is the one heard through



the QRM? How about all modes on all amateur bands? Or a continuous coverage triple conversion superhet receives from DC to light (well, almost)? An automatic antenna tuner built in? Die-cast aluminium & ducted cooling giving 30 minutes output at full power? The incredible new FT767GX is all this and more — much, much more. It's the most complete amateur station available anywhere. In any brand. At any price. **Because the FT767 goes where others** complete arrateur station available anywhere. In any brand. At any price, Because the FT767 goes where others cannot. As well as the complete HF transceiver, it is also the complete VHF & UHF transceiver — the 767 covers every amateur band from 160 metres to 70 centimetres!!! That's right — 1.8 to 440MHz in one transceiver. Crossbanding? Now you're really talking — to the world. And because it's the new generation of tansceivers, it's made to suit packet. Yes, the FT767GX is the most expensive transceiver Yaesu have ever produced. But once you've seen it, you'll agree — it's worth every cent! Cat D-2935

Brief Specifications:

Receiver: 100kHz to 29.9999MHz, 50 to 53.999, 144 to 147.999, 430 to 439.999MHz*

Transmitter: All WARC bands to 30MHz, VHF & UHF as above Emission: J3E, A1A, J1B, A3E, F3E

Output: 100W (AM 25W carrier) on HF, 10W (2.5W AM) VHF & UHF Antenna Imp: 20-100 ohms HF (nominal 50 ohms), 50 ohms UHF/VHF Harmonics: <-50dB HF, <-60dB VHF/UHF

Carrier Suppression (SSB): <-40dB.
3rd order IMD (vs single tone, 100WPEP, 14MHz: <-35dB
Image and IF rejection: <70dB
Sensitivity: 0.25uV (SSB/CW/FSK, 1.5-450MHz, 10dB)





The New Generation FT757GX "II"

HF All Mode Computer Aided Transceiver

There's only one thing better than the FT757GX — and that's the amazing FT757GX II! Combining all the finest features of its predecessor with new advances in digital control which allow far greater versatility and operator convenience on ALL modes and ALL hf amateur bands

There's no need for options... it's all built in! AM & FM modes, 600Hz narrow CW filter, iambic keyer, 25kHz marker generator, IF shift & notch filters, triple conversion receiver covers full 0.15 to 30MHz, effective noise blanker and AF speech processor. As well you'll get... Cat D-3492

New digital features -

- 10 memory channels (stores mode & frequency!)
 Improved CAT (computer) interface allows simplified programming and greater control
- Programmable memory scanning
- Auto-resume loop scanning between dual VFOs
 Full duty cycle (100W DC output 100% transmitter duty cycle)
- High performance receiver (>100dB dynamic range in CW/N)

Specifications:

Coverage: TX 10, 12, 15, 17, 20, 30, 80 & 160 metre bands; RX 0.15-30MHz Tuning Steps: 10Hz & 500kHz Emission Types: LSB, USB, CW, AM & FM

Emission Types: LSB, USB, CW, AM & FM
Carrier Suppression: Better than 40dB below peak o/p
Spurious Suppression: Better than 50dB below peak o/p
3rd Order IM Distortion: Better than -35dB below peak o/p (14MHz, 100W)
Rx Sensitivity: (1.5-30MHz; 10dB S+N/N) SSB, CW-W, FSK-0.25uV,
CW-N 0.16uV, AM 1.0uV, FM 0.6uV for 12dB Sinad)

Image Rejection: Better than 70dB



Automatic Antenna Coupler FC757AT

This amazing coupler actually has its own 4 bit microprocessor to allow fast, acccurate automatic impedance matching. Not only that, but it has an automatic SWR meter AND an inbuilt inline RF wattmeter! It remembers which antenna you've selected along with the settings of the matching network so when you go back to that band, everything is done for you: instantly. And if antenna conditions change while you're using it—it adjusts for you Can also be operated manually.



1.2kW... **SOLID STATE!**

Yaesu's new FL-7000 **Linear Amplifier**

The one you've been waiting for: a fully solid state HF linear amplifier with a massive 1200W PEP (SSB) 1200W DC (CW/FSK) input — and that's rated at 30 minutes continuous on SSB! It needs less than 100W drive for full output, with spurious less than -50dB and 3rd order IMD less than -25dB. More than that, it also includes an automatic antenna tuner (range 16 to 150 ohms) so you won't cook anything with a poor match! Perfectly matches the new FT767GX, or the FT757GX, or just about any HF transmitter/transceiver you care to put on it (even those other brands!). Cat D-2549

- Covers all WARC bands to 30MHz
- Size 390 x 1130 x 400mm
- Weight 30kg (also doubles as a great paperweight!)

\$4299



Heavy Duty Power Supply

The FP757HD also suitable for



Note: Limited stocks only held. If out of stock

stores we can order in for you. A 6m version (FT690MkII) is available on indent basis only at

similar price — it too can be ordered through

any DSE store or DSXpress.

R290MkII

Yaesu had a pretty hard act to follow — the FT290R was one of the most popular sets we've ever sold (and one of the best sellers around the world). Here's the successor and what a beauty! The FT290MkII has all the features of the "old" FT2909 — and then some! Cat D-2875

- ALL mode (LSB, USB, CW & FM)
- 2.5W output (switchable to 250mW)
 Standard or NiCad batteries

- . Twin VFO's
- And much, much more!

\$Q49





2M Mobile FT-211RH

Not just one, but two microprocessors to do everything for you except make coffee (they're working on that one!) That's the new FT-270RH mobile 2m. Absolutely the latest word in flexibility and performance — including 45 watts output! With 10 memories, dual VFO's and incredible scanning facilities, you're ready to take on the two meter pile-up: and win! Aparthis is packed into just w power output (45/5W) so it's 140 × 162 × 40mm; small enough to go anywhere! Features and



Tiny on size huge on performance

Yaesu's Hand-Helds

Small enough to fit in the pocket, the glove box, the brief case.. big on features and power. Just $60 \times 150 \times 30$ mm (including battery)! Yet these hand-helds pack all the performance of their monstrous predecessors — and more... Fully microprocessor controlled, 10 memories, repeater splits, scanning (busy/ memory/priority), 6 digit LCD display, up to 5 watts output (with 12V supply)... the amazing features of these mini marvels goes

70 centimetre: FT73

Covers 430 to 440MHz (440 to 450MHz available on special order "indent" basis). 2.0W output from FNB-10 battery supplied. Cat D-3495

2 metre: FT23

Full 144 to 148MHz band coverage. Supplied with FNB-10 NiCad battery giving 2.5W output, plus mini rubber duckie antenna. Optional FNB-11 12V battery available SOON. Cat D-3490

Push Button 70cm FT-709R

All of those who do want al the bells and whistles

you can't go past the FT709R! that the serious UHF'er coul held! For a start, 10 me favourite repeaters to check a longer! Add y for high or low ck (10.8V, 425mAh) power operat for 2.7W out o 12.5V, 500mAh) for 3.5W out, standard cells out) or even NiCads. (The FT-709R operates from 6 to 15V, so the latitude is there!)

• Full 10MHz coverage

 Microprocessor controlled Microprocessor controlled 10 memories, up to 3.7W out

· Complete with soft carry case, rubber duckie antenna

NB: Not supplied

with batteries.



It's like having two transceivers in one...

Yaesu's 2m/70cm FT-2700RH

2 metres and 70 centimetres — in one compact transceiver! The FT-2700RH is excellent value for the increasing number of amateurs who like to transfer from one band to the other. It's as simple to operate as it is enjoyable to listen to! Instead of buying two transceiver, you only need the ONE that offers the two band.s The FT-2700RH is a superbly designed unit with a host of impressive features. Enjoy Yaesu's renowned programmable memory scan. 10 memory channels. Priority scan. Dual independant front ends, local synthesizers, IFs and transmitter RF stages. Full duplex crossbanding— it's more child's play. More and more amateurs are adopting the adage: that 'two bands are better than one'! Cat D-3515

25 watts continuous on both bands

Two 4-bit CPUs for complete control
 Wide angle LCD display

 Includes scanning microphone and mobile mounting bracket.

Amazing amateur value at only...

\$1299

2 position

Coaxial Switch

At last! A really high quality coaxial switch suitable for all HF, VHF and UHF (900MHz) uses. Made by Welz in Japan, it offers the serious amateur better isolation, lower insertion loss and better performance than most other switches on the market. Cat D-5208

Specifications Impedance: 50 ohms Frequency: DC-900MHz Insertion Loss: Less than 0.1dB Isolation: Better than 50dB SWR: Better than 1.15
Power rating: 1kW (Cont) Maximum



Hand-Held Whip Antenna

Flexible 1/2 wave ground independent antenna with BNC fitting to suit UHF CB hand-

As above, 430MHz amateur. Cat D-4335 \$2495

VHF Amateur

Flexible replacement "rubber duck" antenna for 2m hand-helds. Cat D-4330

AMATEUR-RADI

VHF/UHF Universal **Antenna Kit:**

Whip, coax and

No more wondering 'which one to buy?': this one does the lot! And everything you need is supplied:

- · Quality stainless steel 520mm whip, complete with cutting chart, suitable for mid VHF band (about 120MHz)
- 5/16", 26TPI coaxially fed antenna base (intended for UHF work — even better at VHF!) which fits gutter
- gripper base perfectly.

 2 metres UHF quality RG58C/U coaxial cable
- PL-259 UHF connector (as used on most transceivers).

All this makes the perfect solution to your mobile antenna problems, whether they're amateur, UHF CB or commercial radio. Complete kit. Cat D4025

\$4995

Egg Insulators

Small insulator, unbreakable nylon construction. Ideal for maller antenna installations Cat D5300 \$4 25

Medium size - made of the same material, but will handle much larger installations; eg for extra long arrays or guy wires. Cat D-5302

Folded J 2M Vertical

Every amateur has heard of the Slim Jim. Many have made their own! Now there's no need - our J Pole is so low in price you probably couldn't make it (not as well, anyway!) Covers full 2m band with VSWR <1.2:1, power rating 500W. Cat D-4211 \$3695

HF System

A range of HF antennas made for Australian conditions. Just fit the base — and place the whip on according to the band you're on. All whips are approximately 2m long, appropriately loaded, and feature adjustable tuning.

80m Cat D-4310 \$44.95 40m Cat D-4311 \$39.95 20m Cat D-4312 \$34.95

Standard 5/16" 26TPI to suit above whips. Cat D-4313

Novice Course

to enter the hobby of Amateur Radio this is an easy to follow first instruction. Complete with Morse tape which gives you full novice standard, Cat D- 7110

Shipping Weight:250g Shipping size: 280 × 205 × 20mm

RF Balun Contains a large,

quality balun core (50.8 diam.) with a quantity of heavy gauge wire, suitable for up to 1kW. Full instructions supplied Can be used for a number of antenna types up to 30MHz. Can also be used for RFI suppression, from amateur and CB Gear into audio amplifiers. If the speaker leads are wound through the core (as many turns as will fit) the core stops RF energy entering the amplifier in this way.

Shipping Weight: 165g Shipping Size: 140 × 100 × 15mm

RAK **BL-50A** Balun

'T' shape design for use as a centre support for dipoles or yagi antenna. Input 52 ohms balanced Output 52 ohms unbalanced. RF input power 1kW with an insertion loss of less than 1dB. Frequency range entire HF band (1.8 to 30MHz).



Shipping Weight: 139g Shipping Size: 100 × 75 × 25mm

Mounting Clips

Magnetic: Cure a dangerous dangling microphone with this clip. It attaches to the rear of most hand-held microphones. A strong magnet holds the microphone securely in place to any errous surface. Cat C-1260

Shipping Weight: 40g Shipping Size: 40 × 35 × 20mm

Screw-in: A simpler type clip, can be screwed to any convenient location — the mic is held securely by a spring in the clip. Complete with mounting screws. Cat C-1262

Shipping Weight: 15g Shipping Size: $50 \times 25 \times 10$ mm

\$4 50

For the person wishing

7-000-



Key Ideal for practice, just the shot for a youngster wanting to learn Morse. Great

with our Morse Code Oscillator project in the FunWay series!

Yaesu YM24A

Speaker Mic

8 ohm speaker and 2k microphone in one. 6 pin plug suits FT207/FT208. Mounting bracket attached to mic.

Shipping Weight: 125g Shipping Size: 140 × 70 × 80mm



Yaesu YE-7A

600 ohm microphone for general purpose communications use. Large PTT bar for such switching, button on mic matches screw-in mounting bracket (supplied). 4 pin plug also suits most CB's — particularly older style. Cat C-1117 Committee of the second

Shipping Weight: 166g Shipping Size: 160 × 100 × 80mm

Yaesu YM49 speaker Mic

older-style line socket suits FT290,



button plug lock for scanning 7 pin FT690. etc. Also includes matching screw-on dash backet. Cat C-1110



As above, but also includes up/down

Shipping Weight: 250g Shipping Size: 210 × 95 × 60mm



MICROPHONES Universal

Noise Cancelling Mic

Hand-held model where high QRM is a problem. Fitted with 8 pin plug, eliminates or reduces noise by out-ofphase insets. Impedance 500 ohms.

Shipping Weight: 190g Shipping Size: $230 \times 100 \times 75 \text{mm}$

\$4995

Desk Mic

Superbly elegant desk mic to really set off your station. Locking PTT, up-down scanning buttons plus removable base Impedance 500 ohms. Cat C-1114

Shipping Weight: 850g Shipping Size: 240 × 140 × 110mm

\$499

Hand-Held Scan

Suits all Yaesu transceivers with scanning function. 8 pin plug, very easy to hold for long period. Ideal mobile mic. Impedance 500 ohms. Cat C-1116

Shipping Weight: 165g Shipping Size: 213 × 100 × 50mm

The above microphones all suit Yaesu transceivers shown on these pages plus older types with 8 pin plug such as FT-ONE, FT-707, FT-107, FT-480, etc.

Dynamic Mic

Designed especially for AM and SSB transceivers. This economical mic is supplied with a 5-wire (4 lead plus shield) 2 metre lead that can be adapted to any transceiver — even ones with electronic switching! Has a nominal 600 ohms impedance, can be re-wired with internal transformer for 50k. Supplied with a standard 4 pin socket, Cat C-1102

Shipping Weight: 125g Shipping Size: 120 × 105 × 25mm

YD148 Desk Mic

Smart styling, great performance. Dual impedance to suit many rigs. (500 ohms and 50k). Cat C-1118

Shipping Weight: 666g Shipping Size: 285 × 165 × 90mm \$QQ

Noise Cancelling Mic

Ideal for the amateur or CB'er. Noise cancelling is achieved by use of twin out-of-phase inserts. Fitted with a high quality PTT switch and coiled lead. Impedance is 250-600 ohms with a frequency response of 300-5000Hz. Cat C-1105

Shipping Weight: 150g Shipping Size: $145 \times 80 \times 50$ mm

MH-12A2B Speaker Mic

Designed for the FT203, 209, 703 and 709 hand-helds. Allows greater flexibility (eg vehicle operation) with both mic and speaker in one. 3.5/2.5mm plugs. Cat C-1112

Shipping Weight: 130g Shipping Size: $110 \times 100 \times 50$ mm



Bearcat **Scanners**



The World's **Most Exciting** Hobby

Hundreds of thousands of people world wide have been turned on to the fun, the excitement and the challenge of scanning! Why not try it yourself?

Listen to the world - not commercial radio and television stations but the hundreds of groups and organisations that use the air waves for communications. And it's the kind of hobby that needn't cost you the earth!

Easy to start, inexpensive to continue and there's no need for licences, training courses or qualifications. What's more, with the great range of portable scanners you can take your hobby anywhere! Come in and talk to our experienced staff for expert advice - it could be the best thing you've ever done for

Uniden Bearcat 100XL

The Uniden Bearcat 100XL scanner would do any avid radio listener proud! There's hardly anything it won't do — except keep the tinnies cold. Still, it's easier to listen to than the fridge. Featuring: • 16 channels • 9 band coverage Automatic search • Selective scan delay • Automatic lockout • Selectable manual search • Direct channel acces
• Priority channel • Track tuning • Crystal free • Display light • Battery low indicator • Custom antenna.... and that's not all! Comes with 6 NiCad batteries (installed) and a heavy duty carry case which can be clipped onto a belt. The Bearcat 100XL Scanner is heaps more fun than a fridge! Frequency coverage: 66-88MHz, 118-135.975MHz, 136-174MHz, 406-512MHz. Cat D-2813

Optional M-9526 plug pack available for power/charging

Shipping weight: 900g Shipping size: 335 x 255 x 85mm

Uniden Bearcat 50XL

A compact, lightweight Hand-Held Scanner packed with features and sporting famous Uniden reliability! You won't believe these features: • Fully programmable • 10 channels • 10 band coverage • Crystal free • Custom antenna • Automatic lockout • Manual or auto select • Large LCD channel readout • Track tuning • Direct channel acc Plus battery or external DC operation! Comes complete with belt clip and full instruction manual. Frequence coverage: 29-54MHz, 136-174MHz, 406-512MHz. Cat D-2814

Shipping weight: 440g Shipping size: 215 x 125 x 75mm


LIMITED STOCKS

All band, all mode general coverage receiver — FRG-8800



Here it is: the receiver everyone's been waiting for. It's the brilliant FRG-8800 from Yaesu — the world's leading manufacturer of amateur radio equipment. With specifications to more than match its outstanding looks, the FRG-8800 is a worthy successor to the rest of the 'frog' series. But this one has more: much more: 10 memories inbuilt — nothing extra to buy (they even remember the mode and filter!) And digital frequency entry as well as standard knob tuning. Provision for a converter inside the receiver. CAT control capability. And much, much more. Ask for a copy of the free FRG-8800 colour brochure.

- All mode/selectable IF & BW
- Multi scanner
- 8 bit microprocessor
- S/SINPO graphic indicator
- Dual 24-hour clock
- CAT system computer control
 Wide-band VHF option



FRG-8800 HF 150kHz to 30MHz Cat D-2820

Shipping size: 400 x 370 x 210mm

FRV-8800 VHF Frequency FRT-7700 Antenna Converter

Fits right inside case — complete with its own telescopic antenna. Frequency range 118-147MHz. Cat D-2823

Shipping weight: 769g Shipping size: 165 x 65 x 225mm

Coupler

Ensures best performance from all types of antennas. A must if your antenna is not low impedance. Cat D-2843

\$4395



FRG-8800 SW

Shipping weight: 6.6kg Shipping size: 400 x 370 x 210mm

2MHz to 30MHz

Cat D-2821

FRA-7700 Active Antenna Great for flat dwellers! No need for an outside antenna and preamp will pull in stations you didn't think possible!

\$45995

FRG-8800 DC Kit

Allows operation of your FRG-8800 on 12V DC. Great for field operation, monitoring, etc. Cat D-2822

Shipping weight: 108g Shipping size: 120 x 40 x 65mm

Hear more... hear better **Helical Dipole Scanner Antenna**

Now there's no excuse not to hear everything on your scanner - not when you have this scanner antenna. Designed by a scanner expert especially to suit the bandwidth of today's scanner, it featues performance approximately equal to a quarter wave in free space. Covers all major scanner bands — 70 to 174 and 400 to 500MHz, with easy mounting via the eye hook (or if you prefer, can be mounted on mast with 50 or 75mm stainless steel hose clamps). Overall length is 155mm, and it weighs just 1.5kg. Fitted with 3.5m cable, terminated in standard car-radio type coax plug (as used by 99% of scanners). Cat D-4432


Get the most from your scanner

Mobile Scanner Antenna

Get a clearer signal with this bargain priced Mobile Scanner Antenna. covers VHF hi/lo aircraft and UHF band! Just screw it onto your mobile antenna base

Shipping Weight: 90g

Shipping Size: 770 × 15 × 15mm \$4 495



COMMUNICATIO

Yaesu FRG-9600

All Mode VHF/UHF Receiver



To call this receiver impressive would be the understatement of the decade... if not the century! There are more features, more listening capabilities packed into this receiver than would have been dreamed possible just a few short years ago!

The FRG-9600 is a scanning receiver capable of covering the complete 60 to 905MHz VHF/UHF spectrum. But even more than that, the FRG-9600 is all mode — FM, AM, CB, SSB... the lot. At the touch of a button, it opens up an exciting world of communication: FM-wide for standard FM and TV station sound transmissions. FM-Narrow is your passport to the arena of two-way communication emergency services, business, military and amateur radio. Other amateur bands plus aircraft bands are accessible through the AM and SSB modes (SSB covers up to 460MHz).

An impressive array of features

All the controls and functions that make listening a pleasure. Your choice of keypad frequency entry or

tuning dial. Advanced selectable scanning functions which allow a variety of scanning types: busy, clear, audio scan (avoids 'carrier only' channels), specific band scanning, memory scanning... and so much more.

And computer control if you want it!

Full external computer control is possible using Yaesu's CAT (Computer Aided Transceiver) interface. Multiple memory banks, automatic tuning, customised scanning, searching... if your game is serious listening, then this is what you've been looking for!

Outstanding specifications

Take a look at the specifications panel. You'll agree it offers absolutely outstanding performance.

Expensive?

Of course, the FRG-9600 doesn't come cheap. Or does it? Think, for a moment, of all that the FRG-9600 replaces. Everything right there inside one package. In fact, the technology is so advanced that money probably couldn't have bought it until very recently! Cat D-2825

Shipping Weight: 3.7kg Shipping Size: $405 \times 145 \times 250$

Specifications: Frequency: Modes:

60-905MHz (up to 460MHz for SSB) BU-9USMHZ (Up to 46UMHZ for SSS)
FM Narrow (15KHZ BW); FM Wide
(180kHz BW); AM Narrow (2.4kHz
BW); AM Wide (6kHz BW); SSB
(2.4kHz BW)
Triple (FM-N, AM, SSB); Double (FM-

mage rejection:

Sensitivity (typ):

45.754, 1U.7MHz and 466KHz 60-460MHz -50dB typical; 460-905MHz -40dB typical FM-N 0.5uV (for 12dB SINAD); FM-W 1.0uV (for 12dB SINAD); AM-N 1.0uV (for 10dB S+N/N); AM-W 1.5uV (for

W); Single (Optional Video) 45.754, 10.7MHz and 466kHz

10dB S+N/N); SSB 1.0uV (for 15dB S+N/N)

FM-N* 5/10/12.5/25kHz; FM-W Tuning steps:

100kHz; AM-N 100Hz/1kHz; AM-W* 5/10/12.5/25kHz; SSB 100Hz/1kHz. Selected steps show on display

100

Audio output: Voltage:

Memories:

1W (into 8 ohms <10% THD)

DC 12-15V

BEWARE OF IMITATIONS

There is only one Yaesu FRG-9600. Some unscrupulous traders have been passing off foreign models (with a different type number) as the FRG-9600. The genuine FRG-9600 is only available from the factory authorised Yaesu agents in Australia. Dick Smith Electronics.

10 Band Portable Radio

Here's a great little 10 band portable at a fantastic value for money price! At $160 \times 76 \times 28$ mm it's small enough to carry with you to the beach, football, work — anywhere! With AM/FM, 8 shortwave bands built-in antenna, carry cord, slide band selectors and much more! Superb sound reproduction and quality construction makes this the ideal portable. Has phones and DC adaptor sockets and comes with it's own soft carry case. Runs on 3 AA size batteries. Cat D-2834 **Shipping Weight: 572g**

Shortwave:

3. 7.05-7.50MHz

1. 2.30-5.20MHz 5. 11.55-12.05MHz 2. 5.80-6.20MHz 6. 15.05-15.55MHz 7. 17.45-18.05MHz

4. 9.45-9.90MHz

8. 21.45-21.95MHz

Frequency range: MW: 78-108MHz FM: 522-1620kHz





Direction Finder Radio

With AM/FM/CB/SW/SSB

Top value for the avid radio listener - or the boat owner who wants to know just where he is! This quality radio receiver has a built-in radio direction finder to pinpoint your position against AM radio stations. Plus you get 6 bands including all 40 CB channels plus shortwave AND VHF! Operates from either mains or batteries (not included) and can even double as a P amplifier with optional microphone! You also iust one, but two different manuals SW listening guide. Cat D-2832

- AM Broadcast Band
- FM Broadcast Band
- CB Band (26.94-27.45MHz)
- VHF Bands (59-218MHz) Shortwave Bands (3.9-12.5MHz)

Shipping Weight: 3.9kg Shipping Size: $405 \times 170 \times 303$

Air Band VHF Radio & AM/FM

You've probably wondered what goes on, what pilots and air traffic controllers talk to each other about. Wonder no more! This budget aircraft band radio tunes the entire band, so you don't miss a thing. It also covers the normal AM broadcast band too, so you won't miss out there either! Operates from 4 penlight batteries (supplied) with telescopic whip antenna for aircraft band and internal ferrite rod for broadcast band, Cat D-2836

Specifications:

530-1600kHz; and 108-174MHz Ranges:

455kHz and 10.7MHz

Output power: 450mW max

Power source: 6V DC (4 penlight cells) 10 transistors and 7 diodes Circuitry:

22 x 11 x 5cm



Lowest priced SSB CB in Australia?

AM/SSB CB under \$250!



Australia's lowest priced full-feature AM/SSB CB? We're sure you won't find better value With maximum legal power, full 40 channels and the extra range and performance that SSB gives, this is the ideal CB for the truckle, the car driver — even the home base with optional power supply. It's fully approved, fully licensable (not like some "bargain" CB's being flogged around!) Cat D-1713

Features:


- Very simple to operate
 Maximum legal power on AM and SSB
- Fully guaranteed (12 months extended guarantee)
- State-of-the-art circuitry with advanced specifications
 Complete with microphone, mounting hardware and instructions.

Shipping weight: 2kg Shipping size: 345 x 215 x 75mm

DOC Approval No. 2440040

PEARCE-SIMPSON





 Space saving: just 160 x 44 x 122mm
 Full 40 channels
 Maximum legal power
 Built-in noise limiter
 Digital Channel readout and power/strength indicators • Just three controls: so simple!

Shipping weight: 1.8kg Shipping size: 215 x 220 x 80mm

DOC Approval No. 249A0123





3W 3 Channel **Transceiver**

At this price, you can't afford to be without one!

Medium power, medium price but top performer! A new model, exclusive to Dick Smith Electronics, with a multitude of uses. Approved for CB use. Has one CB channel fitted in the channel one position. Other channels left open for your choices Great for fishermen, too: keep in touch (just in case!). Cat D-1106

DOC Approval No. 249A072 Shipping weight: 920g Shipping size: 350 x 95 x 90m

Pocket Com II Walkie Talkie

This is THE transceiver for aspiring James Bonds or Dick Tracys in our community. Full 2-way transmission and a size that fits secretly into your pocket. A great gift for any child. Also ideal for the more serious use: a mother who wants to know what Johnny is doing in the backyard; for construction workers, etc. Buy a few and start a spy ring! Cat D-1101

Shipping weight: 137g Shipping size: 250 x 120 x 30mm



CUB: Deluxe AM

But if you DO want all the bells and whistles, try this one: the CUB from Pearce-Simpson. Full scanning facilities means you don't have to take your eyes off the road when listening for a signal: just push the button and the set scans up or down. And the Channel 9 switch allows instant access to the emergency channel — no matter which channel you're on. Also includes switchable ANL (automatic noise limiter) to reduce ignition and other pulse noise. Unit size is just 130mm wide, 35mm high and 180mm deep perfect for today's compact cars. Cat D-1460 DOC Approval No. 249A0129

- Maximum legal power
- Full 40 channels

DSE 0-1450

- LED readout
- Push-button channel selection Tiny size — fits mini car spacel

hipping weight: 1.7kg Shipping size: 235 x 265 x 60mm **LIMITED STOCKS**



Compact Pro Series CB

Professional quality 40 channel CB from Uniden — the PRO510e! Compact, stylish design with a wealth of truly advanced features including ANL (automatic noise limiter), squelch control to help eliminate background noise, S/RF meter, large LED channel display... the lot!

Measuring just 115(W) × 35(H) × 167(D)mm it fits easily in most modern vehicles and looks great against contemporary dashboard designs. Of course, the PRO510e comes with PTT mic. all

mounting hardware and the reliability you



The All NEW Series 2 Sundowner



Upholding its reputation as the best value UHF transceiver on the market today is the new Series 2 Sundowner from Uniden! Much more than your average mobile with many of the most advanced features available.

All 40 channels are available with features like duplex switch which allows operation via a repeater station, squelch for a clear signal, TX/RX indicators, S/RF indicator, tone squelch switch and more. Beautifully constructed to give years of trouble free service it's the obvious choice for the serious CBer.

Specifications: Channels: 40 Frequency Range: 476.425MHz to 477.400MHz Repeater use (Ch1 to Ch8, TX only) 477.175MHz to 477.350MHz **Carrier Power: 5 Watts Current Drain (Trans.): Current Drain at maximum** output (receiver): 800mA Jacks & Connectors: Mic, Extn Speaker, DC Power Size: 150(W) × 50(H) × 190(D)mm



Get The Range! AM SSB CB

Ideal as a mobile or as a base station! Superb quality and value make the AX144 from Uniden one of the best value AM SSB CBs around. Of course, it has the Uniden quality and reliability built-in, but it also has much more.

All 40 channels on AM, USB & LSB, maximum legal power — PLUS the extra range SSB offers! With PA capability, automatic gain control, effective

squelch and automatic noise limiter, LED mode indicators, emergency Ch9 switch, etc, etc. Fully approved and fully

Specifications: Channels: 40 AM, LSB & USB Frequency Range: 26.956 to 27.405MHz Transmitter Output Power: AM. 4 Watts

SSB. 12 Watts PEP Sensitivity (Receiver): SSB: Better than .25uV for 10dB (S+N)/N at >.5W of audio output

AM: Better than .5uV for 10dB (S+N)/N at >.5W of audio output

UHF HAND-HELD SEE PAGE 79.

Accessories Lightweight Spring

Designed to suit standard loaded ¼ wave mobile whips, to give the type of flexibility required in today's low car parks!



Male Thread Antenna Adaptor

USA %" x 24 tpi male thread to Australian female socket. Used for connecting USA %" x 24 tpi base with Scalar or similar antennas. Cat D-4505



Female Thread Antenna Adaptor

The standard Australian Female thread to 9.5mm x 24 tpi female, used for connecting Scalar or similar base to any of our antenna or accessories with 9.5mm x 24 bei avenuing cat 0.4504 x 24 tpi mounting. Cat D-4504



Boot Mount

Stainless steel boot/bonnet mount grips around lip o boot with non-scratch bumpers to protect duco. Ideal for company cars! Suits most antenna types (not the big'uns) Cat D-4515 \$2095



Magna-base Universal Moun

A quality magnetic base - ideal for the company car where holes aren't allowed! Complete with 2m coax and PL-259 plug. Standard thread suits most antennas. Cat D-4514




SO-239 Antenna Base

Coaxial base with integral SO-239 socket for antennas with PL-259 type bases. Waterproof construction (no problem leaving antenna off). Cat D-4035



Quick Disconnect

Enables you to remove your antenna from its mount with an easy press and twist.
Saves your antenna being stolen. \$1295



Gutter Mount

Heavy duty gutter mount fits most cars/ rucks/vans etc with roof gutters. Double Allen Screw adjustment for positive locking, angle also variable. Allen Key supplied. Cat D-5100



Light Duty Antenna Base

Standard 5/6in 26TPI threaded mount in black ABS base. Suits ¼ wave and smaller CB antennas or small VHF whips. Mounting plate includes solder lugs for coax connection. Cat D-4056



Coax Fed Base

Similar to above base but designed specifically for VHF/UHF use with minimum loss. Coax cable enters directly into bottom of mount and terminates on antenna thread. Waterproof construction. Cat D-4516



Folding Snap Down

Allows CB and similar antennas to be Allows CB and similar antennas to be folded down in car parks, garages, etc, without removal. Simply lift and fold over. Male and female 5/16" threads, electrically becomes part of antenna (SWR antenna after fitting). Cat D-4506



RF Signaliser

Inserts in antenna lead to give from -25dB to zero to +20dB gain. The gain lifts signals out of the mud while the cut stops them bending

your needle. Switches automatically on transmit. Needs 12V DC 35mA.

\$6995

Car Radio/CB Antenna Splitter

have to? Use your normal CB antenna for your car radio too: Splitter box allows both to be used simultaneously. You can even transmit on the CB without blasting your car radio's input stage to bits! Cat A-7455

695

3-way Antenna

If you have more than one antenna or use more than one rig then this switch will save you swapping by hand. Handles 50 watts at 30MHz: ideal for base or

Remote **Communications** Speaker

Great for the car, home - in fact anywhere you need an extension speaker for your transceiver or receiver. 8 ohms impedance, supplied with cable and standard 3.5mm audio plug. Because of the larger (10cm) diam. speaker, you'll probably get much clearer sound.

Beat Corrosion!!

The amazing Cortec 101 corrosion inhibitor protects your valuable equipment. Simply slip the Cortec 101 into your electronic devices and an invisible vapour beats the hell outa those nasty little rust bugs. Lasts up to two years!! Cat D-1300



Xtals for Hand-Helds

Standard transmit/receive pairs for the popular 27MHz marine channels. Simply plug into the hand-held (also suit older style in-dash transceivers).

27.550 D-6055 27.910 D-6091 27.620 D-6062 27 940 D-6094 27.860 D-6086 27.960 D-6096 27.880 D-6088 27.980 D-6098

27.900 D-6090

Pair

PEARCE SIMPSON


A truly advanced 12 Channel (10 fitted) marine transceiver! Advanced circuitry, advanced design, advanced ease o operation. The Sea Simba won't leave you floundering! Sea Simba... sounds like it'll get up and dance. With these features nothing would be a surprise! For all normal boat-toboat and boat-to-shore communications. You get all 27MHz marine channels, PTT mic, large LED channel indicator, ANL switch, PA, LED level indicators, squelch control, mic gain control, RF gain control, ext. and PA jacks, wiring harness and in-line fuse and mounting bracket with special design quick release knobs. Cat D-1718

Specifications:

Power Output: 4 watts max. Frequency: 10 channels in the 27MHz band Audio output: 2.5W max. @ 8 ohms Squelch range: 1mV Antenna: Nominal 50 ohms impedance

Dimensions: 146 x 190 x 51mm

'Sea Simba' 12 Channel **AM Marine Transceiver**



Shipping weight: 1.5kg Shipping size: 265 x 250 x 85mm

90 Channel VHE

Seaphone!



The MC724 has to be one of the most advanced VHF Marine Transceivers available! Superb design and quality features from Uniden.. Just Look!

- All Australian & International channels
- Special 'Watch Mode' lets you automatically monitor any channel while you're on another. (Ideal for emergency channel)
 • Programmable scanning
- Instant Ch 16 (emergency channel) selection Keypad channel selection
- Scans telephone channels
- With memory, reversible front panel, direct access to weather channels, Intercom/PA facility and morel

Specifications:

Channels — Transmit: 55

Receive: 90 Frequency Range — 156 to 158MHz trans. 156 to 163MHz receive. Standby Drain — 1.2A at rated audio output: 0.6A squelched. Transmit Drain - 4.5A at 25W output: 1A at 1W output

Power Output - 25 or 1 watt

 20dB quieting: -117dBm Sensitivity

12dB sinad: -114dBm

- 1W/25W, Intl/USA, Instant Ch16, watch, hail, scan, man. select, memory **Switches** backup. Cat D-1719

\$649

55 Channel VHF Marine Radiotelephone

Another classic transceiver from Uniden — the MC610. Economical yet packed with features including emergency Ch16 selector, large LED display, 1W/25W power saving selector, Seaphone capability, all 55 international frequencies, universal mounting bracket and more!

Channels — 55 transmit/receive

Frequency Range — 156 to 158 transmit 156 to 163 receive

Power Output — 25/1W selectable

Receiver Sensitivity — 0.35uV for 12dB Sinad

0.50uV for 20dB S/N - 185 (W) x 245 (L) x 58mm (H)



Uniden Barracuda AM/ SSB Marine Transceiver

Trust Uniden and DSE to bring you state-of-the-art equipment at this fantastic low price! The Barracuda gives you 10 AM and 10 USB channels including the one-touch Emergency Channel 88 switch. Sensible design means that all controls

are conveniently placed and easy to use. With PTT mic., large positive grip channel selector, Ch88/TX/RX indicator, signal/power meter,

switchable PA, clarifier, gain control and more! A special feature of this amazing transceiver is the Dual Watch Button which gives emergency channel 88 priority over main channel!

Specifications:

Power Output: AM — 4 watts SSB — 12 watts, P.E.P.

PA - 3 watts

Frequency range: 27.680-27.980MHz Output impedance: 52 ohms unbalanced

Frequency response: 350-2500Hz Cat D-1714

Shipping weight: 2.26kg Shipping size: 365 x 225 x 100mm

Mobile CB Antennas


- 1. 27MHz Gutter Grip Antenna. Simply clips onto the rain gutter of most vehicles. Features no hole installation and can be installed or removed without tools. Antenna has centre loading coil to increase effective antenna length. Complete with lead and PL-259 plug. Cat D-4411
- 2. 27MHz Magnet Base Antenna. Centre loaded stainless steel construction with heavy magnetic base and 3.3m coax cable with PL-259 plug. Cat D-4635
- 3. Mini Mini Whip. If you thought the above one was small... just 33cm long! Helically wound, extremely flexible. Standard 5/16" thread, suits 5/16" base (not \$15.95 supplied), Cat D-4635
- 4. Bush Bandit Adjustable Helical. Another one from Mobile One! Toploaded helical with fully adjustable top stud. Great for use as a spear, too. Standard thread, mount not supplied. Cat D-4420
- **5. Mini Whip.** Just 1 metre long with really great performance. Less wind resistance, less danger of being hit by low flying aircraft. Standard thread, mount not included. Cat D-4072
- 6. Helical Whip and Base. Our most popular CB antenna. 1.5m long, complete with coax cable and special base. Cat D-4076 \$29.95
- 60. Whip only for above system. Cat D-4074 \$12.95 7. 183cm Whip, Super Heavy Duty. Just right for 4WD's vans etc. – or anyone really serious about CB! Heavy duty unbreakable mounting base unit

and massive spring, complete with PL-259 coax lead. Requires 13mm mounting hole — in something real solid! Cat D-4078

Base CB Antenna - 27MHz

8. 3/4 Wavelength Vertical.

Brand new design for 27MHz base stations. Very easy to erect, and very easy to SWR in. Not just for CB—also ideal for surf clubs, boating clubs, etc. And easily adapted to 28MHz for amateur. Cat D-4427



3 Channel Safety **Transceiver**

Our most popular hand-held

Nice and small for the bushwalker. rock-hopper, fisherman or hiker to keep in the back-pack: just in case! Fitted with bushwalking frequency of 27.620, two other channels left open for your choice of crystals (take about ten seconds to fit!) Not normally used on marine band, but in an emergency vou can use

anything! Keep one in the tackle box! Cat D-1102

DOC Approval No 242H0108



Medium power, medium price but top performer! A new model, exclusive to Dick Smith Electronics, with a multitude of uses. Approved for CB use. comes with one CB channel fitted. Other channels left open for your choices. Great for fishermen, too: keep in touch (just in case!). Comes with one CB channel fitted.

DOC Approval No: 249A072

6 Channel Marine

At this low price anyone on the water can have the security of a quality transceiver! This high power hand-held has all the power and performance of a fixed model. With maximum legal power and fitted with 27MHz marine frequencies it's ideal for the small boat owner and weekend fisherman. Cat D-1126

- 27.880MHz crystals (5 channels left open for crystals of your choice).
- External power jack
 Huge 5 watt power
- Signal/battery meter
- High/Low power switch
 High/Low mic. gain
- On/Off/Volume, channel select, PTT, squelch switches

PEARCE-SIMPSON





Don't leave shore without one!

A top quality high power handheld from Uniden: the world's largest manfacturer of 27MHz equipment. All the power and performance of a fixed transceiver - in a transceiver you can take home with you. (It won't be pinched from your boat!)Maximum legal power, and all 6 channels fitted with 27MHz marine frequencies. Nothing more to buy! And you can connect a boat antenna and power for maximum performance if your wish: external antenna and power sockets fitted. DOC Approval No: 242M0172. Also approved for

CB use (DOC Approval No. 2494022 with

crystals fitted). Cat D-1125

appropriate CB



\$139 \$149

Mobile CB Antennas — UHF

1. 2.5dBd Gain

End fed half-wave base loaded whip for UHF mobile use. Ground independent type, complete with base loading coil with integral mounting hardware. 1MHz bandwidth with SWR 1.5:1 or better. Needs 11mm mounting hole, antenna height (inc base from mounting plane) 32cm. Cat D-4020 \$32.95 (inc base from mounting plane) 32cm. Cat D-4020

2. 4.5dBd Gain

Colinear UHF antenna with 1/4 plug 5/8 wave for outstanding performance in such a short antenna: just 60cm long. Standard thread, suits any standard UHF base (not inc.) Cat D-4013 \$14.95

3 AdR Gain

When it's real performance you want, you won't beat this one: a huge 6dB gain means you're really going to get heard! this ground independent design includes a mounting base and UHF quality coax it's ready to mount. Needs 9mm mounting hole. Antenna height (inc. base, from mounting plane) 94cm. Cat D-4015 \$49.95

Base Antenna

Colinear base station antenna with omnidirectional characteristics. Ground independent construction, terminated in SO-239 socket. 2.4 metres high, needs only saddle clamp to mount to mast. cat D-4011 \$49.95

Marine Antennas

27MHz Marine Helical

A whip antenna and base suitable for virtually all craft — wood, ferro, glass, cement, etc. It doesn't require the normal "ground plane" as it has its own simulated ground plane. Also supplied with mounting base, cables and PL-259 connector. Cat D-4070

VHF Marine Whip

Fibreglass marine antenna to suit international VHF Marine Canal (156-164MHz). Supply Constitution of VHF-grade Canal Supply Canal C VHF-grade cox. of VHF ros the traperfectly. Over VI

\$7095

Portable Mobile Versatile... Two in One!

A new direction in AM CBs from Uniden -the astounding PRO310e! Not just a mini hand held transceiver with clip on battery pack and DC car adaptor but it also doubles as a mobile.

That's right, the PRO310e has all 40 channels (including instant select Ch 9), Up/ Down electronic channel selection, HI/LOW switch, portable antenna, built in mic, snapon battery pack, squelch and LED station readout — all in a compact unit that fits easily in the hand!

But that's not all! Included is magnetic antenna base and car adaptor so it's equally at home as a mobile.

And the lot comes in a handy vinyl



Sundowner **UHF Hand-**Held

\$18**9**

Go-anywhere action on UHF CB: that's the Sundowner Hand-Held. All 40 channels fitted with very healthy 1.5W output (switchable to 0.15W to save battery). It's supplied complete with 10.8V NiCad battery (recharge also inc) and whip antenna — so you don't need anything else to start talking! Hand strap and belt clip supplied (use belt clip with optional base station with suitable power supply and external antenna.

> Shipping weight: 975g Shipping size: 255 x 150 x 90mm

ANTENNAS

Deluxe 3 Band Indoor

Ideal for strong reception areas, you'll save heaps on complex outside systems with this quality UHF, FM, VHF indoor antenna. Colour, black and white and stereo, nothing's a worry for this one. Installed in seconds for the perfect picture. Cat L-4005

Shipping weight: 570g Shipping size: 210 x 135 x 190mm

\$3495



Economy Indoor

If you're lucky enough to live in a strong signal area, you'll probably get by with one of these spiral antennas, even with colour. Don't expect miracles if you're out of sight of the transmitter, (it is quite probable you will require an outside antenna). Cat L-4010

Shipping weight: 1.5kg Shipping size: 1000 x 200 x 100mm



Good Ol' Rabbit Ears...

When an outdoor antenna isn't possible or connecting a second TV set is too much trouble, count on the good old rabbit ears... the indoor antenna that sits on your TV set. Delivers great picture quality. Easy to set up: connect 300 ohm cable to back of set, adjust 'V' antennae for precise signal. Extending telescopic antennae fine tunes reception on individual channels.



Shipping weight: Shipping size: 222g 270 x 108 x 47mm

Indoor Ribbon TV/FM Antenna

A simple flexible dipole antenna suitable for both FM and TV reception. It is best suited to primary reception areas where it is unnecessary for a full scale outside system. It is ideal for use in situations where space is at a premium. Simply connect to your terminals, find the best reception position and then secure with thumb tacks or adhesive. Cat L-4060

• 300 ohms impedance

Shipping Weight: 50g Shipping Size: 170 imes 140 imes 20mm



Band 4 UHF

With Reflector

Get good VHF reception but having trouble with SBS? Our band 4 VHF antenna solves the problem. Can easily be coupled with your existing antenna. Reflector helps eliminate ghosting and with the corrosion resistant finish you'll get years of service. Cat L-4082



Budget Band 5

With Reflector

If you're lucky enough to be in a good reception area then this is the antenna for you! Quality corrosion resistant UHF band 5 antenna with reflector to help eliminate ghosting. It's a great money saver too!



Deluxe Band 4 & 5 UHF

Ideal if you live close to a signal source! Uses 'Butterfly' elements for much greater gain and anti-ghosting. Use it alone or couple it with our superb Ghostbuster (L-5058) antenna for the best of both worlds. Gold anodised finish. Cat L-4084



Metropolitan High Gain V.H.F. This antenna has proven to be our

biggest seller. Extremely popular in the metropolitan areas and near fringe areas, because it has been designed to give maximum gain on channels 2, 7, 9 & 10. Complete with mast clamps, suits twin lead with its 300 ohms impedance. Use a balun if you want to use 75 ohms coax cable with this antenna. Cat L-4022

Shipping weight: 2kg Shipping size: 2120 x 200 x 100mm

\$6995



Ideal For Fringe Areas...

Top Performing VHF/UHF

Superb high gain antenna with reflector that's just the thing for fringe area reception. Designed for UHF/VHF so you'll save money and the hassle of two antenna installations! Highest quality, construction and Australian design. Cat L-4051



Take It Anywhere...

Combined UHF/VHF

For Caravan, Boat, Camper, Etc.

You can even use it at home where the signal levels are reasonable! With optional mounting hardware it's perfect for the van, boat, etc. Suits horizontal or vertical mounting and with the new anti-corrosion finish it'll perform this holiday, and the next, and the...! Cat L-4055



Combined UHF/ VHF Antenna

Why put up two antennas when one antenna will give you both UHF and VHF signals? One of our most popular antennas. Has the latest 14 element design which needs just one feed line. Suits 300 ohm ribbon. Easy to install on existing mast. Comes complete with mast clamp. Great value for dual purpose antennal Cat. L-420

Shipping weight: 2kg Shipping size: 2340 x 180 x 100mm



The NEW Ghostbuster... VHF Antenna

Superb anti-ghosting antenna for areas where ghosting is a problem. Can be coupled with L-4084 for the best reception on both UHF & VHF. Blue powder coating finish and sturdy plastic insulators for long long life! Cat L-4058

3 YEAR GUARANTEE

UHF/VHF Down Converter

Like to get Channel 28 on that old set? Here's what you'll need! Our new UHF/VHF Down Converter is great value and saves heaps on buying a new set. With adjustable channels 21-69 it tunes in perfectly. Ideal for suburbs with local area translators. Comes complete with power supply and full instructions! Cat L-4473



Gutter Mount

Allows L-4055 Go-Anywhere antenna to go anywhere — along the gutter! Clamp arrangement holds antenna firm. Ideal for flats, etc. where larger installation not allowed. Cat L-4056

\$595

Caravan/Utility Bracket

Along with above L-4065 mounts the L-4055 Go-Anywhere antenna to your caravan, camper, RV, etc. Cat L-4057

\$395

TV Mast Pipe

2.4m length of 27.5mm diam. heavily galvanised steel pipe, ideal for use as a TV antenna mast. Use in conjunction with any of the standoffs or supports on these pages. Cat L-4156

Shipping Weight: 1kg Shipping Size: (road only) 2400 × 80 × 235mm

4m Mast

2 part telescopic mast, extending to approx. 4.5m. Bolt tightens onto top section allowing any height selection. Top of mast same diameter as above pipe.

\$**29**95

FM Radio Antenna

3 element dipole antenna specifically cut to suit 88 to 108MHz FM radio band. Very simple to erect, uses 300 ohm receivers (some may need balun). Top performance from a very economical antenna. Cat L-4064



Easy Outdoor Antenna Connection

Saves heaps of time and trouble! This 12 metre coax cable comes complete with outdoor Balun — already fitted. Just connects straight onto your antenna

Shipping weight: 450g Cat L-4466 Shipping size: 160 x 200 x 40mm

\$2495



Yes! All Antenna Signal TV Antennas from Dick Smith Electronics carry a 3 year guarantee on workmanship and

* Normal usage and wear & tear only, accidental damage and damage due to external causes excluded.

Barge-board Mount

Designed to mount any TV antenna from a vertical surface, barge-board, wall, chimney, etc. 139cm long. (Hot dipped galvanised to prevent corrosion.)

Shipping Weight: 85g Shipping Size: 1450 × 90 × 70mm

28cm Wallmount


28cm long, can be used for wall or barge mounting of vertical masts up to 5cm diameter. Complete with saddle clamp assembly, Cat L-4152

Shipping Weight: 570g Shipping Size: $300 \times 135 \times 70$ mm



69cm Wall Mount

69cm long, used for mounting vertical mast sections up to 5cm in diameter. Complete with saddle clamp assembly.



Shipping weight: 750g Shipping size: 710 x 200 x 30mm

Chimney Mount

This is a double arm, single strap, easy to mount unit. Complete mast mount assembly. Cat L-4154


Shipping weight: 161g Shipping size: 320 x 80 x 70mm



Vertical Stand Off

Here's a great idea! Changes mast plane to reverse polarity. Designed for those areas where standard antennas can't normally be used. Yes, it's galvanised so the rust bugs can't get to it! Cat L-4170

Shipping weight: 190g Shipping size: 390 x 50 x 40mm



Saddle Clamp

Beats using fence wire and old pieces of string! Designed for holding two pieces at right angles: eg. mast pipe onto mount, or antenna onto mast pipe. U and V clamp combined in one unit. Cat L-4165

Shipping weight: 44g Shipping size: 80 x 55 x 5mm



TV Game Balun

Makes it easy to use your colour TV game with a black and white set. Spade lugs make connections simple, no soldering required. Excellent value, Cat L-4454



Shipping weight: 13g Shipping size: 110 x 80 x 10mm

10 up \$2.66

TV Game Computer Switch Box/Balun



Indoor/Outdoor Balun

Successully matches 75 ohm coaxial cable to the 300 ohm ribbon terminals on your TV. FM tuner or antenna. Weather resistant for either outdoor or indoor use. Comes complete with coaxial plug connector and cover and can be installed in minutes

Shipping weight: 2.8kg Shipping size: 200 x 25 x 20m



Universal Balun

The universal balun - has 300 ohm screw terminals and 75 ohm coaxial plug - can be used either way round. Ideal for the person requiring a balun but not really knowing which type! Cat L-4456

Shipping weight: 15g Shipping size: 110 x 80 x 20mm

10 up \$2.66



Indoor UHF/VHF Diplexer

Many TV sets and videos have only one antenna input: tough luck if you're running VHF and UHF antennas! Now there's a solution — the Diplexer, Accepts lead-ins (75 ohm) from both antennas and combines them without the normal losses associated with couplers used at UHF. Then you can run one lead-in to the TV/Video.



ARDWAR

Crook Pic? Fix it quick! Mast Head Amplifier

Poor signal? Lousy picture? We can't help you with the rubbish the TV stations put out, but we might be able to help fix a poor signal! The DSE Masthead can make an unbelivable difference: it amplifies the signal right at the antenna - where there's less noise, giving you more comph and allowing a longer lead in, too. Two piece unit includes amplifier box and power supply (240V operated — draws negligible current) Cat 1-4200

Shipping weight: 356g Shipping size: 150 \times 80 \times 120mm

40-400MHz bandwidth (covers VHF TV and FM radio)
24dB gain

To ohms input and output (suis coax)
 Zero gain at 27MHz (for CB interference suppression)

• Includes power supply

Indoor 75 ohm

Similar to L-4474, but for two sets only. Covers 50-890MHz, Isolation: 25dB. Insertion loss: 3.5dB. Cat L-4472

Shipping weight: 50g ng size: 100 x 65 x 30mm

Splitter



Standoff Assembly

Complete with standoff and strap assembly. Used for standing cable off masts sections, 8.8cm long, Holds ribbon or coax. Cat L-4512



Nail-in Cable Clamps Ribbon Type

Suitable for running flat ribbon cables on walls, skirting boards, etc. Gives a neat professional job. Cat L-4514



Coax Type

As ribbon type but suitable for coaxial

Coax Clamp Bargain Pack

In a pack of 25, about the right number for a proper installation. And look how much you save! Cat L-4516

Shipping weight: 25.5g Shipping size: 145 × 75 × 15mm

4-way Splitter for **300 ohm Ribbon**

Handles either colour or black and white TV with absolute minimum loss of signal strength even when all sets are operating at the same time. Compact plastic case can be mounted at any convenient location near antenna lead. 300 ohms input/output impedance

NOTE: If all inputs are not being used at once, a 330 ohm resistor should be placed across the unused outputs. Covers 50-890MHz. Cat L-4220

Shipping weight: 70g Shipping size: 70 × 110 × 35mm

7 43 10 up \$6.53

2-way 300 ohm Splitter


As 4-way splitter but 2 sets only. Covers 50-890MHz. Cat L-4218

\$495 10 up \$3.78

Shipping weight: 70g Shipping size: $60 \times 35 \times 70$ mm



2-way Coax Splitter



Shipping size: 40 × 50 × 110

Shipping weight: 23g \$250 Shipping size: 10 up \$2.65

In-Line Amp/VCR **Booster**

The output signal from video often too low for opting when trying to re solution: just con the signal level to give viewing. And the bes into your existing sys boosting signal on lo (our M-9525 is ideal)

Made in Australia for DSE by



Giant Handbook of Electrical Circuits

Baymond A. Collins — 880 pages Giant isn't the word: it's a whopping 880 pages! With 60 chapters covering everything from crystal sets to computer circuitry, you're sure to

find what you want here! Cat B-1780 Size: 210 × 130mm



Chris Bowick - 176 pages

For the person with design experience, experts in the field of rf circuit design or engineers needing a good reference manual. Gives complete design procedures for multipole Butterworth, Chebyshev

and Bessel filters, examines Q, bandwidth and coupling resonant circuits and more! Cat B-1150

Size: 210 × 210mm

\$**30**95



Compact Disc Player

Maintenance & Repair

G. McComb & John Cook - 245 pages

Everything you wanted to know about... but didn't know who to ask. Bargain

Everything you ever wanted to know about everything you ever wanted to know about. DSE

> If you own, or are thinking about purchasing a CD and you're good with your hands, you'll find this book a gem. How CD players work, how to install them, simple maintenance, CD first aid, troubleshooting, CD reference guide, specs on a broad range of players and much more! Cat B-1892

Size: 190 × 240mm

DSE's OWN "HOW TO...



Basic Electronics Theory

Delton T. Thorn — 666 pages With projects and experiments. Starts with very basic principles and ends

with computers - with just about all aspects of electronics in between. Ideal reference work for tech. school students, etc. Cat B-1615 Size: 210 × 130mm

\$2995

Laser Experiments

Wow! The future is yours today. This amazing book is a comprehensive guide to building

your own laser. It takes you from basic physics, through to actual laser experiments Cat B-1860

Size: 210 × 130mm

\$74 95



priced data sheets and booklets by DSE's own technical staff.

This booklet explains how to install a burglar alarm and protect your property whilst

you still have some property to protect! Cat B-6000

\$4 95



How to install your How to install your own Burglar Alarm own TV/FM Aerial

Save on costly fees, understand what is going on and do-ityourself. Cat B-6010

50¢



Laser Technology

Hrand M. Muncheryan - 298 pages The principles and practice of laser technology. The ideal reference or trainer for hobbyist, technician or anyone interested in

the many fascinating applications of laser technology. Covers everything from scientific applications to industrial medical and educational uses. Cat B-1861

Size: 210 × 135mm \$4 095

Databook

Complete listing of all COS/MOS, HS-C2MOS and 74HC00 series

IC's. Cat B-3632



How to deal with CB Interference

Enjoy your CB radio but stay friendly with neighbours. Stop TVI before it starts! Cat B-6025

50¢



How to make **Printed Circuits**

Save a fortune by making and even designing your own PCBs experience required. Cat B-6005

35¢




Electronic Projects for Photographers

Walt Bregach — 243 pages

With this exceptional guide, you'll enter a whole new world of photography. Amateurs will learn new facets of the art they never thought of and even

professionals can pick up a trick or two. Cat B-1740

Size: 235 × 135mm



Level II Radio and **Electronics** Handbook

Ian Ridpath

Over 150 pages covering advanced electronic theory up to the level equivalent to most technicians! Presented in a clear and concise manner as in a classroom situation. Covers areas such as single phase power supplies, single sideband modulation, digital circuits logic and boolean algebra and much more! Cat B-2312

Size: 216 × 153mm



VHF Listening Guide

radio and a handy frequency chart, listening frequencies from 57 through to 174MHz

100

Cat B-6015



NiCad Cells and **Batteries**

7 pages Handy reference guide to charge, discharge, voltage drain, temperature and life characteristics. Cat B-6040




Electronics: A Practical Introduction

B. Brown and P. Carr - 100 pages With this handy study guide you'll become a regular bright spark on the subject of electronics. Learn the theoretical and practical aspects of current electrical measurement, power supplies, amplifiers

linear and digital circuits transistors and much more. Used as a school and college textbook. Cat B-3005

Size: 245 × 135mm



Electronics Math



Dick Smith

Inside Story on Cassettes

DSE — 11 pages

Covers eveything from choosing a recorder and cassettes to maintenance and recording hints. A MUST if you do any recording on cassettes! Cat B-6035

50°



How to Beat the Buralar

Bruce Stannard — 128 pages Not just electronics and alarms, it also delves into the crim's mind so

vou're ready to fight hack! A must for every person with property to protect.



\$895

Cat B-1040

The Ion Controversy

Dr. Charles Wallach - 128 pages Why do thunderstorms, waterfalls and even your morning shower leave you so refreshed? Why does air-conditioning affect some people so badly? This fascinating book

outlines the history and more recent Cat B-9000

Size: 172 X 110mm



Active-Filter Cookbook

Don Lancaster - 240 pages Everything about active-filters. From how to build an active filter, the many types available, and the one to suit your needs, etc... all of practical

interest to the hobbyist and Cat B-1250 Size: 215 × 135mm

\$7095

The Automotive **Security System** Desian Handbook

UTOMOTIVE

J. Daniel Gifford — 227 pages

This book is an in depth look at designing, building and installing a variety of vehicle security systems. Cat B-1050



Electronics for Model Railways

Ken Stone - 74 pages Now railway modellers can achieve a great degree of realism on their layouts. Level crossing flashing unit,

scale fluorescen lamps, street signs. Devices Cat B-3633


Size: 275 X



Encyclopedia of Electronic Circuits

Rudolf F. Graf - 750 pages This comprehensive reference book is the A-Z of electronic circuits: from alarms to zero crossing detectors it's all there. It will save you valuable time searching for a particular circuit, plus eliminates all quess work in deciding whether 'that' circuit will meet your requirements.

Over 750 pages needed circuit schematics. Cat B-1760 Size: 235 × 184mm



TTL Cookbook

Don Lancaster - 335 pages A complete guide to the understanding and use of Transistor Logic (TTL) integrated circuits — the basics of TTL are given, what it is, how to power it and so on! Also contains a catalogue of TTL devices, giving TIL Cookbook

physical and electrical specs. Cat R-1246 Size: 215 X

Introductory **Electronics**

An introductory text for students and enthusiasts. Starting with basic electronic theory. Well defined

chapters and you through to constructing electrical circuits Cat B-3635

\$4 295



Starting in TTL

Colin Mitchell - 74 pages The best way to learn about digital electronics is by understanding TTLs. And this excellent publication is the perfect introduction to the subject. Over 70 pages containing 22 experiments, information,

diagrams and instruction on how to build a trainer Cat B-3629 Size: 275 × 205mm



\$495

Transistor Equivalents

239 pages This reference book enables the user to find substitutes for approximately 9,500

Size: 184 x 139mm

Cat B-4507

CMOS Cookbook

First an explanation of what CMOS is, how it works, and how to power it. Then a mini catalogue of over

COOKBOOK

100 devices including pinouts and usage descriptions Cat R-1248 Size: 215 ×

\$2995

Design of PLL Circuits With Experiments

Howard M. Berlin - 254 pages A fascinating introduction to PLL circuits: the theory, design and practical applications. Learn everything from the phase detector,

voltage-controlled oscillator to digital freq. synthesizers and more! Includes experiments to tes vour newly acquired knowledge Cat B-1249



Alternate Energy Projects

Andrew Motes - 286 pages A state-of-the-art electronic design and construction manual for alternate energy projects. Includes building instructions, circuit diagrams and components part

numbers for monitoring and control devices for wind and solar nower systems Cat B-1775

Size: 130 ×

Electronics Notebook 4

Colin Mitchell - 65 pages The latest in the tremendously popular series. This issue deals with the Thyristor, soldering, heatsinks,

using a CRO, the inductor, how a zener diode works and more! Size: 210 ×

Cat B-3637 275mm \$795





International **Transistor** Selector

Towers - 128 pages Computer listings of over 10,000 transistors with substitutes, outline diagrams, terminal identification. manufacturers, codes and specifications. Cat B-1826

Design of Op-**Amp Circuits**

With Experiments

Howard M. Berlin

Over 220 pages of information. Renowned author, Howard M. Berlin teaches you how to distinguish one type of op-amp from the other.

about the use of op-amps in basic linear amp circuits their use in active filters and more. Cat B-1251

Size: 215 × \$2495



Electronics Notebook Vol 3

Colin Mitchell — 66 pages The latest in the series. You've benefited by the information in the first two: now keep right up-to-date.

Cat B-3634 Size: 275 × 205mm \$295



The World **Transistor Cross- The Cellular** Reference

Guide A DSE Book Printed especially for Dick Smith

Electronics, this specifications for all major manufacturers and some minor ones as well Cat B-4506



IC Timer Cookbook Second Edition

Walter G. Jung - 430 pages Gives a good explanation of the operation of timer circuits and recipes for cooking

them. Shows a huge number of applications of the timer IC's in individual circuits and larger systems Cat B-1245 Size: 215 × 135mm

A First Electronics

Course R.B. Arnold and P&T Lawson - 87 pages A great beginner's book for learning

about the fascinating world of electronics. 8 chapters giving theory. simple experiments and loads of puzzles and questions to make learning enjoyable. Cat B-2615

Size: 230 × 275mm




Learning **Electronics** Theory — 196 pages

Editors of Elementary Electronics

Great reference or beginner's material with 25 projects to build as you learn. Covers basic electronics, audio electronics radio electronics and digital electronics Cat B-3008 Size: 185 X 235 mm

\$4 495



Electrostatic Loudspeaker

Design And Construction

Ronald Wagner — 248 Pages Step by step instructions on how to build your own electrostatic speakers as well as theory and

history of electrostatic speakers and transducers. Cat B-3612 Size: 190 ×

\$**24**95



Connection

Josef Bernard — 152 pages The complete guide to cellular

phones. How they work, cellular phone equipment, what to look for in a cellular phone, how calls are charged, options and accessories, even Cat B-1890

\$4 995

Size: 150 × 230mm **Loaic Data**

Book Volume 1 Corporation - 50mm thick and it's all hard information on National Semiconductor high speed micoCMOS logic families MM54HC/ 74HC, CD4000, MM54C.74C and the many unique CMOS LSI products. An invaluable reference

guide for anyone working or delving circuits. Cat B-4015 Size: 170 × 230mm

\$34 95



Logic Data Book Volume II

The other essential reference work from National Semiconductor Corporation. Covers everything on

the extensive Bipolar Logic Families, ALS, AS, LS, S, TTL and Low Power Cat B-4016 Size: 170 ×



Make full use of your computer and peripherals! Learn everything there is to know with the DSE range of books. Hardware, software, peripherals it's all at your nearest DSE store!

VZ 300 Technical Manual

DSE - 70 pages

Learn to use your VZ 300 Colour Computer to maximum effect with this handy manual containing additional information concerning programming, hardware operation and expansion. Cat X-7324



Giant Book of VZ 300 Games

Tim Hartnell - 278 pages

Computers are fun! Combined with your VZ 300 Colour Computer, games can be entertaining and educational too. This superb book lists games and how to play them: from adventure, space action to old favourites like checkers. Plus a chapter on how to create your own

Cat Y-7326 Weight: 460a



Programming the VZ 300

Tim Hartnell — 171 pages

Get into the exciting world of programming with this easy to read manual. First you'll be familiarised with the keyboard and then start learning all those programming tricks: random number generation, strings, arrays, PEEK and POKE, debugging - all you need to enjoy the wonders of rogramming on your VZ 300.



The Great VZ 300 Omnibus

Tim Hartnell — 188 pages

Learn how flexible your VZ 300 is with this superb book. It takes you beyond off the shelf software use by teaching you how to create an artificial intelligence program, a language translator or utilise sound and graphics capabilities. Even

learn search and sorting techniques from this Cat X-7327



Weight: 350g Size: 220 × 175mm

Beginner's Guide to Computer Machine Language Connection

Christopher D. Metcalf and Marc B. Sugiyama — 410 pages

For those BASIC programmers who want to learn Machine Language, this is the book for you! It is an excellent guide to Machine Language and a handy reference source too. Learn how to use Machine Language

with BASIC, merge with Pascal, how to use BIOS and DOS interrupts plus much more. Cat x-8643

Weight: 560g Size: 228 × 160mm



Mysteries Solved

Graham Wideman - 260 pages

Expand your computer system without fuss. Graham Wideman offers the best peripheral connection advice this side of Silicon valley: from simple to advanced connections, RS-232C, parallel and video interfacing

and software too! There's even a troubleshooting

chart and helpful hints. Cat X-8636 **\$24**95

Weight: 515g Size: 247 × 188mm



The RS-232 Solution

Joe Campbell — 194 pages

Easy to read, illustrated and loaded with helpful case studies: that's the secret to the success of this excellent book. Author Joe Campbell's knowledge of connecting printers, modems and plotters via the RS- 232 port

has helped a large number of computer Cat X-8637

\$2995

Weight: 370g Size: 227 × 178mm

Baby 'AT' Instruction Manual

The complete guide to building the DSE Baby AT Kit Computer. Comprehensive assemble manual and user's quide, circuit diagrams, layout... the lot! Cat X-1004



Introduction to **Turbo Pascal**

Douglas S. Stivison — 270 pages Want to learn Pascal? Here's the best reference book available — for beginners and experienced programmers alike — on elementary programs, advanced data construction, bit and byte manipulation. Plus advanced computer options, how to line files, debugging and



Programming the 8086 & 8088

Your guide to the basic concepts of programming the powerful 8086 and 8088 16-bit microprocessor. Learn internal

structures, memory organisation and complete interrupts plus how to apply the 8088 in controlling an IBM PC. Sample programs included. Cat X-8634

\$2995

Weight: 470g Size: 227 × 152mm




Turbo Pascal for Basic Programmers

Paul Garrison — 400 pages

Compared to BASIC Pascal is a faster and more efficient programming language. Because BASIC is widely used, author Paul Garrison teaches Pascal by describing the BASIC equivalent and showing the differences. It's an ideal way to learn structured Pascal programs - including data base, currency conversion and many

personal programs Cat X-2375

Weight: 750g



Programmer's Guide to the IBM PC


Peter Norton — 426 pages

The ultimate programmer's reference guide! Create programs, solve problems and learn the differences between the IBM PC, XT, AT, Portable and PCjr. Includes: BIOS basics, DOS functions, linking programs and interface routines for language

Cat X-8648

\$**33**95

Weight: 900g Size: 233 × 188mm



DSE's OWN HANDBOOK SERIES

Australian Radio Frequency Handbook

Jack McDonald — 170 pages

This is the fantastic second edition of this best selling introduction to the fastest growing hobby in Australia today... scanning! This edition has not only been updated and revised where neces but it also contains hundreds of NEW frequency listings. Cat B-9600

\$695 Size: 213 × 135mm

Tony Clegg — 154 pages This book will help boat owners find out just how simple

choosing, fitting and using a marine radio can be. Packed with all the essential details, here in a book that will not only inform, but can lead to lives being saved as w Cat B-9604

\$695

Size: 213 × 135mm

Australian Marine

Radio Handbook

Australian Amateur Radio

Handbook

Covers every aspect of this unique and exciting hobby... How to get your licence, what to buy what to build, how to mak your radio shack tick, etc Detailed info on radio operating procedures and courtesies never before available in print! Cat B-2320

Size: 213 × 135mm

Australian CB Radio Handbook DSF - 144 pages

CB Radio including latest marine radio service details. The dition includes ne regulations and allocations Cat B-2325

A complete guide to

\$695

Size: 213 × 135mm

HERO 1: Advanced Programming & Interfacing

Mark J. Robillard - 234 pages

A must for anyone interested in machine language as well as Hero 1 owners. Deals firstly with basic machine language, then to a comprehensive explanation of firmware on board the Hero 1 then finally into an in-depth analysis of the Hero 1 operating system. Cat B-4850 Size: 215 × 280mm

\$3250





World Radio TV

Frequencies, addresses, call signs, ID's... it all

here! A complete, comprehensive listing of

international radio and TV stations. The

not so serious amateur! Cat B-2088

Size: 225 × 250mm

handbook that opens up a whole world of

airwaves action. A must for the serious and

Handbook

Magazine Binder

rods for placement and protection of those valuable mags. Vinyl covered. Holds 12 issues (one year) of any mag to a maximum size of 280mm high by 210mm. Cat B-4045

Weight: 350g Size: 295 × 225 × 105mm


Want to know anything about Amateur Radio? Technical data, world radio, TV, CB... everything to do with communications. DSE books — turning out professional amateurs!

Into Electronics

An introductory course into electronics from the Wireless Institute Of Australia Educational Service. An excellent educational production providing information and fundamental theory of electronics. Each chapter gives simple experiments and revision questions. Cat B-2313

Size: 185 × 245mm

\$695



Now in Hardback! **1988 ARRL** Handbook

AMATEUR

The amateur bible is now exclusively in hardback! And it's still the same price as last year. There's heaps of new construction projects as part of this year's theme. As usual there's all the up-to-date theory you've come to expect from the world's leading amateur handbook, Cat B-2221

\$4995



Novice **Electronics**

Another quality text from the Wireless Institute Of Australia Aims to complete the knowledge needed to attempt the theory examination for the Novice Amateur Operator's Certificate of Proficiency as set by the DOTC. The end of each chapter has a summary, terms that should be known and questions. Cat B-2317

Size: 185 × 245mm



1000 Questions for Novice **Candidates**

Ken Hargreaves, Dave Wilson, Rex Black -116 pages

Published by the W.I.A. 4th Edition. For the aspiring amateur this book is essential. Asks the questions most likely to arise in the exams. Covers all aspects from electrical laws to regulations and test equipment, etc. Cat B-2316

Size: 194 × 150mm




Manual of Q & A Yaesu Logbook for the Novice Licence

Keith Howard - 100 pages

For the would-be novice this book asks a question, then gives the answer in simple but explicit terms, an excellent means of learning. Covers everything from the ohm to regulations. Cat B-2315

Size: 243 × 180mr



Yaesu - 50 pages

The finishing touch to your Yaesu station (and will really life the level of the Ke****d or I**M station!). Provision for all QSO details including QSL data. Cat B-2029

Size: 300 × 215mm



ARRL Antenna Book

Gerald L. Hall - 327 pages

The latest revision of this extremely popular ARRL handbook. Information, data and technical tips on all types of antennas, plus many antenna projects to build. A must for every shack. Cat B-2207

Size: 275 × 207mm



Amateur Radio and Electronics **Study Guide**

A clear and concise study manual for the amateur syllabus. Designed to make learning easier in a short uncluttered text with large clear illustrations in Students-Own-Note form. This invaluable publication has been tailored to fill the gap between high level amateur radio handbooks and over simplified beginners manuals.

Size: 90 × 206mm




500 Questions for A.O.C.P. **Candidates**

Bill Dunn, Fred Santos, Keith Hargraves, Dave Wilson — 94 pages

NSW W.I.A. Y.R.S. Education Service. Written to aid candidates preparing for the multiple choice format A.O.C.P. exams. Contains 500 questions with answers and a proposed syllabus for study for the A.O.C.P.

Size: 234 × 165mm




CB PLL Data Book

Lou Franklin - 110 pages

A mine of information for the avid CB'er. Contains details of the phase locked loops used in just about every CB ever made. So what? It also tells you how to modify the PLL circuitry to give more channels, to push it, to repair it, to do just about anything except talk. (They're working on that one!). And if you repair CB's, this is indespensable for the technical data it gives — data you won't find anywhere else. Cat B-2326

Size: 250 × 178mm




The Ham Exam Cram Book

Keith Howard — 72 pages


A study and revision guide for the A.O.C.P. This book is not intended to replace recommended text books but it will certainly sharpen your knowledge and prepare you for the theory exam without wasting effort. Contains concisely explained and clearly illustrated examples as well as many multiple choice questions with answers explained. Cat B-2314

Size: 200 × 163mm



Resistor and Capacitor Colour Codes

Resistors Carbon film . Metal glazed. Metal film _ Metal film (close tolerance) figures figures figures multiplier (\O) tolerance 0.01 0.1 5% 0 1 0 0 10 100 3 3 3 1k 4 10k 4 4 5 5 5 100k 1M 10M 8 8 8 9 9 9



CIRCUIT LAWS

OHM'S LAW

The relationship between voltage, current and resistance in a circuit is defined by Ohm's law, which may be simply stated by the formula:

where E is in volts, I is in amps and R is in ohms. This can be turned around to look like:

$$I = \frac{E}{B}$$

POWER IN A CIRCUIT

When a current passes through a component, energy is given off in the form of heat. Normally, we associate resistors with this action: that's part of their job. We often need to know how much power is being given off by a resistor – and we find this out by using the formula:

$$W = E \times I$$

where W is in watts, E is in volts and I is in amps. This formula too can be turned around if required:

$$\mathbf{E} = \frac{\mathbf{W}}{\mathbf{I}}$$

RESISTORS IN SERIES

Resistors in a series circuit are simply added together to find the total resistance. In other words, a 10 ohm, 150 ohm and 1000 ohm-resistor connected in series would be the equivalent of a single 1.160 ohm resistor. The formula is:

$$R_T = R_1 + R_2 + R_3 + \dots$$

RESISTORS IN PARALLEL

Resistors in a parallel circuit are a little more difficult. The formula to use is:

$$R_{T} = \frac{1}{\frac{1}{R_{1}} + \frac{1}{R_{2}} + \frac{1}{R_{3}}} - \frac{\text{Two resistors in parallel}}{\frac{R_{1}}{R_{1}} + \frac{R_{2}}{R_{2}}}$$

$$R_{T} = \frac{R_{1}}{R_{1}} \times \frac{R_{2}}{R_{2}}$$

CAPACITORS IN SERIES

Capacitors in series, on the other hand, are similar to resistors in parallel. You add the reciprocals:

$$C_{T} = \frac{1}{\frac{1}{C_{1}} + \frac{1}{C_{2}} + \frac{1}{C_{3}}} + \frac{1}{C_{3}} + \frac{1}{C_{4}} + \frac{1}{C_{4}} + \frac{1}{C_{4}} + \frac{1}{C_{4}} + \frac{1}{C_{4}} + \frac{1}{C_{4}}$$

CAPACITORS IN PARALLEL

Capacitors behave exactly the opposite to resistors; when capacitors are in parallel, you add them;

$$C_{\tau} = C_1 + C_2 + C_3 + \dots$$

$$C_1$$

$$C_2$$


$$C_3$$

$$C_3$$

INDUCTORS IN SERIES

$$L_7 = L_1 + L_2 + L_3 + \dots$$

INDUCTORS IN PARALLEL



RESISTORS

Resistors are usually so small it is impractical to try and print each one with its value, so they are marked with a code printed on them in bands of different coloured paint. These bands give


Depending on the tolerance of the resistor there will be either 4 bands (5% E24 Series) or 5 bands (1½% E96 series).

How to read common 5% resistors (4 bands):

Start with the band closest to one end or, if it is difficult to work out, the band furthest away from the gold or silver band. Take the resistor shown below: let's say that the first band is orange from the table this means three. If the second band is white, then its value is 9, from the table. And finally if the third band is brown we have a value of 2, so we add one zero to the first two figures: 3, 9 and 0 - or 390 ohms.

The fourth, or tolerance band, is silver: 10%. Therefore, the resistor is 390 ohms, 10% tolerance (or somewhere between 390 -10% and 390 +10%, or 351 and 429 ohms). This is more than adequate for most circuit requirements. Resistors are available which are 'spot on' in value - however, these are not required in most circuits, and are often very, very expensive.

WHAT THEY MEAN:




Tolerance band colours: Red 2%, Gold 5%, Silver 10%, No band 20%

Note how the bands are closer to one end of the resistor than the other

1% Resistors (5 bands)

These are read in a similar manner. However, the first three bands give a three figure value. The fourth band gives the number of zeros/multiplier and the fifth is the tolerance.

WHAT THEY MEAN



olerance band colours: Brown 1%, Red 2%, Gold 5% Silver 10%, No band 20%


Some circuits show capacitor and resistor values as straight figures – e.g. 4.7 pF. Others replace the decimal point with the first letter of the sub-multiple (e.g. 4p7 is the same as 4.7pF). Similarly with resistors. 6k8 means the same as 6.8k.

PREFERRED VALUES

provide a logical progression whereby each higher value always represents an increase by the same factor or percentage, according to the percentage tolerance on which the table is based. (The mathematical term is "geometric progression".)

10	12	15	18	22	27	33	39
47	56	68	82				
serie	es E24 (5	·%)					
10	11	12	13	15	16	18	20
22	24	27	30	38	36	39	43
47	51	56	62	68	75	82	91
121	124	127	130	133	137	140	143
100	102	105	107	110	113	115	118
147	150	154	158	162	165	169	174
178	182	187	191	196	200	205	210
215	221	226	232	237	243	249	255
261	267	274	280	287	294	301	309
316	324	332	340	348	357	365	374
383	392	402	412	422	432	442	453
464	475	487	499	511	523	536	549
562	576	590	604	619	634	649	665
681	698	715	732	750	768	787	806
825	845	866	887	909	931	953	976

RESISTOR VALUE EXAMPLES



METRIC MULTIPLIERS

Throughout this book, and indeed, most electronic publications, metric multipliers are used to simplify and shorten component values, etc.

For example, capacitance is measured in Farads but the Farad is a huge unit of measurement, much too large to be of any use in expressing capacitor values. So we use a suitable metric sub-multiple to save a lot of figures. Instead of saying, for example, .00000000001 Farads we say 1 pico Farad (1 pF).

We have used only micro Farads (uF) and pico Farads (pF) in this book; however, some publications use the abbreviation nano Farad (nF) so you should get to know these eventually, too.

Abbreviation	Means	Multiply unit by Or
Р	pico	.00000000001 10- 12
n	nano	.00000001 10-9
u	micro	.000001 10 ⁻⁶
m	milli	.001 10 ⁻³
_	UNIT	1 10 ⁰
k	kilo	1 000 10 ³
М	mega	1 000 000 10 ⁶

1000 pico units = 1 nano unit 1000 nano units = 1 micro unit 1000 micro units = 1 milli unit 1000 milli units = 1 unit 1000 units = 1 kilo unit 1000 kilo units = 1 mega unit


CAPACITORS

Most capacitors will have their value printed on them. However, there are a number of capacitor manufacturers who use the 'IEC' code. This code is a numerical code, but works in a similar way to the resistor colour code: two figures followed by a multiplier There is often a single letter code showing tolerance.

The code is worked out in picofarads, so you may have to use the appropriate metric multiplier


A capacitor may have a code '104K'. This decodes as follows - 0.1uF, 10%. The first two figures give us 10, the third figure gives us 0000, and the latter 10%. Therefore, the capacitor is 10 0000pF, 10%. We normally express this as 0.1uF - capacitors with a value below 001uF are expressed in picofarads

There may be a further figure marked - this would be the voltage rating of the capacitor (the maximum voltage at which you can use that capacitor).



CAPACITORS AND THEIR USES

Aluminium Electrolytic Capacitors
Ideal for use in filtering or smoothing rectified A.C. energy storage as in Power Supplies. Also used for bypassing and coupling in audio applications and the timing element for non critical circuits



Solid Tantalum Canacitors

Lower leakage High reliability, long life and offer a size advantage

Ceramic Capacitors

Offer low cost and high capacitance in a small physical volume There are generally two types:

For tight tolerance and high stability in radio frequency (RF) tuned circuits.

Bypass capacitors in RF and in digital circuits for spike suppression and power supply filtering.

Paper Capacitors

An original construction of capacitors for use in A.C. circuits Still used for power factor correction in mains supply applications. For example in Lighting and electric motors.

Polyester Capacitors

Lowest cost, most widely used for general purpose application

Polycarbonate Capacitors
Offer low temperature coefficient and lower dielectric losses at high frequency. Most often chosen for temperature stability characteristics

Polystyrene Capacitors
Usually chosen for applications requiring tight tolerance coupled with high stability. Predictable temperature coefficient used in conjunction with particular ferrite coils makes highly stable tuned circuits or oscillators.

Polypropylene Capacitors
Offer very low dielectric losses rivalling polystyrene. Suitable for high power inverters and converters and T.V. deflection

BIPOLAR TRANSISTORS

TYPE	CASE	POL	Vce	Vcb	IC mA	Vces @	IC	Hfe @ IC		MHz Ft @	IC mA	Ptot mW	USE	COMPARABLE TYPES
AC126 AC127 AC128 AC132 AC187 AC188 AD161 AD162 AF116 ASZ15 ASZ18	TO-1 TO-1 TO-1 TO-1 TO-1 TO-1 PT1 PT1 TO-7 TO-3 TO-3	P	12 16 16 12 15 15 20 20 15 60 32	32 32 32 32 25 25 25 32 32 32 100 100	100 500 1000 200 1000 1000 3000 3000 10 10A 10A	0.6 0.35 0.8 0.6 0.6 0.4	1A 200 1A 1A 1A 1A 1A	105 60-175 115 100-500 100-500 80-320 80-320 150 20-55	2 50 300 50 300 300 500 500 1 1A	1.7 1.5 1 1.3 1 1 0.02 0.015 75 0.2 0.22	10 10 10 10 10 10 300 300 1 1A	500 340 1W 216 1W 220 4W 6W 50 30W 30W	Audio driver Audio O/P Audio O/P Audio O/P Audio O/P Audio O/P Audio Amp. Audio Amp. H.F. Amp. H.C. Sw. H.C. Sw.	2N406 AC187 AC188 AC188 AC127 AC128 AD165, 2N1218, 2N1292 AD143, AD152, AD147 AF135, AF136, 2N3127 OC28 O.C.36
BC107 BC108 BC109 BC109 BC157 BC158 BC159 BC177 BC178 BC179 BC182(L)	TO-18 TO-18 TO-18 TO-18 SOT-25 SOT-25 SOT-25 TO-18 TO-18 TO-18 SOT-30 (TO-92/74)	NS NS NS PS PS PS PS PS NS	45 20 20 20 45 25 20 45 25 20 50	50 30 30 30 50 30 25 50 30 25 60	100 100 100 100 100 100 100 100 100 200	0.2 0.2 0.2 0.2 0.25 0.25 0.25 0.25 0.25	10 10 10 10 10 10 10 10 10 10 10	110-800 200-800 200-800 75-260 75-500 125-500 75-260 75-500 125-500	222222222222222222222222222222222222222	300 300 300 300 150 150 150 150 150 150	10 10 10 10 10 10 10 10 10 10	300 300 300 300 300 300 300 300 300 300	S.S. Amp. S.S. Amp. Low Noise S.S. Amp. Low Noise S.S. Amp.	BC207, BC147, BC182 BC208, BC148, BC183 BC209, BC149, BC184 BC209C, BC184C, BC149C BC177, BC307, BC212 BC178, BC308, BC213 BC179, BC309, BC214 BC157, BC307, BC212 BC158, BC306, BC213 BC159, BC309, BC124 BC107, BC307, BC124
BC183(L) BC184(L)	SOT-30 TO-92/74) SOT-30	NS NS	30 30	45 45	200 200	0.25 0.25	10 10	100-850 2 250-850 2	2 2	150 150	10 10	300 300	S.S. Amp. Low Noise High Gain	BC108, BC208, BC148 BC109, BC209, BC149
BC207 BC208 BC209 BC213(L)	TO-106 TO-106 TO-106 SOT-30	NS NS NS PS	45 20 20 30	50 25 25 45	100 100 110 200	0.25 0.25 0.25 0.25 25	10 10 10 10	110-220 110-800 200-800	2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	150 150 150 150 200	10 10 10 10	300 200 200 300	S.S. Amp. S.S. Amp. Low Noise High Gain S.S. Amp	BC107, BC182, BC147 BC108, BC183, BC148 BC109, BC184, BC149 BC308, BC158, BC178
BC214(L)	(TO-92/74) SOT-30 (TO-92/74)	PS	30	45	200	0.25	10		2	200	10	300	S.S. Amp	
BC327 BC328 BC337 BC338 BC546 BC547 BC558 BC557 BC558 BC635 BC635 BC636 BC639 BC640	TO-92(VAR) TO-92(VAR) TO-92(VAR) TO-92(VAR) TO-92(VAR) TO-92(VAR) TO-92(VAR) TO-92(VAR) TO-92(VAR) TO-92(VAR) TO-92(74) TO-92(74) TO-92(74)	PS NS NS NS NS PS	45 25 45 25 80 45 30 45 30 45 45 80 80	50 30 50 30 80 50 30 50 30 45 45 100	800 800 1000 1000 100 100 100 100 100 1A 1A 1A	0.7 0.7 0.7 0.7 0.6 0.6 0.6 0.5 0.5	500 500 500 100 100 100 100 500 500 500	100-600 100-600 100-600 125-500 110-800 110-330 75 125-600 40-250 40-250 40-160	100 100 100 100 2 2 2 2 2 2 150 150 150	100 100 200 200 300 300 300 150 150 150 130 130 50	10 10 10 10 10 10 10 10 500	800 800 800 500 500 500 500 500 1W 1W 1W	O/P O/P O/P O/P O/P S.S. Amp. S.S. Amp. S.S. Amp. G.P. Small Sig. G.P. Small Sig. G.P. Small Sig. Audio O/P Audio O/P Audio O/P Audio O/P	2N3638 BC327,2N3643 2N3642 BC337 BC107, BC207, BC147 BC108, BC208, BC148 BC157, DS557 BC158, DS558 BC159 BC639 BC640 MU9610, TT801 MU9660, TT800
BCY70 BCY71 BCY72	TO-18 TO-18 TO-18	PS PS PS	40 45 25	50 45 25	200 200 200	0.5 0.5 0.5	50 50 50	100-600	10 10 10	250 200 200	50 50 50	350 350 350	G.P. G.P. G.P.	BC212 BC212 BC213
BD137 BD138 BD139 BD140 BD262 BD263 BD266A BD267A BD681 BD682	TO-126 TO-126 TO-126 TO-126 TO-126 TO-126 TO-220 TO-220 TO-126 TO-126	NSSSSSSSSSSSSSSSSSSSSSSSSSSSSSSSSSSSSS	60 60 80 60 60 80 80 100	60 60 100 100 60 80 80 100 100	1A 1A 1A 1A 4A 4A 4A 4A	0.5 0.5 0.5 0.5 2.5 2.5 2	500 500 500 500 1.5A 1.5A 3A	40-160 40-160 40-160 750 750 750 750 750 500	150 150 150 150 150 1.5A 1.5A 3A 3A 4A 1.5A	250 75 250 75 7 7 7 7 7 1	500 500 500 500 1.5A 1.5A	8W 8W 8W 36W 36W 60W 40W 40W	G.P. O/P G.P. O/P G.P. O/P G.P. O/P High Gain Darl. O/P High Gain Darl. O/P High Gain Darl. O/P Darlington O/P Darlington O/P	BD139 BD140 40409 40410 BD266 BD267 BD263 BD263
BDY20	TO-3	NS	60	100	15A	1.1	4A	20-70	4A	1	4A	115	Power O/P	2N3055
BF115 BF167 BF173 BF178 BF179 BF180 BF184 BF185 BF194 BF195 BF199	TO-72(28) TO-72(28) TO-72(28) TO-39 TO-72(25) TO-72(28) TO-72(28) TO-72(28) SOT-25/1 SOT-25/1	NS N	30 40 25 115 115 20 20 20 20 20 25	50 25 40 185 250 30 30 30 30 30	30 25 50 50 20 30 30 30 30 25			20 20 13 75-750 34-140 65-220 35-125	7 30 20 2 1 1	230 350 550 120 120 675 300 220 260 200 550	1 4 5 10 10 2 1 1 1	145 130 230 600 600 150 145 145 250 250	V.H.F. Amp T.V. I.F. Amp T.V. I.F. Amp T.V. Video Amp T.V. Video Amp U.H.F. Amp H.F. Amp H.F. Amp H.F. Amp H.F. Amp H.F. Amp	BF336 BF338 BF200 BF195 BF185 BF180
BF200 BF336 BF337 BF338 BF469 BF470	(VAR)2 TO-72(25) TO-39 TO-39 TO-126 TO-126	NS NS NS NS NS PS	20 180 200 225 250 250	30 185 300 250 250 250	20 100 100 100 50 50			20-60 20-60 20-60 50	3 30 30 30 30 25 25	650 130 130 130 60 60	3	150 3W 3W 3W 1.8W	V.H.F. Amp Video Amp Video Amp Video Amp G.P. High V. Amp G.P. High V. Amp	BF180
BFR90 BFR91 BFY50 BFY51 BFY52 BFY90	SOT-37(2) SOT-37(2) TO-39 TO-39 TO-39 TO-70(25)	NS NS NS NS NS	15 12 35 30 20 30	20 15 80 60 40 30	25 35 1A 1A 1A 25	0.3 0.2 0.35 0.35	30 150 150 150	25-250 3 30 40 60	14 30 150 150 150 2	5GHz 5GHz 60 50 50 1.3GHz	14 30 50 50 50 25	180 180 2.85W 2.85W 2.85W 200	Wide Band Amp Wide Band Amp G.P. G.P. G.P. U.H.F. Amp	

PLEASE NOTE:

Not all devices shown in this section are stocked by Dick Smith Electronics. In most cases, however the specifications should enable substitution to be made with a transistor from the DSE range in all but the most critical applications. Most circuits published by the electronics magazines deliberately use 'garden variety' transistors for which a large number of substitutes are possible. If a device is critical they will usually specify it as such.

While every effort is made to ensure that this data is correct and as up-to-date as possible, no responsibility will be accepted for its use or consequences arising therefrom. If in doubt, please consult manufacturer's data sheets.

NOTE: Some small signal transistors may be supplied in a TO-92 case with a 'PN' prefix. The electrical specifications are the same; only the case is changed. See case outline TO-92(72) for pin detail.

BIPOLAR TRANSISTORS

							BIPC	LAR T	RAN	SIST	ORS			
TYPE	CASE	POL	Vce	Vcb	IC mA	Vces @	IC	Hfe @ I	C mA	MHz Ft @	IC mA	Ptot mW	USE	COMPARABLE TYPES
BUX80	то-з	NS	400		10A	1.5	5A			8		100W	Deflection, High	
DS547	TO-92	NS	45	50	100	0.6	100	110-800	2	300	10	500	current Sw.G.P. Power S.S. Amp	BC107, BC207, BC147
DS548	TO-92	NS	30	30	100	0.6	100	110-800	2	300	10	500	S.S. Amp	BC108, BC208, BC148
DS549	TO-92	NS	30	30	100	0.6	100	200-800	2	300	10	500	Low Noise Small Sig.	BC109, BC209, BC149
DS557	TO-92	PS	45	50	100	0.25	100	75-260	2	150	10	300	S.S. Amp	BC177, BC307, BC212
DS558	TO-92	PS	25	30	100	0.25	100	75-100	2	150	300	S.S.Amp	BC178, BC308, BC213	
MJ802 MJ2501	TO-3 TO-3	NS PS	90 80	100 80 70	30A 10A	0.8 2	7.5A 5A	25-100 1000	7.5A 5A	2	1A	200W 150W	HighPower O/P Darl. O/P	MJ2955
MJ2955 MJ3001	TO-3 TO-3	PS PS NS	60 80	80	15A 10A	1.1	4A 5A 7.5A	20-70 1000	4A 5A	4	500	115W 150W	High Power O/P Darl. O/P	2N4908, 2N4909, 2N5871
MJ4502 MJ15003 MJ15004	TO-3 TO-3 TO-3	PS NS PS	90 140 140	100 140 140	30A 20A 20A	0.8	7.5A	25-100 25-150 25-150	7.5A	2 2 2	1A	200W 250W 250W	High Power O/P HighPower O/P High Power O/P	
MJE340 MJE350	77-03/199-0 77-03/199-0	04NS 04PS	300 300	140	500 500	0.75 0.77	100	30-240 30-240	50 50			20W 20W	G.P. High V. Power G.P High V. Power	
MJE2955 MJE3055	90-05/199-0 90-05/199-0	04NS	60 60	70 70	10A 10A	1.1 1.1	4A 4A	20-100 20-100	4A 4A	2 2	500 500	75W 75W	G.P. Power G.P. Power	TIP2955 TIP3055
MRF629 MRF660 MU9610	79-03 TO-220AB 152	NS NS NS	16 16 30	70 36 36 40 40 40	400 2.4A 2A	0.4	1.5a	20-200 20-160 80-400	100 250 350	70	250	5W 25w 1W	R.F Power UHF R.F. Power UHF O/P	TT801
MU9611 MU9660	152-01 152	NS PS	30 30	40 40	2A 2A	0.4 0.4 0.4	1.5A 1.5A	80-400 80-400	350 350	70 70	250 250 250	1W 1W	O/P O/P	TT801 TT800
MU9661	152-01	PS	30	40	2A	0.4	1.5a	80-400 50-150	350	70	250 50	1w	O/P Driver-O/P	TT800
NSD106 NSD206	TO-202(35) TO-202(35)) PS	100	140 100	14	2.9 2.1	100 100	50-150	100	150	50		Driver-O/P	
OC26 OC28	TO-3 TO-3	PG PG PG PG PG PG PG	30 60	50 100	3.5A 10A	0.7 10A	3A 0.4	300-100 20-55 45-225	1A 1A	0.3 0.2 7.5	500 1A 1	32W 30W 85	G.P. O/P H.C. Switch R.F. Amp	AD149 ASZ15 AF125, AF135, AF172
OC44N OC45 OC70	TO-1 GT-3 GT-3	PG	5 5 10	15 15 30	10 10 50	2		25-125 30	1 1 5	3 0.5	3	85 125	R.F. Amp G.P. Amp	AF132, AF185, AF196 AC121, AC126, 2N1190
OC71 OC72	GT-3 GT-6	PG PG	10	15 30 30 32 20	50 50 250			30-75 45-120	3 10	0.6 0.35		125 165	G.P.Amp Audio O/P	AC126, 2N2429 AC122, AC125, AC162
OC74N OC75	TO-1 GT-3	PG PG	10 10	20 30	300 50	0.6	300	60-150 60-130	50 3	0.1 0.1		550 125	Audio O/P G.P. Amp	AC125, AC180, AC192 AC173, AC192
TIP31B TIP32B	TOP-66 TOP-66	NS PS	80 80	80 80	3A 3A	1.2 1.2	3A 3A	20 20	500 500	3	500 500	40W 40%	Power Amp-Sw Power Amp-Sw	第二十十五十
TIP2955 TIP3055	TOP-3 TOP-3	PS NS	70 70	100 100	15A 15A	1:1	4A 4A	20 20	4A 4a	0.8 0.8		90W 90W	Power Amp-Sw Power Amp-Sw	MJE2955 MJE3055
TT800 TT801	TO-39(Mod TO-39(Mod		60 60	60 80	1A 1A			40-120 40-120	100 150	100 60		800 800	Audio Driver-Sw Audio Driver-Sw	TT797, NSD206, 2N4030 TT798, NSD106, 2N3019
2N301 2N706A	TO-3 TO-18	PG NS	32 15	40 25	3A 200			50 20	1A 10	0.2 200	1A	11W 300	Audio O/P High S.Sw	AT1138, OC26
2N2222A 2N2904A	TO-18 TO-39	NS PS	40	25 75 60	800 600 600	1.6	500 500	20 75 40-120	10 150	200 300 200	20 50	500 600	High S.Sw High S.Sw	
2N2905A 2N2926 2N3019	TO-39 TO-92(74) TO-39	NS PS PS NS NS NS NS	60 25 80 40	60 25 140	600 100 1A	1.6 0.5	500 500	100-300 150 50-100	150 2 500	200 100 100	50 50	600 200 800	High S.Sw G.P. H.F. Amp	BC108 etc
2N3053 2N3054	TO-39 TO-66	NS NS	55	60 90	700 4A	1.4 0.1	150 200	50-250 25	150 500	100	50 200	2.86W 25W	G.P. Switch Audio O/P	BD137 TIP31B
2N3055 2N3563	TO-3 TO-106	NS	60 12	90 30	15A 50	1.1	4A	20 20-200	4A 8	0.8 600	1A 8	115W 200	O/P - Sw R.F I.F. Amp & Ass	BDY20 BF173
2N3564 2N3565 2N3566	TO-106 TO-106 TO-105	NS NS NS	15 25 30	30 30 40	100 50 200	0.3 0.35	20 1 100	20-500 150-600 150-600	15 1 10	400 400 40	15 1 30	200 200 300	R.F I.F. Amp & Ass Low Level Amp G.P. Amp & Sw	BF167 BC108, BC208 BC183
2N3567 2N2568	TO-105 TO-105	NS NS	40 60	80 80	500 500	0.25 0.25	150 150	40-120 40-120	1	60 60	30 50 50	300 300	G.P. Amp & Sw G.P. Amp & Sw	BC337
2N3569 2N3638	TO-105 TO-105	NS PS	40 25	80 25	500 500	0.25 0.25	150 50	100-300 30	1 50 50	100	50	300 300	G.P. Amp & Sw G.P. Amp & Sw	BC327
2N3638A 2N3640 2N3641	TO-105 TO-106 TO-105	PS PS PS NS	25 25 12 30	25 25 12 60	500 80 500	0.25 0.2 0.22	50 10 150	100 30-120 40-120	10	150 300 250	50 50 10	300 200 350	G.P. Amp & Sw Saturated Switch G.P. Amp & Sw	BC558 BC337
2N3642 2N3643	TO-105 TO-105	NS NS	45 30 45 60	60 60	500 500	0.22	150 150	40-120	150 150	250 250	50 50 50 20 20 50	350 350	G.P. Amp & Sw G.P. Amp & Sw G.P. Amp & Sw G.P. Amp & Sw	BC337 BC337
2N3644 2N3645	TO-105 TO-105	NS NS PS PS PS NS	45 60	45 60	500 500 200	11	300 300	115-300 115-300 60-300 10-200	50 500	200	20	300 300	G.P. Amp & Sw G.P.Amp & Sw	BC327
2N3702 2N3866 2N3904	TO-92(74) TO-39 TO-92	NS NS	25 30 40	40 55 60	400 200	0.25	50	10-200 100-300	50 50 1mA	100 500	50	360 1W 310	G.P. Amp & Sw V.H.F. Amp Low Level Amp	BC213 BC167A, BF194
2N3905 2N3948	TO-92 TO-39	NS PS NS PS PS PS NS	40 20	40 36	200 400	0.4	50	50-200 15	1mA 50	200 700	20 50	310 1W	G.P. Amp & Sw V.H.F. Amp	2010171, 31 104
2N4030 2N4250	TO-39 TO-106	PS PS	60 40	60 40	1A 100	0.5 0.25	500 10	15 250-400	100 0.1	260 50	100	800 200	G.P. Amp & Sw Low Level Amp	BC559
2N4258 2N4292 2N4403	TO-106 TO-92 TO-92	NS NS	12 15 40	12 30 40	50 50 600	0.5 0.6	50 10	30-120 20 100-300	10 3 10	700 600	10	200 200 310	Saturated Sw Saturated Sw G.P.	BC307A, 2N2904
2N4427 2N4429	T0-39 TO-39	PS NS NS	20 20	40	400 400	0.4	100	10-200 10-200	100	500 500	50 50	1W 1W	VHF/UHF/Driver V.H.F. Amp	2N3866
2N5589 2N5590	MT-71C MT-72C	NS NS NS	18 18	36 36 36 60	600 2A			5 5	100 250	175 175	3W 10W	15W 30W	H.F. Mobile R.F. H.F. Mobile R.F.	
2N5591 2N5871	MT-72C TO-3 MT-72C	NS PS NS	18 60 18	36 60 36	4A 7A	1	4A 6A	5 20-100 5X	500 2.5A 1A	175 4 175X	25W 250 40W	70W 100W 80W	H.F. Mobile R.F. Power Transistor VHF Output	2N5872, 2N4908, MJ2955 B40-12
2N6084 2SA733	TO-92/74	PS	40	50	100	0.3	100	200	1	180-250		AF Amp	BC417	
2SB367	PT-1	PG	25	25			1A	45-70	500	0.5		4W	Audio Output	AD162
2SC710 2SC1096	TO-92/76 TO-202-R	NS NS	25 30 65 70	30 40	30	90	1 2A	45-250	1A	60		10W	GP RF Amp G.P.Output	BFS18 2SC1098, TIP31
2SC1306 2SC1307	TOP-66 TOP-66	NS NS	65 70 20	65 70 30 60	00	0.3	3A 8A	40-200 20-150	500 2A	300 150	1	12W 25W	H.F. Output H.F. Output	2SC2166 2SC1969
2SC1674 2SC1969 2SC2166	TO-92 TOP-66 TOP-66	NS NS NS	30 75	60 75	20	0.3	10 6A 4A	40-180 10-180 35-180	1 10 100	600 150		250 20W	VHF Amp H.F. Output H.F. Output	2SC1307 2SC1306
40250	TO-66	NS	50	50	4A	1.5	1.5A	25	100	1		29W	Power Transistor	2N3054
40408 40409 40410	TO-5 TO-39(H) TO-39(H)	NS NS PS	80 80 80		700 700 700	1.4 1.4 1.4	150 150 150	40-200 50-250 50-250	200 150 150	100 100 100		1W 3W 3W	Power Transistor Power Transistor Power Transistor	BC639 BD139 BD140
10110	10-03(H)	-3	30		700		.50	00-200	,00	1.00			. Otto: // airoia(UI	

FETS

FETS	Case	BVGS V @	S IG(uA)	VGS(@ VDS	ID(nA)	IDss(Min	mA) Max	@ VDS	vgs	Yfs(un Min	nhos) Max @	VDS	Ptot mW	Use/Comments
BF245B BF981 BFW10 BFW11 BFW61 BFW61 MFM631 MF131 MPF102 MPF103 MPF104 MPF104 MPF104 MPF131 2N4342 2N4342 2N4342 2N4346 2N5245 2N5459 2N5458 2N5458 2N5458 3S440 3SK40 3SK40	TO-92 Var 1 S0T-103 TO-72(25) TO-72(25) TO-72(25) TO-72(25) TO-72(2) TO-92(72)	60 > 6 300 25±±±5 255 255 6 40 305 25±±±5 255 255 255 255 255 255 255 255 255 255 255	± 10 ± 10 10 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	0.5 2.5 0.5 0.5 1.5 0.5 1 2 0.3 0.5 2 -2.5 -2	8 4 4 4 8 6 7 8 4 4 4 4 5 6 6 6 7 8 8 4 4 4 4 5 6 7 8 8 9 8 9 4 9 1 9 1 9 1 9 1 9 1 9 1 9 1 9 1 9 1	15 10 15 15 15 15 15 15 15 15 15 15 15 15 15	10 200uA 200uA 2 2 1 1 1 10 10 200uA 200uA 100 10 10 10 10 10 10 10 10 10 200uA 200u	6 4 8 4 2 5 2 1 2 4 4 5 3 12 1 1 1 1 1 2 4 4 8 8 8 8 8 9 1 1 1 1 1 1 1 1 1 1 1 2 4 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8	15 25 20 10 20 30 30 20 5 9 16 10 30 30 5 10 20 5 10 20 10 20 5 10 20 5 10 20 5 10 20 20 20 20 20 20 20 20 20 20 20 20 20	15 10 15 15 15 15 15 15 15 15 15 15 15 15 15	000000000000000000000000000000000000000	3000 14000 1600 8000 2000 1000 1500 2500 1000 1000 1000 1	6500 typ 6500 6500 6500 7500 5000 5500 6000 7000 20000 20000 5000 5800 5500 6000 7000 5000 5000 5000 5000 50	15 15 15 15 15 15 15 15 15 15 15 15 15 1	300 225 300 300 300 310 310 310 310 350 180 310 310 310 310 310 310 310 310 310 31	N/CH Junction Audio to H.F. N/CH Dual Gate MOS. VHF Amp N/CH Junction Audio to H.F. N/CH Dual Gate MOS. VHF Amp N/CH Junction — VHF N/CH Junction — Audio Sw. P/CH Junction — Audio Sw. P/CH Junction — Audio Sw. N/CH Junction — VHF N/CH Dual Gate MOS. VHF Amp N/CH Dual Gate MOS. VHF Amp
POWER	FETS Case	V _{DSS}	(m	nin)		^I D (і	max)		on)/ ^I D /GS =	10V	V _{GS(d}	off) I _D =	= 1mA	-	r Diss 25°C Us	
VN46AF VN66AF VN86AF 2SJ48 2SJ49 2SJ50 2SK133 2SK134 2SK135	TO-202 F TO-202 F TO-202 F TO-3 F TO-3 F TO-3 F TO-3 F TO-3 F TO-3 F	40 60 80 -120 -140 -160 120 140 160	-10 -10 -10 10 10			2.0 2.0 2.0 -7 -7 -7 7 7		3.0/1. 3.0/1. 4.0/1. -12/-7 -12/-7 12/-7 12/-7 12/-7	(VGD+	0)	0.8 0.8 0.15 -0.15 -0.15 0.15 0.15 0.15	2.0 .20 2.0 -1. -1. -1.4 1.4	45 45 45 5 5	12.5 12.5 12.5 100 100 100 100 100	N-1 P-1 P-1 P-1 N-1	chan Enhancement Mode VMOS FET chan Enhancement Mode VMOS FET chan Enhancement Mode VMOS FET chan Enhancement Mode MOS FET

DIODES

TYPE	CASE	VR	IF (mA)	Cd (pF)	VF @	IF (mA)	IR (uA)	@ VR	Trr (nS)	Use/Comparable Types
Germanium										
AA119	DO-7	30	100	1.2 3.5	2.2	10 10	150	30 25 20 75		AM/FM Detection Point Contact
OA47	DO-7	25	110	3.5	0.45	10	100	25	70	Gold Bonded G.P. Switching
OA90	DO-7	20	45		1.5	10 10	450	20		G.P. Point Contact OA70, OA80
OA91	DO-7	90	50 30 50		1.9	10	180	75		G.P. Point Contact OA71, 79, 81
DSOA91	DO-7	50	30	1	1	5	200	10		G.P. OA91, 1N60
OA95	DO-7	90	50		1.5	10	110	0.75		G.P. Point Contact
Silicon										
BA100	DO-7	60	90	25 20-45	0.96	10	10	60		G.P. — Alloyed
BA102	DO-7	20		20-45	Cd Ratio 1.4 @	4/10 V/VV				Variable Capacitance
BA114	DO-7		20		0.7	1				Bias Stabilizer
BA234/4	DO-35	20	100	<2	1	100	0.1	15 75		UHF Sw.
BAW62	SOD-27	75	200	2	0.75	5	5	75	4	High Speed Silicon Sw.
BB119	DO-35	15		20-25 @ 4V	Cd Ratio >>1.3					Varicap — replaces BA102
BB122	DO-35	30		12 @ 3V	Cd Ratio 5.2		0.05	28		Varicap VHF UHF
OA200	DO-7	50	160	25	0.96	10	0.1	50		Small Signal — Alloyed
OA202	DO-7	150	160	25	0.96	10	0.1	150		Small Signal — Alloyed
1N914A	DO-35	75	75	4	1	10	5	75 20 6 50	4	Small Signal Sw. 1N4148
1N4148	DO-35	75	200	4	1	10	0.025	20	4	Small Signal Sw. 1N914A
1N4448	DO-35	75	300	4	1	100	0.025	6	4	G.P. Silicon Sw. 1N4148
5082-2800	DO-7	70	15	2	0.41	1	0.2	50	0.1	Schottky (Hot Carrier) UHF
										Detector, Mixer Switch

SCR's

TYPE	CASE	VDRM	IT (r.m.s.) (A)	IGT (mA)	VGT	PG (AV) (W)	IH (mA)	dv/dt (V/uS)	Comments (25°C)
C103B C106Y	TO-92 TO-202	200 30	.8 4	.2 max .2 max	.8 max .8 max	.01 .1	5 max 5 max	20 typ 8 typ	(RGK=1k) (RGK=1k) (RGK=1k) (Gate o/c)
C106D	TO-202	400	14	.2 max	.8 max	1.1	3 max	8 typ	(Bek=1k)
C122D	TO-220	400	8	25 max	1.5 max	.5	3 max	50 typ	(Gate o/c)
C122E	TO-220	500	8	25 max	1.5 max	.5	30 max	50 typ	(Gate o/c)
C164D	TO-48	400	16	40 — 80	2 typ				
C168D	TO-48	800	16	40 80	2 typ				
S4008	TO-220	400	8	25 max	1.5 max	.5	30 max	50 typ	(Gate o/c)
S6008L	TO-220	600	8	25 max	1.5 max	.5	30 max	50 typ	(Gate o/c)
TIC126E	TO-220	500	8	20 max	1.5 max	.5	40 max	100 typ	(Gate o/c)

TRIAC's

TYPE	CASE	VDRM	IT (r.m.s.) (A)	IGT (mA)	VGT	PG (AV) (W)	IH (mA)	dv/dt (V/uS)	(25°C)
BT139-500	TO-220	500	16	50	1.5(Tj = 25°C)	.5	30	100 min.	(Gate o/c)
Q-40006L4	TO-220	400	6	75 max. all modes	2.5 max. all modes	.9	60 max	100 typ	(Gate o/c)
SC141D	TO-220	400	6	50 "	2.5 "	.5	50 max	100 typ	(Gate o/c)
SC146D	TO-220	400	10	50 "	2.5 "	.5	50 max	150 typ	(Gate o/c)
SC151D	TO-220	400	15	50 "	2.5 "	.5	50 max	250 typ	(Gate o/c)
TIC246D	TO-220	400	16*		2.5 "		50 max	· ·	(* case temp. below 80°)
2N6341	TO-220	400	8	75 "	2.5 "	.5	75 max	5 typ	(commutating)

RECTIFIERS

TYPE	MAT	VR	IF(A)	VF	@ IF(A)	IR(uA) @	VR	USE
A14P	s	1000	2.5	1.25	2.5	0.5	1000	Transient Protected (Controlled Avalanche)
A15P	S	100	5	1.1	5	5	100	G.P. Rectifier
A15B	S	200	5	1.1	5 25 10	5	200 75	Transient Protected (Controlled Avalanche)
BYX21/200/R	S	75	25	1.2	25	1.1mA	75	Automobile H. Duty Press fit.
BYX98/300	S	300	10	1.4	10	200	300	Power Rectifier Stud Mount
DS5404	S	200	3	1.1	3	5	200 50	G.P. Rectifier
EM4005	S	50	1 1	1.1	1	1 5	50	G.P. Rectifier
EM401	S	100	1 1	1.1	1	5	100	G.P. Rectifier
EM404	S	400	1 1	1.1	1	5	400	G.P. Rectifier
EM410	S	1000	1	1.1	1	5	1000	G.P. Rectifier
MR110	S	100	10			1986		G.P. Stud Mount
MR410	S	400	10					G.P. Stud Mount
MR5108	S	1000	3	1.1	3	5	1000	G.P. Rectifier
N3492/R	S	100	25	1.7	18 18	1mA	100	Heavy Duty Automobile Press fit.
N3493/R	l s	200	25	1.7	18	1mA	200	Heavy Duty Automobile Press fit.
N4001	S	50	1 1	1.1	1	5	50	G.P. Řectifier.
N4002	S	100	1 1	1.1	1	5	100	G.P. Rectifier.
IN4004	S	400	1 1	1.1	1	5	400	G.P. Rectifier.
N4007	S	1000	1	1.1	1	0.2	1000	G.P. Rectifier.
IN5059(A14B)	SSS	200	2.5	1.25	2.5 2.5 2.5 2.5 2.5	0.2	200	Transient Protected (Controlled Avalanche).
IN5060(A14D)	S	400	2.5	1.25	2.5	0.2	400	Transient Protected (Controlled Avalanche).
IN5061(A14M)	S	600	2.5	1.25	2.5	0.2	600	Transient Protected (Controlled Avalanche).
N5062(A14N)		800	2.5	1.25	2.5	0.5	800	Transient Protected (Controlled Avalanche).
IN5404	S	400	3	1.1	3	5	400	G.P. Rectifier.
N5408	S	1000	3	1.1	3 5	5	1000	G.P. Rectifier.
N5624	IS	200	5	1.1	5	5	200	Transient Protected (Controlled Avalanche).

RECTIFIER BRIDGES


TYPE	MAT	VR	IF(A)	VF @	IF(A)	IR(uA) @ VR	USE
PA60 PB40 MB1 MB4 PO4 WO2 WO4	S S S S S S S S S S	600 400 100 400 400 200 400	8 25 1.8 1.8 6 1.5 1.5	1.2 (per leg) 1.3 (per leg) 1.1 (per leg) 1.1 (per leg)	12.5 6 1	10 400 5 100 5 400 10 400 10 200 10 400	G.P. Bridge Heavy Duty Bridge Mini Bridge Mini Bridge Medlum Duty Mini Bridge Mini Bridge Mini Bridge Mini Bridge


7 SEGMENT LED DISPLAYS Pin Connections (top view) LN516RK FND500 FND507 FND560 Z-4150 LT302 LT303 DL704 DL707 LT313 Z-4103 LT547EJ Z-4151 **DL747** 7.6mm 7.6mm 7.6mm 15.2mm 12.7mm Digit Size 12.7mm 2.6mm red 25mA red 25mA Av. Fwd. Current 5mA Fwd. Voltage 1.6 1.7V 1.7 2.4 1.7 2.1 1.7 10 Min Reverse Breakdown Voltage 3V 6V 5V 3V Max Rev Current 100uA 100uA 100uA 100uA Z-4150 Z-4151 Z-4117 Light Intensity Seament 320ucd 800ucd 800ucd 600ucd 600ucd 3300ucd 600ucd DI 747 DI 750 FND500 I N516RK 1 T302 LT312 Max Pwr. Dissin 500mW 340mW 340mW 960mW 400mW 400mW Pin out Z-4155 TIL393-9 Common Cathode Common Anode Types Types (B)(B)(B)(B)DI 704 TII 393-9 DL707 13. Seg G Anode 14. Dig 7 Cathode 7. Seg A Anodes FND500 Z 4103 2. Digit 1 Cath 8. Dig 4 Cath DI 747 FND560 Z 4150 FND507 3. Seg C Anode 15. Seg B Anode 9. Seg E Anodes LN516RK Z 4151 LT302 199999999999999999 4. Dig 2 Cath 10. Dig 5 Cath 16. Dig 8 Cath LT303 LT312 5. Dec P. Anodes 6. Dig 3 Cath 11. Seg D Anode 12. Dig 6 Cath 17. Seg F Anode 18. Dig 9 Cath LT313 Z 4117 Multiplexed 9 Digit Z 4155, TIL393-9 Display LT547EJ Z 4152 DL704 DL707 Pin out Z-4150 Z-4151 FND500 FND507 FND560 LT516RK LT547EJ 6680 Pin out Pin out Z-4117 LT302 LT312 1. Seg. A 2. Seg. F 3. Anode 10. Seg. C 11. Seg. G 12. NC 1. Seg. A 2. Seg. F 10. Seg. C 11. Seg. G 1. NC 10. NC 1. Seg. F 10. NC 10. R. Dec Point 1. Seg. E 2. Seg. D 10. Seg. G 1. NC 2. Seg. G 3. NC 11. Seg. C 11. Seg. D 12. Common 2. Seg. A 3. Seg. F 12. Cathode 3. Anode 12. NC 3. Seg. F 12. Seg. B 13. Seg. C 14. Seg. G 4. Seg. C 5. Dec. Point 4. Cathode 5. NC 4. NC 5. NC 4. NC 5. NC 13. Seg. B 14. Anode 4. Seg. G 5. Seg. E 4. Comme 5. Seg. E 15. Seg. B 16. NC 6. Dec. Point 7. Seg. E 6. L. Dec. Point 6. Seg. D 7. NC 6. Seg. B 7. Seg. A 6. Seg. E 7. Seg. G 7. Dec. Point 7. Seg. E 8. Common 9. Seg. F 8. NC 9. NC 8. Seg. C 9. Dec. Point 8. Seg. D 9. Anode 8. Seg. D 9. R. Dec. Point 8. NC 9. Cathodi

USING LEDS

DC Operation
When using a Light Emitting Diode (LED) as an indicator, use the following formula to determine series resistance for various voltage R = (E-1.7) x 1000 : 1; where R is the resistance in ohms, E is the supply voltage (DC) and I is the LED current in milliamps. EG, to operate the LED at 20mA; for 6V, use 220 ohms 9V, use 390 ohms 12V, use 560 ohms 24V, use 1.2k ohms







Mains Operation
To operate a LED directly from the 240V mains, a better scheme is to use the second circuit shown. In this, a capacitor is used as the voltage dropping element. A 114002 diode or similar across the LED provides the rectification required. As the voltage drop across the LED is negligible compared with the supply, capacitor current is almost exactly equal to mains voltage divided by the capacitive reactance Xc.
At 50Hz, 0.47uF will result in an Av LED current of about 16mA. Resistor Rs is to limit turn-on transients. A value of around 3.4k (2 x 6.8k par.) should be adequate.

ZENER DATA


Type No. A 400mW Series	Type No. ▼ 1Watt Series	Nominal Zener Voltage V _z @ I _{ZT} (V)	Test Current I _{ZT} (mA) 400mW 1W		
1N746	1N4728	3.3	20		
1N747	1N4729	3.6	20		
1N748	1N4730	3.9	20		
1N750	1N4732	4.7	20	53	
1N751	1N4733	5.1	20	49	
1N752	1N4734	5.6	20	45	
1N753	1 N4735	6.2	20	41	
1N754,1N957	1N4736	6.8	18.5	37	
1N755,1N958	1N4737	7.5	16.5	34	
1N756,1N959	1N4738	8.2	15	31	
1N757,1N960	1N4739	9.1	14	28	
1N758.1N961	1N4740	10	14	25	

▲ DC Power Dissipation: 400milliwatts @ 50°C Ambient (Derate 3.2mW/°C above 50°C)

	Type No. ▼ 1Watt Series	Nominal Zener Voltage V _z @ I _{ZT} (V)	Test Current I _{ZT} (mA) 400mW 1W		
1N962	1 N4741	11	12.5	23	
1N759,1N963	1N4742	12	11.5	21	
1N964	1N4743	13	10.5	19	
1N965	1N4744	15	9.5	17	
1N966	1N4745	16	8.5	15.5	
1N967,1N4112	1N4746	18	7.8	14	
1N968	1N4747	20	7	12.5	
1N969	1N4748	22	6.2	11.5	
1N970	1N4749	24	5.6	10.5	
1N971	1N4750	27	5.3	9.5	
1N972	1N4751	30	5.3	8.5	
1N973	1N4752	33	5.2	7.5	


▼DC Power Dissipation: 1Watt @ 50°C Ambient) (Derate 6.67mW/°C above 50°C)


This range will dissipate up to 3W @ 75°C with 10mm lead length as heatsink.




THREE TERMINAL REGULATORS

Туре	Polarity	Case	V _{OUT} min typ max	I _{OUT} (nom)	Dropout Voltage
78L05	positive	TO-92	4.8 5 5.2	100mA	1.7
78L62	positive	TO-92	5.95 6.2 6.45	100mA	1.7
78L09	positive	TO-92	8.64 9 9.36	100mA	1.7
78L12	positive	TO-92	11.5 12 12.5	100mA	1.7
78L15	positive	TO-92	14.4 15 15.6	100mA	1.7
7805	positive	TO-220	4.8 5 5.2	1A	2
7806	positive	TO-220	5.75 6.0 6.25	1A -	2 2 2
7809	positive	TO-220	8.64 9 9.36	1A	2
7812	positive	TO-220	11.5 12 12.5	1A	2
7815	positive	TO-220	14.4 15 15.6	1A	2 2
7824	positive	TO-220	23 25 25	1A	
7905	negative	TO-220	4.8 -5 -5.2	1A	1.1
7912	negative	TO-220	-11.5 -12 -12.5	1A	1.1
7915	negative	TO-220	-14.4 -15 -15.6	1A	1.1
LM317K	positive	TO-3	adj. 1.2 to 37	1.5Am	in
LM317T	positive	TO-220	adj. 1.2 to 37	1.5Am	in
LM350K	positive	TO-3	adj. 1.2 to 33	3A	
LM350T	positive	TO-220	adj. 1.2 to 33	3A	
78H05	positive	TO-3	4.85 5 5.25	5A	2.5







LM317T LM350T TO-3 pack

Connection TO-92 Package 78Lxx Positive Regulator Series COMMON (3) OUTPUT (2) INPUT (1) Maximum Power Dissapation for TO-92 Pack 0.75W **Bottom View**

VOLTAGE REGULATORS

These voltage regulators almost make power supply building unnecessary since they require only a filtered DC voltage input, they are essentially indestructible (if used within manufacturer's specs.) because of internal current limiting and thermal shutdown should a short occur. They are ideally suited to local, on board regulation simplifying power supply distribution systems. Excellent for TTL and project supplies. With the advent of microprocessors and microcomputers, these regulators have been used extensively in power supplies for such systems. This type of use extensively in power supplies for such systems. This type of use typifies their versatility and reliability. Another area of supply regulation use is with analogue operational amplifiers. These circuits usually call for both + and - complementary rail voltages. These three terminal devices ideally suit such requirements. Both positive and negative devices will give a current output in excess of 1A and foldback current limiting course if the output is expected. occurs if the output is shorted.

INCREASE THE OUTPUT VOLTAGE OF A 3 TERMINAL VOLTAGE REGULATOR

Regulators like the 7805 and the 7905 can give higher output if two additional resistors are configured into the circuit as shown below.

 $R1 = V_R/0.02$


 $R2 = V_B/0.025$

Where V_R is the normal regulated voltage from the IC and V_B is the amount by which the regulator has to be boosted above V_R . Some examples are given below:

V _{out} Regulator R1	
6 5V 220	39
9 5V 220	150
13.8 12V 560	68
18 15V 680	120

To make a variable regulator, use a potentiometer as R2.


VOLTAGE BOOSTING



INCREASING THE OUTPUT CURRENT OF THE REGULATOR

By adding a PNP power transistor to a positive regulator, the output current can be increased above the normal rating of the regulator itself. The circuit shown below can be expected to deliver in excess of 4A with the pass transistor mounted on a heatsink. The same conditions can also be implemented with a negative regulator, the difference being the polarities of components, the pass transistor in this case would be an NPN type such as a 2N3055.


CURRENT BOOSTING



TYPICAL POWER SUPPLY USING A 3 TERMINAL REGULATOR


Output: 5V @ 1A


The same basic circuit can be used with other regulators of different voltages, only the input ac voltage has to be changed to accommodate the the requirement of that regulator. e.g. If an output of 12V was the requirement, a 7812 IC could be used with an ac input voltage of 15V.




TYPICAL CHARACTERISTICS OF THE 7805 3 TERMINAL REGULATOR


The other members of this 78xx/79xx family have similar characteristics to those shown. For other data, refer to manufacturers literature.









VOLTAGE





Line Transient Response 7805

SEMICONDUCTOR OUTLINES Note: Pin connections may vary with different sources of supply. Check with your dealer if any doubt exists.



SIMPLE DIGITAL CIRCUITS

GATES

SYMBOL	CODE		
OUTPUT "AND" GATE	Output is "on" only when all inputs are "on". Output is "off when any or all inputs are "off".		
INPUTS OUTPUT	Output is "off" only when all inputs are "on". Output is "on" when any or all inputs are "off".		
INPUTS OUTPUT	Output is "on" only when all inputs are "off". Output is "off" when any or all inputs are "on".		
OUTPUT "OR" GATE	Output is "off" only when all inputs are "off". Output is "on" when any or all of the inputs are "on".		

INVERTERS

SY	MBOL	CODE
INPUT	ОИТРИТ	Output is "on" only when the input is "off".
IN	VERTER	Output is "off" only when the input is "on".

FLIP-FLOPS

A flip-flop can be compared with a push button switch connected to two lamps. When the button is pushed and released, one of the lamps will turn "on" and the other "off". If the button is again pushed and released, the lamp that was "off" will

now turn "on" and the lamp that was "on" will turn "off". There are many different types of flip-flops, but they all operate basically in the same way. The difference is in the number and type of inputs.

SYMBOL	CODE
OUTPUTS O	"Q" output is "on" when " $\overline{\mathbf{Q}}$ " output is "off".
FLIP-FLOP	"Q" output is "off" when "Q" output is "on".
INPUT	Outputs change when the input is turned "off".

LATCH


A latch is a flip-flop designed to store information until it is needed. It has an extra latch input. When the latch is turned on, the information on the input will be transferred to the "Q" output.

When the latch is turned "off", the information that was on the input at the time the latch was turned off, will be stored on the "Q" output.

SYMBOL	CODE		
Q OUTPUT Q	"Q" output will follow the information input. "Ō"		
LATCH	output will always be the opposite of the "Q" output.		
LATCH INPUTS MATION			


COUNTERS

SYMBOL	CODE		
OUTPUTS 1 2 4 8 RESET	As the input is turned "on" and "off" the count is accumulated on the outputs in either binary or decimal form depending on circuit. Counters are easily cascaded by using the highest output as the next input. When full the counter will automatically reset to zero. To use as a "N" divider the reset pin is connected to the required digit plus one.		



WIRING PLUGS

BELLING-LEE TYPE







STEP 1. STEP 1:

Cut end of cable even and remove 22mm of outer sheath.

STEP 2: Remove 16mm of braid and dielectric, taking care not to damage centre conductor. Lightly tin conductor.





assembly into body of

body to complete

assembly

plug, and screw cap onto



Cut end of cable even and remove 8mm of outer sheath

BNC TYPE

STEP 2: Slide clamp nut and pressure sleeve over cable, and comb out braid.

STEP 3: Fold braid back and insert ferrule between braid and dielectric. Trim

off excess braid


STEP 4: Remove 5mm of dielectric without damaging centre conductor. Tin conductor.



STEP 5: Slide rear insulator over conductor hard against rear insulator. Solder contact to conductor

STEP 6: Fit front insulator in body and push sub-assembly onto body. Slide pressure sleeve into body and screw in the clamp nut to

BNC TYPE (MALE)



Cut end of cable even and remove 8mm of outer sheath.

STEP 2 Slide clamp nut and pressure sleeve over cable, and comb out braid.

STEP 3: Fold braid back and insert ferrule between braid and dielectric. Trim off excess braid


STEP 4: Remove 5mm of dielectric without damaging centre conductor. Tin conductor.

STEP 5 Slide rear insulator over conductor hard against rear insulator. Solder contact to conductor



STEP 6: Fit front insulator in body and push sub-assembly onto body. Slide pressure sleeve into body and screw in the clamp nut to clamp cable.

'N' TYPE



Cut end of cable even and remove 9mm of outer sheath.

STEP 2 Slide clamp nut and pressure sleeve over cable, and comb out hraid

STEP 3: Fold braid back and insert ferrule between braid and dielectric. Trim off excess braid and remove 5.5mm dielectric without damaging inner conductor. Tin end of conductor.

Slide rear insulator over conductor and position against end of dielectric. Slide contact over conductor until hard against rear insulator Solder contact to conductor.

STEP 5 Fit front insulator in body and push sub-assembly into body. Slide pressure sleeve into body and screw in the clamp nut to clamp cable



UHF TYPE



STEP 1 Cut end of cable even and remove 27mm of outer sheath.

STEP 2 Slide coupling ring and adapter onto sheath. Fan braid back over sheath.

STEP 3: Compress braid around cable and position adapter so braid fans over adapter. Trim off excess braid

STEP 4 Remove 12.5mm dielectric and tin conductor. Screw the plug assembly onto cable and solder plug to braid through solder holes



STEP 5: Solder conductor to centre pin and screw coupling ring onto assembly.



Wiring Mains Plugs & Sockets

More electrocutions are More electrocutions are caused through incorrectly wired or faulty mains and extension leads than any other cause. While every hobbyist should know how to wire up a mains plus it. to wire up a mains plug, it is not a task done every day and many cables ARE wired incorrectly.

Colour Code: Cables throughout the would are now standardising on the colour code recommended by the IEC. However, many cables are still in existence cables are still in existence with the former colour code. The ACTIVE (or live) wire is coloured brown (or red in old cables). The NEUTRAL wire is coloured blue (or black in old cables). The EARTH wire is coloured green with a yellow stripe (plain green in old cables).

Wiring the cable: Following the instructions with the plug and socket. The diagrams below, reproduced by courtesy of HPM, show the right and wrong ways to wire an extension lead. It is essential these are followed exactly.



THE RS232C INTERFACE

The basic RS232C electrical specifications

Communication rate.

Driver output voltage levels, maximum no load, Driver output voltage ranges for loads between 3k and 7k ohms.

Driver output current, short circuit, Driver output impedance with power off.

Maximum driver output slew rate. Receiver input resistance.

Effective receiver input capacitance. Maximum receiver input voltage range.

0-20.00 bits per second -25V logic 1, +25V logic 0 logic 1: -15V (7k) and -5V (3k) logic 0: +15V (7k) and +5V (3k)

500mA maximum 300 ohms minimum

30 volts per microsecond 7k ohms maximum, 3k ohms minimum

2500pF maximum

RS232C CABLE PLUG CONNECTIONS

Pin No. Signal

- Protective Ground
- Transmit Data Received Data 3.
- Request to Send
- Clear to Send
- 6. **Data Set Ready**
- Signal Ground
- Received Line Signal Detector 8.
- 20 Data Terminal Ready

Pin No. Signal

14 15 16 17 18 19 20 21 22 23 24 25

1 2 3 4 5 6 7 8 9 10 11 12 13

View - socket rear

STANDARD CENTRONICS **PRINTER PLUG** CONNECTIONS

View - plug rear

 19.

Data Bit 0

Signal Ground

3. Data Bit 1

Data Bit 2 4.

5. Data Bit 3

Data Bit 4 6

Pin No. Signal

Data Bit 5 Data Bit 6

Data Strobe Data Acknowledge 10

Input Busy Ready

TRAILER CONNECTIONS



6 PIN (looking at trailer plug)

Connection

Tail Lamp Left Turn Indicator Right Turn Indicator Stop Lamps Aux. Circuits

Wire Colour

Brown Yellow Green Red Blue

Earth Terminal



Connection

Left Turn Indicator Reversing Signal Right Turn Indicator

Service Brakes
Stop Lamps
Rear Lamps,
clearance & Side
Marker Lamps


Yellow Black

White Blue Red


Brown

GET IT RIGHT!

Note the correct locations of the active, neutral and earth pins — a power outlet is exactly the same as an extension cord socket. (In almost all cases you will find a power point or socket is labelled A, N & E. Power points may also be colour coded. but usually they are marked with the old [red/black/green] colours.)



9 PIN to 25 PIN **RS232 CONVERSION**



AMATEUR BAND PLAN

160 metres — 1.8 to 1.86MHz full licence only

1.8 to 1.815MHz Morse section 1.815 to 1.860MHz voice section 1.825MHz national call channel 1.820MHz also a popular crystal net

80 metres - 2.5 to 3.8MHz novice and full licence

3.525MHz to 3.625MHz is the Novice Band in Australia 3.5 to 3.550MHz Morse section 3.550 to 3.7MHz voice section 3.7 to 3.74MHz is the US Novice Band 3.565MHz is a popular Novice listing and working channel 3.794 to 3.8MHz full licence only

40 metres - 7.0 to 7.3MHz full licence only

7.1 to 7.15MHz is the American Novice Band 7.0 to 7.035MHz Morse segment 7.035 to 7.3MHz voice segment 7.05MHz national listening channel, some AM stations but mainly Morse and LSB.

30 metres — 10.1 to 10.15MHz full licence only

20 metres — 14.0 to 14.35MHz full licence only

14.0 to 14.1MHz, Morse, 14.1 to 14.35MHz, voice 14.1 to 14.2MHz popular in Europe 14.2 to 14.35MHz popular in USA

15 metres — 21.0 to 21.45MHz novice and full licence only

21.125 to 21.2MHz is the Novice Band in Australia 21.0 to 21.15MHz is Morse 21.15 to 21.45MHz is voice 21.1 to 21.2MHz is the US Novice Band In the US, voice is 21.25 to 21.45MHz. Morse is 21.0 to 21 25MHz

12 metres — 10.1 to 10.15MHz full licence only

10 metres - 28.0 to 29.7MHz novice and full licence only

28.1 to 28.6MHz is the Australian Novice Band 28.1 to 28.2MHz is the US Novice Band 28.0 to 28.5MHz is the Australian Morse section 28.5 to 29.7MHz is the voice section 28.5MHz is the national calling frequency in Australia 28.55MHz is a popular international channel 28.6MHz is the international DX listening frequency 29.6MHz International FM calling channel,

6 metres — 50 to 52, 52 to 54MHz full or limited licence

Limited in area of TV Channel '0'

2 metres - 144 to 148MHz full or limited licence

6025-6400	_	Repeater Inputs
6425	146.425	Secondary voice channel
6450	146.450	Primary voice channel
6475	146.475	Secondary voice channel
6500	146.500	National Calling Channel
6525	146.525	Secondary voice channel
6550	146.550	Primary voice channel
6575	146.575	Secondary voice channel
6600	146.600	National RTTY
6625-7000	<u> </u>	Repeater Outputs
7025-7375	_	Repeater Outputs
7400	147.400	ATV Liaison
7425	147.425	ATV/SSTV/FAX
7475	147.475	SSTV/FAX liaison
7550	147.550	Micro Net
7575	147.575	Micro Net
7600	147.600	Data Packet
7625-7975	- ·	Repeater Inputs

Notes: 144 to 144.600 is a narrow band FM mode area and 145.700 to 146.000 should be avoided because it interferes with satellite operation.

70cm and above: full or limited licence

420 to 450MHz 3300 to 3600MHz 576 to 585MHz 5650 to 5850MHz 1240 to 1300MHz 10000 to 10500MHz 2300 to 2450MHz 24000 to 24250MHz

AMATEUR LICENCING

The Department of Communications conducts examinations for Amateur Operator's Certificate of Proficiency (AOCP) several times each year at centres throughout Australia. There are four classes of licence:

AOCP: Amateur Operator's Certificate of Proficiency **AOLCP:** Amateur Operator's Limited Certificate of

NAOCP: Novice Amateur Operator's Certificate of Proficiency

Combined AOLCP/NAOCP

Proficiency

The requirements for these licences are:

AOCP: Knowledge of radio communication, operation and design of recievers, transmitters, aerials and basic theory. Send and receive in plain language International Morse Code to a speed of 10 words per minute (WPM). The knowledge of the regulations covering operation of Amateur Radio Stations.

AOLCP: As above, but no Morse Code required.

NAOCP: Similar to AOCP but of a lower standard.

Morse Code to 5WPM, same regulations as AOCP. This is a relatively easy exam to pass.

Combined: Normally for those with AOLCP; achieved by possing NAOCP Morse exam (5WPM). Conversely, NAOCP holders can upgrade by passing LAOCP regulations.

The various licences allow:

AOCP: All amateur bands, with maximum of 400W Peak output power (150W AM).

AOLCP: All amateur bands above 30MHz, but no Morse allowed. Same power limits as AOCP.

NAOCP: 3.525 to 3.625MHz, 21.125 to 21.20MHz, 281. to 28.60MHz; Maximum output power 30 watts peak.

Combined: Same as taking either limited or novice

CB RADIO CHANNELS

HF 40 CHANNEL INTERNATIONAL STANDARD

CHANNEL	FREQUENCY	CHANNELFREQUENC		
No.	MHz	No.	MHz	
1	26.965	21	27.215	
2	26.975	22	27.225	
3	26.985	23	27.255	
4	27.005	24	27.235	
5	27.015	25	27.255	
6	27.025	26	27.265	
7	27.035	27	27.275	
8	27.055	28	27.285	
9 (emergency)	27.065	29	27.295	
10	27.075	30	27.305	
11	27.085	31	27.315	
12	27.105	32	27.325	
13	27.115	33	27.335	
14	27.125	34	27.345	
15	27.135	35	27.355	
16	27.155	36	27.365	
17	27.165	37	27.375	
18	27.175	38	27.385	
19	27.185	39	27.396	
20	27.205	40	27,405	

UHF 40 CHANNEL AUSTRALIAN STANDARD

CHANNEL	FREQUENCY	CHANNELFREQUENCY		
No.	MHz	No.	MHz	
1	476.425	21	476.925	
2	476.450	22	476.950	
3	476.475	23	476.975	
4	476.500	24	477.000	
5 (emergency)	476.525	25	477.025	
6	476.550	26	477.050	
7	476.575	27	477.075	
8	476.600	28	477.100	
9	476.625	29	477.125	
10	476.650	30	477.150	
11	476.675	31	477.175	
12	476.700	32	477.200	
13	476.725	33	477.225	
14	476.750	34	477.250	
15	476.775	35	477.275	
16	476.800	36	477.300	
17	476.825	37	477.325	
18	476.850	38	477.350	
19	476.875	39	477.375	
20	476.900	40	477.400	

CB LICENCING

Licences for CB equipment can be obtained from offices of the Department of Communications in each capital city and many country areas for an annual fee. Use of CB equipment requires no technical knowledge (apart from use of the equipment!) and no examination is required. While there are no legal restrictions on the use of channels (apart from the emergency channels) conventions have emerged which determine that certain channels will be used for specific purposes. Details of these channel usages are available through various clubs and magazines.

CB Radio may be used for business or pleasure: however it must be remembered that there is no privacy with CB and anybody may be listening in. Furthermore, no-one has 'occupancy' rights of any channel in any area. Several CB groups have established UHF CB repeaters in their areas. These have the same function as amateur radio repeaters. Input to these repeaters is generally on channels 1 to 5 (UHF). CB enthusiasts in your area will be able to tell you the local repeaters' frequencies.

MARINE FREQUENCIES

Frequency	(MHz) Use
27.680	Commercial organisations. Domestic ship- shore-ship and intership, calling and working.
27.720	Professional fishermen. Domestic, ship-shore ship, calling and working.
27.820	Professional fishermen. Intership.
27.860	Amateur organisations. Alternate calling and working for distress, emergency and safety messages for weather and position reports.
27.880	Distress calling ONLY
27.900	Amateur organisations. Domestic ship-shore-ship, calling and working.
27.910	Amateur organisations. Domestic ship-shore-ship, calling and working.
27.940	Amateur organisations. Club events, ship-shore-ship and intership, calling and working.
27.960	Amateur organisations. Intership.
27.980	Surf rescue.

27MHz marine radio channels should not be confused th 27MHz CB radio channels. While both are in the 27MHz band they are not interchangeable and a 27MHz CB cannot be used on the 27MHz marine band and vice versa

The alternative marine bands are VHF (56 channels available) and HF (many 'spot' frequencies available) Your Dick Smith Electronics store will be happy to advise you on the best marine transceiver for your craft.

CHANNEL	FREQUEN	ICY (MHz))	TYPE
DESIG	SHIP	SHORE		TRAFFIC
P1	157.375	157.375	Non	Com'l
02	156.100	160.700	Port	Ops
03	156.150	160.750	Port	Ops
04	156.200	160.800	Port	Ops
05	156.250	160.850	VTS	
06	156.300	156.300	Safe	ty
07	156.350	160.950	Com	ri
08	156.400	156.400	Com	r'i
09	156.450	156.450	Com	'I & Non Com'I
10	156.500	156.500	Com	r'l
11	156.550	156.550	Com	11
12	156.600	156.600	Port	Ops
13	156.650	156.650	Navi	gational
14	156.700	156.700	Port	Ops
15	156.750	156.750	Envi	ronmental
16	156.800	156.800	Safe	ty Calling
17	156.850	156.850	State	e Control
18	156.900	161.500	Com	
19	156.950	161.550	Com	
20	157.000	161.600	Port	
21	157.050	161.650		st Guard
22	157.100	161.700		st Guard
23	157.150	161.750		st Guard
24	157.200	161.800		lic Corresp.
25	157.250	161.850		ic Corresp.
26	157.300	161.900		lic Corresp.
27	157.350	161.950		ic Corresp.
28	157.400	162.000	Pub	lic Corresp.
60	156.025	160.625		
61	156.075	160.675		
62	156.125	160.725		
63	156.175	160.775		
64	156.225	160.825		eganterior et la casa la company
65	156.275	160.875		Ops
66	156.325	160.925	Port	
67	156.375	156.375	Com	
68	156.425	156.425		Com'l
69	156.475	156.475		Com'l
70	156.525	156.525		Com'l
71	156.575	156.575		Com'l
72	156.625	156.625		Com'l
73	156.675	156.675		Ops
74	156.725	156.725	Port	
77	156.875	156.875		Ops
78	156.925	161.525		Com'l
79	156.975	161.575	Com	
80	157.025	161.625	Com	
81	157.075	161.675		st Guard
82	157.125	161.725		Only
83	157.175	161.775		st Guard
84	157.225	161.825	Pub	ic Corresp.

157.275

157.325

157.375

157.425 161.025 Com'l

87

161.875 Public Corresp.

161.925 Public Corresp. 161.975 Public Corresp.

Amateur Radio Repeaters

TWO METER	DEDE	T FF	01.0					8.4					
TWO METRE	HEPE/	VI E	15	SOUTH AUST				Adelaide		VK5	8525	Crafers	
Conharm	WYADAC	2000	Disale UIII	AREA	CALL	CHAN	SITE						
Canberra ACT	VK1RAC VK1RGI	6900 6950		Gove	VK5	6650	2 24	WA				e (ili.	
				Port Pirie Eyre Penninsula	VK5RMN VK5REP	6700 6800	The Bluff	Perth		VK6RUF	8525	Roleystone	
NEW SOUTH	WALE	5		Adelaide Mt. Gambier	VK5RHO VK5RMG	6850 6900	Houghton	TAS					
AREA	CALL	CHAN	SITE	Adelaide	VK5RAD	7000	Mt. Gambier Crafers	Hobart		VK7	8525	-	
Hunter Region - Newcastle	VK2RPI	6625	Like the total	Alice Springs Darwin	VK5RCA VK5RTE	7000 7000	Alice Springs	North East Hobart		VK7RAB VK7RTC		Mt Arthur Mt Nelson	
North Coast - Coffs Harbou Western Blue Mountains	r VK2RCH VK2RDX	6650 6650	Bruxner Park Mt. Bindo	Daiwiii	VNONTE	7000	I com	North West		VK7RAC	8650	Table Cape	
Moree/Inverell	VK2RMI	6650		WESTERN AU	CTDA	LIA							
Sydney Central West - Orange	VK2RTY VK2RAO	6675 6700	Seven Hills Mt. Canobolas		CALL								
South Coast - Ulladulla	VK2RMU	6700	Milton	AREA	WILL	CHAN	SITE	SIX MET	RE RE	PEAT	ERS		
Mid-N. Coast-Pt.Macquarie Central Coast - Gosford	VK2RPM VK2RAG	6700 6725	Taree Somersby	Bunbury Albany	VK6RSW VK6RAL	6650 6700	Bunbury Albany	WSW					
Far South Coast - Bega	VK2RFS	6750	Mt. Mumbulla	Perth	VK6RAP	6700	Roleystone	AREA		CALL	CHAN	SITE	
New England - Tamworth Riverina - Wagga	VK2RTM VK2RWG	6750 6750	Mt. Crawney Mt. Flackney	Wyndham Wickham	VK6RWH VK6RWK	6700 6700	Wyndham Wickham	Sydney Hunter		VK2RWI VK2	3850 3625	Dural	
Orana Region - W'bungles Far North Coast - Lismore	VK2RCC VK2RIC	6800 6800	Needle Mtn. Parrots Nest	Perth	VK6RTH	6750	Tic Hill	VIC		•	OULU		
Sydney - Metro coverage	VK2RLE	6800	Heathcote	Albany Perth	VK6RAA VK6RTH	6800 6800	Mt. Barker Tic Hill	Melbourne		VK3RTN	3675	Mt Dander	oona
New England - Gunnedah South Coast - Wollongong	VK2RAB VK2RAW	6850 6850	Porcupine Res. Mt. Murray	Karratha	VK6RWP VK6REX	6800 6850	Karratha Tower Zero	Melbourne		VK3MH	3900	Hurstbridg	
Riverina - Griffith	VK2RGF	6850	Mt. Bingar	Exmouth Kambalda	VK6RKB	6850	Kambalda	WA					
Sydney - Northern Beaches Hunter Region - Newcastle	VK2RMB VK2RAN	6875 6900	Terrey Hills Mt. Sugarloaf	Bunbury Mt. Newman	VK6RBY VK6RMN	6900 6900	Mt. William Mt. Newman	Perth		VK6RSM	3200	Tic Hill	
Central West Condoblin	VK2RRT	6900	Boona Mount.	Perth	VK6RPD	6950	W.A.I.T. Bentley						
Sydney - Lower Nth. Shore New England Tablelands	VK2RGR VK2RNE	6925 6950	North Ryde Mt. Rumbee	Emergency Kalgoorlie	VK6REE VK6RAK	6975 7000	Kalgoorlie						
Hunter Region - Newcastle	VK2RAN	6975 7000	Durel	Wagin	VK6RAW	7000	Mt. Latham	Amateur Tel	evision	1 & AT	V Re	peater	S
Sydney - Metro coverage Blue Mountains	VK2RWI VK2RMB	7050	Dural Mt. Tomah	Emergency Geraldton	VK6REE VK6RGN	7000 7000	Geraldton	VK2RTV: Glad					
Sydney - Eastern Suburbs Hunter Region - Newcastle	VK2ROT VK2RTZ	7075 7100	Paddington Mt. Sugarloaf	Port Hedland	VK6RNW	7000	Port Hedland		IR2AIIIR 1	Amateu	nauit) Club I	
Central West - Grenfell	VK2RWM	7100	Grenfell	Perth Perth	VK6RTY VK6RWC	7050 7100	Nedlands Doubleview	Group					
State Wide Emerg (WICEN) Sydney Emergency	- VK2RWS	7125 7150	Chatswood	Cataby Boddington	VK6RCT VK6RMS	7200 7250	Cataby Mt. Saddleback		126.25MHz 579.25MHz				TV Ch35)
South Coast - Nowra	-	7175	-	Eneabba	VK6REN	7300	Ocean Hill	Output: Vision 5 VK2RTV is located					
State Wide Emerg (WICEN) Far North Coast - Byron Ba		7200 7200	Mt Cambewarra	Busselton	VK6RBN	7350	Busselton	Gladesville Amate	ur Radio C	lub's TV	Group.	Li Jagen	indu.c
Sydney	VK2RST VK2RNS	7225	Lane Cove West	TASMANIA				This club is the fo and each Wednes	remost tea	ching bo	dy for al	nateurs ir take place	Australia,
Sydney - Upper Nth Shore South Coast - N Wollongon		7250 7275	Hornsby Sublime Point	MEA	CALL	CHAN	SITE	include tapes of s	ections of	the novic	e or full	call amat	eur radio
Sydney - West Sthn Highlands - Goulburn	VK2RTS VK2RGN	7300 7325	750	January a tracked it				licence courses the items of technical					
Sthn Highlands - Mittagong	VK2RHR	7350	Bowral	North West Hobart	VK7RAD VK7RHT	6625 6700	Mt. Duncan Mt. Wellington	local time with a t	test patterr	1.			
Sydney - South West	VK2RLD	7375	Razorback	North West Coast East Coast	VK7RNW VK7REC	6750 6900	Ulverstone Snow Hill	Licenced amateur reception reports	s within vi	ewing ran	nge are i	nvited to /K2RGR) (give
VICTORIA				North East Coast	VK7RAA	7000	Mt. Barrow	146.925MHz. Info	rmation ab	out the c	lub may	be obtain	ed by
AREA	CALL	CHAN	SITE	70cm REPEAT	ERS			vriting to the club			iesville,	N9W 211	201
Shepparton	VK3RGV	6650	Mt. Wombat	AREA	CALL	CHAN	SITE		144.25MHz		49.75MI	-tz	
Melbourne	VK3RML VK3RNC	6700 6700	Mt. Dandenong Mt. Mittamatite	ACT				Output: Vision 5	579.25MHz	Sound 5	84.75MI	tz (UHF T	
Corryong Ouyen	VK3RON	6700	Ouyen	Canberra	VK1RGI	8525	Mt Ginini	VK2RTS is located input to this repeat	d near Spr	ingwood touch ton	in the lo e onerat	wer Blue I ion and in	Mountains.
Ballarat Latrobe Valley	VK3RBA VK3RLV	6750 6800		Gallborta		JOLO	2100	can be obtained b	y writing t	to SATV 6	Group, B	ox 84, Ha	zelwood
Mt. Macedon	VK3RMM	6850	Mt. Macedon	NSW				2779, or via 147.3 repeater when fur				perating a	as a
East Gippsland Swan Hill	VK3REG VK3RSH	6900 6900	Donalds Knob Swan Hill	Southern Highlands Central Coast - Gosford	VK2RTK VK2RAG	8025 8074	Somersby Terrey Hills	A net is held ever	y Tuesday	night at	7.30PM	on the ab	ove
Grampians	VK3RWZ	6950	Mt. William	Sydney North Beaches	VK2RMB	8175	Port Kembla	frequency. VK2RT VK2RTV transmis	S re-trans	mits the	material	from Wed	Inesday's
Geelong Wodonga	VK3RGL VK3RNE	7000 7000		South Coast - Wollongong Sydney - Emergency	VK2RUW VK2RWS	8225 8275	Chatswood Taree District	Repeater hours: N					0 — 2200.
Omeo Robinvale	VK3RG0 VK3RVL	7050 7050		North Coast - Taree	VK2REE	8325	Kurrajong	VK4RTV: Sou					
Warrnambool	VK3RWL	7050	Mt. Warm'bool	Blue Mountains Sydney Southern Suburbs	VK2RUT VK2RUH	8375 8425	Hurstville Parramatta	Repeater operatio	n is via a	valid telev	vision si	gnal. Tou	ch tone
Bright South Gippsland	VK3RPB VK3RSG	7100 7100		Sydney Western Suburbs Sydney - Metro coverage	VK2RRS VK2RWI	8475 8525	Dural New Lambton	operation is requi	red for rot	ation of th	ne receiv	re antenna T) and the	a. IWO e 70cm
Geelong	VK3RGC	7125	Montepellier	Hunter Region - Newcastle	VK2RUM	8625	Mt. Sugarloaf	liaison frequency				.,	
Bendigo Melbourne	VK3RCV VK3REC	7150 7175		Hunter Region - Newcastle Far North Coast - Lismore	VK2RAN VK2RSC	8675 8675	Mt. Nardi Sublime Point	For more information		contact	SEATV	Group, PO	Box 3,
West Gippsland	VK3RWG	7225		South Coast - N.Wollongong		8725	-	Chermside Qld 40	JOZ.				
Portable Melbourne	VK3RWP VK3RTY	7300 7350		VIC									
QUEENSLAN	D			Melbourne	VK3RMU	8074	Mt. St. Leonard			INPUT	INPUT	OUTPUT	OUTPUT
AREA	CALL	CH	SITE	Melbourne Portable	VK3ROU	8225	Mt. Dandenong	AREA	CVTT	VISION	SOUND	VISION	SOUND
				Gippsland	VK3RWE VK3RGU	8275 8375	Carrajung	CANBERRA	VK1RTV	426.25	431.75		584.75
Rockhampton Townsville	VK4RAR VK4RAT	6700 6700	Rockhampton Mt. Stuart	Melbourne Wodonga	VK3RAD VK3RNU	8525 8525	Mitcham Mt. Stanley	SYDNEY SPRINGWOOD	VK2RTV VK2RTS	426.25 444.25	431.75 449.75		584.75 584.75
Gold Coast	VK4RGC	6700	Mt. Tambourine	Mildura	VK3RRU	8525	Merbein	NEWCASTLE	VK2RTN	426.25	431.75	579.25	584.75
Mt. Isa Darling Downs	VK4RMI VK4RDD	6700 6750	Mt. Mowbullan	Portable Grampians	VK3RWI VK3RWU	8625 8675	Mt. William	WAGGA BENDIGO	VK2RTW VK3RMZ	444.25 426.25	449.75 431.75		584.75 584.75
Bundaberg	VK4RBU VK4RNC	6800 6850	Mt Goon'man Nr Nambour	Mt. Macedon	VK3RCU	9275	Mt. Macedon	MELBOURNE	VK3RTV	444.25	449.75	579.25	584.75
North Coast Ipswich	VK4RAI	6900	Mt. Crosby	Benalla	VK3RDU VK3RBU	9425 9575	Chassney Vale	BRISBANE BRISBANE	VK4RAT VK4RTV	444.25 449.25	449.75 449.75		584.75 584.75
грантоп			Caliana Danga	44-11	VK3RPU	9725	Arthurs Seat	CENTRAL NORTH	VK5RCN	426.25	431.75		449.75
Gladstone	VK4RGB	6900 6950	Caliope Range Mt. B'den Ker	Melbourne				CENTRAL NORTH	VKSRCN	579 25			
Gladstone Cairns Brisbane	VK4RGB VK4RCA VK4RBN	6950 7000	Mt. B'den Ker Mt. Glorious	QLD				CENTRAL NORTH ADELAIDE	VK5RCN VK5RTV	579.25 426.25	584.75 431.75	444.25 579.25	449.75 584.75
Gladstone Cairns Brisbane Mackay	VK4RGB VK4RCA VK4RBN VK4RMK	6950	Mt. B'den Ker		VK4RNC	8074	Mt. Nambour	ADELAIDE ADELAIDE	VK5RTV VK5RTV	426.25 444.25	584.75 431.75 449.75	444.25 579.25 579.25	449.75 584.75 584.75
Gladstone Cairns Brisbane Mackay Brisbane Brisbane	VK4RGB VK4RCA VK4RBN VK4RMK VK4RBT VK4RAG	6950 7000 7000 7050 7150	Mt. B'den Ker Mt. Glorious North Mackay	QLD North Coast Gold Coast	VK4RNC VK4RGC	8074 8225	Mt. Nambour Mt. Tambourine	ADELAIDE ADELAIDE HOCKHAM PERTH	VK5RTV VK5RTV VK5RWH VK6ROD	426.25 444.25 444.25 426.25	584.75 431.75 449.75 449.75 431.75	444.25 579.25 579.25 1246.25 579.25	449.75 584.75 584.75 1251.75 584.75
Gladstone Cairns Brisbane Mackay Brisbane	VK4RGB VK4RCA VK4RBN VK4RMK VK4RBT	6950 7000 7000 7050	Mt. B'den Ker Mt. Glorious North Mackay Mt. Cotton	QLD North Coast	VK4RNC	8074	Mt. Nambour	ADELAIDE ADELAIDE HOCKHAM	VK5RTV VK5RTV VK5RWH	426.25 444.25 444.25	584.75 431.75 449.75 449.75	444.25 579.25 579.25 1246.25 579.25	449.75 584.75 584.75 1251.75

INFORMATION

STOCK AND PRICES

This catalogue is produced to cover the year from April 1988, until March 1989. Because of this, plus the fact that this catalogue is in print production from January 1988, there may be items shown in this catalogue that are not in stock at the time of your receiving this catalogue, or could even be sold out. Likewise, prices are subject to revision during the life of this catalogue. We are aware of the inconvenience that this sometimes causes and would like to take this opportunity to ask you to bear with our problems and if your are not sure as to prices and stock availability, please phone and check with us before making a long journey.

Thank you — the staff of Dick Smith Electronics.

GUARANTEES

Manufacturer's guarantee.

- 1. All Australian manufacturer's guarantees are fully valid on products we sell.
- are rully valid on products we sell.

 2. Semiconductor guarantee policy. Most manufacturers will not replace semiconductors, as all semiconductors shipped from their factories are computer quality controlled. However, in some cases when the value of the semiconductor is considerable (eg over \$5), a manufacturer's engineer will test the semiconductor if it is returned unsoldered to them. Value on return engineer will test the semiconductor in its returned unsoldered to them. You can return your semiconductor to the manufacturer's agents either through our company, if purchased from us, or deal direct, to save time.
- Periods of guarantee. Unless stated otherwise, and subject to any statutory rights, items in this catalogue carry a standard warranty of 90 days from date of purchase. If you are not supplied with a guarantee card, keep your sales dockets, including cash register receipt, in a safe place, as the sales docket will become your place, as the sales docket will become your guarantee card. If your purchase requires warranty service within the warranty period, you will be requested to produce your docket when returning the product under warranty for repair.
- 4 Freight, Although repairs under warranty Freight. Although repairs under warranty are carried out free of charge, the customer is required to pay the freight both ways. Therefore, to save yourself money, make absolutely certain that the unit is faulty before returning for repair.

QUANTITY/RESELLER'S PRICES

On many of our lines we can offer extremely attractive prices for large quantities. Our wholesale company will be glad to advise you on either large quantity purchases or purchasing for re-sale. (In normal circumstances, all sales tax is paid on our goods on the understanding that the goods are not to be resold. This keeps the price down for the sold. This keeps the price down for the hobbyist). For enquiries regarding re-selling or quantity prices, please call

DSE Wholesale, Cnr Lane Cove & Waterloo Rds, North Ryde, NSW, 2113 Telephone 888 3200

SCHOOLS, COLLEGES, ETC.

We supply a very large number of schools with components, etc for their electronics courses Obviously, the bulk discounts apply for schools purchasing in quantity. A 30 day account is available for schools — please apply direct to General Manager on your

SALES TAX

All prices shown in this catalogue include sales tax, where applicable. Goods can only be supplied less tax, if:

- 1 A sales tax number or exemption certificate is supplied on an official order, or
- 2. The goods are to be directly exported by us,
- Travel documents, etc. are supplied by bona-fide overseas travellers. (See 'Overseas'

In all cases for sales tax exemption, the minimum value of each item must be at least

SUBSTITUTION

When a certain product is no longer available, where possible we will substitute an equal or better quality product on the understanding that a substitute is available. If our purchasing power makes this substitute cheaper, then w will pass the savings on to the customer. I however, we can improve on the product, the price could either increase or remain the same as the original product. To summarise, all prices and specifications are subject to change

COMPUTER HOTLINE

If you have any queries or problems regarding our range of computers or peripherals, call the Computer Hotline for assistance.

Information on many other DSE technical products, such as Yaesu amateur radio products, CB & Marine radio, etc., may also be obtained through the Computer Hotline.

Answers, particularly on non-computer products, may not always be available immediately. However, someone will call you back with the information you require.

> 9.00am to 5.00pm Monday to Friday On (02) 888 2002



PRICES ON PRODUCTS

All prices in this catalogue were checked at time of compilation, but are subject to change without notice.

The price savings shown are either off our previous price, or off our competitor's normal selling prices for equivalent goods.

We can offer credit terms through AGC to customers who personally visit our stores. These terms are offered on condition that the Inese terms are offered on condition that the customer is approved by the finance company (*TAP: To Approved Purchasers). Terms are NOT available to DSXpress customers: we suggest you use your credit card.

RAIN CHECK POLICY

If advertised goods are sold out during the currency of the advertisement or if goods are otherwise unavailable for unforeseen reasons, our policy is to issue a 'Rain Check' to enable you to buy the goods at a later date for the advertised price. This does not apply to special scoop purchases limited stock offers and the like which will normally be noted as such and say 'No Rain Checks'.

OVERSEAS TRAVELLERS

As a service to overseas travellers visiting Australia, our stores can supply goods free of sales tax providing:

- 1. Airline tickets, passport, etc. are produced
- at the time of purchase.

 Certificate 'C' is properly filled out and handed to the store manager

NOTE: This concession is NOT available for Australians travelling overseas.

In order to avoid the obligation to pay sales tax, an overseas traveller must export his goods overseas within six months of purchase

SPECIAL PURCHASES

We normally stock the goods shown in this catalogue and in our regular advertisements in the daily press and in electronics magazines the daily press and in electronics magazines. New items are continually being sourced and added to our range to cater for as wide a range of needs as possible. A great deal of effort is put into searching for new products. For this reason, it is impossible for us to purchase operinal items for individual customers outside our normal range. However, each store maintains a 'products asked for' book and if demand is sufficient for any particular item we will investigate the viability of stocking it in all stores.

QUOTATIONS

We do give written quotations if required. We must emphasise however, that prices are subject to confirmation at time of order. This is because there are many factors in our prices that are beyond our control and therefore responsibility

STORE HOURS

All Dick Smith Electronics stores are open for All Dick Smith Electronics stores are open for trading during normal trading hours for their particular area (either 9 to 5.30 or 8.30 to 5). Many stores are also open for extended hours trading where applicable: please ring the store concerned for their particular hours. (Numbers on page 4)

LIABILITY

As the use of our products is completely beyond our control or supervision, we cannot be held responsible for damage or destruction, consequential or otherwise, of equipment or articles in or on which our products are used, attached, or otherwise employed.

Liability is limited to repair, replacement or refund (at our option) of goods purchased.

HAVE YOU ANY PROBLEMS OR COMPLAINTS?

We are particularly proud of the reputation our company has earned with electronics enthusiasts. The last thing we want is an unhappy customer. If there is something that you don't like, or if you have any suggestions which may help us serve you better please let us know. Every call or letter will receive personal attention.

Because problems can be solved most quickly at local level, we suggest that our State
Managers will be able to help you best. Contact
them on the following direct numbers:

NSW: (02) 888 3200 Vic/Tas: (03) 674 781 Qld: (07) 391 6490 WA: (09) 227 8243 SA/NT: (08) 212 3159

SATISFACTION GUARANTEE

If for any reason you are not satisfied with your purchase, return the goods to us within **7 days** of purchase, in original condition and in original carton, and we will exchange or return your money, less transportation costs. Goods returned to us must be unmarked and in the

returned to us must be unm exact condition as supplied. You must include all sales dockets when you return the goods. This policy does not cover semiconductors, valves, books and computer software. For mail order customers our guarantee period is specially extended to 14 days.



ELECTRONIC ORDERING

Electronic ordering is quickest and easiest. For your convenience, we have also included two mail order forms in this catalogue. Orders on this form receive preferential treatment over all other systems except electronic ordering. Extra forms are despatched with each order.

CATALOGUE NUMBERS

To minimise the chance of error in your order please use the catalogue number as well as a description of the product.

PAYMENTS

Money orders or crossed cheques to be sent with order. DO NOT SEND CASH through the post. Please make money orders payable at North Ryde Post Office, and cheques made payable to Dick Smith Electronics.

CREDIT CARDS

For your convenience, we accept orders for mail orders on Credit Cards. The minimum order value Bankcard, Visa, Mastercard, American Express and Diners Club purchase is

DSXpress TOLL-FREE PHONE ORDER

To make ordering even easier we have installed a special 'Order-by-Credit Card' phone line. To place an order, ring us on

(008) 22 6610

For the price of a local call, anywhere in Australia, 24 hours a day (answer machine takes your order after hours). Quote your credit card number and street address and we'll have your order on its way within 24 hours. Mail Order enquiries or Sydney area orders should be directed to the normal DSXpress Number:

(02) 888 2105.

NEW ZEALAND CUSTOMERS

Despite opening 11 DSE stores throughout. New Zealand with their own DSXpress order centre, we still have a large number of New Zealand customers buying from DSXpress (mainly because of the increased range available). When buying from overseas, please the account currency. remember to take into account currency differences between your currency and the Australian Dollar.

NEW ZEALAND BANKCARD

We accept New Zealand Bankcard as payment for international mail orders. Simply fill in the Bankcard details on the Mail Order Form.

OPEN CHEQUES

If you are not sure of the total amount of your mail order and are paying by cheque, simply cross the cheque and make it payable to Dick cross the cheque and make it payable to Dick Smith Electronics. Leave the amount blank, and we will fill in the cost of the goods and delivery charges if applicable. This eliminates charging for small balances or issuing credit vouchers. Many of our customers have been using this system for years and find it very satisfactory.

MINIMUM MAIL ORDER VALUE

otherwise implied in 'Special Offers' through

OVERSEAS MAIL ORDERS

We are happy to sell to foreign countries. Simply address your order to 'DSXpress International Mail Orders' at the above address on the mail order form or phone ISD 612 888 2105. Where possible, we will deduct Australian Sales Tax (note the \$10 minimum for sales tax exemption) sales tax exemption).

On more expensive items, the savings in Sales Tax could mean the cost of freight is recovered. Remember, however, that you may have to pay Customs and importing charges at your end (if applicable). We cannot supply full Customs documentation, but all parcels include the required customs dockets.

We would also remind overseas customers that our guarantees are 'ex store'.

off, for any reason, goods are returned to us from overseas (eg for service, etc) it is absolutely essential that Customs documents are included. If they are not it can be a very costly process to obtain Customs Clearance charge must be paid by the customer. Failure to include Customs documents can also result in long delays.

REGISTRATION

The customer may nominate registration and insurance for his goods. Where this is not specified, the goods will be sent at the customers — your — risk!

DAMAGED GOODS

MINIMUM MAIL ORDER VALUE

All claims for damaged or missing goods must

The minimum order amount is \$5 unless be filed with the carrier concerned — do not

open parcel if you suspect that the goods are

DESPATCH OF ORDERS

All goods in stock are despatched promptly. Goods out of stock are 'Back Ordered' and sent later at our expense (and it's an extremely costly job) unless we advise otherwise. All back orders are despatched immediately we receive orders are despatched immediately we receive the goods from our suppliers. When we send a copy of your order back to you, the delay times will be quoted, but because this information is given to us by our suppliers we cannot guarantee their accuracy. We will advise you of any further delays monthly. Minimum back order value \$10. order value \$10.

ENQUIRIES ON ORDERS

If you wish to enquire in any way about your order, please give FULL DETAILS. Give date of posting your order to us, your name, address and postcode, a list of the products ordered, any relevant mail order/cash sale invoice numbers. If the above are not given, we have no way of checking your order. Please quote Customer Number for fast efficient service.

PHONE ENQUIRIES ON ORDERS

You are welcome to enquire about your order by phoning our enquiry line (02) 888 2105. Because our system is computerised, we can normally give you the information you want very quickly — at most within a couple of minutes.

Before phoning, please have available your customer number (from your last invoice or from any correspondence), name and address on order, and the information required.

INDEX

	F	Neon test screwdrivers26	Transformers14, 31, 63,
daptor plugs51, 55,	2 Fans55	Nibbling tool28	Transistor assisted ignition
dhesive		NiCad batteries17, 66	Transistors
rfreight		Noise suppressor38	Transistor sockets34,
larms13,			TRIACS35,
lligator clips			Trimmers
mateur books			TV accessories26, 61,
mateur radio14, 15, 70-		0	TV aerials
mplifiers/audio10-		Operational amplifiers37	TV game switch box
mplifiers/kits10-		Oscillators19, 24, 25	TV pattern generator
mplifiers/RF			Tweeters
ntenna/car radio			Tweezers
ntenna/CB57, 70, 72-73,		P	
ntenna marine		Panel meters18, 42	
ntenna matcher/coupler71,		Part cases29, 46	U
ntenna scanners		Phone plugs51	UHF/VHF antenna72,
ntenna shortwave			UHF/VHF down converter
ntenna/TV	0 Graphic equalizer10	Photo sensitive devices59	Utility box29, 46,
udio accessories			
udio/adaptor	Grommets45		
ables48-51, 60,		Pliers27	V
udio connections		Plugs & sockets48-51, 55, 95	Varistors
	Н	Pot cores57	VHF marine radio
	Hand-held CB72, 74, 79	Power meters25	VHF/UHF antenna72,
	Hardware44, 45, 81	Power supplies11, 14, 65, 71	Video enhancer
atteries66,	7 Headphones10	Power transformers64	Video leads
attery charger17,			Voltage regulators24, 35,
attery eliminator		Printed circuit boards58, 59	VU meters24, 05,
attery holder & clips		5 .	
attery tester/lamp fuse			
ezels44,		_ ` `	W
ooks82-			Walkie talkies
oxes29, 46,			Weather station
rackets29, 40,		R	
readboards		Radios14, 70-77	Wireless microphones 51.60
ulbs		Receivers, communications74, 75	Wire etripper
		Rechargeable cells17, 66	Wire stripper
urglar alarms		m 01.01	Woofers
	IC's59		
	IC sockets49		v
abinets46,	Ignition killer13		X
	_ ig	Resistors/pots39, 40, 87	Xenon flashtubes
ables60-			
ables, computer			
ables,	Innerbond69		Z
es & clamps45, 48-51,			Zippy boxes46,
apacitors			
ar aerials49, 77,			
ar alarms		•	Data Index
ar/bits & pieces62,		3	
ar speaker grilles		Scanners74	Amateur information96,
B radios/accessories71			Bipolar transistors88
eramic filters38,			Capacitor codes
harges, battery17,		Screws44	CB information, marine,
hokes	7	Semi-conductors34-37	amateur
oaxial	L	Service aids33, 59	Circuit laws
ugs/connector49, 61, 62,			Colour code
ommunications receivers74,	5 Lamps63	Sockets48-50, 95	Common component diagrams.
omponent packs		Solder32	Counters
omputer books	4 LDR91	Soldering irons30-32	Diode data
omputer connectors			FET data
onnectors48			Flip flops
ooling fans		Spaghetti61	Gates
ores/ferrite			Inverters
rocodile clips			Latches
ROs19,			LED's
rossovers			Marine frequencies
	LSI IC36		Photo sensitive devices
	Lug packs45		Plug socket wiring
	g puono	Suppressors38, 55	Power supply circuits
ata86-	7	Switches52-55	Repeaters
ata books		SWR meters25	Resistor colour code
evelopers			
igital IC's			SCR dataSemi-conductor outlines
igital multimeters21-			
iodes34, 35, 40,			Tantalum capacitor codes
irection finder			Transistor data88
isco strobe kit			Triac data
own converter12,			Voltage regulators
			Zener diode data
rills28,			
	Mixer12		
	Motion detectors13		Copyright © 1987
	Multimeters20-23	Test equipment18-25	
dge connectors			All rights reserved. The en
lectrolytic caps38,		Toggle Switches52	contents of this catalogue
lectronic ignition	3	Tools26-33	copyright, and no copy, illustrati
		Toroids57	photograph, or diagram may
	L		
nhancer/TV	9 N	Transceivers	reproduced in whole or part with
		Transceivers	reproduced in whole or part with the written consent of Dick Sn

Transformers	34 4, 50 5, 90 38 1, 62
TV game switch boxTV pattern generatorTW pattern generatorTweetersTweezersTweezers	69
Utility box29, 4 V VaristorsVHF marine radio	6, 47
VHF/UHF antenna	2, 80 12 62 5, 65 42
Walkie talkies	24 60, 61 60, 68
X	
Xenon flashtubes	
X Xenon flashtubes Z Zippy boxes4	
Z Zippy boxes	6, 47 6, 97 8, 89
Z Zippy boxes	6, 47 6, 97 8, 89 86 86
Z Zippy boxes	6, 47 6, 97 8, 89 86 86 86 94 90
Z Z Zippy boxes	6, 47 6, 97 8, 89 86 96 94 94 994 94 94 94 94
Z Zippy boxes	6, 47 6, 97 18, 89

